

v23be6p12@system7: ~/p12/e × + v

```
1 // WAP in C using Rec_Fun to sum of even digits
2 |
3 #include<stdio.h>
4 int rec_fun_sum(int);
5 void main()
6 {
7     int num,sum;
8     printf("Enter the number:"); // 2345
9     scanf("%d",&num);
10    sum=rec_fun_sum(num);
11    printf("sum=%d \n",sum); // sum=6
12 }
13 int rec_fun_sum(int num)
14 {
15     //static int sum=0;
16     int r,sum=0;
17     if(num>0)
18     {
19         r=num%10;
20         if(r%2==0)
21             //num=num/10;
22         sum=sum+r;
23         return sum+rec_fun_sum(num=num/10);
24     }
25     else
26         return 0;
27 }
```

~

"1.c" 27L, 409C


```
1 // |
2 // P: 2658942 O/P: count=4:wq
3
4 #include<stdio.h>
5 int rec_fun_count(int);
6 void main()
7 {
8     int num,r,count;
9     printf("Enter the number:");
10    scanf("%d",&num);
11    count=rec_fun_count(num);
12    printf("count=%d \n",count);
13 }
14 int rec_fun_count(int num)
15 {
16     static int count=0;
17     int r;
18     if(num>0)
19     {
20         r=num%10;
21         if(r<6)
22             count++;
23         rec_fun_count(num=num/10);
24     }
25     else
26         return count;
27 }
```

~
-- INSERT --


```
//  
// I/P: 345638    O/P: product=54  
#include<stdio.h>  
int rec_fun_product(int);  
void main()  
{  
    int n,r,product;  
    printf("Enter the number:");  
    scanf("%d",&n);  
    product=rec_fun_product(n);  
    printf("product=%d \n",product);  
}  
int rec_fun_product(int n)  
{  
    static int product=1;  
    int r;  
    if(n>0)  
    {  
        r=n%10;  
        if(r%3==0)  
            product=product*r;  
        rec_fun_product(n=n/10);  
    }  
    else  
        return product;  
}
```

~

~

"3.c" 26L, 375C


```
1 #include<stdio.h>
2 int rec_fun_sum(int, int);
3 void main()
4 {
5     int num, r, sum;
6     printf("Enter the number:");
7     scanf("%d", &num);
8     sum=rec_fun_sum(num, 3);
9     printf("sum=%d \n", sum);
10 }
11 int rec_fun_sum(int num, int c)
12 {
13     static int c1=0;
14     int sum=0;
15     int r;
16     if(num>0)
17     {
18         r=num%10;
19         num=num/10;
20         c1++;
21         if(c1<=c)
22             sum=sum+r;
23         return sum+rec_fun_sum(num, c);
24     }
25     else
26         return 0;
27 }
```

"4.c" 27L, 377C



34°C
Sunny




```
1 |  
2 #include<stdio.h>  
3 int rec_fun_rev(int);  
4 void main()  
5 {  
6 int num,rev;  
7 printf("Enter the number:");  
8 scanf("%d",&num);  
9 rev=rec_fun_rev(num);  
10 printf("rev=%d \n",rev);  
11 }  
12 int rec_fun_rev(int num)  
13 {  
14 static int rev=0;  
15 int r;  
16 if(num>0)  
17 {  
18 r=num%10;  
19 rev=rev*10+r;  
20 rec_fun_rev(num=num/10);  
21 }  
22 else  
23 return rev;  
24 }
```

~
~
~
~

"5.c" 24L, 301C



34°C

Sunny



Search




```
1 int rec_fun_perfect(int);
2 void main()
3 {
4     int num, sum, r;
5     printf("Enter the number:");
6     scanf("%d", &num);
7     r = rec_fun_perfect(num);
8     if(r)
9         printf("yes perfect \n");
10    else
11        printf("not perfect \n");
12 }
13
14 int rec_fun_perfect(int num)
15 {
16     static int i=1, sum=0;
17     if(i<num)
18     {
19         if(num%i==0)
20             sum=sum+i;
21         i++;
22         rec_fun_perfect(num);
23     }
24     if(sum==num)
25         return sum;
26     else
27         return 0;
28 }
29
30
31 }
```



```
v23be6p12@system7: ~/p12/c x
1 //
2 //
3 //
4 #include<stdio.h>
5 int rec_fun_count(int *);
6 void main()
7 {
8     int n,count=0;
9     printf("Enter the number:");
10    scanf("%d",&n);
11    count=rec_fun_count(&n);
12    printf("count=%d \n",count);
13 }
14 int rec_fun_count(int *p)
15 {
16     static int pos=31,c=0;
17     int r;
18     if(pos>=0)
19     {
20         //printf("%d",*p>>pos&1);
21         r=*p>>pos&1;
22         if(r)
23             c++;
24         pos--;
25         rec_fun_count(p);
26     }
27     else
28         return c;
29 }
```

~
"7.c" 29L, 346C



34°C




```
1 #include<stdio.h>
2 int rec_fun_prime(int, int);
3 void main()
4 {
5     int n, a, c;
6     printf("Enter the number:");
7     scanf("%d", &n);
8     a=rec_fun_prime(n, c);
9     if(a==1)
10         //if(a==2)
11         printf("Yes prime \n");
12     else
13         printf("Not prime \n");
14 }
15 int rec_fun_prime(int n, int c)
16 {
17     static int i=1, c1=0;
18     if(i<n)
19         //if(i<=n)
20         {
21             if(n%i==0)
22                 c1++;
23             i++;
24             rec_fun_prime(n, c);
25         }
26     else
27         return c1;
28 }
29
```

"8.c" 29L, 379C

34°C


```
1 | #include <stdio.h>
2 | int rec_fun_count_arr(int *, int);
3 | void main()
4 | {
5 |     int a[6], i, ele, count;
6 |     ele = sizeof(a) / sizeof(a[0]);
7 |     printf("Enter the array elements:");
8 |     for(i=0; i<ele; i++)
9 |         scanf("%d", &a[i]);
10 |    count = rec_fun_count_arr(a, ele);
11 |    printf("count=%d \n", count);
12 | }
13 | int rec_fun_count_arr(int *p, int ele)
14 | {
15 |     static int i=0;
16 |     int c=0;
17 |     if(i<ele)
18 |     {
19 |         if(p[i]>39 && p[i]<99)
20 |             c++;
21 |         i++;
22 |         return c+rec_fun_count_arr(p, ele);
23 |     }
24 |     else
25 |         return 0;
26 | }
```

~
~
~
~

"9.c" 26L, 419C

v23be6p12@system7: ~/p12/

```
1 |#include<stdio.h>
2 int rec_fun_sum_arr(int *,int);
3 void main()
4 {
5     int a[6],sum,i,ele;
6     ele=sizeof(a)/sizeof(a[0]);
7     printf("Enter the array elements:");
8     for(i=0;i<ele;i++)
9         scanf("%d",&a[i]);
10    sum=rec_fun_sum_arr(a,ele);
11    printf("sum=%d \n",sum);
12 }
13 int rec_fun_sum_arr(int *p,int ele)
14 {
15     static int sum=0,i=0;
16     if(i<ele/2)
17     {
18         sum=sum+p[i];
19         i++;
20         rec_fun_sum_arr(p,ele);
21     }
22     else
23         return sum;
24 }
```

"10.c" 24L, 380C

34°C
Sunny


```
v23be6p12@system7: ~/p12/ε ×
#include<stdio.h>
void rec_fun_rev_arr(int *, int *);
void main()
{
    int a[6], i, ele, *b;
    ele = sizeof(a) / sizeof(a[0]);
    printf("Enter the array elements:");
    for(i=0; i<ele; i++)
        scanf("%d", &a[i]);
    printf("Before...\n");
    for(i=0; i<ele; i++)
        printf("%d ", a[i]);
    printf("\n");
    b = &a[ele-1];
    rec_fun_rev_arr(a, b);
    printf("after\n");
    for(i=0; i<ele; i++)
        printf("%d ", a[i]);
    printf("\n");
}
void rec_fun_rev_arr(int *p, int *q)
{
    int t;
    if(p < q)
    {
        t = *p;
        *p = *q;
        *q = t;
        p++;
        q--;
        rec_fun_rev_arr(p, q);
    }
}
```



34 C



v23be6p12@system7: ~/p12/e

```
#include<stdio.h>
#include<string.h>
void rec_fun_rev_string(char *,char *);
void main()
{
    int i,l;
    char s[20],ch,*q;
    printf("Enter the string:");
    scanf("%s",s);
    for(l=0;s[l];l++);
    q=s+(l-1);
    rec_fun_rev_string(s,q);
    printf("%s",s);
}
void rec_fun_rev_string(char *p,char*q)
{
    int t;
    if(p<q)
    {
        t=*p;
        *p=*q;
        *q=t;
        p++;
        q--;
        rec_fun_rev_string(p,q);
    }
}
```

"12.c" 27L, 356C



34°C
Sunny



v23be6p12@system7: ~/p12/

```
1 #include<stdio.h>
2 #include<string.h>
3 int rec_fun_count_string(char *,char );
4 void main()
5 {
6     int i,count;
7     char s[20],ch;
8     printf("Enter the string:");
9     scanf("%[^\n]",s);
10    printf("Enter the char:");
11    scanf(" %c",&ch);
12    count=rec_fun_count_string(s,ch);
13    printf("count=%d \n",count);
14 }
15 int rec_fun_count_string(char *p,char ch)
16 {
17     static int c,i;
18     if(p[i])
19     {
20         if(p[i]==ch)
21             c++;
22         i++;
23         rec_fun_count_string(p,ch);
24     }
25     return c;
26 }
```

"13.c" 26L, 413C

34°C

Sunny


```
1 #include <stdio.h>
2 int rec_fun_rev_bit(int);
3 void rec_fun_binary(int);
4 void main()
5 {
6     int num, pos, n;
7     printf("Enter the number:");
8     scanf("%d", &num);
9     rec_fun_binary(num);
10    printf("\n");
11    n = rec_fun_rev_bit(num);
12    for(pos=31; pos>=0; pos--)
13        printf("%d", n>>pos&1);
14    printf("\n");
15 }
16 void rec_fun_binary(int num)
17 {
18     static int pos=31;
19     if(pos>=0)
20     {
21         printf("%d", num>>pos&1);
22         pos--;
23         rec_fun_binary(num);
24         pos=31;
25     }
26 }
27 int rec_fun_rev_bit(int num)
28 {
29     static int i=0, j=31;
30     int m, n;
31     if(i<j)
32     {
33         m=num>>i&1;
34         n=num>>j&1;
35         if(m!=n)
36         {
37             num=num^1<<i;
38             num=num^1<<j;
39         }
40         i++;
41         j--;
42         rec_fun_rev_bit(num);
43     }
44     else
45         return num;
46 }
```


v23be6p12@system7: ~/p12/

```
1 #include<stdio.h>
2 char *my_strchr(char *, char);
3 void main()
4 {
5     char s[20],ch;
6     char *p;
7     printf("Enter the string:");
8     scanf("%s",s);
9     printf("Enter the char:");
10    scanf(" %c",&ch);
11    p=my_strchr(s,ch);
12    if(p==0)
13        printf("Not present...\n");
14    else
15        printf("Present...\n");
16 }
17 char *my_strchr(char *s,char ch)
18 {
19     static int i;
20     if(s[i])
21     {
22         if(s[i]==ch)
23             return s+i;
24         i++;
25         my_strchr(s,ch);
26     }
27     else
28         return 0;
29 }
```

~
"17.c" 29L, 388C

Tomorrow's high
To tie record



Search