

```
#include <iostream>
#include <string>
using namespace std;
namespace A{

    int var = 10;
}
namespace B{
    int var = 5;
}
int main()
{
    int var = 20;
    using namespace B;
    cout<<var;
}
```

- ☐ 5
- ☒ 10
- ☐ 20
- ☐ Error

Declare the following statement?
"An array of three pointers to chars".

- ☐ char *ptr[3];
- ☐ char **ptr[3];
- ☐ char (*ptr[3])();
- ☐ char *ptr[3]();

```
#include<stdio.h>
typedef int s32;
#define FUN(n,i) n^(3<<i)
int main(){
    s32 c,d;
    c= FUN(31,3);
    d= FUN(16,4);
    printf("%d %d\n",c,d);
    return 0;
}
```

- ☐ error
- ☐ 31 16
- ☐ 7 32
- ☐ 7 16

```
#include<stdio.h>

int main()
{
int vector = 200;

char *Chennai = &vector;

*++ Chennai = 3;

*-- Chennai = 32;

printf("blr-> %d    ,   hyd-> %d \n", vector ,
*++Chennai * 33);

}
```

```
#include<stdio.h>
int test()
{
static int n = 10;
return n--;
}
int main()
{
for(test(); test(); test())
printf("%d ", test());
return 0;
}
```

- ☐ 7 4 1
- ☐ Infinite loop
- ☐ Compilation Error
- ☒ 8 5 2

```
#include<stdio.h>
int main()
{
extern int i;
i = 20;
printf("%d\n", sizeof(i));
return 0;
}
```

- ☐ 1
- ☐ 4
- ☐ 20
- ☒ Linker Error

```
#include<stdio.h>
int main()
{
    char smile = 200;
    smile = smile - 8 * 4 ;
    printf("%d \n", smile);
    return 0;
}
```

```
#include<stdio.h>
int main(){
//data file content --> 12345 abcd
    char k,i=3,s[10];
    FILE *fp;
    fp=fopen("data","r");
    while(k=fgetc(fp),--i);
    printf("%d\n",k);
    fscanf(fp,"%s",s);
    printf("%s\n",s);
    return 0;
}
```

- ☐ 123 45
- ☐ error
- ☐ 50 345
- ☐ 51 45


```
main(){  
printf("%d", printf("tips""traps"));  
}
```

- ☐ tipstraps9
- ☐ 9tipstraps
- ☐ tips
- ☐ traps

What is the output of below code ?

```
#include<stdio.h>
#define sq(x) x*x
main()
{
    int i;
    i=64/sq(4);
    printf("%d\n",i);
}
```

What is the type of variable f2 and p2 in the following declaration?

```
#define floatptr float *  
#define intptr int *  
  
floatptr f1,f2;  
intptr p1,p2;
```

- ☒ Float *, int *
- ☐ float, int
- ☐ Compiler Error
- ☐ None of the above

```
#include<stdio.h>
int main(){
    int i=0xa,j='a';
    int *p=&i,*q=&j;
    *p+=*q;
    printf("%d\n",*p);
    return 0;
}
```

```
#include<stdio.h>
main()
{
    struct ABC
    {
        int abc:2;
    }KK;
    KK.abc=3;
    printf("%d\n",KK.abc);
}
```

- ☐ 2
- ☒ -1
- ☐ 3
- ☐ -3

What is the default storage class for function?

- ☐ auto
- ☐ static
- ☒ Extern
- ☐ register

The typedef statement is used to

- ☐ create a new data type
- ☒ rename the existing data type
- ☐ to define a storage class
- ☐ create a structure

```
#include<stdio.h>
int main(){
short int i=32;
if(i&(i-1) ==0)
printf("power\n");
printf("star \n");
return 0;
}
```

- ☐ power
- ☐ star
- ☐ power star
- ☐ error


```
#include<stdio.h>
#define x 10;
int main()
{
    printf("%d",x);

}
```

The function call `fseek( fp,0,0);` is same as

- ☐ `fp=fopen()`
- ☐ `rewind(fp);`
- ☐ `fclose(fp)`
- ☐ `ftell(fp);`

```
#include<stdio.h>
#include<stdlib.h>
void *DMA();
int main(){
int *p=DMA();
*p=*p+3;
printf("%d \n",*p);
return 0;
}
void *DMA(){
return calloc(1,4);
}
```

```
#include<stdio.h>
struct vector
{
    int id;
    char name[8];
    struct vector *z;
};
void main()
{
    struct vector p[2]={{31,"coding",&p[1]},
                        {51,"sirji",&p[0]}};
    printf("%c \n",(*p[0].name)+4);
}
```

```
#include<stdio.h>
#define coding float
typedef int sirji;

int main(){
    union u{
        sirji a;
        char b;
    }u1={513};
    struct s{
        sirji a;
        char b;
    }s1={500};
    coding f1=s1.a-u1.b;
    printf("%.3f\n",f1);
    return 0;
}
```

```
#include<stdio.h>
#define GURUJI(a,b) a%b
#define SIRJI printf
int main(){
    SIRJI("%d \n",GURUJI(1+'A',0+'A'));
    return 0;
}
```

```
struct st
{
    int x;
    int y;
};
main()
{
    struct st *p={10,20};
    printf("%d %d",p->x,p->y);
}
```

```
main ( )  
{  
    static char *s[ ] = {"black", "white",  
"yellow", "violet"};  
    char **ptr[ ] = {s+3, s+2, s+1, s}, ***p;  
    p = ptr;  
    **++p;  
    printf("%s",*--*++p + 3);  
}
```



```
#include<stdio.h>
struct dir{
    int d,m;
    char n[10];
}*p;
int main(){
    struct dir vec={19,05,"raju"};
    p=&vec;
    printf("%d \n",p->m>>1);
    vec.d=p->m;
    printf("%c \n",p->n[1]+1);
    return 0;
}
```

- ☐ 2 b
- ☐ error
- ☐ 5 j
- ☐ 2 a

```
#include<stdio.h>
int main(){
    int i=0xa,j='a';
    int *p=&i,*q=&j;
    *p+=*q;
    printf("%d\n",*p);
    return 0;
}
```

```
#include<stdio.h>
#define coding float
typedef int sirji;

int main(){
    union u{
        sirji a;
        char b;
    }u1={513};
    struct s{
        sirji a;
        char b;
    }s1={500};
    coding f1=s1.a-u1.b;
    printf("%.3f\n",f1);
    return 0;
}
```

```
#include<stdio.h>
int fun(int,int *,int *,int **);
int main(){
    int a=100;
    int *p=&a;
    fun(a,&a,p,&p);
    printf("%d \n",*p);
}
int fun(int a,int *p,int *q,int **pp){
    a=a+10;
    *p=*p+20;
    printf("%d \n", *p);
    *q=*q+30;
    printf("%d \n", *q);
    **pp=**pp+40;
}
```

- ☐ 120 150 190
- ☐ error
- ☒ 130 160 200
- ☐ 120 160 190

```
#include<stdio.h>
int main()
{
    printf("12345\babc\rGSM\n");
}
```