

Find the output for the following programs

```
1.#include<iostream>
using namespace std;
main()
{
    int i=10;
    int &r=i;
    r++;
    int *p=&i;
    p++;
    cout << "i="<< i <<"r="<< r << endl;
}
```

```
2.#include<iostream>
using namespace std;
int i=20;
main()
{
    int i=5;
    cout<<i<<::i<<endl;    // 5 20
    {
        int i=10;
        cout<<i<<::i<<endl;    10 20
    }
}
```

```
3.#include<iostream>
using namespace std;
class abc
{
    int x,y;
public:
    void set_data(int a,int b)
    {
        x=a,y=b;
    }
};
main()
{
    set_data(10,20);    error due to the without object you cant call any member function
}
```

```
4.#include<iostream>
using namespace std;
class ab
{
    int x,y;
public:
    void set_data(int a,int b)
    {
        x=a,y=b;
    }
}
```

```

    }
};
main()
{
    ab n;
    n.set_data(10,20,30);
}

```

Error -> argument mismatch

```

5.#include<iostream>
using namespace std;
class def
{
    int x,y;
    public:
    void set_data(int a,int b)
    {
        x=a,y=b;
    }
};
main()
{
    def *n;
    n.set_data(10,20);
}

```

Error due to dma is not allocate for n pointer
to access member function must should use (->)operator

```

6.#include<iostream>
using namespace std;
class A
{
    int x,y;
    public:
    void set_data(int a,int b)
    {
        x=a,y=b;
    }
};
main()
{
    A n;
    n.a(10,20);
}

```

10 20

```

7.#include<iostream>
using namespace std;
class Test
{
    static int count;
    public:
    static void get_data()
    {

```

```

        count++;
    }
};
int Test::count=1;
main()
{
    Test t;
    t.get_data();
}

```

```

8.#include<iostream>
using namespace std;
class sample
{
public:
    void set_data(char c)
    {
        ch=c;
    }
    void get_data()
    {
        cout<<a<<ch<<endl;
    }
private:
    int a;
    char ch;
};
main()
{
    sample s;
    s.set_data('A');
    s.get_data();
}

```

a=garbadge value ,ch= A

```

9.#include<iostream>
using namespace std;
class sample
{
public:
    void set_data(char c);
    void get_data();
private:
    int a=10;
    char ch;
};
void sample::set_data(char c)
{

```

```

        ch=c;
    }
    void sample::get_data()
    {
        cout<<a<<ch<<endl;    a=10 ,ch= A
    }

```

```

main()
{
    sample s;
    s.set_data('A');
    s.get_data();
}

```

```

10.#include<iostream>
using namespace std;
class Test
{
private:
    static int count;
public:
    static void get_data()
    {
        count++;
    }
};
main()
{
    Test t;
    t.get_data();
}

```

Error -> (int Test::count need) to use

```

11.#include<iostream>
using namespace std;
int main()
{
    int x = 5;
    if(x==5)
    {
        if(x==5) break;
        cout<<"Hello";
    }
    cout<<"Hi";
}

```

Error -> break is not in loop
break sholud not be use in if control statement

```

12.#include<iostream>
using namespace std;
int main()
{

```

```

class student {
    int rno =10;
    } v;
    cout<<v.rno;
}

```

Error -> rno is in private section

```

13.#include <iostream>
using namespace std;
namespace first
{
    int var = 5;
}
namespace second
{
    double var = 3.1416;
}
int main ()
{
    int a;
    a = first::var + second::var;
    cout << a;
}

```

8

```

14.#include <iostream>
using namespace std;
int main()
{
    const int i = 20;
    const int* const ptr = &i;
    (*ptr)++; // Error -> read only variable trying to modify
    int j = 15;
    ptr = &j; // Error -> raed only constante pointer trying to modify
    cout << i;
}

```

```

15.#include <iostream>
using namespace std;
int main()
{
    int arr[] = { 4, 5, 6, 7 };
    int* p = (arr + 1);
    cout << *arr + 10;
}

```

14

```

16.#include <iostream>
using namespace std;

```

```
int main()
{
    int a = 10, *pa, &ra;
    pa = &a;
    ra = a;
    cout << "a=" << ra;
    return 0;
}
```

```
17.#include<cstdio>
int main()
{
    int a = 35;
    int b = 12;
    printf("%d ", ~a);           -36
    printf("%d ", ~ - b);       11 --> ~(-12)
}
```

```
18.#include <iostream>
using namespace std;
int main()
{
    char ch='A';
    void *ptr1=&ch;
    char *ptr2;
    ptr2 = ptr1;   Error -> typecast is mandatory for void pointer
    cout << ptr2 << " " << ptr1 << endl;   Error -> type cast needed while printing void pointer
}
```

```
19.#include <iostream>
using namespace std;
int main()
{
    int i;
    i = 1 + (1,4,5,6,3);
    cout << i;   4 -> in comma operator evalutes L->R and tekes right most value which is 3
}
```

```
20#include<iostream>
using namespace std;
class ab
{
    int x,y;
public:
    void set_data(int x, int y)
    {
        x=x,y=y;
    }
};
main()                                     if print the answer will be -> 10 20
```

```
{  
    ab n;  
    n.set_data(10,20);  
}
```

21.#include <iostream>

using namespace std;

int main()

{

int a = b = c = 0;

cout << a << " " << b << " " << c;

}

Error -> b and c is not declared