

## **EXPERIMENT NO.7 : JOIN OR CARTESIAN PRODUCT**

/\*1.Give name of customers having living city BOMBAY and branch city NAGPUR\*/

```
SELECT D1.CNAME,D1.BNAME,C1.CNAME,C1.CITY,B1.CITY,B1.BNAME FROM DEPOSIT D1,CUSTOMER C1,BRANCH B1 WHERE C1.CITY = 'BOMBAY' AND B1.CITY = 'NAGPUR' AND D1.CNAME = C1.CNAME AND D1.BNAME = B1.BNAME;
```

/\*2.Give names of customers having the same living city as their branch city\*/

```
SELECT distinct(customer.CNAME), BRANCH.CITY FROM BRANCH, customer WHERE BRANCH.city = customer.city;
```

/\*3.Give names of customers who are borrowers as well as depositors and having city NAGPUR.\*/

```
SELECT C1.CNAME FROM CUSTOMER C1,DEPOSIT D1,BORROW B1 WHERE C1.CITY='NAGPUR' AND C1.CNAME=D1.CNAME AND D1.CNAME = B1.CNAME;
```

/\*4.Give names of borrowers having deposit amount greater than 1000 and loan amount greater than 2000.\*/

```
SELECT BR1.CNAME, BR1.AMOUNT, D1.CNAME, D1.AMOUNT FROM BORROW BR1,DEPOSIT D1 WHERE D1.CNAME = BR1.CNAME AND D1.AMOUNT > 1000 AND BR1.AMOUNT > 2000;
```

/\*5.Give names of depositors having the same branch as the branch of Sunil\*/

```
SELECT D1.CNAME FROM DEPOSIT D1 WHERE D1.BNAME IN (SELECT D2.BNAME FROM DEPOSIT D2 WHERE D2.CNAME = 'SUNIL');
```

/\*6.Give names of borrowers having loan amount greater than the loan amount of Pramod\*/

```
SELECT BR1.CNAME,BR1.AMOUNT FROM BORROW BR1 WHERE BR1.AMOUNT > ALL (SELECT BR2.AMOUNT FROM BORROW BR2 WHERE BR2.CNAME = 'PRAMOD');
```

/\*7.Give the name of the customer living in the city where branch of depositor Sunil is located.\*/

```
SELECT C.CNAME FROM CUSTOMER C WHERE C.CITY IN (SELECT B.CITY FROM BRANCH B WHERE B.BNAME IN (SELECT D.BNAME FROM DEPOSIT D WHERE D.CNAME='SUNIL'));
```

/\*8.Give branch city and living city of Pramod\*/

```
SELECT B1.CITY , C1.CITY FROM BRANCH B1,CUSTOMER C1, DEPOSIT D1 WHERE C1.CNAME = 'PRAMOD'  
AND C1.CNAME = D1.CNAME AND D1.BNAME = B1.BNAME;
```

/\*9.Give branch city of Sunil and branch city of Anil\*/

```
SELECT B1.CITY FROM DEPOSIT D1, BRANCH B1 WHERE D1.BNAME = B1.BNAME AND D1.CNAME IN  
('SUNIL' , 'ANIL');
```

/\*10.Give the living city of Anil and the living city of Sunil\*/

```
SELECT C1.CNAME, C1.CITY FROM CUSTOMER C1 WHERE C1.CNAME = 'ANIL' OR C1.CNAME = 'SUNIL';
```