

GE23131-Programming Using C-2024

Quiz navigation

1

2

3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Saturday, 30 November 2024, 6:23 PM
Duration	22 days 23 hours

Question 1

Correct

Marked out of 3.00

Flag question

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.
The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Input:

2
3

Output:

WBW

BWB

WBW

WBWBW

BWBWB

WBWBW

BWBWB

WBWBW

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t,d,i=0,i1,i2,o;
5     char c;
6     scanf("%d",&t);
7     while(i<t)
8     {
9         scanf("%d",&d);
10        i1=0;
11        while(i1<d)
12        {
13            o=1;
14            i2=0;
15            if(i1%2==0)
16            {
17                o=0;
18            }
19            while(i2<d)
20            {
21                i2=i2+1;
22                if(i2%2==0)
23                {
24                    o=1;
25                }
26                else
27                {
28                    o=0;
29                }
30                i2=i2+1;
31            }
32            i1=i1+1;
33        }
34        printf("%d\n",o);
35        i=i+1;
36    }
37    return 0;
38 }
```

```
24  c='W';
25  }
26  printf("%c",c);
27  i2++;
28  }
29  i1+=1;
30  printf("\n");
31  }
32  i=i+1;
33
34  }
35  return 0;
36  }
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
```

	Input	Expected	Got	
✓	2	WBW	WBW	✓
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	

Passed all tests! ✓

Question **2**

Correct

Marked out of
5.00

🚩 [Flag
question](#)

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:

2

2 W

3 B

Output:

BW

BWB

WBW

BWB

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int T,d,i,i1,i2,o,z;
5      char c,s;
6      scanf("%d",&T);
7      for(i=0;i<T;i++)
8      {
9          scanf("%d %c",&d,&s);
10         for(i1=0;i1<d;i1++)
11         {
12             z=(s=='W')?0:1;
13             o=(i1%2==z)?0:1;
14             for(i2=0;i2<d;i2++)
15             {
16                 c=(i2%2==o)?'W':'B';
17                 printf("%c",c);
18             }
19             printf("\n");
20         }
21     }
22     return 0;
23 }
```

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	
		BWB	BWB	

Passed all tests! ✓

Question **3**

Correct

Marked out of
7.00

🚩 [Flag
question](#)

Decode the logic and print the Pattern that corresponds to given input.

If N= 3

then pattern will be :

10203010011012

**4050809

****607

If N= 4, then pattern will be:

1020304017018019020

**50607014015016

****809012013

Constraints

$2 \leq N \leq 100$

Input Format

First line contains T, the number of test cases

Each test case contains a single integer N

Output

First line print Case #i where i is the test case number

In the subsequent line, print the pattern

Test Case 1

- 3
- 3
- 4
- 5

Output

Case #1

****607

Case #2

1020304017018019020

**50607014015016

****809012013

*****10011

Case #3

102030405026027028029030

**6070809022023024025

****10011012019020021

*****13014017018

*****15016

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main()
3  {
4      int n,v,p3,c,in,i,i1,i2,t,ti;
5      scanf("%d",&t);
6      for(ti=0;ti<t;ti++)
7      {
8          v=0;
9          scanf("%d",&n);
10         printf("Case #%d\n",ti+1);
11         for(i=0;i<n;i++)
12         {
13             c=0;
14             if(i>0)
15             {
16                 for(i1=0;i1<i;i1++) printf("**");
17             }

```

```
21         printf("%d", ++v);
22     }
23     if(i==0)
24     {
25         p3=v+(v*(v-1))+1;
26         in=p3;
27     }
28     in=in-c;
29     p3=in;
30     for(i2=i; i2<n; i2++)
31     {
32         printf("%d", p3++);
33         if(i2!=n-1) printf(" ");
34     }
35     printf("\n");
36 }
37
38 return 0;
39 }
40
41
42
43
44
45
46
47
48
```

	Input	Expected	Got	
✓	3	Case #1	Case #1	✓
	3	10203010011012	10203010011012	
	4	**4050809	**4050809	
	5	****607	****607	

*****809012013
*****10011
Case #3
102030405026027028029030
**6070809022023024025
***10011012019020021
*****13014017018
*****15016

*****809012013
*****10011
Case #3
102030405026027028029030
**6070809022023024025
***10011012019020021
*****13014017018
*****15016

Passed all tests! ✓

Finish review