



Vijayaragavan S 251801381-2025-AIDS ▾

V2

Started on	Tuesday, 15 September 2026, 9:19 AM
State	Finished
Completed on	Tuesday, 15 September 2026, 9:24 AM
Time taken	4 mins 50 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than $\lfloor n / 2 \rfloor$ times. You may assume that the majority element always exists in the array.

Example 1:

Input: `nums = [3,2,3]`

Output: 3

Example 2:

Input: `nums = [2,2,1,1,1,2,2]`

Output: 2

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 104`
- `-231 <= nums[i] <= 231 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  int main() {
3      int n;
4      if (scanf("%d", &n) != 1) return 0;
5      int candidate = 0, count = 0;
6      for (int i = 0; i < n; i++) {
7          int num;
8          scanf("%d", &num);
9          if (count == 0) {
10             candidate = num;
11             count = 1;
12         } else if (num == candidate) {
13             count++;
14         } else {
15             count--;
16         }
17     }
18     printf("%d\n", candidate);
19     return 0;
20 }
```

	Input	Expected	Got	
✓	3	3	3	✓
	3 2 3			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Back to Course