



Started on	Monday, 24 August 2026, 11:05 PM
State	Finished
Completed on	Monday, 24 August 2026, 11:06 PM
Time taken	48 secs
Marks	1.00/1.00
Grade	10.00 out of 10.00 (100%)

Question 1 | Correct | Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is $\text{SUM}(A[i] * B[i])$ for all `i` is minimum.

For example:

Input	Result
3	28
1	
2	
3	
4	
5	
6	

Answer: (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3
4  int cmp_asc(const void *a, const void *b) {
5      long long x = *(const long long *)a;
6      long long y = *(const long long *)b;
7      if (x > y) return 1;
8      if (x < y) return -1;
9      return 0;
10 }
11
12 int cmp_desc(const void *a, const void *b) {
13     long long x = *(const long long *)a;
14     long long y = *(const long long *)b;
15     if (x < y) return 1;
16     if (x > y) return -1;
17     return 0;
18 }
19
20 int main() {
21     int n;
22     if (scanf("%d", &n) != 1) return 0;
23
24     long long *a = (long long *)malloc(n * sizeof(long long));
25     long long *b = (long long *)malloc(n * sizeof(long long));
26
27     for (int i = 0; i < n; i++) {
28         scanf("%lld", &a[i]);
29     }
30     for (int i = 0; i < n; i++) {
31         scanf("%lld", &b[i]);
32     }
33
34     qsort(a, n, sizeof(long long), cmp_asc);
35     qsort(b, n, sizeof(long long), cmp_desc);
36
37     long long min_sum = 0;
38     for (int i = 0; i < n; i++) {
39         min_sum += a[i] * b[i];
40     }
41
42     printf("%lld\n", min_sum);
43
44     free(a);
45     free(b);
46     return 0;
47 }
```

	Input	Expected	Got	
✓	3 1 2 3 4 5 6	28	28	✓
✓	4 7 5 1 2 1 3 4 1	22	22	✓
✓	5 20 10 30 10 40 8 9 4 3 10	590	590	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Back to Course