Status	Finished
Started	Tuesday, 20 October 2026, 3:21 PM
Completed	Tuesday, 20 October 2026, 3:26 PM
Duration	4 mins 30 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

a. True

b. Error

c. Error

d. False ✓

Question **2**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

a. <class 'str'> ✓

b. <class 'tuple'>

c. str

d. <class 'int'>

Question **3**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {2,5,3,1}

b. {}

c. {2,5,1}

d. {3} ✓

Question **4**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. A tuple is unordered

b. A tuple maintains the order of items ✓

c. None of these

d. We can change the tuple once created

Question **5**

Correct

Mark 1.00 out of 1.00

Select all the correct options to remove “ECE” from the set.

```
sampleSet = {"ECE", "R&A", "MCT"}
```

a. del.sampleSet("ECE")

b. sampleSet.delete("ECE")

c. remove.sampleSet("ECE")

d. sampleSet.discard("ECE") ✓

Question **6**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. True ✓

b. False

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

```
t1=(55,12,78,64,25)
t1.pop(12)
print(tuple1)
```

a. 12

b. (12)

c. (55,78,64,25)

d. Error ✓

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, 10, '10', 50, 20, 60, 30} ✓

b. {40, 10, 50, 20, 60, 30}

c. {40, '10', 50, 20, 60, 30}

d. SynatxError: Different types cannot be used with sets

Question **9**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl= (5,2,7,0,3)?

a. tupl.append(2)

b. tupl[1]=2

c. tupl.sort()

d. tupl1=tupl+tupl ✓

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following is a Python tuple?

a. ("Wonder")

b. [1,2,3,4]

c. {1,3,8,9,41}

d. (1,4,5,6,7) ✓

Question **11**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. [1, 2, 4, 3, 8, 9]
b. (1, 4, 8)
c. [1, 4, 8] ✓
d. [2, 3, 9]

Question **12**

Correct

Mark 1.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['2', '3', '8', '30']
b. ['2', '3', '30', '8']
c. ['8', '30', '3', '2'] ✓
d. ['30', '8', '3', '2']

Question **13**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. {0,9} ✓

b. It will throw an error as there are two 0 while creating the set.

c. {9}

d. {0,0,9}

Question **14**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t = (11, 3)
x = 3 * t
print(x)
```

a. (11, 3, 11, 3, 11, 3) ✓

b. (11,3)(11,3)(11,3)

c. [11,11,11,3,3,3]

d. (11,3,11,11,3,11,11,11,3)

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
my_t1 = (1, 2, 3, 4)
my_t1.append( (5, 6, 7) )
print(len(my_t1))
```

a. 2

b. 5

c. Error ✓

d. 1