

DeployPilot AI - InfraAudit Report

Generated: May 21, 2026 09:32 UTC

Project: Manual Scans

Scan Date: May 21, 2026 09:08

Status: COMPLETED

Risk Score

69 / 100

Summary

Total Findings: 9 | Critical: 1 | High: 2 | Medium: 5 | Low: 1

Findings (9)

[CRITICAL] Container Running as Root

File: manual_input.kubernetes:9

securityContext.runAsNonRoot is not set to true. Containers running as root pose a significant security risk.

Fix: Add securityContext.runAsNonRoot: true to the pod or container spec.

Framework: CIS-K8S-1.8

[HIGH] Missing Resource Limits

File: manual_input.kubernetes:9

Container does not define CPU/memory resource limits. This can lead to resource exhaustion and noisy neighbor issues.

Fix: Add resources.limits and resources.requests with appropriate CPU and memory values.

Framework: CIS-K8S-1.8

[HIGH] Privilege Escalation Not Disabled

File: manual_input.kubernetes:1

allowPrivilegeEscalation is not explicitly set to false, allowing potential privilege escalation.

Fix: Set securityContext.allowPrivilegeEscalation: false on all containers.

Framework: CIS-K8S-1.8

[MEDIUM] Missing Liveness Probe

File: manual_input.kubernetes:9

No liveness probe configured. Kubernetes cannot detect if the application is in a broken state.

Fix: Add a livenessProbe with appropriate httpGet, tcpSocket, or exec check.

Framework: CIS-K8S-1.8

[MEDIUM] Missing Readiness Probe

File: manual_input.kubernetes:9

No readiness probe configured. Traffic may be sent to pods that are not ready to serve.

Fix: Add a readinessProbe to ensure traffic is only routed to healthy pods.

Framework: CIS-K8S-1.8

DeployPilot AI - InfraAudit Report

Generated: May 21, 2026 09:32 UTC

[MEDIUM] Using :latest Image Tag

File: manual_input.kubernetes:11

Image uses :latest tag which is mutable and can lead to unexpected deployments.

Fix: Pin images to specific versions or SHA digests for reproducible deployments.

Framework: CIS-K8S-1.8

[MEDIUM] No NetworkPolicy Defined

File: manual_input.kubernetes:1

No NetworkPolicy found. All pods can communicate freely without network segmentation.

Fix: Define NetworkPolicy resources to restrict pod-to-pod communication.

Framework: CIS-K8S-1.8

[MEDIUM] Writable Root Filesystem

File: manual_input.kubernetes:1

Root filesystem is not set to read-only, allowing potential file system modifications by attackers.

Fix: Set securityContext.readOnlyRootFilesystem: true and use emptyDir volumes for writable paths.

Framework: CIS-K8S-1.8

[LOW] No Namespace Specified

File: manual_input.kubernetes:1

Resource does not specify a namespace, will be deployed to the default namespace.

Fix: Specify a namespace in metadata to organize resources and apply RBAC policies.

Framework: CIS-K8S-1.8
