RAJALAKSHMI ENGINEERING COLLEGE

Vijay Karthick S 251001301-2025-IT

V2

Started on	Wednesday, 7 October 2026, 9:08 AM
State	Finished
Completed on	Wednesday, 7 October 2026, 9:09 AM
Time taken	58 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare_asc(const void *a, const void *b) {
    long long diff = (*(long long*)a - *(long long*)b);
    return (diff > 0) - (diff < 0);
}

int compare_desc(const void *a, const void *b) {
    long long diff = (*(long long*)b - *(long long*)a);
    return (diff > 0) - (diff < 0);
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) {
        return 0;
    }

    long long *array_One = (long long*)malloc(n * sizeof(long long));
    for (int i = 0; i < n; i++) {
        if (scanf("%lld", &array_One[i]) != 1) {
            free(array_One);
            return 0;
        }
    }

    long long *array_Two = (long long*)malloc(n * sizeof(long long));
    for (int i = 0; i < n; i++) {
        if (scanf("%lld", &array_Two[i]) != 1) {
            free(array_One);
            free(array_Two);
            return 0;
        }
    }

    qsort(array_One, n, sizeof(long long), compare_asc);
    qsort(array_Two, n, sizeof(long long), compare_desc);

    long long min_sum = 0;
    for (int i = 0; i < n; i++) {
        min_sum += array_One[i] * array_Two[i];
    }

    printf("%lld\n", min_sum);

    free(array_One);
    free(array_Two);
```

```
49      return 0;
50  }
51
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course