ML Implementations Vijay Kumar Mishra

Machine Learning

Digits Data Set – Semi Supervised KNNC

Use the digits dataset available under SKLearn.

Consider the data corresponding to classes 0 and 1 only. Each pattern is a 8×8 sized character where each

value is an integer in the range 0 to 16. Convert it into a binary form by replacing a value below 8 by 0 and other values (\geq 8) by 1. Use this binary data in the following tasks

Use 20 patterns from each class with labels and the remaining without the labels for this subtask. Use the *KNNC* and label the patterns without labels. Obtain the % classification accuracy. Perform this task with K values in the set {1, 3, 5, 10, 20}

CODE:

Please find the code attached for KNNC:

- The digits dataset for class 0 and class 1 only are considered and the data values are converted to value 0 or 1 as defined in problem statement above.
- Train and Test split is done and KNNC is applied over the dataset and accuracy is found.
- KNNC is applied for different values of K like 1,3,5,10 and 20.
- Average accuracy is calculated over 10 random iterations

RESULT:

Average Accuracy of 10 iteration is

Average Accuracy for n_neigbours= 1 : 0.999375

Average Accuracy for n_neigbours= 3: 0.9971875000000001 Average Accuracy for n_neigbours= 5: 0.9956250000000001

Average Accuracy for n_neigbours= 10: 0.99 Average Accuracy for n_neigbours= 20: 0.98125

INFERENCE/ANALYSIS:

- The average accuracy is least for 20 neighbors. This shows that when all test data is considered in the neighbor set, then accuracy of classifying this data gets lower when compared to other values of nearest neighbors.
- With smaller smaller values of K (1,3,5) we are seeing relatively higher accuracy which is in line with our understanding of KNNC.
- The overall KNNC gives a high accuracy for this dataset in semi supervised learning scenario.

RESOURCES USED FOR THE ASSIGNMENT:

Environment:

Anaconda, Jupyter notebook

• Software:

Python

Python libraries/modules: Pandas, Numpy, SkLearn etc