

QueryMind AI

Frontend UI Test Guide

Step-by-step test cases for every screen — what to click, what to enter, and what to verify

App URL	http://localhost:3000
API URL	http://localhost:8000
Screens	6 screens — Query · Schema · Examples · Logs · Guardrails · Model Config
Test cases	50+ step-by-step UI tests
Version	1.0
Prepared by	QueryMind QA

Pre-Flight Checklist

Complete every item below before starting any UI test. If any service is not running, the UI will show blank screens or network errors.

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Open Docker Desktop — confirm the whale icon is in your menu bar	Docker Desktop shows 'Engine running'	☐ Pass ☐ Fail	
2	Run: <code>docker compose ps</code> in the project root	Both <code>querymind-postgres-1</code> and <code>querymind-qdrant-1</code> show STATUS = Up (healthy)	☐ Pass ☐ Fail	
3	Run: <code>curl http://localhost:6333/healthz</code>	Response: healthz check passed	☐ Pass ☐ Fail	
4	Verify backend is running at <code>http://localhost:8000/health</code>	Response: <code>{"status":"ok","service":"QueryMind AI"}</code>	☐ Pass ☐ Fail	
5	Open <code>http://localhost:3000</code> in browser	Page loads — dark sidebar visible on left, content on right	☐ Pass ☐ Fail	
6	Confirm <code>backend/.env</code> has a real <code>OPENAI_API_KEY</code> (not <code>sk-...</code>)	Key starts with <code>sk-proj-</code> or <code>sk-</code> and is not the placeholder	☐ Pass ☐ Fail	
7	Confirm database is seeded — open DBeaver and run: <code>SELECT COUNT(*) FROM customers</code>	Count = 1000	☐ Pass ☐ Fail	Run <code>seed_db.py</code> if empty

Sidebar Navigation

The sidebar is present on every page. It contains the app logo, six navigation links, and a version badge. Test it first since it is used on every subsequent screen.

Location	Left edge of every page — dark navy background
Logo	Lightning bolt ⚡ icon + 'QueryMind AI' text
Nav items	Query · Schema · Examples · Logs · Guardrails · Model Config
Active item	Highlighted with sky-blue background
Version	v0.1.0 badge at the bottom

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Open http://localhost:3000	Redirected to /query page. Sidebar visible with 'Query' nav item highlighted in blue	☐ Pass ☐ Fail	
2	Click 'Schema' in sidebar	URL changes to /admin/schema. Schema nav item highlighted. Page title 'Schema Manager' appears	☐ Pass ☐ Fail	
3	Click 'Examples' in sidebar	URL changes to /admin/examples. Examples nav item highlighted	☐ Pass ☐ Fail	
4	Click 'Logs' in sidebar	URL changes to /admin/logs. Logs nav item highlighted	☐ Pass ☐ Fail	
5	Click 'Guardrails' in sidebar	URL changes to /admin/guardrails. Guardrails nav item highlighted	☐ Pass ☐ Fail	
6	Click 'Model Config' in sidebar	URL changes to /admin/config. Model Config nav item highlighted	☐ Pass ☐ Fail	
7	Click 'Query' in sidebar to return	URL changes back to /query. Query nav item highlighted	☐ Pass ☐ Fail	
8	Resize browser window to narrow width	Sidebar remains visible and functional	☐ Pass ☐ Fail	

Screen 1 — Query

 **Query Interface**
URL: <http://localhost:3000/query>

The main user-facing screen. Displays a chat-style interface where users type natural language questions and receive SQL results with a plain-English summary.

UI Elements

Header	Title 'Query' + subtitle 'Ask any question in plain English'
Empty state	Center message: 'Ask anything about your data' with a sample question hint
Input box	Text field with placeholder 'Ask a question about your data...'
Send button	Sky-blue button with arrow icon — disabled when input is empty or loading
User bubble	Right-aligned, sky-blue background — shows your question
Answer bubble	Left-aligned, white card — shows NL summary + stats bar + result table
Stats bar	Row count · latency in ms · query type badge (e.g. SELECT_AGGREGATE)
Result table	Paginated to 20 rows max. Column headers from the SQL result
View SQL button	Toggles a dark code block showing the generated SQL
Error bubble	Red card with alert icon — shown when pipeline returns an error
Loading state	Spinner + 'Generating query...' text while waiting for API

Test Cases

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Navigate to /query. Do NOT type anything	Empty state visible: 'Ask anything about your data' hint text in center	☐ Pass ☐ Fail	
2	Check the Send button with empty input	Send button is disabled (opacity 50%) — cannot click	☐ Pass ☐ Fail	
3	Type 'How many customers do we have?' and press Enter	User bubble appears right-aligned in sky-blue. Spinner 'Generating query...' appears	☐ Pass ☐ Fail	
4	Wait for response (~3s)	Answer bubble appears left-aligned. Shows NL summary: 'The total number of customers is 1,000'	☐ Pass ☐ Fail	
5	Check the stats bar under the answer	Shows: '1 rows · ~2600ms · SELECT_AGGREGATE' badge	☐ Pass ☐ Fail	
6	Click 'View SQL' link under the answer	Dark code block expands showing the generated SQL (SELECT COUNT(*) ...)	☐ Pass ☐ Fail	

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
7	Click 'View SQL' again	Code block collapses	☐ Pass ☐ Fail	
8	Type 'What are the top 5 products by revenue?' and press Enter	Second user bubble appears. New answer with a result table showing 5 rows	☐ Pass ☐ Fail	
9	Inspect the result table	Table has correct column headers (name, revenue). Rows display product data	☐ Pass ☐ Fail	
10	Scroll up in the conversation	Previous messages are still visible — conversation history preserved	☐ Pass ☐ Fail	
11	Type 'Show me average order value by customer segment' and press Enter	Answer shows 3 rows (standard, premium, enterprise) with avg_order_value column	☐ Pass ☐ Fail	
12	Type 'List all orders placed in 1990' and press Enter	Answer bubble shows: 'The query returned no results.' Row count = 0	☐ Pass ☐ Fail	
13	Type 'Show me data' (ambiguous question) and press Enter	Red error bubble appears with the pipeline's error/clarification message	☐ Pass ☐ Fail	
14	Type 'What is the capital of France?' and press Enter	Red error bubble — classified as off-topic/invalid	☐ Pass ☐ Fail	
15	Press Enter on empty input	Nothing happens — submission is blocked	☐ Pass ☐ Fail	
16	Type a question and click the blue Send button instead of pressing Enter	Same behaviour as pressing Enter — question submitted	☐ Pass ☐ Fail	

Screen 2 — Schema Manager

 **Schema Manager**
URL: `http://localhost:3000/admin/schema`

Displays the live PostgreSQL schema grouped by table. For each column you can add a description, synonyms, and mark it as sensitive — all of which improve the LLM's SQL accuracy.

UI Elements

Page header	Title 'Schema Manager' + subtitle + Refresh button
Table cards	One card per table — table name in sky-blue mono font + column count
Column table	Columns: Column · Type · Description · Synonyms · Sensitive · Action
Add (+) button	Appears in the Action column for columns with no metadata yet
Edit (pencil)	Appears for columns that already have metadata
Description	Inline text input when editing
Synonyms	Comma-separated list input when editing
Sensitive toggle	Eye / EyeOff icon — red when sensitive, grey when not
Save button	Sky-blue Save button appears only when editing a row

Test Cases

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Navigate to /admin/schema	Loading spinner appears briefly then 7+ table cards load (categories, customers, orders, order_items, products, reviews, suppliers)	☐ Pass ☐ Fail	
2	Inspect the 'orders' table card	Card header shows 'orders' in sky-blue mono + '8 columns'. All 8 columns listed (id, customer_id, status, total_amount, discount_amount, created_at, shipped_at, delivered_at)	☐ Pass ☐ Fail	
3	Click the '+' button on the 'orders / status' row	Row saves with empty metadata. '+' button changes to pencil icon	☐ Pass ☐ Fail	Edit the row next
4	Click the pencil on the 'orders / status' row	Row enters edit mode — Description and Synonyms fields become text inputs. Save button appears	☐ Pass ☐ Fail	
5	Type 'Order lifecycle state. Values: pending, shipped, delivered, cancelled' in Description	Text appears in the Description input field	☐ Pass ☐ Fail	
6	Type 'state, order state, fulfillment status' in Synonyms	Text appears in the Synonyms input field	☐ Pass ☐ Fail	

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
7	Click Save	Row exits edit mode. Description and Synonyms columns now show the entered values. Pencil icon returns	☐ Pass ☐ Fail	
8	Click the '+' button on 'customers / segment'	Row saves. Click pencil → enter Description: 'Customer tier: standard, premium, enterprise' → Synonyms: 'tier, customer type, plan' → Save	☐ Pass ☐ Fail	
9	Click the eye icon (Sensitive toggle) on 'customers / email'	Icon changes to EyeOff (red) — column is now marked sensitive	☐ Pass ☐ Fail	
10	Click the EyeOff icon again	Icon returns to Eye (grey) — sensitive flag cleared	☐ Pass ☐ Fail	
11	Click the Refresh button (top-right)	Page reloads all table data. Saved descriptions are still visible	☐ Pass ☐ Fail	
12	Add description to 'order_items / line_total'	Pencil → Description: 'Computed revenue per line item (quantity x unit_price)' → Save. Appears correctly	☐ Pass ☐ Fail	

Screen 3 — Examples Manager



Examples Manager

URL: <http://localhost:3000/admin/examples>

Manages few-shot (question → SQL) pairs. Each example saved here is automatically embedded and stored in Qdrant for semantic retrieval during query generation.

UI Elements

Page header	Title + Sync Embeddings button + Add Example button
Filter bar	All · SELECT_SIMPLE · SELECT_AGGREGATE · SELECT_JOIN · SELECT_TEMPORAL pills
Example card	Question text · SQL in mono code block · query type badge · Edit + Delete icons
Add/Edit form	Question input · SQL textarea · Query Type dropdown · Save + Cancel buttons
Sync Embeddings	Triggers re-indexing of all examples into Qdrant — shows 'Syncing...' while in progress
Empty state	'No examples yet. Add your first one.' when list is empty
Delete confirm	Browser confirm dialog before deleting

Test Cases — Add Examples

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Navigate to /admin/examples	Page loads. If no examples exist, shows 'No examples yet' message. Filter bar shows 'All (0)'	☐ Pass ☐ Fail	
2	Click 'Add Example' button	Form panel slides open above the list with 'New Example' heading. Question, SQL, and Query Type fields visible	☐ Pass ☐ Fail	
3	Leave all fields empty and click Save	Form submits with empty values. (Note: validation is minimal — rely on API level)	☐ Pass ☐ Fail	Optional improvement
4	Fill in Question: 'How many customers do we have?'	Text appears in the Question input	☐ Pass ☐ Fail	
5	Fill in SQL: 'SELECT COUNT(*) AS total_customers FROM customers'	SQL text appears in the monospace textarea	☐ Pass ☐ Fail	
6	Select Query Type: SELECT_AGGREGATE from dropdown	Dropdown shows SELECT_AGGREGATE selected	☐ Pass ☐ Fail	
7	Click Save	Form closes. New example card appears in the list showing question, SQL, and	☐ Pass ☐ Fail	

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
		SELECT_AGGREGATE badge. Filter pill updates to 'All (1)'		
8	Click 'Add Example' again and add: Question='What are the top 5 products by revenue?' SQL='SELECT p.name, SUM(oi.line_total) AS revenue FROM order_items oi JOIN products p ON p.id = oi.product_id GROUP BY p.name ORDER BY revenue DESC LIMIT 5' Type=SELECT_JOIN	Second example card appears	☐ Pass ☐ Fail	
9	Add example 3: Question='How many orders last month?' SQL='SELECT COUNT(*) FROM orders WHERE created_at >= NOW() - INTERVAL '1 month' Type=SELECT_TEMPORAL	Third card appears. Filter shows 'All (3)'	☐ Pass ☐ Fail	
10	Add example 4: Question='Show total revenue by customer segment' SQL='SELECT c.segment, SUM(o.total_amount) AS revenue FROM orders o JOIN customers c ON c.id = o.customer_id GROUP BY c.segment ORDER BY revenue DESC' Type=SELECT_AGGREGATE	Fourth card appears. Filter shows 'All (4)'	☐ Pass ☐ Fail	

Test Cases — Filter, Edit, Delete, Sync

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
11	Click 'SELECT_AGGREGATE' filter pill	Only 2 examples with type SELECT_AGGREGATE are shown. Pill turns sky-blue	☐ Pass ☐ Fail	
12	Click 'SELECT_JOIN' filter pill	Only 1 JOIN example shown	☐ Pass ☐ Fail	
13	Click 'All' pill	All 4 examples shown again	☐ Pass ☐ Fail	
14	Click the pencil icon on any example	Form opens pre-filled with the example's current question, SQL, and query type. Heading changes to 'Edit Example'	☐ Pass ☐ Fail	
15	Modify the Question text and click Save	Form closes. Card updates with the new question text	☐ Pass ☐ Fail	
16	Click Cancel without saving	Form closes. No changes made	☐ Pass ☐ Fail	
17	Click the trash icon on any example	Browser confirm dialog: 'Delete this example?' appears	☐ Pass ☐ Fail	
18	Click Cancel on the confirm dialog	Dialog dismissed. Example still in list	☐ Pass ☐ Fail	

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
19	Click trash icon again and click OK to confirm	Example card removed from list. Count decreases by 1	☐ Pass ☐ Fail	
20	Click 'Sync Embeddings' button	Button shows 'Syncing...' briefly. Returns to 'Sync Embeddings'. All examples re-indexed in Qdrant	☐ Pass ☐ Fail	
21	Go to http://localhost:6333/dashboard → Collections → few_shot_examples	Point count matches the number of examples in the UI	☐ Pass ☐ Fail	Verify Qdrant sync
22	Run a query on the Query page: 'Which products sold the most?'	Answer is returned. The query benefits from the few-shot examples now in Qdrant	☐ Pass ☐ Fail	

Screen 4 — Query Logs

 **Query Logs**
URL: `http://localhost:3000/admin/logs`

Displays a full audit trail of every query submitted through the system. Supports status filtering and pagination. Each row expands to show the generated SQL or error message.

UI Elements

Page header	Title 'Query Logs' + subtitle 'Full audit log of every query'
Filter pills	All · success · error · blocked
Total count	Right-aligned count label (e.g. '7 total')
Log table	Columns: Time · Question · Type · Status · Rows · Latency · expand icon
Status badge	Green (success) · Red (error) · Yellow (blocked)
Expand row	Chevron icon — click to reveal generated SQL or error message
Pagination	Previous / Page N of M / Next — disabled when at boundaries

Test Cases

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Navigate to /admin/logs	Log table loads. Rows visible for all queries submitted so far. Total count shown top-right	☐ Pass ☐ Fail	
2	Inspect a successful query row	Status badge is green ('success'). Rows column shows the result count. Latency shows e.g. '2608ms'	☐ Pass ☐ Fail	
3	Click the chevron expand button on a success row	Row expands below showing the generated SQL in monospace font	☐ Pass ☐ Fail	
4	Click chevron again	Row collapses	☐ Pass ☐ Fail	
5	Click the 'error' filter pill	Only error rows shown. Status badges are all red. Pill turns sky-blue	☐ Pass ☐ Fail	
6	Click the expand chevron on an error row	Expanded row shows the error_message in red text below the SQL area	☐ Pass ☐ Fail	
7	Click 'success' filter pill	Only green success rows shown	☐ Pass ☐ Fail	
8	Click 'All' filter pill	All rows returned	☐ Pass ☐ Fail	
9	Submit 5+ more queries from the Query page, then return to Logs	New entries appear at top (most recent first). Total count increased	☐ Pass ☐ Fail	

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
10	If total > 20, click 'Next' pagination button	Page 2 loads. Button text shows 'Page 2 of N'. Previous button becomes enabled	☐ Pass ☐ Fail	
11	Click 'Previous'	Returns to page 1. Previous button becomes disabled again	☐ Pass ☐ Fail	
12	Verify the Time column format	Dates shown in locale format e.g. '5/13/2026, 2:36:00 PM'	☐ Pass ☐ Fail	
13	Verify the Type column on a successful query	Shows badge like 'SELECT_AGGREGATE' or 'SELECT_SIMPLE'	☐ Pass ☐ Fail	
14	Check a row from the off-topic query ('capital of France')	Status = error. Type column may be empty. Rows = —. Latency = —	☐ Pass ☐ Fail	

Screen 5 — Guardrails Config

 **Guardrails Config**
URL: `http://localhost:3000/admin/guardrails`

Controls what SQL operations are permitted and caps the maximum result rows. Boolean settings use toggle switches; numeric settings use a number input.

UI Elements

Page header	Title 'Guardrails Config' + subtitle
Config card	White rounded card — one row per guardrail key
Row layout	Shield icon + key name (mono) + description text + control (right side)
Toggle switch	Sky-blue = enabled (true). Grey = disabled (false). Animated transition
Number input	Right-aligned input for max_rows — saves on blur (click away)
Empty state	'No guardrail config found. Make sure the database is seeded.' if empty

Test Cases

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Navigate to /admin/guardrails	Card loads with 6 rows: allow_select (ON), allow_insert (OFF), allow_update (OFF), allow_delete (OFF), max_rows (500), restrict_to_schema (public)	☐ Pass ☐ Fail	
2	Verify allow_select toggle is ON (blue)	Toggle is sky-blue with knob on right side	☐ Pass ☐ Fail	
3	Verify allow_insert, allow_update, allow_delete toggles are OFF (grey)	All three toggles are grey with knob on left side	☐ Pass ☐ Fail	
4	Click the allow_insert toggle	Toggle animates to sky-blue (ON). Changes saved automatically	☐ Pass ☐ Fail	
5	Navigate to Query page and type: 'Add a new customer named Alice'	Query processes (INSERT is now allowed by guardrails). Note what happens	☐ Pass ☐ Fail	Restore after test
6	Return to Guardrails and click allow_insert again	Toggle returns to grey (OFF). INSERT blocked again	☐ Pass ☐ Fail	
7	Click the allow_select toggle to turn it OFF	Toggle goes grey	☐ Pass ☐ Fail	
8	Go to Query page and type: 'How many customers?'	Red error bubble — SELECT is now blocked by guardrails	☐ Pass ☐ Fail	
9	Return to Guardrails — turn allow_select back ON	Toggle returns to sky-blue	☐ Pass ☐ Fail	

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
10	Click the max_rows number input, clear it, type '5', click elsewhere	Value saves (blur event triggers save). Input shows 5	☐ Pass ☐ Fail	
11	Go to Query page and type: 'List all orders'	Result table shows maximum 5 rows even though thousands of orders exist	☐ Pass ☐ Fail	
12	Return to Guardrails — set max_rows back to 500 and click elsewhere	Input shows 500. Limit restored	☐ Pass ☐ Fail	
13	Verify the shield icon appears on each row	Grey shield icon visible to the left of each key name	☐ Pass ☐ Fail	
14	Check the description text under each key	Each key shows a grey description e.g. 'Allow SELECT queries'	☐ Pass ☐ Fail	

Screen 6 — Model Config

 **Model Config**
URL: `http://localhost:3000/admin/config`

Controls the LLM and SQL generation parameters. Dropdown fields (model, dialect) and text/number inputs (temperature, max_tokens). Each field has an individual Save button.

UI Elements

Page header	Title 'Model Config' + subtitle
Config card	White rounded card — one row per config key
Row layout	Settings icon + key name (mono) + description + input + Save button
Dropdown	Select element for 'model' (gpt-4o / gpt-4o-mini / gpt-4-turbo) and 'dialect' (postgresql / mysql / sqlite)
Text input	Free input for 'temperature' and 'max_tokens'
Save button	Sky-blue — disabled when value matches current saved value or while saving
Saving state	Button shows 'Saving...' while the API call is in flight

Test Cases

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Navigate to /admin/config	Card loads with 4 rows: model · temperature · max_tokens · dialect	☐ Pass ☐ Fail	
2	Verify default values	model=gpt-4o, temperature=0.0, max_tokens=1000, dialect=postgresql	☐ Pass ☐ Fail	
3	Check Save button state before making any change	Save button is disabled (opacity 40%) — no unsaved changes	☐ Pass ☐ Fail	
4	Click the model dropdown and change to 'gpt-4o-mini'	Dropdown shows gpt-4o-mini selected. Save button becomes active (blue)	☐ Pass ☐ Fail	
5	Click Save for model	Button shows 'Saving...' briefly then returns to 'Save' (disabled = saved)	☐ Pass ☐ Fail	
6	Change model back to 'gpt-4o' and Save	Restored to default	☐ Pass ☐ Fail	
7	Change temperature input from 0.0 to 0.5 and click Save	Button shows 'Saving...', completes. Run a query — responses may vary slightly	☐ Pass ☐ Fail	
8	Change temperature back to 0.0 and click Save	Restored to default	☐ Pass ☐ Fail	
9	Change max_tokens to 500 and click Save	Saved. Run a very complex query — LLM may now truncate very long SQL	☐ Pass ☐ Fail	

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
10	Change max_tokens back to 1000 and click Save	Restored to default	☐ Pass ☐ Fail	
11	Change dialect to 'mysql' and click Save	Saved. Run a query — note the LLM generates MySQL-flavoured SQL (e.g. LIMIT syntax)	☐ Pass ☐ Fail	
12	Change dialect back to 'postgresql' and click Save	Restored to default	☐ Pass ☐ Fail	
13	Verify the gear icon appears on each row	Grey Settings2 icon visible left of each key name	☐ Pass ☐ Fail	
14	Change a value, then change it back to the original without saving	Save button disables again — UI tracks that the value matches the saved state	☐ Pass ☐ Fail	

End-to-End Journey Test

This section tests the full lifecycle in sequence across all 6 screens in one sitting. Run this after all individual screen tests pass.

GOAL

Demonstrate that the configuration you set in admin screens directly improves query quality on the Query page.

#	Action (what you do)	Expected Result (what you should see)	Pass / Fail	Notes
1	Go to Schema Manager → add description to orders.status: 'Order lifecycle. Values: pending, shipped, delivered, cancelled'	Description saved and visible in the table row	☐ Pass ☐ Fail	
2	Go to Examples Manager → add example: Q='How many delivered orders?' SQL='SELECT COUNT(*) FROM orders WHERE status = 'delivered'' Type=SELECT_AGGREGATE	Example card appears. Count increases to at least 1	☐ Pass ☐ Fail	
3	Click Sync Embeddings	'Syncing...' appears then completes	☐ Pass ☐ Fail	
4	Go to Guardrails → confirm allow_select=ON, max_rows=500	Settings confirmed	☐ Pass ☐ Fail	
5	Go to Model Config → confirm model=gpt-4o, temperature=0.0	Settings confirmed	☐ Pass ☐ Fail	
6	Go to Query page → type: 'How many shipped orders are there?'	Answer returned with a count. Generated SQL uses WHERE status = 'shipped'. Stats bar shows success	☐ Pass ☐ Fail	
7	Click 'View SQL' on the answer	SQL uses the correct 'status' column and 'shipped' value — influenced by the schema description and few-shot example	☐ Pass ☐ Fail	
8	Go to Logs → verify the query appears at the top	Log row shows the question, SELECT_AGGREGATE type, green success badge, row count, and latency	☐ Pass ☐ Fail	
9	Expand the log row	Generated SQL visible — matches or is similar to what was shown in the Query UI	☐ Pass ☐ Fail	
10	Go to Guardrails → set max_rows to 3	Saved	☐ Pass ☐ Fail	
11	Go to Query → type: 'List all products'	Result table shows exactly 3 rows	☐ Pass ☐ Fail	
12	Go to Guardrails → restore max_rows to 500	Restored	☐ Pass ☐ Fail	
13	Go to Examples Manager → delete one example	Card removed. Count decreases	☐ Pass ☐ Fail	
14	Click Sync Embeddings	Qdrant collection now has one fewer point (verify at localhost:6333/dashboard)	☐ Pass ☐ Fail	

Appendix

Quick Reference — All Screen URLs

Query	http://localhost:3000/query
Schema Manager	http://localhost:3000/admin/schema
Examples	http://localhost:3000/admin/examples
Query Logs	http://localhost:3000/admin/logs
Guardrails	http://localhost:3000/admin/guardrails
Model Config	http://localhost:3000/admin/config
API Docs	http://localhost:8000/docs
Qdrant UI	http://localhost:6333/dashboard

Sample Test Queries

How many customers do we have?	Expected: 1 row — total_customers = 1000
What are the top 5 products by revenue?	Expected: 5 rows — product name + revenue
Show average order value by customer segment	Expected: 3 rows — standard / premium / enterprise
How many orders were placed last month?	Expected: 1 row — count
Which suppliers have most out-of-stock products?	Expected: supplier list ordered by out-of-stock count
List all orders placed in 1990	Expected: 0 rows — no data from 1990
Show me data	Expected: error bubble — ambiguous query
What is the capital of France?	Expected: error bubble — off-topic

Known Guardrail Defaults

allow_select	true — read queries allowed
allow_insert	false — write blocked
allow_update	false — write blocked
allow_delete	false — write blocked
max_rows	500
restrict_to_schema	public

Restart Commands

```
# Stop everything
kill $(lsof -ti :8000) 2>/dev/null
kill $(lsof -ti :3000) 2>/dev/null
docker compose down

# Start everything
docker compose up -d
cd backend && uv run uvicorn app.main:app --reload --port 8000
cd frontend && npm run dev
```