Lab Exercise 7- Install Minikube on Linux (Ubuntu /MacOS/Windows)

Install Minikube on macOS

```
brew install minikube

brew install kubectl
```

```
[mohdanas@Mohds-MacBook-Air ~ % brew install minikube                    ]

 ==> Auto-updating Homebrew...
 Adjust how often this is run with `$HOMEBREW_AUTO_UPDATE_SECS` or disable with
 `$HOMEBREW_NO_AUTO_UPDATE=1`. Hide these hints with `$HOMEBREW_NO_ENV_HINTS=1` (see
 `man brew`).
 ==> Auto-updated Homebrew!
 Updated 3 taps (hashicorp/tap, homebrew/core and homebrew/cask).
 ==> New Formulae
 betterleaks: Secrets scanner built for configurability and speed
 cwalk: Cross-platform path library for C/C++
 lld@21: LLVM Project Linker
 llvm@21: Next-gen compiler infrastructure
```

```
[mohdanas@Mohds-MacBook-Air ~ % brew install kubectl
 Warning: kubernetes-cli 1.35.2 is already installed and up-to-date.
 To reinstall 1.35.2, run:
   brew reinstall kubernetes-cli
 mohdanas@Mohds-MacBook-Air ~ %
```

Start:

```
minikube start
```

```
mohdanas@Mohds-MacBook-Air ~ % minikube start
😄  minikube v1.38.1 on Darwin 26.2 (arm64)
✨  Automatically selected the docker driver
❗  Starting v1.39.0, minikube will default to "containerd" container runtime. See #
21973 for more info.
📌  Using Docker Desktop driver with root privileges
👍  Starting "minikube" primary control-plane node in "minikube" cluster
🚜  Pulling base image v0.0.50 ...
💾  Downloading Kubernetes v1.35.1 preload ...
    > preloaded-images-k8s-v18-v1...:  243.95 MiB / 243.95 MiB  100.00% 5.22 Mi
    > gcr.io/k8s-minikube/kicbase...:  483.40 MiB / 483.40 MiB  100.00% 6.05 Mi
🔥  Creating docker container (CPUs=2, Memory=3072MB) ...
❗  Failing to connect to https://registry.k8s.io/ from inside the minikube containe
r
💡  To pull new external images, you may need to configure a proxy: https://minikube
.sigs.k8s.io/docs/reference/networking/proxy/
🐳  Preparing Kubernetes v1.35.1 on Docker 29.2.1 ...
🔗  Configuring bridge CNI (Container Networking Interface) ...
🔎  Verifying Kubernetes components...
    ▪ Using image gcr.io/k8s-minikube/storage-provisioner:v5
🌟  Enabled addons: storage-provisioner, default-storageclass
🏄  Done! kubectl is now configured to use "minikube" cluster and "default" namespac
e by default
mohdanas@Mohds-MacBook-Air ~ %
```

Verify Kubernetes Cluster

```
kubectl get nodes
```

```
mohdanas@Mohds-MacBook-Air ~ % kubectl get nodes
NAME       STATUS   ROLES           AGE   VERSION
minikube   Ready    control-plane   42s   v1.35.1
mohdanas@Mohds-MacBook-Air ~ %
```

Expected output:

NAME STATUS ROLES AGE VERSION

minikube Ready control-plane xx v1.xx

Useful Minikube Commands (Lab Ready)

Command	Purpose
minikube dashboard	Open K8s UI
minikube stop	Stop cluster

Command	Purpose
minikube delete	Delete cluster
minikube ssh	Access node
kubectl get pods -A	View all pods