

Observer DP

I remember growing up with television, from the time it was just a test pattern, with maybe a little bit of programming once in a while. – Francis Ford Coppola

Problem

- Weather information is available via functions:
 - `getTemperature`, `getHumidity` and `getPressure`
- When any weather parameter changes,
 - the `measurementsChanged` function is called.
 - We need to update the display of
 - Temperature. It shows average temp, max temp, min temp.
 - Current conditions.
 - Forecast.
 - Custom plug-in displays.


Dirty Solution

```
public class WhetherData {  
    public void measurementsChanged() {  
        double t = getTemperture();  
        double h = getHumidity();  
        double p = getPressure();  
        tempStatisticsDisplay.update(t, h, p);  
        currentConditionsDisplay.update  
            (t, h, p);  
        forecastDisplay.update(t, h, p);  
        //Call custom displays here.  
    }  
...}
```




Observer Pattern


- When the subject changes state, it notifies the interested Observers.



Better Solution




Observer DP




Graph for Excel cells

observers



Real Life Analog




Uses of Observer pattern

- The Observer pattern is used heavily in JDK
 - In a GUI framework like Swing, we listen for events. The observer pattern is normally used to notify the interested parties about the events.
- On application exit, we want some processing to be done. Multiple exit Listeners can exist.
- In stock market, when a price reaches some level, we want certain actions to be taken.

Examples

- When a customer is added,
 - We need to send a welcome email
 - We need to verify the customer's address
- Also in a rich-client, the GUI thread (EDT) is separate from the Model thread.
 - The Observer can decouple the GUI logic from business Logic
- Real-life Observer Patterns
 - A radio station is broadcasting. Only the radios that are tuned in listen
 - A newspaper is publishing. Subscribers are getting the paper



Replace
hard coded
notifications
by Observer

