

BINARY OPERATOR OVERLOADING

Date: _____

Page No.: _____

B) Notes:

23BAI10917
08 - Nov - 23

a) iostream class :-

* It provides basic input & output services for c++ programs

* Iostream uses the objects cin, cout, cerr and clog for sending the data to and from the standard streams input, output, error (unbuffered), and log (buffered) respectively.

b) istream class :-

* This class provides a wide range of functions for handling, characters, strings and objects, including get, getline, read, ignore, putback and cin.

* These functions enabled developers to manipulate input in various ways.

c) Ostream class :-

* This class is responsible for handling output stream. It provides number of function for handling chars, strings, and objects such as write, put etc.

d) std::cout :-

* It is used printing or providing output inside the double quotes in c++.

eg: `std::cout << "Hello! This is c++!"`

output:

Hello! This is c++!

e) std::cin :-

* This command is used to provide an input to the C++ program.

* It gets input from the user to do specific operations if instructed.

f) std::cerr :-

* It is known as standard error stream (cerr): it is the standard error stream used to output the errors. It is the instance of an ostream class.

g) std::clog :-

* clog is an object of ostream class of C++. It is used for error and event logging purposes. The object is declared in the iostream header.

* It is associated with the stderr, standard error output stream.