

2) (10 pts) ANL (Algorithm Analysis)

(a) (5 pts) An algorithm for searching for a housing contract in a database of n records takes $O(\lg n)$ time. When $n = 2^{20}$, one million searches can be performed in one fifth of a second. If we increase the database to size $n = 2^{25}$, how long will 500,000 searches take?

Let $T(n)$ represent the time one search takes. Thus, $T(n) = c \lg n$, for some constant c . Using the given information, we have:

$$\begin{aligned} 10^6 T(n) &= .2 \text{sec} = 10^6 c \lg(2^{20}) \\ .2 \text{sec} &= 10^6 (20)c \\ c &= 10^{-8} \text{sec} \end{aligned}$$

We are being asked to find $500000T(2^{25})$:

$$\begin{aligned} 500000T(2^{25}) &= 5(10^5)(10^{-8} \text{sec}) \lg(2^{25}) \\ &= 5(10^5)(10^{-8} \text{sec}) 25 \\ &= 125(10^{-3} \text{sec}) \\ &= 125 \text{ms, or } .125 \text{ sec} \end{aligned}$$

Grading: 1 pt setting up valid equation, 2 pts solving for constant, 2 pts for plugging into second part and getting the answer - can be represented in any unit of time, though sec and ms are probably going to be the most common.

(b) (5 pts) A shortest distance algorithm on an $n \times m$ street grid runs in $O(nm)$ time. If the algorithm takes 2 seconds to run on a 4000×3000 sized grid, how long will it take on a grid of size 2000×18000 sized grid?

Let $T(n, m)$ represent the time algorithm takes. Thus, $T(n, m) = cnm$, for some constant c . Using the given information, we have:

$$\begin{aligned} T(4000, 3000) &= 2 \text{sec} = c(4000)(3000) \\ c &= \frac{1}{6} 10^{-6} \text{sec} \end{aligned}$$

Now we solve for $T(2000, 18000)$:

$$T(2000, 18000) = \left(\frac{1}{6} 10^{-6} \text{sec} \right) (2000)(18000) = \frac{36}{6} \text{sec} = 6 \text{sec}$$

Grading: 1 pt setting up valid equation, 2 pts solving for constant, 2 pts for plugging into second part and getting the answer - can be represented in any unit of time, though sec is probably going to be the most common.