

LMJuly18-02 — LaunchMind: Database Schema

Date: July 18, 2026 · Part 2 of 6 **Database:** Supabase Postgres (`gseqtbwdenjkwysregpp`) **Total migrations:** 61 (migrations 001–061) **Rule:** Additive only — never drop/rename/retype columns, never delete tables

Table of Contents

- Migration History Overview
- Core Founder & Product Tables
- Campaign & Metrics Tables
- Content & Learning Tables
- Intelligence & Memory Tables
- AI Platform Tables
- Mission & Agent Tables
- Owner Experience Tables
- Analytics & Reporting Tables
- Infrastructure Tables
- RLS Summary

1. Migration History Overview

Migration		Date	Description
001	2026-05-16	founders table	
002	2026-05-16	products table	
003	2026-05-16	platform_tokens table	
004	2026-05-16	campaigns table	
005	2026-05-16	campaign_metrics table	
006	2026-05-16	weekly_briefs table	
007	2026-05-16	playbook_signals table	
008	2026-05-16	audit_logs table	
009	2026-05-16	embedding_store table	

010	2026-05-17	campaigns unique channel+market constraint
011	2026-05-17	utm_links table
012	2026-05-17	waitlist table
013	2026-05-18	founders.onboarding_step column
014	2026-05-18	founder_feedback table
015	2026-05-18	workspaces table
016	2026-05-18	products.workspace_id column
017	2026-05-18	api_keys table
018	2026-05-18	playbook_signals enrichment (week 14)
019	2026-05-19	seed playbook_signals base (28 rows)
020	2026-05-19	consume_tokens_fn SQL function
021	2026-05-20	campaigns.action column
022	2026-05-23	auto_create_founder_on_signup trigger
023	2026-05-24	products intake v2 (11 new columns)
024	2026-05-24	seed ClientPulse demo product
025	2026-05-25	seed ClientPulse fix (aligned with spec)
026	2026-05-30	content_assets table
027	2026-05-30	content_preferences table
028	2026-05-30	content_learnings table
029	2026-05-30	product_archive columns
030	2026-06-19	products.full_strategy column
031	2026-06-20	video_concept_status column
032	2026-07-08	workspace_members table
033	2026-07-08	products intake v3 columns
034	2026-07-08	integrations_extend table
035	2026-07-08	marketing_memories table
036	2026-07-08	marketing_memory_versions table
037	2026-07-08	knowledge_nodes table
038	2026-07-08	knowledge_edges table
039	2026-07-08	evidence table

040	2026-07-08	learning_events table
041	2026-07-08	prompts table
042	2026-07-08	ai_requests table
043	2026-07-08	seed_prompts (11 initial prompts)
044	2026-07-08	missions table
045	2026-07-08	mission_steps + mission_logs + mission_approvals
046	2026-07-08	saved_opportunities + notifications tables
047	2026-07-08	content_versions (append-only)
048	2026-07-08	asset_approvals (append-only)
049	2026-07-08	publishing_targets table
050	2026-07-08	content_assets_extend (tags, mission_id, 5 new types)
051	2026-07-08	campaigns_extend (type, new statuses, new channels)
052	2026-07-08	experiments + experiment_variants tables
053	2026-07-08	campaign_approvals (append-only)
054	2026-07-08	campaign_publish_attempts table
055	2026-07-08	execution_calendar_events table
056	2026-07-09	decision_rules table (8 seeded rules)
057	2026-07-09	recommendation_feedback table
058	2026-07-09	intelligence_trends table
059	2026-07-09	saved_opportunities_m10 (extends 046)
060	2026-07-09	reports table
061	2026-07-09	optimization_insights table

Pushed to hosted Supabase: Migrations 001–031 confirmed pushed. **Pending push:** Migrations 032–061 must be pushed before production traffic.

2. Core Founder & Product Tables

founders

```
CREATE TABLE founders (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  email       TEXT NOT NULL UNIQUE,  
  name        TEXT,  
  plan        TEXT NOT NULL DEFAULT 'free'  
              CHECK (plan IN ('free','solo','builder','studio')),  
  mfa_enabled BOOLEAN NOT NULL DEFAULT false,  
  token_balance INTEGER DEFAULT NULL,  
  deleted_at   TIMESTAMPTZ,  
  onboarding_step INTEGER DEFAULT 0,  
  created_at   TIMESTAMPTZ NOT NULL DEFAULT now(),  
  updated_at   TIMESTAMPTZ NOT NULL DEFAULT now()  
);  
ALTER TABLE founders ENABLE ROW LEVEL SECURITY;  
CREATE POLICY "founders_self" ON founders USING (id = auth.uid());
```

Soft-delete only: `deleted_at` is set, email is anonymised. GDPR `DELETE /founders/me` sets this.

products

```

CREATE TABLE products (
  id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id        UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  name              TEXT NOT NULL,
  store_url         TEXT NOT NULL,
  platform          TEXT NOT NULL CHECK (platform IN ('app_store','play_store')),
  category          TEXT,
  markets           TEXT[] DEFAULT ARRAY['usa'],
  price_tier        TEXT,
  confirmed_icp      JSONB,
  competitor_set     JSONB,
  scraped_meta       JSONB,      -- includes marketingImages[] (permanent CDN URLs)
  brand_voice_profile JSONB,
  last_scraped_at    TIMESTAMPTZ,
  icp_embedding      VECTOR(1536),
  workspace_id       UUID REFERENCES workspaces(id),
  -- Intake v2 columns (migration 023)
  primary_channel    TEXT,
  target_markets     TEXT[],
  founder_context    JSONB,
  intake_step        INTEGER DEFAULT 0,
  intake_completed_at TIMESTAMPTZ,
  website_url        TEXT,
  website_meta       JSONB,      -- includes logoUrl
  app_store_url      TEXT,
  play_store_url     TEXT,
  screenshots        JSONB,
  -- Archive columns (migration 029)
  archived_at        TIMESTAMPTZ,
  archive_reason     TEXT,
  -- Strategy column (migration 030)
  full_strategy      JSONB,
  -- Intake v3 columns (migration 033)
  intake_version     INTEGER DEFAULT 2,
  created_at         TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at         TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE products ENABLE ROW LEVEL SECURITY;
CREATE POLICY "products_owner" ON products USING (founder_id = auth.uid());

```

platform_tokens

```
-- NEVER return encrypted_token to the frontend under any circumstance.
CREATE TABLE platform_tokens (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  platform    TEXT NOT NULL
              CHECK (platform IN ('meta','google','whatsapp','linkedin','email')),
  encrypted_token TEXT NOT NULL,  -- AES-256 encrypted, key via AWS KMS only
  kms_key_id  TEXT NOT NULL,
  scopes      TEXT[] NOT NULL,
  expires_at  TIMESTAMPTZ,
  revoked_at  TIMESTAMPTZ,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now(),
  UNIQUE(founder_id, platform)
);
ALTER TABLE platform_tokens ENABLE ROW LEVEL SECURITY;
CREATE POLICY "tokens_owner" ON platform_tokens USING (founder_id = auth.uid());
```

workspaces

```
CREATE TABLE workspaces (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  name        TEXT NOT NULL,
  client_name TEXT,
  workspace_type TEXT DEFAULT 'personal',
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE workspaces ENABLE ROW LEVEL SECURITY;
CREATE POLICY "workspaces_owner" ON workspaces USING (founder_id = auth.uid());
```

workspace_members

```
CREATE TABLE workspace_members (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  workspace_id UUID NOT NULL REFERENCES workspaces(id) ON DELETE CASCADE,
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  role        TEXT NOT NULL DEFAULT 'member' CHECK (role IN ('owner','admin','member')),
  invited_by  UUID REFERENCES founders(id),
  joined_at   TIMESTAMPTZ NOT NULL DEFAULT now(),
  UNIQUE(workspace_id, founder_id)
);
```

api_keys (Studio-only)

```
CREATE TABLE api_keys (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,  
  name        TEXT NOT NULL,  
  key_hash    TEXT NOT NULL UNIQUE, -- bcrypt hash, never store plaintext  
  scopes      TEXT[] NOT NULL,  
  last_used   TIMESTAMPTZ,  
  expires_at  TIMESTAMPTZ,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);
```

3. Campaign & Metrics Tables

campaigns

```
CREATE TABLE campaigns (
  id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  product_id        UUID NOT NULL REFERENCES products(id) ON DELETE CASCADE,
  founder_id        UUID NOT NULL REFERENCES founders(id),
  channel            TEXT NOT NULL
  CHECK (channel IN
    ('meta', 'google', 'whatsapp', 'linkedin', 'email', 'aso_rewrite',
     'tiktok', 'youtube', 'pinterest', 'snapchat')),
  market            TEXT NOT NULL CHECK (market IN ('usa', 'india')),
  status            TEXT NOT NULL DEFAULT 'draft'
  CHECK (status IN
    ('draft', 'pending_approval', 'approved', 'launched', 'paused',
     'completed', 'scheduled', 'cancelled', 'failed')),
  hook_type          TEXT,
  copy_text          TEXT,
  audience_config    JSONB,
  spend_cap          JSONB,      -- { daily_usd, weekly_usd, monthly_usd }
  external_campaign_id TEXT,
  action             TEXT,
  ai_tokens_consumed INTEGER DEFAULT 0,
  approved_at        TIMESTAMPTZ, -- §1.5: must be non-null before any platform post
  launched_at        TIMESTAMPTZ,
  -- Extension columns (migration 051)
  type               TEXT DEFAULT 'standard' CHECK (type IN ('standard', 'retargeting', 'aso', 'expe
  scheduled_at        TIMESTAMPTZ,
  cancelled_at        TIMESTAMPTZ,
  failed_at           TIMESTAMPTZ,
  failure_reason      TEXT,
  created_at          TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at          TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE campaigns ENABLE ROW LEVEL SECURITY;
CREATE POLICY "campaigns_owner" ON campaigns USING (founder_id = auth.uid());
CREATE INDEX campaigns_product_status ON campaigns(product_id, status);
```


campaign_metrics

```

CREATE TABLE campaign_metrics (
  id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  campaign_id       UUID NOT NULL REFERENCES campaigns(id) ON DELETE CASCADE,
  founder_id        UUID NOT NULL REFERENCES founders(id),
  week_start        DATE NOT NULL,
  impressions        INTEGER DEFAULT 0,
  clicks            INTEGER DEFAULT 0,
  installs          INTEGER DEFAULT 0,
  cpi               NUMERIC(10,4),
  ctr               NUMERIC(6,4),
  roas              NUMERIC(10,4),
  top_performing_asset TEXT,
  raw_platform_data JSONB,
  collected_at       TIMESTAMPTZ NOT NULL DEFAULT now(),
  UNIQUE(campaign_id, week_start)
);
ALTER TABLE campaign_metrics ENABLE ROW LEVEL SECURITY;
CREATE POLICY "metrics_owner" ON campaign_metrics USING (founder_id = auth.uid());

```

campaign_approvals (append-only, migration 053)

```

CREATE TABLE campaign_approvals (
  id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  campaign_id       UUID NOT NULL REFERENCES campaigns(id) ON DELETE CASCADE,
  founder_id        UUID NOT NULL REFERENCES founders(id),
  status            TEXT NOT NULL CHECK (status IN ('approved','rejected')),
  note              TEXT,
  created_at        TIMESTAMPTZ NOT NULL DEFAULT now()
);
-- REVOKE UPDATE, DELETE FROM authenticated;

```

campaign_publish_attempts (migration 054)

```

CREATE TABLE campaign_publish_attempts (
  id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  campaign_id       UUID NOT NULL REFERENCES campaigns(id) ON DELETE CASCADE,
  attempt_num       INTEGER NOT NULL DEFAULT 1,
  status            TEXT NOT NULL CHECK (status IN ('pending','success','failed')),
  error             TEXT,
  platform_response JSONB,
  created_at        TIMESTAMPTZ NOT NULL DEFAULT now()
);

```

utm_links (migration 011)

```
CREATE TABLE utm_links (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,  
  campaign_id UUID REFERENCES campaigns(id),  
  original_url TEXT NOT NULL,  
  utm_url     TEXT NOT NULL,  
  utm_source  TEXT,  
  utm_medium  TEXT,  
  utm_campaign TEXT,  
  clicks      INTEGER DEFAULT 0,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);
```

experiments (migration 052)

```
CREATE TABLE experiments (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,  
  product_id  UUID REFERENCES products(id) ON DELETE CASCADE,  
  title       TEXT NOT NULL,  
  hypothesis  TEXT,  
  status      TEXT NOT NULL DEFAULT 'draft'  
              CHECK (status IN ('draft','running','completed','archived')),  
  winner      TEXT CHECK (winner IN ('a','b',NULL)),  
  learning_summary TEXT,  
  start_date  TIMESTAMPTZ,  
  end_date    TIMESTAMPTZ,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now(),  
  updated_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);  
ALTER TABLE experiments ENABLE ROW LEVEL SECURITY;  
CREATE POLICY "experiments_owner" ON experiments USING (founder_id = auth.uid());
```

experiment_variants

```
CREATE TABLE experiment_variants (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  experiment_id UUID NOT NULL REFERENCES experiments(id) ON DELETE CASCADE,  
  label       TEXT NOT NULL CHECK (label IN ('a','b')),  
  copy_text   TEXT,  
  audience_config JSONB,  
  impressions INTEGER DEFAULT 0,  
  clicks      INTEGER DEFAULT 0,  
  installs    INTEGER DEFAULT 0,  
  cpi         NUMERIC(10,4),  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);
```

4. Content & Learning Tables

content_assets

```
CREATE TABLE content_assets (
  id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id        UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  product_id        UUID REFERENCES products(id) ON DELETE CASCADE,
  campaign_id        UUID REFERENCES campaigns(id),
  type              TEXT NOT NULL CHECK (type IN (
    -- Original 26 types
    'instagram_reel', 'tiktok_video', 'youtube_short', 'meta_static_ad', 'google_display_ad',
    'whatsapp_message', 'linkedin_post', 'email_subject', 'email_body', 'push_notification',
    'app_store_title', 'app_store_description', 'app_store_keywords', 'play_store_listing',
    'tweet', 'facebook_post', 'voice_note', 'video_script', 'ad_copy_short', 'ad_copy_long',
    'headline', 'tagline', 'aso_title', 'aso_description', 'aso_keywords',
    -- M08 new types (migration 050)
    'blog_post', 'landing_page_copy', 'release_notes', 'press_release',
    -- Visual types
    'image_photorealistic', 'image_graphic', 'image_mockup'
  )),
  channel            TEXT,
  market            TEXT CHECK (market IN ('usa', 'india', NULL)),
  asset_data         JSONB NOT NULL, -- { text?, imageUrl?, videoUrl?, audioUrl?, metadata? }
  status             TEXT NOT NULL DEFAULT 'draft'
                    CHECK (status IN ('draft', 'approved', 'published', 'archived')),
  -- Extension columns (migration 050)
  tags              TEXT[],
  mission_id         UUID REFERENCES missions(id),
  growth_brain_version INTEGER,
  archived_at        TIMESTAMPTZ,
  published_at       TIMESTAMPTZ,
  model_used         TEXT, -- 'real-screenshot+mockup+logo' | 'sonnet+flux-schnell+...'
  tokens_consumed    INTEGER DEFAULT 0,
  ctr               NUMERIC(6,4),
  performed_at       TIMESTAMPTZ,
  parent_asset_id    UUID REFERENCES content_assets(id),
  render_started_at  TIMESTAMPTZ,
  created_at         TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at         TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE content_assets ENABLE ROW LEVEL SECURITY;
CREATE POLICY "assets_owner" ON content_assets USING (founder_id = auth.uid());
```

content_preferences (migration 027)

```
CREATE TABLE content_preferences (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,  
  product_id  UUID REFERENCES products(id),  
  asset_type  TEXT,  
  preferences JSONB,           -- per-type settings  
  voice_clone_id TEXT,         -- ElevenLabs voice ID  
  visual      JSONB,           -- { logoUrl, imageStyle: 'photorealistic' 'graphic' 'mockup' }  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now(),  
  updated_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);
```

content_versions (append-only, migration 047)

```
CREATE TABLE content_versions (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  asset_id    UUID NOT NULL REFERENCES content_assets(id) ON DELETE CASCADE,  
  founder_id  UUID NOT NULL REFERENCES founders(id),  
  version_num INTEGER NOT NULL,  
  asset_data  JSONB NOT NULL,   -- snapshot before update  
  changed_by  TEXT,            -- 'founder' 'ai_transform' 'api'  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);  
-- REVOKE UPDATE, DELETE FROM authenticated; -- append-only
```

content_learnings (migration 028)

```
CREATE TABLE content_learnings (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,  
  product_id  UUID REFERENCES products(id),  
  learning_type TEXT NOT NULL,  
  insight     TEXT NOT NULL,  
  confidence  NUMERIC(4,2),  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);  
-- Note: currently 0 rows for demo founder
```

asset_approvals (append-only, migration 048)

```
CREATE TABLE asset_approvals (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  asset_id    UUID NOT NULL REFERENCES content_assets(id) ON DELETE CASCADE,
  founder_id  UUID NOT NULL REFERENCES founders(id),
  status      TEXT NOT NULL CHECK (status IN ('approved','rejected')),
  note        TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
-- REVOKE UPDATE, DELETE FROM authenticated;
```

publishing_targets (migration 049)

```
CREATE TABLE publishing_targets (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  content_asset_id UUID NOT NULL REFERENCES content_assets(id) ON DELETE CASCADE,
  channel      TEXT NOT NULL,
  status       TEXT NOT NULL DEFAULT 'pending' CHECK (status IN ('pending','published','failed')),
  external_id  TEXT,
  published_at TIMESTAMPTZ,
  error        TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
```

weekly_briefs

```
CREATE TABLE weekly_briefs (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  product_id  UUID NOT NULL REFERENCES products(id) ON DELETE CASCADE,
  founder_id  UUID NOT NULL REFERENCES founders(id),
  week_of     DATE NOT NULL,
  what_worked TEXT,
  what_to_kill TEXT,
  next_actions JSONB,
  generated_assets JSONB,
  ai_tokens_consumed INTEGER DEFAULT 0,
  status       TEXT NOT NULL DEFAULT 'draft'
                CHECK (status IN ('draft','sent','acknowledged')),
  sent_at     TIMESTAMPTZ,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now(),
  UNIQUE(product_id, week_of)
);
ALTER TABLE weekly_briefs ENABLE ROW LEVEL SECURITY;
CREATE POLICY "briefs_owner" ON weekly_briefs USING (founder_id = auth.uid());
```

5. Intelligence & Memory Tables

marketing_memories (migration 035)

```
CREATE TABLE marketing_memories (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  product_id  UUID REFERENCES products(id) ON DELETE SET NULL,
  title       TEXT NOT NULL,
  body        TEXT,
  memory_type TEXT NOT NULL CHECK (memory_type IN (
    'brand','product','customer','campaign','founder',
    'channel','market','competitor','experiment'
  )),
  source       TEXT NOT NULL,      -- 'intake_completed' 'campaign_result' 'review_ingested' etc.
  confidence   NUMERIC(4,2) NOT NULL DEFAULT 0.5,
  version      INTEGER NOT NULL DEFAULT 1,
  tags         TEXT[],
  archived     BOOLEAN NOT NULL DEFAULT false,
  embedding    VECTOR(1536),
  metadata     JSONB,
  created_at   TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at   TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE marketing_memories ENABLE ROW LEVEL SECURITY;
CREATE POLICY "memories_owner" ON marketing_memories USING (founder_id = auth.uid());
```

Current seed data: 5 rows for demo founder vijay@lm.com (brand: 0.81, product: 0.79, customer: 0.86, campaign: 0.58, founder: 0.63)

marketing_memory_versions (append-only, migration 036)

```
CREATE TABLE marketing_memory_versions (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  memory_id   UUID NOT NULL REFERENCES marketing_memories(id) ON DELETE CASCADE,
  version     INTEGER NOT NULL,
  body        TEXT,
  confidence   NUMERIC(4,2),
  changed_by  TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
-- REVOKE UPDATE, DELETE FROM authenticated;
```

knowledge_nodes (migration 037)

```

CREATE TABLE knowledge_nodes (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  node_type   TEXT NOT NULL CHECK (node_type IN (
    'product','channel','market','competitor','audience_segment',
    'campaign_type','metric','insight','founder'
  )),
  label       TEXT NOT NULL,
  properties  JSONB,
  confidence  NUMERIC(4,2) DEFAULT 0.5,
  embedding   VECTOR(1536),
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at  TIMESTAMPTZ NOT NULL DEFAULT now(),
  UNIQUE(founder_id, node_type, label)
);
ALTER TABLE knowledge_nodes ENABLE ROW LEVEL SECURITY;
CREATE POLICY "nodes_owner" ON knowledge_nodes USING (founder_id = auth.uid());

```

knowledge_edges (migration 038)

```

CREATE TABLE knowledge_edges (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  source_node_id UUID NOT NULL REFERENCES knowledge_nodes(id) ON DELETE CASCADE,
  target_node_id UUID NOT NULL REFERENCES knowledge_nodes(id) ON DELETE CASCADE,
  relation_type TEXT NOT NULL, -- 'outperforms', 'targets', 'competes_with', etc.
  weight      NUMERIC(4,2) DEFAULT 1.0,
  evidence    TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE knowledge_edges ENABLE ROW LEVEL SECURITY;
CREATE POLICY "edges_owner" ON knowledge_edges USING (founder_id = auth.uid());

```

evidence (migration 039)

```

CREATE TABLE evidence (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  memory_id   UUID REFERENCES marketing_memories(id) ON DELETE CASCADE,
  content     TEXT NOT NULL,
  source      TEXT NOT NULL,
  confidence  NUMERIC(4,2),
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);

```

learning_events (migration 040)

```
CREATE TABLE learning_events (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,  
  event_type  TEXT NOT NULL CHECK (event_type IN (  
    'intake_completed', 'campaign_result', 'review_ingested', 'founder_feedback',  
    'growth_brain_approved', 'analytics_synced', 'experiment_result', 'ai_conversation'  
  )),  
  payload     JSONB NOT NULL,  
  processed   BOOLEAN NOT NULL DEFAULT false,  
  result      JSONB,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);
```

playbook_signals (anonymized)

```
-- ANONYMIZED. No founder_id. No product_id. No PII.  
-- service_role may INSERT. authenticated: SELECT only.  
CREATE TABLE playbook_signals (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  category    TEXT NOT NULL,  
  market      TEXT NOT NULL CHECK (market IN ('usa', 'india')),  
  channel     TEXT NOT NULL,  
  hook_type   TEXT,  
  price_tier  TEXT,  
  install_delta_pct NUMERIC(8,2),  
  conversion_rate NUMERIC(6,4),  
  retention_d7 NUMERIC(6,4),  
  week_number  INTEGER,  
  signal_embedding VECTOR(1536),  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);  
GRANT SELECT ON playbook_signals TO authenticated;  
REVOKE INSERT, UPDATE, DELETE ON playbook_signals FROM authenticated;  
-- 52 rows seeded (28 from migration 019 + 24 from migration 018)
```


embedding_store

```
CREATE TABLE embedding_store (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,  
  product_id  UUID REFERENCES products(id) ON DELETE CASCADE,  
  type        TEXT NOT NULL CHECK (type IN ('icp','campaign_history','learning_log')),  
  content     TEXT NOT NULL,  
  embedding   VECTOR(1536),  
  metadata    JSONB,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);  
ALTER TABLE embedding_store ENABLE ROW LEVEL SECURITY;  
CREATE POLICY "embeddings_owner" ON embedding_store USING (founder_id = auth.uid());
```

intelligence_trends (anonymous, migration 058)

```
-- No founder_id, no product_id - fully anonymous aggregates  
-- Min cohort=3 before a trend row is published  
CREATE TABLE intelligence_trends (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  category    TEXT NOT NULL,  
  market      TEXT NOT NULL CHECK (market IN ('usa','india')),  
  channel     TEXT NOT NULL,  
  period_start DATE NOT NULL,  
  period_end   DATE NOT NULL,  
  signal_count INTEGER NOT NULL DEFAULT 0, -- cohort size  
  avg_install_delta NUMERIC(8,2),  
  avg_conversion  NUMERIC(6,4),  
  avg_retention_d7 NUMERIC(6,4),  
  top_hook_type  TEXT,  
  created_at    TIMESTAMPTZ NOT NULL DEFAULT now(),  
  UNIQUE(category, market, channel, period_start)  
);  
GRANT SELECT ON intelligence_trends TO authenticated;  
REVOKE INSERT, UPDATE, DELETE ON intelligence_trends FROM authenticated;
```

6. AI Platform Tables

prompts (migration 041, 11 seeded via migration 043)

```
CREATE TABLE prompts (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  name        TEXT NOT NULL,          -- 'morning_brief', 'strategy_generation', etc.
  version     INTEGER NOT NULL DEFAULT 1,
  body        TEXT NOT NULL,          -- the prompt text
  model       TEXT,                   -- 'sonnet' | 'haiku'
  max_tokens  INTEGER,
  active      BOOLEAN NOT NULL DEFAULT true,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now(),
  UNIQUE(name, version)
);
```

11 seeded prompt names: morning_brief, strategy_generation, content_assets_generation, brand_voice_extract, brand_voice_apply, icp_structuring, review_analysis, weekly_brief, content_score, recommendation_generation, agent_campaign_draft

ai_requests (immutable audit, migration 042)

```
CREATE TABLE ai_requests (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID REFERENCES founders(id),
  product_id  UUID REFERENCES products(id),
  prompt_id   TEXT,                  -- name of the prompt used
  action      TEXT NOT NULL,         -- action identifier (matches auditCtx.action)
  model       TEXT NOT NULL,         -- 'claude-sonnet-4-6' | 'claude-haiku-4-5-20251001'
  input_tokens INTEGER,
  output_tokens INTEGER,
  cost_usd    NUMERIC(10,6),
  status      TEXT NOT NULL CHECK (status IN ('success','failed','timeout')),
  error_message TEXT,                -- 'output_validation_failed' on Zod parse error
  latency_ms  INTEGER,
  retries     INTEGER DEFAULT 0,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE ai_requests ENABLE ROW LEVEL SECURITY;
CREATE POLICY "ai_requests_owner" ON ai_requests FOR SELECT USING (founder_id = auth.uid());
-- INSERT via service_role only. No UPDATE, DELETE.
```

7. Mission & Agent Tables

missions (migration 044)

```
CREATE TABLE missions (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,  
  product_id  UUID REFERENCES products(id),  
  title       TEXT NOT NULL,  
  type        TEXT NOT NULL CHECK (type IN (  
    'research','strategy','content','campaign','memory',  
    'reporting','planning','creative','publishing','optimization','learning','benchmark'  
  )),  
  status      TEXT NOT NULL DEFAULT 'draft' CHECK (status IN (  
    'draft','queued','running','requires_approval','completed','failed','cancelled'  
  )),  
  priority    INTEGER NOT NULL DEFAULT 5, -- 1=highest, 10=lowest  
  context     JSONB,  
  result      JSONB,  
  idempotency_key TEXT UNIQUE,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now(),  
  updated_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);  
ALTER TABLE missions ENABLE ROW LEVEL SECURITY;  
CREATE POLICY "missions_owner" ON missions USING (founder_id = auth.uid());
```

mission_steps (migration 045)

```
CREATE TABLE mission_steps (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  mission_id  UUID NOT NULL REFERENCES missions(id) ON DELETE CASCADE,  
  step_order  INTEGER NOT NULL,  
  agent_type  TEXT NOT NULL,  
  status      TEXT NOT NULL DEFAULT 'pending' CHECK (status IN (  
    'pending','running','completed','failed','skipped','requires_approval'  
  )),  
  input       JSONB,  
  output      JSONB,  
  error       TEXT,  
  started_at  TIMESTAMPTZ,  
  completed_at TIMESTAMPTZ,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);
```

mission_logs (migration 045)

```
CREATE TABLE mission_logs (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  mission_id  UUID NOT NULL REFERENCES missions(id) ON DELETE CASCADE,  
  founder_id  UUID NOT NULL REFERENCES founders(id),  
  message     TEXT NOT NULL,  
  level       TEXT NOT NULL DEFAULT 'info' CHECK (level IN ('info','warn','error')),  
  metadata    JSONB,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);  
-- Note: 0 rows for demo founder (missions haven't been run)
```

mission_approvals (migration 045)

```
CREATE TABLE mission_approvals (  
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  mission_id  UUID NOT NULL REFERENCES missions(id) ON DELETE CASCADE,  
  step_id     UUID REFERENCES mission_steps(id),  
  founder_id  UUID NOT NULL REFERENCES founders(id),  
  status      TEXT NOT NULL CHECK (status IN ('pending','approved','rejected')),  
  note        TEXT,  
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()  
);
```

8. Owner Experience Tables

saved_opportunities (migration 046, extended by migration 059)

```
CREATE TABLE saved_opportunities (
  id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id        UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  product_id        UUID REFERENCES products(id),
  type              TEXT NOT NULL,           -- 'aso', 'india_launch', 'review_risk', etc.
  title             TEXT NOT NULL,
  description        TEXT,
  expected_impact    TEXT,
  effort            TEXT CHECK (effort IN ('low','medium','high')),
  risk              TEXT CHECK (risk IN ('low','medium','high')),
  confidence         NUMERIC(4,2),
  state             TEXT NOT NULL DEFAULT 'active' CHECK (state IN ('active','saved','dismissed','con
  evidence           JSONB,                  -- always stored as plain array (not JSON.stringify)
  why_now           TEXT,
  source            TEXT,
  -- M10 extension columns (migration 059)
  recommendation_type TEXT,
  score             NUMERIC(6,4),
  priority          INTEGER,
  source_signals     JSONB,
  expires_at        TIMESTAMPTZ,
  related_mission_id UUID REFERENCES missions(id),
  feedback_summary   JSONB,
  created_at         TIMESTAMPTZ NOT NULL DEFAULT now(),
  updated_at        TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE saved_opportunities ENABLE ROW LEVEL SECURITY;
CREATE POLICY "opportunities_owner" ON saved_opportunities USING (founder_id = auth.uid());
```

notifications (migration 046)

```
CREATE TABLE notifications (
  id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id        UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  type              TEXT NOT NULL,
  title             TEXT NOT NULL,
  body              TEXT,
  read              BOOLEAN NOT NULL DEFAULT false,
  link              TEXT,
  metadata          JSONB,
  created_at        TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE notifications ENABLE ROW LEVEL SECURITY;
CREATE POLICY "notifications_owner" ON notifications USING (founder_id = auth.uid());
```

execution_calendar_events (migration 055)

```

CREATE TABLE execution_calendar_events (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  title       TEXT NOT NULL,
  event_type  TEXT NOT NULL CHECK (event_type IN (
    'campaign_launch', 'experiment_start', 'brief_delivery', 'content_publish',
    'review_window', 'manual'
  )),
  source      TEXT NOT NULL DEFAULT 'manual' CHECK (source IN ('manual', 'campaign', 'experiment', 'br
  source_id   UUID,                -- id of the source campaign/experiment/brief
  start_date  TIMESTAMPTZ NOT NULL,
  end_date    TIMESTAMPTZ,
  notes       TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE execution_calendar_events ENABLE ROW LEVEL SECURITY;
CREATE POLICY "calendar_owner" ON execution_calendar_events USING (founder_id = auth.uid());

```

9. Analytics & Reporting Tables

reports (migration 060)

```

CREATE TABLE reports (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  product_id  UUID REFERENCES products(id),
  type        TEXT NOT NULL CHECK (type IN (
    'weekly', 'monthly', 'executive', 'campaign', 'experiment'
  )),
  period_start DATE NOT NULL,
  period_end   DATE NOT NULL,
  content      JSONB NOT NULL,    -- AI narrative cache: { headline, whatWorked, fix, insights, ac
  tokens_used  INTEGER DEFAULT 0,
  created_at   TIMESTAMPTZ NOT NULL DEFAULT now(),
  UNIQUE(founder_id, product_id, type, period_start)
);
ALTER TABLE reports ENABLE ROW LEVEL SECURITY;
CREATE POLICY "reports_owner" ON reports USING (founder_id = auth.uid());

```

optimization_insights (migration 061)

```

CREATE TABLE optimization_insights (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID NOT NULL REFERENCES founders(id) ON DELETE CASCADE,
  product_id  UUID REFERENCES products(id),
  type        TEXT NOT NULL CHECK (type IN (
    'channel_shift','budget_reallocation','copy_refresh',
    'audience_expand','timing_optimization','market_opportunity'
  )),
  title       TEXT NOT NULL,
  body        TEXT NOT NULL,
  confidence  NUMERIC(4,2) NOT NULL,  -- high-confidence (≥0.8) triggers generateRecommendations
  impact      TEXT,
  status      TEXT NOT NULL DEFAULT 'pending' CHECK (status IN ('pending','applied','dismissed')),
  applied_at  TIMESTAMPTZ,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE optimization_insights ENABLE ROW LEVEL SECURITY;
CREATE POLICY "insights_owner" ON optimization_insights USING (founder_id = auth.uid());

```

decision_rules (8 seeded, migration 056)

```

CREATE TABLE decision_rules (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  name        TEXT NOT NULL UNIQUE,
  description  TEXT,
  rule_fn     TEXT NOT NULL,          -- identifier for the TypeScript function
  active      BOOLEAN NOT NULL DEFAULT true,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
-- Seeded rules: approve_before_post, spend_cap, budget_increase_reapproval,
-- studio_plan_gate, content_regen_limit, experiment_min_runtime,
-- token_balance_gate, workspace_tenant_isolation

```

recommendation_feedback (append-only, migration 057)

```

CREATE TABLE recommendation_feedback (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  recommendation_id UUID NOT NULL REFERENCES saved_opportunities(id) ON DELETE CASCADE,
  founder_id  UUID NOT NULL REFERENCES founders(id),
  feedback_type TEXT NOT NULL CHECK (feedback_type IN (
    'helpful','not_relevant','too_early','already_done','wrong_context'
  )),
  note        TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
-- REVOKE UPDATE, DELETE FROM authenticated;

```

10. Infrastructure Tables

audit_logs (immutable)

```
-- IMMUTABLE. INSERT only. REVOKE UPDATE, DELETE from all non-superuser roles.
CREATE TABLE audit_logs (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID REFERENCES founders(id),
  action      TEXT NOT NULL,
  resource_type TEXT,
  resource_id UUID,
  metadata    JSONB,
  ip_address  INET,
  user_agent  TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
ALTER TABLE audit_logs ENABLE ROW LEVEL SECURITY;
CREATE POLICY "audit_owner_read" ON audit_logs FOR SELECT USING (founder_id = auth.uid());
REVOKE UPDATE, DELETE ON audit_logs FROM authenticated, anon;
```

waitlist (migration 012)

```
CREATE TABLE waitlist (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  email       TEXT NOT NULL UNIQUE,
  source      TEXT DEFAULT 'landing',
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
```

founder_feedback (migration 014)

```
CREATE TABLE founder_feedback (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  founder_id  UUID REFERENCES founders(id),
  rating      INTEGER CHECK (rating BETWEEN 1 AND 5),
  message     TEXT,
  context     TEXT,
  created_at  TIMESTAMPTZ NOT NULL DEFAULT now()
);
```

11. RLS Summary

Table	Policy	Access
-------	--------	--------

founders	<code>id = auth.uid()</code>	Self only
products	<code>founder_id = auth.uid()</code>	Owner only
platform_tokens	<code>founder_id = auth.uid()</code>	Owner only
campaigns	<code>founder_id = auth.uid()</code>	Owner only
campaign_metrics	<code>founder_id = auth.uid()</code>	Owner only
weekly_briefs	<code>founder_id = auth.uid()</code>	Owner only
embedding_store	<code>founder_id = auth.uid()</code>	Owner only
content_assets	<code>founder_id = auth.uid()</code>	Owner only
marketing_memories	<code>founder_id = auth.uid()</code>	Owner only
knowledge_nodes	<code>founder_id = auth.uid()</code>	Owner only
knowledge_edges	<code>founder_id = auth.uid()</code>	Owner only
ai_requests	<code>founder_id = auth.uid()</code> (SELECT)	Owner read, service_role write
missions	<code>founder_id = auth.uid()</code>	Owner only
saved_opportunities	<code>founder_id = auth.uid()</code>	Owner only
notifications	<code>founder_id = auth.uid()</code>	Owner only
audit_logs	<code>founder_id = auth.uid()</code> (SELECT only)	Owner read, INSERT all
playbook_signals	SELECT authenticated	All founders read, service_role write
intelligence_trends	SELECT authenticated	All founders read, service_role write

Continue to: [LMJuly18-03-Backend.md](#)