

LMJuly18-04 — LaunchMind: Frontend

Date: July 18, 2026 · Part 4 of 6 **Runtime:** Next.js 14 App Router **Host:** Vercel (auto-deploy on push to main)

Design System: Slate & Sage v1.0 (light theme only)

Table of Contents

- [File Structure](#)
 - [Routing Map](#)
 - [Public Pages](#)
 - [Auth Pages](#)
 - [Dashboard Layout](#)
 - [Primary Dashboard Pages](#)
 - [Product Intake Wizard \(7 steps\)](#)
 - [Intelligence Pages](#)
 - [Settings Pages](#)
 - [Components Library](#)
 - [Design System v1.0](#)
 - [API Client \(lib/api.ts \)](#)
 - [Utility Libraries](#)
 - [Key Patterns & Rules](#)
-

1. File Structure

```

app/
├── page.tsx                # Marketing homepage
├── layout.tsx              # Root layout (DM Sans + Syne + DM Mono, PostHog)
├── globals.css             # Design system CSS variables + base styles
├── pricing/page.tsx
├── checkout/success/page.tsx
├── (auth)/
│   ├── login/page.tsx + actions.ts
│   ├── signup/page.tsx
│   ├── mfa/page.tsx
│   ├── forgot-password/page.tsx
│   └── reset-password/page.tsx
├── (dashboard)/
│   ├── layout.tsx          # Sidebar + MobileNav + main
│   ├── error.tsx           # Error boundary → ErrorState
│   └── dashboard/
│       ├── page.tsx        # redirect → /dashboard/brief
│       ├── brief/page.tsx
│       ├── opportunities/page.tsx
│       ├── ask/page.tsx
│       ├── approvals/page.tsx
│       ├── results/page.tsx
│       ├── analytics/page.tsx
│       ├── reports/page.tsx
│       ├── campaigns/page.tsx
│       ├── experiments/page.tsx
│       ├── calendar/page.tsx
│       ├── content/page.tsx
│       ├── briefs/page.tsx
│       ├── channels/page.tsx
│       ├── billing/page.tsx
│       ├── missions/
│       │   ├── page.tsx
│       │   └── [id]/page.tsx
│       ├── products/
│       │   ├── page.tsx
│       │   ├── [id]/page.tsx
│       │   ├── [id]/strategy/page.tsx
│       │   ├── new/page.tsx + layout.tsx
│       │   ├── new/context/page.tsx
│       │   ├── new/analysis/page.tsx
│       │   ├── new/icp/page.tsx
│       │   ├── new/competitors/page.tsx
│       │   ├── new/markets/page.tsx
│       │   └── new/confirm/page.tsx
│       ├── workspaces/
│       │   ├── page.tsx
│       │   └── [id]/page.tsx
│       ├── settings/
│       │   ├── page.tsx
│       │   ├── billing/page.tsx
│       │   ├── usage/page.tsx
│       │   └── [tab]/page.tsx

```

```
├── tabs/
│   ├── ProfileTab.tsx
│   ├── SecurityTab.tsx
│   ├── ContentTypesTab.tsx
│   ├── VoiceCloneTab.tsx
│   ├── NotificationsTab.tsx
│   ├── ProductsTab.tsx
│   └── AccountManagementTab.tsx
├── intelligence/
│   ├── layout.tsx
│   ├── growth-brain/page.tsx
│   ├── memory/page.tsx
│   ├── knowledge/page.tsx
│   ├── market/page.tsx
│   ├── reviews/page.tsx
│   ├── timeline/page.tsx
│   ├── ideas/page.tsx
│   └── ai-audit/page.tsx
├── admin/
│   ├── page.tsx
│   └── mrr/page.tsx
├── insights/page.tsx
└── metrics/page.tsx
└── api/
    ├── admin/feedback/route.ts
    ├── admin/mrr/route.ts
    ├── admin/stats/route.ts
    └── auth/callback/route.ts
```

```
components/launchmind/           # 24 custom components

lib/
├── api.ts                        # Type-safe API client
├── coerce.ts                     # toStringArray() + toRecord()
├── auth.ts
├── analytics.ts                  # PostHog helpers
├── design-system/tokens.ts
├── types/content.ts
├── types/intake.ts
├── types/settings.ts
└── supabase/client.ts + server.ts + middleware.ts

middleware.ts                     # Next.js edge middleware (auth redirect)

tailwind.config.ts               # Design system v1.0 config
```

2. Routing Map

URL	File	Description
-----	------	-------------

/	app/page.tsx	Marketing homepage
/pricing	app/pricing/page.tsx	Public pricing
/login	app/(auth)/login/page.tsx	Sign in
/signup	app/(auth)/signup/page.tsx	Create account
/mfa	app/(auth)/mfa/page.tsx	TOTP verification
/forgot-password	(auth)/forgot-password/page.tsx	Reset request
/reset-password	(auth)/reset-password/page.tsx	New password
/dashboard	→ redirect to /dashboard/brief	
/dashboard/brief	dashboard/brief/page.tsx	Morning Brief — primary entry
/dashboard/opportunities	dashboard/opportunities/page.tsx	Growth backlog
/dashboard/ask	dashboard/ask/page.tsx	Ask LaunchMind
/dashboard/approvals	dashboard/approvals/page.tsx	Unified approvals
/dashboard/results	dashboard/results/page.tsx	Interpreted metrics
/dashboard/analytics	dashboard/analytics/page.tsx	KPI drill-down
/dashboard/reports	dashboard/reports/page.tsx	Report generation
/dashboard/campaigns	dashboard/campaigns/page.tsx	Campaign management
/dashboard/experiments	dashboard/experiments/page.tsx	A/B experiments
/dashboard/calendar	dashboard/calendar/page.tsx	Execution calendar
/dashboard/content	dashboard/content/page.tsx	Content Studio
/dashboard/briefs	dashboard/briefs/page.tsx	Weekly briefs + assets
/dashboard/channels	dashboard/channels/page.tsx	Platform integrations
/dashboard/billing	dashboard/billing/page.tsx	Plan + token top-ups
/dashboard/missions	dashboard/missions/page.tsx	Mission Center
/dashboard/missions/:id	dashboard/missions/[id]/page.tsx	Mission detail
/dashboard/products	dashboard/products/page.tsx	Product list
/dashboard/products/:id	dashboard/products/[id]/page.tsx	Product detail
/dashboard/products/:id/strategy	[id]/strategy/page.tsx	Strategy view

/dashboard/products/new	products/new/page.tsx	Intake step 1
/dashboard/products/new/context	new/context/page.tsx	Intake step 2
/dashboard/products/new/analysis	new/analysis/page.tsx	Intake step 3
/dashboard/products/new/icp	new/icp/page.tsx	Intake step 4
/dashboard/products/new/competitors	new/competitors/page.tsx	Intake step 5
/dashboard/products/new/markets	new/markets/page.tsx	Intake step 6
/dashboard/products/new/confirm	new/confirm/page.tsx	Intake step 7
/dashboard/workspaces	workspaces/page.tsx	Workspaces (Studio)
/dashboard/workspaces/:id	workspaces/[id]/page.tsx	Workspace detail
/dashboard/settings	settings/page.tsx	Settings (7 tabs)
/dashboard/intelligence/growth-brain	Growth Brain	
/dashboard/intelligence/memory	Marketing Memory	
/dashboard/intelligence/knowledge	Knowledge Graph	
/dashboard/intelligence/market	Market Intelligence	
/dashboard/intelligence/reviews	Review Intelligence	
/dashboard/intelligence/timeline	Timeline	
/dashboard/intelligence/ideas	Ideas	
/dashboard/intelligence/ai-audit	AI Audit	

3. Public Pages

app/page.tsx — Marketing Homepage

Dark navy hero (--sidebar background). Sections:

Nav (sticky, dark, background: rgba(40,48,74,0.97) , backdrop-filter: blur(12px)):

- Logo: Launch + Mind (green accent #34d399) in Syne 700
- Links: How it works / Features / Markets / Pricing / Security
- CTAs: Sign in (ghost, border) + Start free (sage bg)

Hero:

- Badge: "AI marketing OS for app founders" (sage tint pill)

- H1: "Stop guessing how to **market your app**" — Syne 800, `clamp(40px, 6vw, 68px)`, green "market your app"
- Sub: "Paste your App Store or Play Store URL. LaunchMind builds your strategy, writes your content, runs your campaigns, and tells you what's working — every week."
- Primary CTA: "Start free — no card required →" (sage bg, large)
- Secondary: "See it in 90 seconds" (ghost, IconPlayerPlay)
- Fine print: "Free forever · No credit card · 3-minute setup"
- Market badges: 🇺🇸 USA · Stripe · USD (sage) + 🇮🇳 India · Razorpay · INR (amber)
- Mini dashboard mockup (dark sidebar + metric cards + product list preview)

Sections: How it works (4 steps), Features (6 cards), Markets (USA+India CPI data), Pricing (4-tier grid), Security (MFA/AES-256/RLS badges), Footer CTA (waitlist email).

4. Auth Pages

`login/page.tsx`

Email + password form. Supabase `signInWithPassword()`. On MFA required → redirect to `/mfa`. OAuth future-ready slots. Uses `actions.ts` for server action form submission.

`signup/page.tsx`

Email + password + name. Supabase `signUp()`. Triggers `auto_create_founder_on_signup` DB trigger (migration 022) which creates the `founders` row.

`mfa/page.tsx`

6-digit TOTP input. `supabase.auth.mfa.challengeAndVerify()`. Redirect to `/dashboard/brief` on success.

`forgot-password/page.tsx`

Email input. `supabase.auth.resetPasswordForEmail()`. Resend link.

`reset-password/page.tsx`

New password + confirm. `supabase.auth.updateUser({ password })`.

5. Dashboard Layout

app/(dashboard)/layout.tsx

```
<div className="flex h-screen">
  <Sidebar />                                {/ dark navy, lg:flex hidden on mobile /}
  <main className="flex-1 overflow-y-auto bg-page pb-16 lg:pb-0">
    {children}
  </main>
  <MobileNav />                               {/ bottom tab bar, lg:hidden /}
</div>
```

Sidebar.tsx :

- `hidden lg:flex flex-col` (mobile hidden)
- Width: 196px, background: `--sidebar` (#28304a)
- Logo: LaunchMind in Syne 700, `Mind` in sage-l (#34d399)
- Nav items: active state = `bg-[--sage-d] border border-[--sage-b] text-[--sage-l]`, inactive = `text-[--s-text2] hover:bg-white/6`
- Tabler icons v3 (Icon prefix), size 16
- Plan badge at bottom
- Token balance display

MobileNav.tsx :

- `flex lg:hidden` — 5-item bottom tab bar
- `bg-sidebar`, height 56px + iOS safe-area-inset-bottom
- Items: Brief / Campaigns / Content / Ask / More

app/(dashboard)/error.tsx :

- Route group error boundary
- Renders `<ErrorState>` with retry button
- Sentry-ready: `useEffect(() => { Sentry.captureException(error); }, [error])`

app/(dashboard)/dashboard/not-found.tsx :

- 404 handler
- "Back to home" link to `/dashboard/brief`

6. Primary Dashboard Pages

`brief/page.tsx` — Morning Brief (Primary Entry Point)

State: `data: BriefResponse null`, `loading`, `recState: 'loading''ready''failed'`, `token` **Data flow:** `api.owner.brief(token)` → single fetch, no polling. 8-second hard ceiling on recommendation state. **Layout:**

Header

- └─ Greeting + narrative ("I reviewed {productName} overnight. {rec.title}")
- └─ Product name (12px, ink3)
- └─ 3-up MetricCard grid: Installs this week (+delta%) Avg CPI Active campaigns

SinceThenStrip (suppressed if only-bullet = approvals AND banner showing)

ApprovalBanner (amber, full-width, links to /approvals)

Main grid [1fr 360px on xl]

Left:

- └─ Today's recommendation (RecommendationCard or skeleton/unavailable)
- └─ Growth opportunities (up to 3 OpportunityCards)
- └─ Ask LaunchMind (AskBox with 4 starters)

Right:

- └─ Growth Brain status card
- └─ What I learned (marketing_memories, violet --ai-b left border)
- └─ Awaiting approval (if pendingApprovals.total > 0)
- └─ Recent activity (recentTimeline events)

RecommendationCard: sage border-1.5, sparkle icon, `rec.title` bold, `rec.summary` body, WhyThisPanel expandable, ConfidenceBadge, action button (sage bg → /missions). **SinceThenStrip:** Bullets from BriefResponse. If `bullets.length === 1 && bannerVisible` → return null (deduplication). **"What I learned" panel:** Top-2 marketing memories from BriefResponse. Violet `--ai-b` left border per memory. Shows `mem.memoryType` label (uppercase, ink3), `mem.body ?? mem.title` text, ConfidenceBadge. AI badge in panel header. Link → /intelligence/memory.

`opportunities/page.tsx` — Growth Backlog

Filter tabs: Active / Saved / All. Each opportunity: title, expected_impact (sage), why_now, effort/risk tags. Actions: Save / Dismiss / Create Mission. EvidenceChips via toStringArray().

`ask/page.tsx` — Ask LaunchMind

8 starter prompts. Free-text input. `api.owner.ask(q, token)` → structured answer: summary, recommendedAction (sage), evidence chips, suggestedMissionType. Full answer modal with WhyThisPanel.

`approvals/page.tsx` — Unified Approvals

Two sections: Campaign approvals + Mission approvals. Individual approve/reject per item (paid campaigns = individual approval). Uses `api.owner.brief` for pending count, then `api.campaigns` / `api.missions.approvals` for details.

`campaigns/page.tsx` — Campaigns

Channel filter pills. Table: channel icon (bare, no box) + market badge + status badge + copy preview + spend cap + CTA. Launch flow: pending_approval → approved (ApprovalCard inline) → launched. Channel icons: bare colored icons (no square background).

`experiments/page.tsx` — A/B Experiments

Create dialog (title + hypothesis). Variant cards (A/B) with metrics (impressions/clicks/installs/CPI). Start / Select Winner / Archive lifecycle. Learning summary display after winner selected.

`calendar/page.tsx` — Execution Calendar

Month view (mini grid with event pills by type color) + List view. Prev/next month navigation. Create event dialog (title + type + date). Delete authored events. Auto-scheduled events from campaigns/experiments/briefs are non-deletable (shown in gray).

`content/page.tsx` — Content Studio

Three-tab layout: Library Generate Stats.

- **Library:** Search + type/status filter pills + asset grid (AssetBlock components) + pagination.
- **Generate:** 31-type selector grid with channel filter pills + options panel (market/style selector).
- **Stats:** 4 aggregate cards + type breakdown bar chart.
- **Editor panel** (right drawer): text edit + 7 AI transforms + version history slider + publish button.

`campaigns/page.tsx`, `briefs/page.tsx`

Responsive: `p-4 sm:p-6 lg:p-8` outer padding. Full-width content area (no max-width on outer wrapper).

`missions/page.tsx` — Mission Center

Mission list with status filter pills (all/running/completed/failed). Create mission modal (type + title). Retry button on failed missions. Approval banner when `pendingApprovals.total > 0`. EmptyState when no missions.

`missions/[id]/page.tsx` — Mission Detail

Step cards (expandable — shows input/output/error). Execution log feed. Progress bar. ApprovalCard (approve/reject + note). Auto-polls every 5s when mission is running. Stops polling on completed/failed/cancelled.

analytics/page.tsx — Analytics

4 KPI cards (cross-product totals). Install funnel with per-channel breakdown. ROI table by channel. AI optimization insights panel (apply/dismiss). Weekly installs sparkline. Product tab selector. "Generate insights" button → `POST /analytics/optimize`.

reports/page.tsx — Reports

Report grid with type badge + period. Generate form (type + date range picker). Report drawer: headline callout, whatWorked / fix / insights / actions sections. JSON export download. 1–5 star feedback.

products/page.tsx — Products List

Product cards with platform badge (App Store / Play Store), market tags, campaign count. Three-dot ProductMenu: View / Archive / Edit. ArchivedSection (collapsible, shows archived products with Restore action).

7. Product Intake Wizard (7 Steps)

Progress bar: `IntakeSteps.tsx` — 7-step with active/completed/pending states.

State persisted to `sessionStorage` (INTAKE_STORAGE keys from `lib/types/intake.ts`).

Step 1: `/products/new` — URL Entry

Multi-URL input: Play Store URL + App Store URL + Website URL. At least one required. "Analyze my app →" → calls `api.products.setupStart()` → creates product + queues intake job → navigate to step 2.

Step 2: `/products/new/context` — Founder Context

5 contextual questions (ChipGroup selection UI):

- Primary marketing channel preference
- Target markets (USA / India / Both)
- Current monthly budget range
- Biggest marketing challenge
- Any specific campaigns running now

Screenshot upload (optional). "Save & continue →" → `api.products.saveIntakeStep(2, context)`.

Step 3: `/products/new/analysis` — Live Analysis

Polls `/products/intake/status` every 2s. Shows 6 progress items with animated states:

- Scraping App Store / Play Store

- Analysing reviews
- Building competitor map
- Structuring ICP
- Collecting marketing images
- Extracting brand voice

On completion: saves auto-detected `logoUrl` from `websiteMeta` to `sessionStorage`.

Step 4: `/products/new/icp` — ICP Review

Inline editable fields: target persona, pain points (chip UI with add/remove), goals, channels. "Looks right →" → `api.products.saveIntakeStep(4, icp)`.

Step 5: `/products/new/competitors` — Competitors

List of auto-discovered competitors. Actions: Confirm / Reject / Add custom. "Continue →" → `api.products.saveIntakeStep(5, competitors)`.

Step 6: `/products/new/markets` — Markets

4-market grid: USA (sage), India (amber), Canada, UK. CPI estimates per market. Amber alerts for India: "UPI install base: 400M users". Sage indicators for strong market signals. "Continue →" → `api.products.saveIntakeStep(6, markets)`.

Step 7: `/products/new/confirm` — Confirm & Launch

3-column summary: Product info + ICP + Competitors. MOAT box (brand differentiation from confirmed_icp). **Brand assets card**: 48×48 logo preview (if auto-detected), logo URL input (pre-filled), "Include logo in ads" toggle. Strategy preview (30/60/90 pillars). "Generate strategy →" → `api.products.confirmEnriched({ logoUrl, includeLogo })` → navigate to `/dashboard/products/:id/strategy`.

8. Intelligence Pages

`intelligence/layout.tsx`

Tab navigation: Growth Brain / Memory / Knowledge Graph / Market / Reviews / Timeline / Ideas / AI Audit

`intelligence/growth-brain/page.tsx`

- Multi-product switcher (shown when >1 product)
- ICP display: target persona, pain points, channels
- Brand voice panel: tone, style, vocabulary examples

- Confidence bars for each ICP dimension
- "No products" → "Add app" CTA; "No active product" → product picker
- Links to strategy and memory

`intelligence/memory/page.tsx`

Two-column layout: left memories / right learning events timeline.

- Search input + filter tabs (all/brand/product/customer/campaign/founder)
- MemoryCard: title, type badge (violet --ai), confidence bar, body preview, source, edit/archive actions
- LearningEventRow: event_type, timestamp, processed badge
- ConfidenceBar component (0-100 gradient bar)

`intelligence/knowledge/page.tsx`

- NodeGroup (collapsible by node_type): expand to see nodes
- ConfidenceDot: colored dot sized by confidence
- RelationshipRow: "Product X outperforms Channel Y" (plain English)
- Stats grid: total nodes, total edges, avg confidence
- Delete node (with confirmation)

`intelligence/market/page.tsx`

- Category benchmarks: install delta, conversion, D7 retention, top channel
- 30-day trend badges (up/down/flat with percentage)
- Competitor grid with per-product tab selector, real scraped_meta data
- Synthetic benchmark label when signalCount < 20 (seed data disclosure)
- ErrorState with retry on fetch failure

`intelligence/reviews/page.tsx`

- Overall rating star display + review count
- Sentiment breakdown: positive/negative/neutral percentages with colored bars
- Star distribution (1-5) with bar chart
- Recurring themes chips
- AI review summary callout (violet --ai border)
- Expandable review cards with sentiment filter pills
- Product tab selector
- Data from `products.scraped_meta` (no separate reviews table)

intelligence/ai-audit/page.tsx

- 4 stat cards: total requests, tokens consumed, total cost (\$), success rate
- Model breakdown grid: Sonnet vs Haiku requests/tokens/cost
- Paginated request table: time, prompt, model, status badge, input/output tokens, cost, latency, retries
- Filter by status (success/failed/timeout) + promptId
- Pagination (20 per page)

9. Settings Pages

settings/page.tsx

Left nav (170px) + content area. 7 tabs:

Tab	File	Contents
Profile	ProfileTab.tsx	Name, avatar, email (read-only), timezone
Security	SecurityTab.tsx	Password change, MFA status (always enabled), active sessions
Content types	ContentTypesTab.tsx	Default image style picker (photo/graphic/mockup), logo URL input
Voice clone	VoiceCloneTab.tsx	Upload voice sample → ElevenLabs voice clone ID
Notifications	NotificationsTab.tsx	Email notification preferences
Products	ProductsTab.tsx	List products, archive/restore from settings
Account	AccountManagementTab.tsx	Delete account (type "DELETE" to confirm), data export

settings/billing/page.tsx

Plan comparison grid (2-col at normal width, grid-cols-2 xl:grid-cols-4 for token top-ups). Current plan highlighted with indigo border. Upgrade/downgrade CTA. Token top-up packs.

settings/usage/page.tsx

Token usage history chart. Current balance. Monthly token burn rate.

workspaces/page.tsx (Studio-gated)

Studio plan required. Workspace list (create/delete). Brand voice preview per workspace.

workspaces/[id]/page.tsx

Workspace detail: name, client name, member list. Invite by email. Remove member. Role management (owner/admin/member).

10. Components Library

All in `components/launchmind/`. Every component uses CSS variable design tokens. No inline dark colors.

Sidebar.tsx

```
// hidden lg:flex flex-col – desktop only
// Mobile: MobileNav handles it
// Active item: bg-[var(--sage-d)] border border-[var(--sage-b)] text-[var(--sage-l)]
// Inactive: text-[var(--s-text2)] hover:bg-white/6
// Icons: @tabler/icons-react v3, size={16}, outline only
```

MobileNav.tsx

```
// flex lg:hidden – mobile only
// Position: fixed bottom-0, full width
// bg-sidebar (dark navy), height 56px
// 5 items: Brief / Campaigns / Content / Ask / More
// style={{ paddingBottom: 'env(safe-area-inset-bottom)' }} – iOS support
// IMPORTANT: use className="flex lg:hidden" not inline display style
// (inline style overrides Tailwind lg:hidden – always use Tailwind class)
```

MetricCard.tsx

```
interface MetricCardProps {
  label: string;
  value: string | number;
  delta?: string; // "+12%" auto-colors sage; "-3%" auto-colors danger
  sub?: string; // secondary context line
  accent?: 'sage'|'indigo'|'amber'|'danger';
  insight?: string; // violet (--ai) AI interpretation text
  confidence?: number; // 0-100, shows badge if insight provided
}
// bg-surface border border-[--border] rounded-[10px] p-[14px_16px]
// value: font-mono 22px
// delta: font-mono 11px auto-colored by + / - prefix
```

AIBadge.tsx

```
// "⚡ AI generated" – violet bg (--ai-d), border (--ai-b), text (--ai)
// font-size: 10px, padding: '2px 7px', border-radius: var(--r3)
// Use ONLY for AI-generated content provenance
// NEVER use violet for buttons or interactive elements
```

ConfidenceBadge.tsx

```
// value: 0-100 (normalized – always pass as 0-100, not 0-1)
// Renders as: "82%" in violet badge (--ai-d / --ai-b / --ai)
// Used in: RecommendationCard, OpportunityCard, MemoryCard, "What I learned" panel
```

EvidenceChips.tsx

```
interface EvidenceChipsProps {
  chips: unknown; // ALWAYS use unknown – jsonb can be anything
}
// Internally calls toStringArray(chips) for safe coercion
// Renders each string as a small pill: bg-raised border border-[--border2] text-ink3
```

WhyThisPanel.tsx

```
interface WhyThisPanelProps {
  signal: string; // whyNow
  evidence: unknown; // toStringArray() internally
  confidence: number; // 0-100
  risk?: string;
  source?: string;
}
// Expandable accordion (collapsed by default)
// Header: "Why now?" with ChevronDown/Up
// Body: signal text, evidence chips, confidence badge, risk/source if provided
```

Button.tsx

```
// 4 variants: solid (sage bg), ghost (border + ink2), sage (sage-d bg + sage-b border), danger
// 3 sizes: sm (px-2.5 py-1 text-[11px]), md (px-3 py-1.5 text-[12px]), lg (px-4 py-2 text-[13px])
// All variants use rounded-[var(--r2)]
```

AssetBlock.tsx

```
// Renders all 31 content asset types
// Text assets: markdown display, edit button
// Video assets: video player (if videoUrl), script text
// Visual assets: image preview, style selector pills (📷 Photo / 🎨 Graphic / 📱 Mockup)
// Audio: audio player (if audioUrl), transcript
// Actions: download, regenerate, edit, style override
// onGenerateImage(id: string, style?: ImageStyle) callback
```

IntakeSteps.tsx

```
// 7-step progress bar
// completed: sage checkmark + full color
// active: sage border + bold label
// pending: ink3 color + lighter
```

ProductMenu.tsx

```
// Three-dot (IconDots) overflow menu per product card
// Options: View / Edit / Archive / Restore (context-dependent)
// Uses: IconDots, IconEye, IconPencil, IconArchive, IconArchiveOff
```

EmptyState.tsx, **ErrorState.tsx**, **LoadingState.tsx**

The state trio. Every data-dependent section uses one of these three.

```
<EmptyState title="No campaigns yet" description="..." action={{ label: "Create", href: "/"... }} />
<ErrorState title="Couldn't load" description="..." onRetry={() => refetch()} />
<LoadingState /> // pulsing skeleton
```

PageShell.tsx

```
<PageShell title="Campaigns" subtitle="Manage your active campaigns">
  {children}
</PageShell>
// Renders: page title (Syne), subtitle, optional breadcrumb
```

11. Design System v1.0

CSS Variables (`app/globals.css`)

```
:root {  
  / Surfaces /  
  --page:      #f2f3f6;  
  --surface:   #ffffff;  
  --raised:    #ecef3;  
  --sidebar:   #28304a;  
  --sidebar-2: #323c58;  
  
  / Borders /  
  
  --border:    rgba(27,31,46,0.07);  
  --border2:   rgba(27,31,46,0.12);  
  --s-border:  rgba(255,255,255,0.07);  
  
  / Sidebar text /  
  
  --s-text:    rgba(255,255,255,0.88);  
  --s-text2:   rgba(255,255,255,0.42);  
  --s-text3:   rgba(255,255,255,0.22);  
  
  / Ink (text) /  
  
  --ink:       #1b1f2e;  
  --ink2:      #626880;  
  --ink3:      #9ca4be;  
  
  / Sage – ALL interactive actions, primary CTA, success /  
  
  --sage:      #059669;  
  --sage-l:    #34d399;  
  --sage-d:    rgba(5,150,105,0.12);  
  --sage-b:    rgba(5,150,105,0.28);  
  
  / Indigo – accent, current plan badge /  
  
  --indigo:    #4f46e5;  
  --indigo-d:  rgba(79,70,229,0.10);  
  --indigo-b:  rgba(79,70,229,0.22);  
  
  / Amber – India market, warnings /  
  
  --amber:     #d97706;  
  --amber-d:   rgba(217,119,6,0.10);  
  --amber-b:   rgba(217,119,6,0.22);
```

```

/ Danger – errors, negative delta, kill signals /

--danger:    #dc2626;
--danger-d:   rgba(220,38,38,0.09);
--danger-b:   rgba(220,38,38,0.22);

/ AI – provenance ONLY. Border/badge/text. Never button. Never gradient fill. /

--ai:        #7c5cff;
--ai-d:       rgba(124,92,255,0.10);
--ai-b:       rgba(124,92,255,0.22);
--ai-l:       #a78bfa;

/ Radius /

--r:          10px;
--r2:         6px;
--r3:         4px;
--r-full:     9999px;

/ Elevation /

--e1:         0 1px 3px rgba(0,0,0,0.07);
--e2:         0 4px 12px rgba(0,0,0,0.09);
--e3:         0 8px 24px rgba(0,0,0,0.12);

/ Motion /

--dur-fast:   120ms;
--dur:        180ms;
--dur-slow:   280ms;
--ease:       cubic-bezier(0.4, 0, 0.2, 1);
--ease-out:   cubic-bezier(0, 0, 0.2, 1);
}

@media (prefers-reduced-motion: reduce) {

  , ::before, *::after {
    animation-duration: 0.01ms !important;
    transition-duration: 0.01ms !important;
  }
}

```

Typography

Usage	Font	Size	Weight
-------	------	------	--------

Body text	DM Sans	13px	400
Body line-height	1.5		
Headings, sidebar logo, section titles	Syne	varies	600–800
Metrics, token counts, data values, code	DM Mono	varies	400–500

Google Fonts loaded: Syne:wght@400;500;600;700;800 + DM+Sans:wght@300;400;500 + DM+Mono:wght@400;500

Component Conventions

```
/ Card /
background: var(--surface);
border: 1px solid var(--border);
border-radius: var(--r);          / 10px /
padding: 14px 16px;

/ Card featured (recommendation) /

border: 1.5px solid var(--sage-b);

/ Input /

background: var(--raised);
border: 1px solid var(--border2);
border-radius: var(--r2);          / 6px /
padding: 8px 12px;
/ focus: border-[--sage-b], ring-2 ring-[--sage-d] /

/ Button solid /

background: var(--sage);
color: white;
border-radius: var(--r2);

/ Button ghost /

border: 1px solid var(--border2);
color: var(--ink2);
/ hover: background: var(--raised) /

/ Button sage (tint) /

background: var(--sage-d);
border: 1px solid var(--sage-b);
color: var(--sage);
border-radius: var(--r2);

/ Sidebar nav item /

color: var(--s-text2);
border-radius: var(--r2);
margin: 0 6px;
/ hover: background: rgba(255,255,255,0.06) /
/ active: background: var(--sage-d), border: 1px solid var(--sage-b), color: var(--sage-l) /

/ Metric block /
```

```
background: var(--raised);
border-radius: var(--r2);
padding: 11px 13px;

/ Topbar /

background: var(--surface);
border-bottom: 1px solid var(--border);
```

Badge Conventions

Type	Background	Border	Text color
USA market	<code>--sage-d</code>	<code>--sage-b</code>	<code>#046c4e</code>
India market	<code>--amber-d</code>	<code>--amber-b</code>	<code>#92400e</code>
Draft	<code>--raised</code>	<code>--border2</code>	<code>--ink2</code>
Active/Success	<code>--sage-d</code>	<code>--sage-b</code>	<code>--sage</code>
Pending	<code>--amber-d</code>	<code>--amber-b</code>	<code>--amber</code>
Error/Pausing	<code>--danger-d</code>	<code>--danger-b</code>	<code>--danger</code>
Accent/Indigo	<code>--indigo-d</code>	<code>--indigo-b</code>	<code>--indigo</code>
AI	<code>--ai-d</code>	<code>--ai-b</code>	<code>--ai</code>

Icons (`@tabler/icons-react` v3)

- **Prefix:** `Icon` (NOT `Tb` — that's v2)
- **Style:** Outline only, never filled
- **size prop:** accepts `string | number` (`size={16}` or `size="16"`)

Commonly used icons:

IconLayoutDashboard	IconSparkles	IconBolt
IconRoute	IconSpeakerphone	IconFileAnalytics
IconPlug	IconCreditCard	IconSettings
IconCheck	IconAlertCircle	IconShieldCheck
IconArrowRight	IconBrandWhatsapp	IconBrandFacebook
IconBrandGoogle	IconBrandLinkedin	IconMail
IconLock	IconDownload	IconDots
IconArchive	IconEye	IconPencil
IconChevronDown	IconChevronUp	IconSearch
IconX	IconRefresh	IconPlayerPlay

Tailwind Config

Extended from default in `tailwind.config.ts` :

```
colors: {
  page: 'var(--page)',
  surface: 'var(--surface)',
  raised: 'var(--raised)',
  sidebar: 'var(--sidebar)',
  ink: 'var(--ink)',
  ink2: 'var(--ink2)',
  ink3: 'var(--ink3)',
  sage: 'var(--sage)',
  indigo: 'var(--indigo)',
  amber: 'var(--amber)',
  danger: 'var(--danger)',
  ai: { DEFAULT: 'var(--ai)', d: 'var(--ai-d)', b: 'var(--ai-b)', l: 'var(--ai-l)' },
}
fontSize: {
  lg: '18px',
  xl: '24px',
  '2xl': '32px',
}
transitionDuration: { fast: '120ms', DEFAULT: '180ms', slow: '280ms' }
boxShadow: { e1: 'var(--e1)', e2: 'var(--e2)', e3: 'var(--e3)' }
```

12. API Client (`lib/api.ts`)

All namespaces and key methods:

```
// Core pattern: every call takes a token param
api.owner.brief(token): Promise<BriefResponse>
api.owner.opportunities(token): Promise<{ opportunities: Opportunity[] }>
api.owner.ask(question, token): Promise<{ answer: AskResponse }>
api.owner.results(token): Promise<ResultsSummary>
api.owner.notifications(token): Promise<{ notifications: Notification[]; unreadCount: number }>

api.products.list(token): Promise<Product[]>

api.products.get(id, token): Promise<Product>
api.products.create(body, token): Promise<Product>
api.products.confirm(id, body, token): Promise<Product>
api.products.confirmEnriched(id, { logoUrl, includeLogo }, token): Promise<Product>
api.products.generateStrategy(id, token): Promise<void>
api.products.setupStart(urls, token): Promise<{ productId: string }>
api.products.saveIntakeStep(step, data, token): Promise<void>
api.products.completeIntake(token): Promise<Product>
api.products.intakeStatus(token): Promise<IntakeStatus>
api.products.archive(id, reason, token): Promise<void>
api.products.restore(id, token): Promise<void>
api.products.activate(id, token): Promise<void>
api.products.generateImage(assetId, token, style?): Promise<ContentAsset>

api.campaigns.create(body, token): Promise<Campaign>

api.campaigns.list(token): Promise<Campaign[]>
api.campaigns.launch(id, token): Promise<void>
api.campaigns.schedule(id, scheduledAt, token): Promise<void>
api.campaigns.cancel(id, token): Promise<void>

api.studio.generate(body, token): Promise<ContentAsset>

api.studio.listAssets(filters, token): Promise<{ assets: ContentAsset[]; total: number }>
api.studio.getAsset(id, token): Promise<ContentAsset>
api.studio.transform(id, transformType, token): Promise<ContentAsset>
api.studio.publish(id, channel, token): Promise<void>
api.studio.archive(id, token): Promise<void>
api.studio.restore(id, token): Promise<void>
api.studio.stats(token): Promise<StudioStats>

api.missions.create(body, token): Promise<Mission>

api.missions.list(token): Promise<Mission[]>
api.missions.get(id, token): Promise<{ mission: Mission; steps: MissionStep[] }>
api.missions.approvals(token): Promise<MissionApproval[]>
api.missions.cancel(id, token): Promise<void>
api.missions.retry(id, token): Promise<void>
api.missions.respond(id, stepId, status, note, token): Promise<void>

api.memory.list(token): Promise<MarketingMemory[]>
```

```
api.memory.search(query, token): Promise<MarketingMemory[]>
api.memory.ingest(event, token): Promise<void>

api.knowledge.graph(token): Promise<KnowledgeGraph>

api.ai.context(productId, token): Promise<AIContextPackage>
api.ai.audit(filters, token): Promise<{ requests: AIRequest[]; total: number }>
api.ai.auditStats(token): Promise<AIAuditStats>

api.analytics.summary(token): Promise<AnalyticsSummary>

api.analytics.kpi(productId, token): Promise<KPIPoint[]>
api.analytics.insights(token): Promise<OptimizationInsight[]>

api.recommendations.list(token): Promise<Recommendation[]>

api.recommendations.generate(productId, token): Promise<Recommendation[]>
api.recommendations.convert(id, token): Promise<Mission>

api.benchmarks.get(category, market, token): Promise<BenchmarkResult>

api.benchmarks.trends(category, market, token): Promise<TrendSummary>

api.calendar.list(month, token): Promise<CalendarEvent[]>

api.experiments.list(token): Promise<Experiment[]>
api.experiments.winner(id, variantLabel, token): Promise<void>

api.workspaces.list(token): Promise<Workspace[]>

api.billing.status(token): Promise<BillingStatus>
api.settings.getContentPreferences(token): Promise<ContentPreferences>
api.settings.updateContentPreferences(body, token): Promise<ContentPreferences>
api.founders.me(token): Promise<Founder>
api.founders.deleteAccount(token): Promise<void>
api.founders.export(token): Promise<Blob>
```

BriefResponse (key type):

```
export interface BriefResponse {
  founder: { name: string; plan: string };
  product: { id: string; name: string; platform: string } | null;
  recommendation: {
    title: string; summary: string; whyNow: string;
    confidence: number; evidence: string[]; action: string; missionType: string | null;
  } | null;
  pendingApprovals: { total: number; items: Array<{ id, type, title, preview, missionId }> };
  opportunities: Opportunity[];
  recentTimeline: TimelineEvent[];
  growthBrain: { hasStrategy: boolean; confidence: number null; lastUpdated: string null };
  metrics: { weeklyInstalls: number null; cpi: number null; activeCampaigns: number; weekOverWeekIns
  memories: Array<{ id: string; title: string; body: string | null; memoryType: string; confidence:
```

13. Utility Libraries

lib/coerce.ts

Defensive coercion for JSONB fields (never throw):

```
export function toStringArray(value: unknown): string[]
// Handles: string[] ✓, JSON.stringify'd array ✓, null/undefined → [], objects → values, scalars →

export function toRecord(value: unknown): Record<string, unknown>

// Handles: object ✓, JSON string ✓, null/undefined → {}, arrays → {}
```

Critical usage: `evidence` field in `saved_opportunities` can be any JSONB shape. Always use `toStringArray(opp.evidence)` before rendering `EvidenceChips`. Never trust the TypeScript type alone.

lib/supabase/client.ts

```
export function createClient(): SupabaseClient
// Browser-side Supabase client (anon key)
// Uses @supabase/ssr get/set/remove (NOT getAll/setAll – that's 0.2.x API, silently breaks auth)
```

middleware.ts

Next.js edge middleware. Runs before every request.

- Unauthenticated → /login
- Authenticated + hitting / → /dashboard/brief
- Authenticated + hitting /login → /dashboard/brief

14. Key Patterns & Rules

No max-width on page outer wrapper

```
// CORRECT: full-width content area
<div className="p-4 sm:p-6 lg:p-8">
  {/ content fills full available width (viewport - 196px sidebar) /}
</div>

// WRONG: never do this

<div className="max-w-5xl mx-auto p-6">
```

Fresh JWT on every user action

```
// CORRECT: fetch fresh session inside action handler
const handleSubmit = async () => {
  const supabase = createClient();
  const { data: { session } } = await supabase.auth.getSession();
  if (!session) { window.location.href = '/login'; return; }
  await api.products.generateStrategy(id, session.access_token);
};

// WRONG: using a stale token stored in state from page load (15-min JWT expires)

// const { token } = useAuth(); // ← may be stale if user sits on page > 15 min
```

Inline style vs Tailwind responsive

```
// CORRECT: Tailwind responsive class controls display
<div className="flex lg:hidden"> // MobileNav: hidden on desktop

// WRONG: inline style overrides Tailwind responsive variants

// style={{ display: 'flex' }} className="lg:hidden" // lg:hidden won't work
```

JSONB field safety

```
// CORRECT: always coerce before use
import { toStringArray } from '@lib/coerce';
<EvidenceChips chips={opp.evidence} /> // EvidenceChips uses toStringArray internally

// WRONG: trusting TypeScript type for DB-sourced JSONB

// opp.evidence.map(...) // ← crashes if DB returns non-array
```

Supabase session in intake wizard

```
// All 7 intake pages: fetch fresh session inside every action handler
// (prevents stale 15-min JWT from causing 401 at button-click time)
const handleContinue = async () => {
  const { data: { session } } = await createClient().auth.getSession();
  if (!session) { window.location.href = '/login'; return; }
  await api.products.saveIntakeStep(stepNum, data, session.access_token);
  router.push(nextStep);
};
```

Continue to: [LMJuly18-05-Intelligence-Agents.md](#)