RAJALAKSHMI ENGINEERING COLLEGE

Vijay V 251801378-2025-AIDS

V2

Started on	Monday, 24 August 2026, 8:39 PM
State	Finished
Completed on	Monday, 24 August 2026, 8:40 PM
Time taken	46 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b)
{
    return (*(int *)a - *(int *)b);
}

int main()
{
    int n;
    scanf("%d", &n);

    int A[n], B[n];

    // Read first array
    for (int i = 0; i < n; i++)
    {
        scanf("%d", &A[i]);
    }

    // Read second array
    for (int i = 0; i < n; i++)
    {
        scanf("%d", &B[i]);
    }

    // Sort both arrays in ascending order
    qsort(A, n, sizeof(int), compare);
    qsort(B, n, sizeof(int), compare);

    int sum = 0;

    // Pair smallest A with largest B
    for (int i = 0; i < n; i++)
    {
        sum = sum + A[i] * B[n - 1 - i];
    }

    printf("%d", sum);

    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course