

PRACTICAL DBMS

NAME: K.VIJAYALAKSHMI

REG.NO:192511189

COURSE CODE: CSA0503

COURSE NAME: DATABASE MANAGEMENT SYSTEMS

EXPERIMENT NO:5 SELECT with various clause – WHERE, pattern matching

AIM:

To view the records from the tables using SELECT commands with WHERE Clause and Pattern matching.

DESCRIPTION:

The SELECT statement allows you to get the data from tables. A table consists of rows and columns like a

spreadsheet. Often, you want to see a subset rows, a subset of columns, or a combination of two. The result of the

SELECT statement is called a result set that is a list of rows, each consisting of the same number of columns.

SELECT:

SELECT column_1, column_2, ...

FROM table_1

[INNER | LEFT | RIGHT] JOIN table_2 ON conditions

WHERE conditions

GROUP BY column_1

HAVING group_conditions

ORDER BY column_1

LIMIT offset, length;

The SELECT statement consists of several clauses as explained in the following list:

- SELECT followed by a list of comma-separated columns or an asterisk (*) to indicate that you want to return all columns.
- FROM specifies the table or view where you want to query the data.
- JOIN gets related data from other tables based on specific join conditions.

- WHERE clause filters row in the result set.
- GROUP BY clause groups a set of rows into groups and applies aggregate functions on each group.
- HAVING clause filters group based on groups defined by GROUP BY clause.
- ORDER BY clause specifies a list of columns for sorting.
- LIMIT constrains the number of returned rows.

```
mysql> select name,gender from student;
+-----+-----+
| name  | gender |
+-----+-----+
| swetha | f      |
| harini | f      |
+-----+-----+
2 rows in set (0.10 sec)
```

```
mysql> select * from student;
+-----+-----+-----+
| regno  | gender | name  |
+-----+-----+-----+
| 192435163 | m      | manoj |
| 192453678 | m      | sanoop |
| 192511149 | f      | swetha |
| 192521245 | f      | harini |
+-----+-----+-----+
4 rows in set (0.01 sec)
```

```
mysql> select * from student where gender='f';
+-----+-----+-----+
| regno  | gender | name  |
+-----+-----+-----+
| 192511149 | f      | swetha |
| 192521245 | f      | harini |
+-----+-----+-----+
2 rows in set (0.01 sec)
```

LIKE:

- The LIKE operator is commonly used to select data based on patterns. Using the LIKE operator in the right way is essential to increase the query performance.

➤ The LIKE operator allows you to select data from a table based on a specified pattern. Therefore, the LIKE

operator is often used in the WHERE clause of the SELECT statement.

➤ MySQL provides two wildcard characters for using with the LIKE operator, the percentage % and underscore _ .

➤ The percentage (%) wildcard allows you to match any string of zero or more characters.

➤ The underscore (_) wildcard allows you to match any single character.

```
mysql> select * from student where name like 's%';
+-----+-----+-----+
| regno   | gender | name   |
+-----+-----+-----+
| 192453678 | m      | sanoop |
| 192511149 | f      | swetha |
+-----+-----+-----+
2 rows in set (0.02 sec)
```

RESULT:

The records from the tables are displayed using SELECT commands with WHERE Clause and Pattern matching.