

<b>Status</b>	Finished
<b>Started</b>	Saturday, 1 November 2025, 6:44 PM
<b>Completed</b>	Saturday, 1 November 2025, 7:25 PM
<b>Duration</b>	41 mins 16 secs

Question **1**

Correct

The k-digit number N is an Armstrong number if and only if the k-th power of each digit sums to N.

Given a positive integer N, return true if and only if it is an Armstrong number.

Example 1:

Input:

153

Output:

true

Explanation:

153 is a 3-digit number, and  $153 = 1^3 + 5^3 + 3^3$ .

Example 2:

Input:

123

Output:

false

Explanation:

123 is a 3-digit number, and  $123 \neq 1^3 + 2^3 + 3^3 = 36$ .

Example 3:

Input:

1634

Output:

true

Note:

$1 \leq N \leq 10^8$

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<math.h>
3 int main()
4 {
5     int n;
6     scanf("%d",&n);
7     int x=0,n2=n;
8     while(n2!=0)
9     {
10        x++;
11        n2=n2/10;}
12     int sum=0;
13     int n3=n,n4;
14     while(n3!=0)
15     {
16        n4=n3%10;
17        sum=sum+pow(n4,x);
18        n3=n3/10;
19     }
20     if(n==sum){
21         printf("true");}
22     else{
23         printf("false");}
24     return 0;
25 }
```

	Input	Expected	Got	
✓	153	true	true	✓
✓	123	false	false	✓

Passed all tests! ✓

Question **2**

Correct

Take a number, reverse it and add it to the original number until the obtained number is a palindrome.

**Constraints** $1 \leq \text{num} \leq 999999999$ **Sample Input 1**

32

**Sample Output 1**

55

**For example:**

Input	Result
32	55
1234	5555

**Answer:** (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main(){
3      int rn,n,nt=0,i=0;
4      scanf("%d",&n);
5      do{
6          nt=n;
7          rn=0;
8          while(n!=0)
9          {
10             rn=rn*10 + n%10;
11             n=n/10;
12         }
13         n=nt+rn;
14         i++;
15     }
16     while(rn!=nt||i==1);
17     printf("%d",rn);
18     return 0;
19 }
20
```



	Input	Expected	Got	
✓	32	55	55	✓
✓	1234	5555	5555	✓

Passed all tests! ✓



Question **3**

Correct

Maya, a student in an arts and crafts class, wants to create a pattern using stars (\*) in a specific format. She plans to use a program to help her construct the pattern.

Write a program that takes an integer as input and constructs the following pattern using nested for loops.

Input: 5

Output:

```
*
* *
* * *
* * * *
* * * * *
* * * *
* * *
* *
*
*
```

**Answer:** (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int n,i,j;
5      scanf("%d",&n);
6      for(int i=1; i<=n; i++){
7          for(int j=1;j<=i;j++)
8              printf("* ");
9              printf("\n");
10     }
11     for(i=n-1;i>=1;i--){
12         for(j=1;j<=i;j++)
13             printf("* ");
14             printf("\n");
15     }
16     }
17     return 0;
18 }
```



	Input	Expected	Got	
✓	5	<pre>* *</pre>	<pre>* *</pre>	✓

Passed all tests! ✓