### CP321 Data Visualization

Jiashu (Jessie) Zhao

## Visualizing data: Mapping data onto aesthetics

- Position Coordinate systems
- Color Scales
- Shape Markers in Python
- Line Type


### Data Visualization in Practice: Color Scales

- There are three fundamental use cases for color in data visualizations:
  - (i) distinguish groups of data from each other
  - (ii) represent data values
  - (iii) highlight

#### Color as a tool to distinguish

- We frequently use color to distinguish discrete items or groups that do not have an intrinsic order, such as different countries on a map or different manufacturers of a certain product.
- In this case, we use a *qualitative* color scale. Such a scale contains a finite set of specific colors that are chosen to look clearly distinct from each other while also being equivalent to each other.
- The second condition requires that no one color should stand out relative to the others.


# Okabe Ito ColorBrewer Dark2 ggplot2 hue



### Color to represent data values


- Color can also be used to represent data values, such as income, temperature, or speed.
- In this case, we use a sequential color scale. Such a scale contains a sequence of colors that clearly indicate
  - (i) which values are larger or smaller than which other ones and
  - (ii) how distant two specific values are from each other.
- Sequential scales can be based on a single hue (e.g., from dark blue to light blue) or on multiple hues (e.g., from dark red to light yellow).

# ColorBrewer Blues Heat Viridis




- In some cases, we need to visualize the deviation of data values in one of two directions relative to a neutral midpoint.
- The appropriate color scale in this situation is a *diverging* color scale.
- Diverging scales need to be balanced, so that the progression from light colors in the center to dark colors on the outside is approximately the same in either direction.


## CARTO Earth ColorBrewer PiYG Blue-Red



- Color as a tool to highlight
- There may be specific categories or values in the dataset that carry key information about the story we want to tell, and we can strengthen the story by emphasizing the relevant figure elements to the reader.
- This effect can be achieved with accent color scales, which are color scales that contain both a set of subdued colors and a matching set of stronger, darker, and/or more saturated colors.

# Okabe Ito Accent Grays with accents ColorBrewer Accent






#### Color in Python

#### Matplotlib Recognizes:

- A single letter string, i.e. one of {'b', 'g', 'r', 'c', 'm', 'y', 'k', 'w'};
- An RGB or RGBA tuple of float values in [0, 1] (e.g. (0.1, 0.2, 0.5) or (0.1, 0.2, 0.5, 0.3)). RGBA is short for Red, Green, Blue, Alpha;
- A hex RGB or RGBA string (e.g., '#0F0F0F' or '#0F0F0F0F');
- A string representation of a float value in [0, 1] inclusive for gray level (e.g., '0.5');
- a X11/CSS4 ("html") color name, e.g. "blue";
- A name from the <u>xkcd color survey</u>, prefixed with 'xkcd:' (e.g., 'xkcd:sky blue');
- a "Cn" color spec, i.e. 'C' followed by a number, which is an index into the default property
  cycle (matplotlib.rcParams['axes.prop\_cycle']); the indexing is intended to occur at
  rendering time, and defaults to black if the cycle does not include color.
- Oneof {'tab:blue', 'tab:orange', 'tab:green', 'tab:red', 'tab:purple', 'tab:brown', 'tab:pink', 'tab:gray', 'tab:olive', 'tab:cyan'} which are the Tableau Colors from the 'tab10' categorical palette (which is the default color cycle);

### Markers in python matplotlib


un-filled markers








#### filled markers





### Line Styles in python matplotlib

