```
//Gaurav Rai 1706019
#include<bits/stdc++.h>
using namespace std;
class PCB
    public :
    static float avgWt,avgTat,avgCt;
    int pid;
    int pri;
    bool vis;
    float bt,at,ct,tat,wt;
    bool operator ==(const PCB p) const
        if(at!=p.at || bt!=p.bt ||pri!=p.pri)
        return false;
        return true;
    }
};
float PCB::avgWt =0;
float PCB::avgTat =0;
float PCB::avgCt =0;
class less_than_at
{
    public:
    inline bool operator() (const PCB& struct1, const PCB& struct2)
        return (struct1.at < struct2.at);</pre>
};
class less_than_bt
{
    public:
    inline bool operator() (const PCB& struct1, const PCB& struct2)
        return (struct1.bt < struct2.bt);</pre>
};
void SJF(deque<PCB> &P,deque<PCB> &ganttChart,int n)
{
    P[0].ct=P[0].at+P[0].bt;
    P[0].tat=P[0].ct-P[0].at;
    P[0].wt=0;
    P[0].vis=true;
    ganttChart.push_back(P[0]);
    int countt=1;
    P.pop_front();
    while(countt<n)</pre>
    {
```

```
vector<PCB> t;bool flag=false;
        for(int i=0;i<P.size();i++)</pre>
             if(P[i].at<=temp.ct)</pre>
             { t.push_back(P[i]); flag=true; }
        if(flag)
             sort(t.begin(),t.end(),less_than_bt());
             int i=0;
             if(t[0].at<=temp.ct)</pre>
             {
                 t[i].ct=temp.ct+t[i].bt;
                 t[i].tat=t[i].ct-t[i].at;
                 t[i].wt=t[i].tat-t[i].bt;
             }
            else
             {
                 t[i].ct=t[i].at+t[i].bt;
                 t[i].tat=t[i].ct-t[i].at;
                 t[i].wt=t[i].tat-t[i].bt;
             ganttChart.push_back(t[i]);
             for(i=0;i<P.size();i++)</pre>
             {
                 if(t[0]==P[i])
                 {
                     flag=false;
                     break;
                 }
             }
             if(flag)
             cout<<"Error\n";</pre>
             P.erase(P.begin()+i);
        }
        else
             int i=0;t.push_back(P[0]);
             t[i].ct=t[i].at+t[i].bt;
             t[i].tat=t[i].ct-t[i].at;
             t[i].wt=t[i].tat-t[i].bt;
             ganttChart.push_back(t[i]);
            P.pop_front();
        }
             countt++;
    }
}
int main()
```

PCB temp=ganttChart.back();

```
int n;
    cout<<"Enter the number of processes ...";cin>>n;
    deque<PCB> P(n);
    for(int i=0;i<n;i++)</pre>
        cout<<"Process Id : ";cin>>P[i].pid;
        cout<<"Arrival Time : ";cin>>P[i].at;
        cout<<"Burst Time : ";cin>>P[i].bt;
        P[i].vis=false;
    sort(P.begin(),P.end(),less_than_at());
    deque<PCB> ganttChart;
    SJF(P,ganttChart,n);
    P.clear();
    copy(ganttChart.begin(), ganttChart.end(), back_inserter(P));
    for(int i=0;i<P.size();i++)</pre>
        PCB::avgWt +=P[i].wt;
        PCB::avgTat+=P[i].tat;
        PCB::avgCt+=P[i].ct;
    }
    PCB::avgWt/=P.size();
    PCB::avgTat/=P.size();
    PCB::avgCt/=P.size();
    cout<<"\tSJF(Non Preemptive) CPU SCHEDULING\n";</pre>
    cout<<"PID\tAT\tBT\tCT\tTAT\tWT\n";</pre>
    for(int i=0;i<n;i++)</pre>
cout<<P[i].pid<<"\t"<<P[i].at<<"\t"<<P[i].bt<<"\t"<<P[i].ct<<"\t"<<P[i].tat<<"\t"<<
P[i].wt<<endl;
    cout<<"\tAverage Waiting Time : "<<PCB::avgWt<<endl;</pre>
    cout<<"\tAverage TurnAround Time : "<<PCB::avgTat<<endl;</pre>
    cout<<"\tAverage Completion Time : "<<PCB::avgCt<<endl;</pre>
    return 0;
}
```