RISK LENS

Adaptive Risk Monitoring Platform

DESIGN SPECIFICATION

Engineering handoff for the RiskLens design system, responsive screens, financial risk visualizations and prototype behavior.

Document control	
Version	2.1
Primary source	RiskLens Figma file
Figma file key	xDDU1m6ZtyvMkoeFlhv4wh
Prepared for	Zetheta Algorithms Private Limited
Product status	Fictional fintech product; non-production data

This is a working handoff: it records decisions the frontend team should not have to infer from the canvas.

Design source: https://www.figma.com/design/xDDU1m6ZtyvMkoeFlhv4wh

1. Document purpose and scope

This document converts the current RiskLens Figma source into an implementation reference. It covers reusable UI, responsive behavior, risk-data presentation, interaction rules and validation handoff.

Current Figma structure

Page	Purpose	State
01_Cover	Project overview and consolidated index	Complete
02_Design_Tokens	Variables, styles and breakpoint contract	Complete
03_Atoms	40 reusable component nodes with state examples	Complete
04_Molecules	Reusable compositions and nested instances	Complete
05_Organisms	Financial and enterprise widgets	Complete
06_Templates	Persona-oriented page compositions	Complete
07_Desktop	12 core screens at 1440 × 900	Complete
08_Tablet	12 core screens at 768 × 1024	Complete
09_Mobile	12 core screens at 375 × 812	Complete
10_Prototype_Flows	Three core interaction flows	Complete
11_Documentation	Engineering handoff reference	Complete
12_Exploration	Design directions and decision matrix	Complete

2. Product architecture and UX principles

RiskLens is organized around decision speed. The interface answers the immediate risk question first and exposes deeper evidence only when the user asks for it.

Layer	User question	UI response
Glance	How risky are we right now?	Primary KPIs, limit status, timestamp, decision summary
Investigation	What changed and where?	Risk drivers, trends, alerts and drill-down controls
Deep Dive	Why did it change and what supports the decision?	Attribution, scenario detail, event timeline and audit evidence

Persona contracts

Persona	Primary goal	Density	Interaction emphasis
Junior Risk Analyst	Verify daily risk and anomalies	Moderate	Guidance, contextual help and clear next action
Senior Portfolio Manager	Investigate breaches and decisions	High	Fast comparisons, drill-down and keyboard efficiency
Chief Risk Officer	Understand firm-level posture and report	Low / summary	Executive trends, exceptions, presentation-ready output
Compliance Officer	Investigate and evidence breaches	High / audit	Chronology, ownership, acknowledgement and mandatory comments

3. Design tokens

RiskLens uses semantic tokens so screens share the same visual language without hard-coding values into each component.

Color

Token	Value	Use
Background	#0B0F14	Application canvas
Surface	#111820	Primary cards / panels
Surface Elevated	#17212C	Elevated controls
Border	#2A3644	Dividers / boundaries
Text Primary	#F2F5F7	Primary text
Text Secondary	#9BA8B5	Supporting text
Accent	#3DD6E8	Interaction / data highlight
Success	#43D17A	Positive / compliant
Warning	#F2B84B	Watch / caution
Critical	#FF5C6C	Breach / critical

Spacing, sizing and breakpoints

Token	Value	Use
Space / 1	4 px	Micro spacing
Space / 2	8 px	Base rhythm
Space / 3	12 px	Compact spacing
Space / 4	16 px	Component spacing
Space / 5	24 px	Section / card spacing
Control	40 px	Standard control height
Touch	44 px	Primary touch target
Radius	6 / 10 / 14 px	Small / medium / large surfaces
Breakpoints	375 / 768 / 1440 px	Mobile / tablet / desktop

4. Typography and visual hierarchy

Inter is the product UI family. The report uses the same simple hierarchy to keep the handoff readable without turning every label into a heading.

Style	Use	Level
Display	Hero / large statements	Highest
Heading	Page titles / major sections	High
Section	Card headings	Medium-high
Body	Labels / explanation	Medium
Caption	Timestamps / metadata	Low

Type rules

Use semibold for page titles, decision values and action labels. Use regular weight for supporting text. Keep numerical risk values visually stable. Never communicate a critical state by color alone; pair it with text such as Critical, Breach or Watch.

Component states

State	Purpose	Visual contract
Default	Resting	Neutral surface / border
Hover	Pointer affordance	Stronger border or surface
Focus	Keyboard target	Visible focus treatment
Active	Selected/current	Persisted active styling
Disabled	Unavailable	Reduced emphasis
Error	Invalid/blocked	Error styling + recovery text

5. Component library and API contract

The current working file contains 40 reusable component nodes with documented state examples. This document does not re-label those nodes as formal Component Sets when they are not.

Component families

Family	Examples	API direction
Buttons	Primary / Secondary / Tertiary / Danger	label, state, disabled, loading, onClick
Inputs	Text / Search / Select / Date Range	value, placeholder, state, errorText, onChange
Controls	Checkbox / Radio / Toggle / Segmented	selected, disabled, onChange
Navigation	Tabs / Breadcrumbs / Pagination / Filters	items, activeKey, onChange
Status	Positive / Watch / Critical / Neutral	tone, label, icon, detail
Analytics	KPI / Metric Header / Alert Row / Risk Driver	metric, value, delta, status
Context	Portfolio Selector / Role Switcher / Table Controls	selection, role, actions
Feedback	Focus / Loading / Error / Empty	state, message, retry
Utility	Tooltip / Help / Timestamp	content, placement, timestamp

Core API examples

Component	Props	Behavior
Button	variant, state, label	onClick; disabled blocks interaction; focus stays visible
Input	type, value, placeholder, state	onChange/onFocus/onBlur; error text on invalid input
KPI Card	label, value, status, delta, timestamp	Drill-down when actionable
Alert Row	severity, id, timestamp, owner, status	Acknowledge/open; comment when policy requires
Role Switcher	currentRole, availableRoles	Change role while preserving context
Table Controls	columns, sort, filters	onSort/onFilter/onExport

Naming: ComponentSet / Variant / State | Button / Primary / Default | Button / Primary / Active | Input / Text / Error

6. Molecules and reusable patterns

Molecules combine existing atoms into patterns that recur across screens.

Molecule	Atomic composition	Use
KPI Card	Analytics + Status	Live risk metric
Filter Bar	Input + Search + Context	Portfolio / horizon / confidence / methodology filters
Alert Row	Analytics + Status	Breach summary + next action
Role Switcher	Context + Button	Persona-aware dashboard switching
Table Controls	Context + Secondary Button	Sort / columns / export
Action Footer	Context + Focus treatment	Audit-sensitive primary action

Composition rule

Use instances of matching atomic components. Limit overrides to approved content and visual properties. State logic belongs to the component model, not duplicated screen shapes.

7. Responsive implementation

Responsive behavior is driven by information priority. The product model stays consistent, but the spatial arrangement changes.

Breakpoint	Frame	Strategy
Desktop	1440 × 900	High density; persistent rail; multi-panel layout
Tablet	768 × 1024	Reduced columns; preserved analytical hierarchy; touch-friendly controls
Mobile	375 × 812	Single-column priority stack; bottom tabs on authenticated screens

Responsive rules

Component	Desktop	Tablet	Mobile
Sidebar	Persistent rail	Compact rail	Removed pre-auth; bottom tabs after auth
KPI group	3-4 per row	2-3 per row	Stack; priority metrics first
Tables	Full columns	Hide low-priority columns	List / key-value rows
Filters	Inline toolbar	Compact grouped controls	Summary + edit
Charts	Full analytical chart	Reduced plot area	Focused chart + selected metric
Action footer	Full context	Full-width / split	44 px+ primary action

Do not scale desktop screens down. Recompose the information architecture so critical decision data remains visible above the fold.

8. Screen inventory and implementation intent

The current core product set contains 12 screen families. Login, settings, historical analytics and onboarding are documented as supporting experiences in the Figma source.

#	Screen	Primary decision
1	Executive Risk Overview	What is the current risk posture?
2	Portfolio Overview	Where is risk concentrated?
3	Portfolio Detail	What contributes to portfolio risk?
4	VaR Analysis	Is VaR inside limits and why?
5	CVaR / Expected Shortfall	How severe is the tail beyond VaR?
6	Greeks	How sensitive is exposure?
7	Drawdown Analysis	How deep and how quickly are we recovering?
8	Stress Testing	Which scenarios create breaches?
9	Risk Alerts	What needs attention now?
10	Alert Investigation	What evidence supports the decision?
11	Compliance	Can the event be defended in audit?
12	Reports	What needs to be distributed?

Supporting experiences

Experience	Intent
Login / Authentication	Secure access: SSO, email/password, MFA, recovery
Settings / Role Configuration	Role, density, risk defaults, alert routing
Historical Risk Analytics	Trend, period comparison and driver movement
Onboarding / First-Time User Flow	Three-step setup and guided learning

9. Financial data visualization specification

Risk metrics are presented with their units, time context and semantic state so users can interpret them without guessing.

VaR

Property	Required behavior
Value	Show current VaR as the primary numeric metric
Confidence	Display confidence level explicitly
Horizon	Show holding period, e.g. 1D
Methodology	State methodology
Limit	Show utilization / breach status
Trend	Provide historical/directional context
Drill-down	Portfolio attribution position

CVaR / Expected Shortfall

Show tail severity beyond the VaR threshold. Keep confidence and horizon beside the metric and provide distribution/contribution context when space allows.

Greeks

Greek	Representation
Delta	Directional sensitivity
Gamma	Convexity / second-order sensitivity
Theta	Time decay
Vega	Volatility sensitivity
Rho	Rate sensitivity

Drawdown and stress

Drawdown shows current and maximum values with recovery context. Stress scenarios cover GFC, COVID crash, equity -20%, rates +200 bps and EM FX -30%.

10. Core prototype flows

The prototype demonstrates the three interaction paths used as the primary behavior checks.

Flow 01 - Portfolio Overview VaR Drill-down

Step	State	Expected interaction
1	Portfolio Overview	Open VaR context
2	VaR Analysis	Review value, confidence, horizon and limit
3	Position / attribution	Open contribution detail
4	Deep dive	Inspect material position or driver

Flow 02 - Risk Alert Acknowledge Comment Confirmation

Step	State	Validation
1	Alert open	Severity, ID, owner, timestamp visible
2	Acknowledgement	Actor and time recorded
3	Comment	Mandatory when policy requires
4	Confirmation	Review before committing
5	Complete	Audit event retained; return to alerts

Flow 03 - Junior Analyst Senior PM

Step	Role	Behavior
1	Junior Analyst	Guided, simplified verification view
2	Role switch	Explicit role change control
3	Senior PM	Higher density and direct drill-down
4	Return	Preserve product context

11. Interaction and animation specification

Motion communicates state changes. It should not make market data look more dynamic than the underlying information.

Interaction	Property	Duration	Trigger	Notes
Page navigation	Opacity / dissolve	200 ms	On click	Prototype navigation
Focus ring	Stroke / effect	Immediate	On focus	Remain visible
Loading	Opacity / skeleton	150-250 ms	State change	Do not block status messaging
Alert state	Surface / emphasis	150-200 ms	On acknowledge	Severity label persists
Chart highlight	Opacity / emphasis	150 ms	Hover / select	Do not animate raw data continuously

Performance rule

Live updates should not cause layout shifts. Keep containers stable and update values in place. Motion communicates state change rather than simulating market motion.

12. Accessibility implementation specification

The target is WCAG 2.1 AA. This section defines implementation expectations; it is not evidence that the final build has already passed.

Area	Implementation target
Color contrast	Verify all text/background combinations against WCAG 2.1 AA
Non-text contrast	Keep controls, focus indicators and boundaries perceivable
Keyboard	Logical focus order and visible focus treatment
Screen reader	Announce role, label, value, state and critical risk context
Error handling	Text explanation plus recovery path
Touch targets	Primary mobile actions use the 44 px token
Charts	Accessible summary; never rely on color alone
Dynamic updates	Use appropriate live-region semantics for material status changes

Critical screen-reader sequences

Flow	Sequence
Login	Page heading SSO email password sign in security note
VaR drill-down	Portfolio VaR confidence/horizon limit drill-down
Alert acknowledgement	Alert ID severity owner timestamp acknowledge comment confirm

13. Asset export manifest

RiskLens is typography-and-data-led. Icons and data marks are the main export surface.

Asset	Format	Size / behavior	Status
Brand mark / RL wordmark	SVG	Vector; preserve aspect ratio	In Figma
Navigation icons	SVG	20-24 px viewBox	Approved export surface
Status icons	SVG	16-20 px	Pair with status text
Data visualization marks	CSS/SVG/canvas	Responsive to container	Rendered from data
Loading indicator	CSS/SVG/Lottie optional	Within 40-44 px	Figma component exists
Focus indicator	CSS outline/box-shadow	2 px emphasis	Figma effect style exists

Suggested export names

risklens-logo.svg
risklens-icon-alert.svg
risklens-icon-search.svg
risklens-icon-chevron.svg
risklens-status-critical.svg
risklens-status-warning.svg
risklens-status-success.svg

14. Engineering checklist

Use this as an implementation review sheet. It describes acceptance criteria, not completed code QA.

Area	Acceptance criterion
Tokens	Create CSS variables from approved RiskLens mapping
Components	Use reusable definitions for repeated controls and states
Responsive	Match the desktop/tablet/mobile composition contract
Navigation	Keep authenticated and pre-auth shells distinct
Data viz	Keep VaR, CVaR, Greeks, drawdown and stress semantics explicit
Role logic	Change density/defaults without resetting session context
Alerts	Keep acknowledgement/comment requirements stateful and auditable
Accessibility	Implement keyboard, contrast, focus, screen-reader and non-color status behavior
Performance	Avoid layout shifts during live updates
Handoff	Map every screen/component back to a Figma source

15. Figma source map and current metrics

The source map below is the handoff index. Counts are deliberately conservative and describe the current working structure.

Source page	Engineering use
02_Design_Tokens	Variables, typography, colors, spacing and breakpoints
03_Atoms	Reusable component foundations
04_Molecules	Composed instances and reusable patterns
05_Organisms	Complex risk widgets
06_Templates	Persona-specific architecture
07_Desktop	Desktop screen source
08_Tablet	Tablet screen source
09_Mobile	Mobile screen source
10_Prototype_Flows	Interaction source
11_Documentation	Additional implementation notes

Metric	Current value
Figma pages	12
Core screen families	12
Responsive frames	36
Reusable component nodes	40
Core prototype flows	3
Figma variables	23
Text styles	5
Paint styles	9
Effect styles	1

Count note

The 40 components are individual reusable nodes with documented states. This handoff does not present them as 60 formal variants or 10 formal component sets.

16. Assumptions, limitations and open validation items

This is a design handoff. It should be read together with the Figma source and the separate validation deliverables.

Item	Current state	Follow-up
Visual design system	Implemented in Figma	Frontend implementation QA
Responsive compositions	Implemented for 3 breakpoints	Verify intermediate widths
Prototype flows	Specified in Figma	Run end-to-end QA
WCAG target	Specified	Run separate accessibility audit
Usability evidence	Separate deliverable	Complete usability report
Error identification	Separate deliverable	Complete error log
Asset export	Manifest provided	Confirm exported filenames/sizes
Competitive audit	Separate deliverable	Complete competitive audit report
Presentation deck	Separate deliverable	Create final deck

Final acceptance

Use the Figma file and this specification as a pair. Review any implementation change that affects hierarchy, role behavior, responsive composition, risk semantics or accessibility.