

# ASSIGNMENT

## Task Description#1

- Paste a function with a missing colon (add(a, b)), and let AI fix the syntax error.

python

```
def add(a, b)
    return a + b
```

Expected output with fixed errors given by google colab :

```
[1] def add(a, b):
    return a + b

num1 = float(input("Enter first number: "))
num2 = float(input("Enter second number: "))

result = add(num1, num2)
print(f"The sum is: {result}")

Enter first number: 4
Enter second number: 5
The sum is: 9.0
```

explanation of the code :

Cell 1 (cell\_id: dd45bf10):

```
def add(a, b):
    return a + b
```

This cell defines a simple Python function named `add` that takes two arguments, `a` and `b`. The function's purpose is to return the sum of these two arguments.

Cell 2 (cell\_id: df66ddb1):

```
num1 = float(input("Enter first number: "))
num2 = float(input("Enter second number: "))

result = add(num1, num2)
print(f"The sum is: {result}")
```

This cell is the main part of the program that interacts with the user and uses the `add` function.

1. `num1 = float(input("Enter first number: "))`: This line prompts the user to enter the first number using the `input()` function. The text inside the parentheses is displayed to the user as a prompt. The `float()` function is used to convert the user's input (which is initially a string) into a floating-point number, allowing for decimal values. The converted number is then stored in the variable `num1`.

2. `num2 = float(input("Enter second number: "))`: Similar to the previous line, this prompts the user for the second number and converts it to a floating-point number, storing it in the variable `num2`.
3. `result = add(num1, num2)`: This line calls the `add` function that was defined in the first cell, passing `num1` and `num2` as arguments. The value returned by the `add` function (the sum of `num1` and `num2`) is then stored in the `result` variable.
4. `print(f"The sum is: {result}")`: This line prints the final output to the console. It uses an f-string (formatted string literal) to embed the value of the `result` variable directly into the output string.

CODE AND OUPUT PROVIDED BY GITHUB COPILOT :

```
1  def add(a, b):
2      return a + b
3
4  # Get user input
5  a = float(input("Enter first number: "))
6  b = float(input("Enter second number: "))
7
8  # Perform sum and print result
9  result = add(a, b)
10 print("The sum is:", result)
```

```
vikaskathroju@vickys-MacBook-Air ~ % /usr/local/bin/python3 "/U
Enter first number: 2
Enter second number: 3
The sum is: 5.0
vikaskathroju@vickys-MacBook-Air ~ %
```

## Task Description 2


- Identify and fix a logic error in a loop that causes infinite iteration.


python

```
def count_down(n):  
    while n >= 0:  
        print(n)  
        n += 1  # Should be n -= 1
```

EXPECTED CODE AND OUTPUT WITH FIXED ERRORS IN GOOGLE COLAB :

```
[3] def count_down(n):  
    while n >= 0:  
        print(n)  
        n -= 1 # Fixed logic error
```

 count\_down(5)

 5  
4  
3  
2  
1  
0

EXPLANATION OF THE CODE PROVIDED BY THE GOOGLE COLAB :

I've executed the `count_down(5)` command, and you can see the output in the cell above, counting down from 5 to 0.

Since the task is complete, here are some further things you might want to explore:

1. **Count down from a different number:** Call `count_down()` with a different integer argument.
2. **Modify the `count_down` function:** Change the function to count down to a specific number other than 0.
3. **Explore other loop types:** Implement a similar countdown using a `for` loop instead of a `while` loop.

## EXPECTED CODE AND OUTPUT PROVIDED BY GITHUB COPILOT :

```
ai 7.3 2 2 ×
Users > vikaskathroju > ai 7.3 2 > count_down
1 def count_down(n):
2     while n >= 0:
3         print(n)
4         n -= 1
5
6 # Count down from 5
7 count_down(5)
```

```
vikaskathroju@vickys-MacBook-Air ~ % /u
5
4
3
2
1
0
vikaskathroju@vickys-MacBook-Air ~ %
```

### Task Description 3

- Debug a runtime error caused by division by zero. Let AI insert try-except.

```
# Debug the following code
def divide(a, b):
    return a / b

print(divide(10, 0))
```

## EXPECTED CODE AND OUTPUT GIVEN BY THE GOOGLE COLAB :

```
def divide(a, b):
    try:
        return a / b
    except ZeroDivisionError:
        return "Error: Cannot divide by zero."

print(divide(10, 0))
print(divide(10, 2))
```

Error: Cannot divide by zero.  
5.0

## explanation fo the code given by the google colab :

1. **def divide(a, b):**: This line defines a function called **divide** that takes two arguments, **a** and **b**.
2. **try:**: This block starts a **try** statement. Code inside the **try** block is executed normally. If an error occurs during the execution of the code in the **try** block, Python will look for a corresponding **except** block to handle the error.
3. **return a / b**: This line attempts to perform the division of **a** by **b**. If **b** is zero, a **ZeroDivisionError** will occur.
4. **except ZeroDivisionError:**: This block is an **except** block that specifically catches the **ZeroDivisionError**. If a **ZeroDivisionError** occurs in the **try** block, the code inside this **except** block will be executed.
5. **return "Error: Cannot divide by zero."**: If a **ZeroDivisionError** is caught, this line will be executed, and the function will return the string "Error: Cannot divide by zero.".
6. **print(divide(10, 0))**: This line calls the **divide** function with **a=10** and **b=0**. Since **b** is 0, a **ZeroDivisionError** will occur within the function, and the **except** block will be executed, returning "Error: Cannot divide by zero.". This string will then be printed to the console.
7. **print(divide(10, 2))**: This line calls the **divide** function with **a=10** and **b=2**. Since **b** is not zero, the division **10 / 2** will be performed successfully within the **try** block, returning **5.0**. This value will then be printed to the console.

expected code and output given by the github copilot :

```
1 def divide(a, b):
2     try:
3         return a / b
4     except ZeroDivisionError:
5         return "Error: Division by zero is not allowed."
6
7 print(divide(10, 0))
8 print(divide(10, 5))
```

```
vikaskathroju@vickys-MacBook-Air ~ % python3 /usr/local/bin/python3
Error: Division by zero is not allowed.
2.0
vikaskathroju@vickys-MacBook-Air ~ %
```

#### Task Description 4

- Provide a faulty class definition (missing self in parameters). Let AI fix it

python

```
class Rectangle:
    def __init__(length, width):
        self.length = length
        self.width = width
```

expected code and output provided by the google colab :

```
[7] class Rectangle:
    def __init__(self, length, width): # Added 'self' and corrected method name
        self.length = length
        self.width = width

    def area(self): # Adding a sample method to demonstrate usage
        return self.length * self.width

# Example of how to use the corrected class
my_rectangle = Rectangle(10, 5)
print(f"The area of the rectangle is: {my_rectangle.area()}")

The area of the rectangle is: 50
```

explanation of the code provide by the google colab :

- **class Rectangle:** : This line declares the beginning of the class definition.
- **def \_\_init\_\_(self, length, width):** : This defines the constructor method for the `Rectangle` class.
  - **self** : This is the required first parameter in instance methods, referring to the instance of the class being created.
  - **length** : This parameter will store the length of the rectangle.
  - **width** : This parameter will store the width of the rectangle.
  - Inside the method, **self.length = length** and **self.width = width** assign the values passed as arguments to the **length** and **width** attributes of the instance (**self**). This initializes the rectangle object with its specific dimensions.
- **def area(self):** : This defines a method called **area** for the `Rectangle` class.
  - **self** : This parameter allows the method to access the attributes of the instance (**self.length** and **self.width**).
  - **return self.length \* self.width** : This line calculates the area of the rectangle by multiplying its length and width and returns the result.

- **my\_rectangle = Rectangle(10, 5)** : This line creates a new instance (object) of the `Rectangle` class. When **Rectangle(10, 5)** is called, the **\_\_init\_\_** method is automatically executed with **self** referring to the new object, **length** set to 10, and **width** set to 5. The created `Rectangle` object is then assigned to the variable **my\_rectangle**.
- **print(f"The area of the rectangle is: {my\_rectangle.area()}")** : This line calls the **area()** method on the **my\_rectangle** object (**my\_rectangle.area()**). The method calculates the area ( $10 * 5 = 50$ ), and the result is then embedded into an f-string and printed to the console.

expected code and output given by github copilot :

```
class Rectangle:
    def __init__(self, length, width):
        self.length = length
        self.width = width

# Example usage:
rect = Rectangle(5, 3)
print("Length:", rect.length)
print("Width:", rect.width)
```

```
vikaskathroju@vickys-MacBook-Air ~ % /usr/
Length: 5
Width: 3
vikaskathroju@vickys-MacBook-Air ~ %
```

### Task Description 5

- Access an invalid list index and use AI to resolve the Index Error.

```
python

numbers = [1, 2, 3]
print(numbers[5])
```

expected code and output provided by google colab :



```
[9] numbers = [1, 2, 3]
# This line will cause an IndexError
# print(numbers[5])
```

---

```
numbers = [1, 2, 3]
index_to_access = 5

try:
    print(numbers[index_to_access])
except IndexError:
    print(f"Error: Index {index_to_access} is out of the range of the list.")

# Example of accessing a valid index
index_to_access = 1
try:
    print(numbers[index_to_access])
except IndexError:
    print(f"Error: Index {index_to_access} is out of the range of the list.")
```

---

```
Error: Index 5 is out of the range of the list.
2
```

**explanation of the code provided by the google colab :**

1. It initializes the `numbers` list again.
2. It sets `index_to_access` to 5, which is an invalid index for the list.
3. The `try` block attempts to access `numbers[index_to_access]`.
4. Because `index_to_access` is 5, an `IndexError` occurs, and the code inside the `except IndexError:` block is executed.
5. This block prints an error message indicating that the index is out of the list's range.
6. The code then shows an example of accessing a valid index (index 1, which contains the value 2) within another `try-except` block. In this case, no `IndexError` occurs, and the value at that index (2) is printed.

expected code and output provided by the github copilot :

```
1 numbers = [1, 2, 3]
2 try:
3     print(numbers[5])
4 except IndexError:
5     print("Error: Index out of range.")
```

```
vikaskathroju@vickys-MacBook-Air ~ %
Error: Index out of range.
vikaskathroju@vickys-MacBook-Air ~ %
```