

AYUSHMAN BHARAT DIGITAL MISSION

Update Mobile via API in Healthcare Professional Registry (HPR) via APIs

Table of Contents

A. Terminology	3
B. Get HPR Token	6
1. Login Via Password	6
2. Login Via Mobile	7
3. Login Via Aadhaar	10
C. Generate Verification Mobile OTP	12
D. Re-Generate Verification Mobile OTP	13
E. Verify Mobile OTP	14

A. Terminology

- **ABDM** - Ayushman Bharat Digital Mission
- **Authorization token** - To obtain, the HRP can call 'sessions API' along with the receivedClientID and Client Secret. Same must be used in header for other APIs.
- **Client ID** - Post internal approval, Integrator will receive Client ID to access ABDM APIs
- **Client Secret** - Post internal approval, Integrator will receive Client Secret to accessABDM APIs
- **HPRID** – Healthcare Professional ID
- **Sandbox - Sandbox** is a framework that will allow technologies or products to be tested inthe contained environment in compliance with ABDM standards.


```
NmFINWYifQ.eyJleHAiOjE2ODkwNTU3MDIsImIhdCI6MTY4OTA1MzkwMiwianRpljoiN2ZhNWY5NmItMTZkMi00MWYwLTk5ZDYtYzQ5ZGU2YzdkODBkliwiaXNzIjoiaHR0cHM6Ly9kZXUubmRobS5nb3YuaW4vYXV0aC9yZWFSbXMvY2VudHJhbC1yZWdpc3RyeSIsImF1ZCI6Imh0dHBzOi8vZGV2Lm5kaG0uZ292Lm1uL2F1dGgvcmlvbmVhbG1zL2NlbnRyYWwtcmVnaXN0cnkiLCJzdWliOiIiY2MwNDdiOC0wZmUzLTRmMWYtODAyOS03MmRiM2ViYWE0YTEiLCJ0eXAiOiJSZWZyZXNoliwiYXpwljoiZGlnaWRvY3RvcilIsInNlc3Npb25fc3RhdGUiOiJIMzNmYzMwYy1jOTRkLTQzOGQtYjYyMi03NDZkZmQ4NDk5YmQiLCJzY29wZSI6Im9wZW5pZCBpbWFpbiBwcm9maWxln0.guN2zUwmlvPLEBQoAWwr7YQzH4VS0BGVyJf948uvyfM",
  "tokenType": "bearer"
}
```

B. Get HPR Token

Users can get HPR Token in three ways.

- i. [Login Via Password API](#),
- ii. [Login Via Mobile OTP API](#),
- iii. [Login Via Aadhaar OTP API](#)

Users can get HPR token by choosing any given option

I. Login Via Password

Users need to input HPR id and password to get HPR token.

Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://hpridsbx.abdm.gov.in/api/v1/auth/authPassword
Request Body	<pre>{ "idType": "hpr_id", "domainName": "@hpr.abdm", "hprId": "username@hpr.abdm", "password": "*****" }</pre>

Sample Response
<pre>{ "token": "eyJhbGciOiJSUzUxMiJ9.eyJzdWIiOiI3MS00MzgZLTZzMDUzMjY4NiIsImNsaWVudElkIjoizGlnaWRvY3RvcilzInN5c3RlbSI6IkhQSUQiLCJocHJJE51bWJlciI6IjcxLTQzODMtMTMwNS0yNjg2IiwibW9iaWxIjojOTU4MjEyNjk5MlIsImhwcklkIjoibmFyZXNoMjBAaH", "expiresIn": 1800, "refreshToken": "eyJhbGciOiJSUzUxMiJ9.eyJzdWIiOiI3MS00MzgZLTZzMDUzMjY4NiIsImNsaWVudElkIjoizGlnaWRvY3RvcilzInN5c3RlbSI6IkhQSUQiLCJ0eXAiOiJSZWZyZXNoIiwiaXNjaW50dGZMzcXLTQzODMtMTMwNS0yNjg2IiwibW9iaWxIjojOTU4MjEyNjk5MlIsImhwcklkIjoibmFyZXNoMjBAaH", "refreshExpiresIn": 10800 }</pre>

II. Login Via Mobile OTP

Users need to follow the following steps to get HPR token

1	Send OTP
2	Get Public Certificate
3	HPRID Verify OTP
4	Login with HPRID

1. Send OTP

Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://hpridsbx.abdm.gov.in/api/v2/auth/loginViaMobileSendOTP
Request Body	{ "mobile": "*****6992" }

Sample Response
{ "txnId": "061c660d-8752-4639-945d-e77a7ea6f564", "mobileNumber": null }

2. Get Public Certificate

Users need to get public certificate to encrypt the OTP.

Method	Get
URL	https://hpridsbx.abdm.gov.in/api/v1/auth/cert
Request Body	{ "mobile": "*****6992" }

Sample Response
-----BEGIN PUBLIC KEY----- MIIBIjANBgkqhkiG9w0BAQEFAAOCAQ8AMIIBCgKCAQEA6avEoNMbZDtjs7RHc1Si hYeLvGPYV76mh2ncU2FAyCkK3ubE/7UE2HkimL4ftAqFN3fcKv8430oV3gAuvrk/ 5sIOoG8NOMrVfInakdFZyDae66MHVuc1Rzrv8fKDRFRz8UTa1S2xZ9uXRCieQCeB xeHmDtgcyGDfQzqcTOLGCPu6tLWda/QhW7zeUpowglIBknhlf2nf916lsM1fWnO7 qVUBh6E3PXoLrW4NtvOwEMh3V62BNGzNmW3u8hxdp+uSe3Us/t4WFJRURnAhO5 IDAzojqkWYHkYZTDvidLBvfoX7ZbBPz03u42AOM/uDu4gG/oYqeB5zXe7qJ1ecLu 5QIDAQAB -----END PUBLIC KEY-----

3. HPRID verify OTP

After receiving public certificate user needs to encrypt OTP with the public key using RSA Encryption Algo RS512.

RSA Encryption to encrypt the data. Cipher Type - RSA/ECB/PKCS1Padding. online tool to encrypt data [click here](#)

Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://hpridsbx.abdm.gov.in/api/v2/auth/loginViaMobileSendOTP
Request Body	{ "otp": "1W/rIffFrl/wOeGml7BhfAGu20To1EQ7HowREwXVikAnXCyeY31KMDUfl/VIQoHs9ocbwwG4rBCC Xof5jcsHsCs4Zntql6PY1e3Ps5IsGH+7sPO8u9SLMYy5x9xBoI3VqnruaRxBb7oQR+l8RAipiDeNgEvTSM TTL SN3pqQ7BG+ ", "txnId": "fc6d879c-e535-4ff1-9443-5dc6031efcc1" }

Sample Response

```
{
  "txnId": "fc6d879c-e535-4ff1-9443-5dc6031efcc1",
  "mobileLinkedHpIdDTO": [
    {
      "hpIdNumber": "***-****-0326-3829",
      "name": "Test",
      "hpId": "*****@hpr.abdm"
    }
  ]
}
```

4. Login with HPRID

Users need to pass hpIdNumber and txnId received in the **HPRID verify OTP** Api.
Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://hpridbeta.abdm.gov.in/api/v2/auth/login/userAuthorizedToken
Request Body	{ "hpId": "***-****-0326-3829", "txnId": "fc6d879c-e535-4ff1-9443-5dc6031efcc1" }

Sample Response

```
{
  "token": "eyJhbGciOiJSUzUxMiJ9.eyJzdWIiOiI3MS0xMzc0LTAzMjYtMzgyOSIsImNsaWVudElkIjoiZGlnaWRvY3RvcilzInN5c3RlbSI6IkhQSUQiLCJocHJJE51bWJlciI6IjcxLTEzNzQtMDMyNi0zODI5IiwibW9iaWx1IjoiOTg3MzgxMDE0NiIsImhwcklkIjoiYWtzaGF5LnBhbEBocHluYWJkbSIsImV4cCI6MTY4OTU4MTMyOSwiaWF0IjoxNjg5NTc5NTI5fQ.TvPFgrmX7QE3aug1AHcO-nxr8HaKPT036-W77aROC4F2gltvUjhtFqEZNPTBxapMRY-vRkNcZFCX_TG8tJ-tFFdyZL-gMv1JfL ",
  "expiresIn": 1800,
  "refreshToken": "eyJhbGciOiJSUzUxMiJ9.eyJzdWIiOiI3MS0xMzc0LTAzMjYtMzgyOSIsImNsaWVudElkIjoiZGlnaWRvY3RvcilzInN5c3RlbSI6IkhQSUQiLCJ0eXAiOiJSZWZyZXNoliwiZXhwljoxNjg5NTkwMzI5LCJpYXQiOiE2ODk1Nzk1MjI5.SVxOjWXYk2LVcD5t3wRYgBIAMxyjVMLjJ0MGtv9ZPpVOBWJUPpwZk8q6KikP8ZPas ",
  "refreshExpiresIn": 10800
}
```

III. Login Via Aadhaar

For login via Aadhaar OTP you need to follow the following steps.

1	Send OTP
2	Verify OTP

1. Send OTP

Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://hpridsbx.abdm.gov.in/api/v1/auth/init
Request Body	<pre>{ "idType": "hpr_id", "domainName": "@hpr.abdm", "authMethod": "AADHAAR_OTP", "hprId": "*****@hpr.abdm" }</pre>

Sample Response
<pre>{ "txnId": "061c660d-8752-4639-945d-e77a7ea6f564", "mobileNumber": null }</pre>

2. Verify OTP

Users need to input otp and txnId from above API Send Aadhaar OTP.

Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://hpridsbx.abdm.gov.in/api/v1/auth/confirmWithAadhaarOtp
Request Body	<pre>{ "otp": "*****", "txnId": "effbf557-9f2b-40f7-a8c1-9658a08bf410" }</pre>

Sample Response
<pre>{ "token": "eyJhbGciOiJSUzUxMiJ9.eyJzdWIiOiI3MS0xNjg3LTI3NTUtNzg1MSIsImNsaWVudElkljoiZGlnaWRvY3RvcilsluN5c3RlbSI6IkhhQSUQiLCJocHJJZE51bWJlciI6IjcxL TE2ODctMjc1NS03ODUxliWibW9iaWxlljoiOTU4MjEyNjk5MilsImhwckkljoibmFyZXNoQGhwci5hYmRtliwiZXhwljoxNjg5NTk1OTc1LCJpYXQiOiJlE2ODk1OTQxNzV9.AwSCEGjjixkwaWfY40nCojLZZR_rOmGnqLspwNOXFFvWkarhF6oJISMyeML", "expiresIn": 1800, "refreshToken": "eyJhbGciOiJSUzUxMiJ9.eyJzdWIiOiI3MS0xNjg3LTI3NTUtNzg1MSIsImNsaWVudElkljoiZGlnaWRvY3RvcilsluN5c3RlbSI6IkhhQSUQiLCJ0eXAIoiJSZWZyZXNoliwiZXhwljoxNjg5NjA0OTc1LCJpYXQiOiJlE2ODk1OTQxNzV9. ", "refreshExpiresIn": 10800 }</pre>

C. Generate Mobile - OTP

In this API's system will send a 6-digit OTP to user inputted mobile number to verify user identity.

Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	Post
URL	https://doctorsbx.abdm.gov.in/apis/v1/doctors/generate-mobile-otp
Request Body	<pre>{ "hpr_token": "xxxxxxxx", "officialMobile": "958212****" }</pre>

Sample Response
<pre>{ "status": "success", "txnId": "3e8457d4-d185-4b8c-b359-3b7f36e27d80" }</pre>

Request body parameters

Field Name	Mandatory	Datatype	Size	Comments
hpr_token	Yes	Varchar		Token you will received in get HPR token
officialMobile	Yes	Number	10	

D. Re-Generate Mobile OTP

In this API's if user didn't receive an OTP after this user will use this api to regenerate OTP again for mobile verification.

Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	POST
URL	https://doctorsbx.abdm.gov.in/apis/v1/doctors/regenerate-mobile-otp
Request	<pre>{ "hpr_token": "eyJhbGciOiJSUzUxMiJ9", "officialMobile": "958212****" }</pre>

Sample Response
<pre>{ "status": "success", "txnId": "386d9909-c825-4b6b-bb61-505324a6a6f0" }</pre>

Request body parameters

Field Name	Mandatory	Data types	Size	Comments
hpr_token	Yes	String		
officialMobile	Yes	String		

E. Verify Mobile-OTP

In this API's user will update mobile by input OTP along with other requested parameters mentioned in the table explaining API which user receive in Generate Mobile OTP and Re-Generate Mobile OTP.

Add the accessToken received from the **HPRID Gateway Token** API for authorization.

Note: Append tokenType Bearer before the access token, give a space and then add your access token as shown below.

Key: Authorization

Value: Bearer<Leave Space><Your Access Token goes here>

Method	POST
URL	https://doctorsbx.abdm.gov.in/apis/v1/doctors/verify-email-otp
Request Body	{ "hpr_token": "eyJhbGciOiJSUzUxMiJ9", "txnId": "386d9909-c825-4b6b-bb61-505324a6a6f", "otp": "629087" }

Sample Response
{ "status": "success", "msg": "Success" }

Request body parameters.

Field Name	Mandatory	Data types	Size	Comments
hpr_token	Yes	String		Token you received in GET hpr token
txnId	Yes	String		You received in response of Generate Mobile OTP and Re-Generate Mobile OTP
otp	Yes	Number	6	