Data Structure & Algorithms

Nilesh Ghule

Doubly Linear Linked List - addFirst()



Doubly Linear Linked List - addAtPos()



① if list empty or adding at pos <=1, add node at start.

```
if(head==null || pos<=1)
    addFirst(val);
```

```
nn=new Node(val);
trav=head;
for(i=1; i<pos-1;i++)
    trav=trav.next;
temp=trav.next;
nn.next=temp;
nn.prev=trav;
trav.next=nn;
temp.prev=nn;
```

Doubly Linear Linked List - addAtPos() - Special case = (2) last pos.




```
nn = new Node(val);
trav = head;
for(i=1; i<pos-1; i++){
    if(trav.next == null)
        break;
    trav = trav.next;
}
temp = trav.next;
nn.next = temp;
nn.prev = trav;
trav.next = nn;
if(temp != null)
    temp.prev = nn;
```

NPE ✗

Doubly Linear Linked List – delFirst()




```
head = head.next;
head.prev = null;
```

if list is empty, do nothing.

```
if (head == null)
    return;
```

if list has single node, then delete it.

```
if(head.next == null)
    head = null;
```

Doubly Linear Linked List – delAtPos()



④ deleting the last node.



① if list empty or delete at first pos, call delfirst();

```
if(head==null || pos==1)
    delFirst();
```

② if deleting at pos less than 1, do nothing.

```
if(pos<1)
    return;
```

③ if deleting beyond last pos, then do nothing.

```
trav=head;
for(i=1; i<pos; i++)
{
    if(trav.next==null)
        return;
    trav=trav.next;
}
temp1=trav.prev;
temp2=trav.next;
temp1.next=temp2;
if(temp2!=null)
    temp2.prev=temp1;
```

Doubly Linear Linked List – delAtPos()




```
trav.prev.next = trav.next;
trav.next.prev = trav.prev;
```

Doubly Linear Linked List – delLast()



① if list is empty, do nothing.

```
if(head==null)
    return;
```

```
trav=head;
while(trav.next!=null)
    trav=trav.next;
trav.prev.next=null;
```

② if list has single node, then delete it.

```
if(head.next==null)
    head=null;
```



Doubly Circular Linked List – displayRev()




```
if(head!=null){
    trav = head.prev;
    do{
        print(trav.data);
        trav = trav.prev;
    }while(trav != head.prev);
}
```

40, 30, 20, 10

Doubly Circular Linked List — addLast()




```
trav = head.prev;
nn.next = head;
nn.prev = trav;
trav.next = nn;
head.prev = nn;
```

① if list empty, add node at start & make it circular.

```
if(head == null) {
    head = nn;
    nn.next = head;
    nn.prev = head;
}
```

Doubly Circular Linked List — addFirst()




```
trav = head.prev;
nn.next = head;
nn.prev = trav;
trav.next = nn;
head.prev = nn;
head = nn;
```

① if list empty, add node at start & make it circular.

```
if(head == null) {
    head = nn;
    nn.next = head;
    nn.prev = head;
}
```

Linked List – Competitive programming -selection Sort

- Sort the singly linked list.




```
Node i, j;
for(i = head ; i != null ;i=i.next){
    for(j = i.next;j!=null ;j=j.next){
        if( i.data > j.data ){
            int t = i.data;
            i.data = j.data;
            j.data = t;
        }
    }
}
```

Linked List – Competitive programming

- Sort the singly linked list.

```
class Emp {
    int id;
    String name;
    double sal;
    =
}

class List {
    static class Node {
        Emp data;
        Node next;
        =
    }
    private Node head;
    :
}
```

```
main() {
    List l=new List();
    l.addLast(new Emp(3, ...));
    l.addLast(new Emp(1, ...));
    l.addLast(new Emp(2, ...));
}
```

```
In List class:
void addLast(Emp val) {
    Node nn=new Node(val);
    if(head==null)
        head=nn;
    else {
        Node trav=head;
        while(trav.next!=null)
            trav=trav.next;
        trav.next=nn;
    }
}
```



Linked List – Competitive programming

- Find middle of singly linear linked list.





Thank you!

Nilesh Ghule <nilesh@sunbeaminfo.com>