OmniAssist — LEARN SHEET

Owner: Vikas · **Started:** 2026-08-02 · **Current version:** v0.1 · **Status:** v0.1 shipped · **v0.2 in progress** — Blocks 1–2 complete; Block 3 (auth) underway **v0.1: SHIPPED** — all 6 blocks complete, CI green, tagged `v0.1`

> Every concept learned, every decision made, and *why*. Append-only — superseded entries are struck through, never deleted, because the reasoning trail is worth more than a tidy document.

DECISION LOG

#	Decision	Why	Reversible?
D1	Flagship project = **OmniAssist**, one evolving codebase Aug→Dec	Real engineering is ~90% working in an existing codebase. Three greenfield toys don't teach that; one evolving system does.	No — this is the program
D2	Dependency tool = **`uv`**	10–100× faster than pip, but the real reason is the **lockfile by default** → reproducible builds, a hard CI/CD requirement later. Replaces venv + pip + pip-tools + pyenv.	Yes, but painful
D3	**Model/provider lives in `.env`, never in code**	Switching models becomes a deploy, not a diff. Paid off within 48 hours (see D10).	n/a — principle
D4	**CI moves from v0.4 → v0.1**	*CI is necessary the moment code exists. CD is necessary the moment there's somewhere to deploy.* Lint/format/type-check now; tests v0.2; build + deploy v0.4.	No
D5	**CI must never require a live `LLM_API_KEY`**	A pipeline calling the live API is expensive (tokens per PR), flaky (network blip → red build → you start ignoring red builds → CI is now worthless), and a leak surface (real key in every fork's CI).	No — constraint
D6	Consequence of D5: **LLM client must be injectable** from Block 2	So tests can substitute a fake. Design decisions in week one are what make week twelve possible.	No
D7	v0.1 stores conversation state in an **in-process dict** — deliberately inadequate	You must *feel* the failure (restart = amnesia; multi-instance = amnesia) before Postgres in v0.2 means anything.	Yes — that's v0.2
D8	**LLM access sits behind a narrow interface in `app/clients/`** — provider is config, not a code dependency	Surveyed 18 models across 6 vendors; prices move monthly, free tiers vary wildly. The senior answer isn't "pick the right vendor," it's "make the vendor swappable." Also satisfies D6 and enables cost/capability routing in v1.0. **Interview story: *"my LLM layer is provider-agnostic and I route by cost/capability"* beats any vendor name.**	No — this is the design
~~D9~~	~~Dev model = `claude-haiku-4-5`~~	*Superseded by D10 (budget = $0). Kept for the reasoning trail.*	—
D10	**v0.1 runs on Groq free tier — `llama-3.3-70b-versatile`**	Budget is $0. Groq = ~1,000 req/day, 30 RPM, **no credit card, ongoing**; Anthropic has no free tier. v0.1 needs ~200 requests total. ⚠ **Groq ≠ Grok** — Groq is an inference provider serving open-weight models (free); Grok is xAI's model ($25 credits then paid). Config is provider-neutral: `LLM_PROVIDER` / `LLM_API_KEY` / `LLM_MODEL`.	Yes — that's the point of D8

D11	**Conversation history must be trimmed** (Block 4), not left unbounded	Groq's free tier caps ~**14,400 tokens/minute**. Per C10, a 40-turn conversation is ~40K tokens in *one* request — over the entire per-minute budget. **A limit that makes you build it right beats unlimited quota that lets you build it wrong.**	No
D13	**Model switched to `openai/gpt-oss-120b`** on Groq	Changed by editing **one line of `.env`** — zero code changes. Live proof that D3 + D8 work.	Yes — one line
D30	**Guarantee loop progress with a clamp**, rather than tightening the `overlap < size` guard	The guard is checked once, at the door, and cannot see what the boundary search does to `end` inside the loop. `size=1000, overlap=900` passes it and still moves `start` backwards. Tightening to `overlap < size * 0.8` would also reject configurations that work. `max(end - overlap, start + 1)` makes progress structural instead of conditional.	Yes
D29	**Chunk size 1000 / overlap 150 live in `Settings`, not as module constants**	These are the main quality knob of retrieval and will be tuned once real documents are indexed. A number you intend to change is configuration by definition; burying it in code guarantees it is changed in the wrong place later.	Yes
D28	**`bge-small-en-v1.5` (384 dims) via `fastembed`**, not `sentence-transformers`	`fastembed` pulls 4 packages and runs on ONNX; `sentence-transformers` pulls ~25 including torch. Same model family, a fraction of the install. Cosine is the trained objective, which fixes the pgvector operator as `<=>`.	Yes — behind the `Embedder` protocol
D27	**Embeddings run locally first, hosted later, behind an `Embedder` protocol**	Groq serves no embedding model (verified against its `/models` endpoint), so the LLM provider cannot supply them. A local model costs nothing per request, which matters on a zero budget, and keeps CI free of network calls. The protocol exists because the hosted swap is coming, not because it might.	Yes, but **not free**: changing embedder invalidates every stored vector and forces a re-index — unlike swapping the LLM
D26	**Ownership is enforced in the repository's `WHERE` clause**, not checked in the service	Both work today. The difference is the next code path — an admin view, a background job, an export endpoint — where a service-level check can be forgotten. A filter inside the query cannot be, because there is no query without it. **Make the secure path the only path.**	No
D25	**Minimum password length 12, no composition rules**	Current NIST guidance: length is what matters. Forcing uppercase/digit/symbol produces `Password1!` and a sticky note — it reduces entropy by making passwords predictable while feeling stricter.	Yes
D24	**React/Next.js stays at v0.4**, Streamlit until then	Streamlit already proves the backend end to end, and the API is UI-agnostic (SSE + JSON), so swapping clients is replacing one consumer rather than rewriting anything. Building login screens now against an auth model that multi-tenancy will change in v0.4 means building them twice.	Yes

D23	**Email normalised (lowercased + stripped) at the Pydantic boundary**, once	Domains are case-insensitive and no real provider treats local parts as distinct, so `Vikas@x.com` and `vikas@x.com` must be one account. Normalising in each route handler means two copies that drift — and the classic bug is signup lowercasing while login doesn't, creating an account the user can never reach. Every entry point goes through a request schema, so the schema is the one place.	No
D22	**JWT over server-side sessions**	A session means a table lookup on every request — shared state, which is exactly what Block 2 removed. A JWT validates with no database round-trip, so any worker can authenticate any request in v0.4. Cost: tokens can't be revoked before expiry, hence short lifetimes.	Yes
D21	**UUID primary key for `users`; integers stay elsewhere**	An integer in a URL is enumerable (`/users/1`, `2`, `3`…), leaks total user count, and reveals signup order. `MessageRow.id` stays an integer because it never appears externally. **The rule is "UUID for anything exposed", not "UUID always."**	No
D20	**Argon2id over bcrypt**	Both are deliberately slow; Argon2id is additionally **memory-hard** (64 MiB per hash by default). bcrypt lets a GPU run thousands of guesses in parallel; Argon2id's memory cost means a 24 GB GPU manages ~375 instead of ~20,000. Current OWASP recommendation. `argon2-cffi` directly rather than a `pwdlib` wrapper — it already ships `check_needs_rehash()`.	Yes
D19	**Integration tests against Postgres deferred to v0.3**	They need a real database in CI (GitHub Actions service containers), which is v0.3's scheduled work. Adding infrastructure mid-refactor breaks "one thing at a time". Unit tests run against the in-memory repository and genuinely constrain the Protocol both implementations honour.	Yes
D18	**Alembic from the very first table**	`Base.metadata.create_all()` works exactly once — it can create tables, never alter them. A migration history with a gap at the start isn't a history. v0.4's deploy pipeline runs `alembic upgrade head` before starting a new version; that only works if every schema change is a script.	No
D17	**Messages get their own table, not a JSON column on `conversations`**	JSON means loading the whole blob to read the last 10, rewriting everything to append one, and nowhere to attach per-message embeddings in Block 4. It would also make the `limit` parameter meaningless — the interface only pays off against a normalised schema.	No
D16	**Tests come before the database**, not after	v0.2 Block 2 replaces the in-memory store with PostgreSQL — surgery on the core. Tests written against *current* behaviour are a characterisation: they pin down what works today so the refactor can't silently change it. Writing them afterwards means verifying the new thing against nothing. *"Changing existing code safely — tests as the safety net."*	No

D14	**Interrupted streams save nothing** (option A) — a disconnect mid-reply leaves the user message with no assistant reply	Only complete assistant responses are stored; a partial must never be recorded as if it were whole. **Accepted consequence:** history can hold a dangling user turn, so the model may see two user messages in a row. The production refinement (roll back the user message on `GeneratorExit`, keeping history strictly alternating) is logged for v0.2.	Yes
D15	Streamlit entrypoint is **`ui/streamlit_app.py`**, not `ui/app.py`	`ui/app.py` resolves to a module named `app`, colliding with the `app/` package; mypy refuses to check either. **Renaming beats configuring around it** — `--exclude ui` would have silenced type checking on a whole directory of real code.	Yes
D12	**The git repo is rooted at the project, not the parent folder**	Learned the hard way — `git init` had landed at `projects/`, mixing study notes with product code. See C13.	No

CONCEPTS LEARNED

C1 — The Claude/LLM API is stateless

There is no conversation stored on the provider's side. **Every request resends the entire message history.** The "memory" is 100% yours.

Three consequences that shape the whole architecture: 1. **Conversation state is your problem.** v0.1 keeps it in RAM → dies on restart → earns the database in v0.2. 2. **Cost grows quadratically with conversation length.** Turn 20 resends turns 1–19. This is *why* prompt caching, token counting, and context compaction exist. 3. **Externalized state is what makes a service scalable** — see C2.

C2 — Persistence ≠ statelessness (two prizes, one change)

Moving history out of process RAM into a database gives you **two** things:

Property	What it buys
Durability	Restart/crash doesn't lose the conversation
Statelessness	*Any* instance can serve *any* request

The second is the bigger deal. If history lives in process #1's RAM and the load balancer routes the next message to process #2, the assistant has amnesia — **the app is unscalable and no number of servers fixes it.**

C3 — 12-Factor config (Factor III): separate config from code

Config = anything that varies between laptop / staging / prod.

- **Security:** a key in source is in git history *forever* — every fork, every CI log. Rotation is the only fix, and you find out too late.
- **Deployability:** one artifact, many environments. If dev and prod need different *builds*, you can't promote a tested image to prod — you can only hope.

Pattern: `.env` (real values, **gitignored**) + `.env.example` (same keys, fake values, **committed**). The *shape* of config is public and versioned; the *values* are private.

C4 — Fail fast at startup

Amateur: `os.getenv("KEY")` scattered around → returns `None` → app boots → crashes on the first

user request at 2am. Production: validate **all** config once at import time → missing value → **the process refuses to start.**

Behaviour	What actually happens
App **won't start**	Orchestrator sees the container die → halts the rollout → old version keeps serving. **Automatic, silent, zero users harmed.**
App **starts then 500s**	Rollout completes → healthy-looking container serves errors → **someone gets paged. That's an incident.**

Same bug. Two completely different nights.

C5 — Config validation ≠ health check

Check	Question	When
Config validation	"Is my configuration present and well-formed?"	Once, at startup
Health / readiness probe	"Are my dependencies reachable *right now*?"	Continuously, in prod

Validating the key at startup proves a key **exists**. It does **not** prove the key is valid, that you have quota, or that the provider is up. Config is a *static* property of your deployment; dependency health is a *live* property of the world. Conflating them is how people build health checks that lie.

C6 — The single choke point (why the UI never calls the LLM directly)

- **v0.4 (React in the browser):** a key shipped to a browser is a key on the internet. Absolute rule.
- **v0.1 (Streamlit is server-side, so the key isn't browser-exposed):** the reason is **architectural control**. Every LLM call funnels through one service you own — the single door where auth, rate limiting, per-user cost tracking, structured logging, retries, and caching get installed. If the UI called the provider directly, none of those have anywhere to live.

Bonus: swapping Streamlit → React in v0.4 doesn't move the LLM logic an inch.

C7 — CI ≠ CD

	Question it answers	Triggered by	Needed when
CI	"Did I break it?"	Every push	**The moment code exists**
CD	"Is it live?"	Merge to main	The moment there's somewhere to deploy

Roadmap: v0.1 lint/format/type-check → v0.2 pytest + coverage gate → v0.3 service containers for integration tests → v0.4 Docker build + registry + **deploy**, dependency scanning → v1.0 LLM eval suite, load-test job, blue-green/canary.

C8 — Production-grade means *sequencing*, not maximalism

> "We'll clean that up later" is a banned phrase. So is writing Terraform for a service that doesn't exist.

The bar: **at every version, the thing runs, and everything it has is done properly.** v0.1 has no database — and its config, git hygiene, error handling, and CI are showable to a staff engineer. Bolting on Kubernetes in week one is a monument, not a system.

C9 — API billing is separate from chat subscriptions

Pro / Max / **Team** / Enterprise are **claude.ai** products (humans logging into a chat UI). The **API** is

billed separately with its own credits. **A Team seat does not grant API access for your application.** Model access isn't gated by subscription tier; what scales with spend is your **rate limits**.

C10 — LLM cost mechanics, and how bills run away

You pay **per token, per call** — input and output, at different rates. No subscription, no cap. 1,000 calls = 1,000 charges.

The quadratic problem. Because the API is stateless (C1), you resend the whole conversation every turn. Assuming ~1,000 tokens added per turn, on a $5/$25 model:

Turn	Input tokens sent	Cost of that one turn
1	200	$0.02
10	9,200	$0.07
30	29,200	$0.17
50	49,200	$0.27

One 50-turn conversation ≈ $7 — not the ~$1 intuition predicts, because turn 50 re-sent turns 1–49. This is *why* prompt caching exists (v0.3 cuts the repeated prefix to ~10%).

Three ways cost runs away: 1. **Retry loop with no cap** — error → retry → error → retry, overnight. Retries need a *maximum*. 2. **Streamlit re-runs the entire script on every interaction** ⚠ *(will bite in Block 5)* — every click re-executes the file top to bottom. An API call at module level = a billable call per interaction. People discover this via their invoice. 3. **Unbounded history** — turn 200 sends 200K tokens *every turn*.

Combined: a retry loop firing a 50-turn conversation 500 times ≈ **$3,500 overnight**, from a one-line bug.

Where this grows up: v0.3 structured logging of tokens + cost per call → v0.3 prompt caching → v1.0 per-tenant cost tracking. *You cannot build cost tracking in v1.0 if you never learned what drives cost in v0.1.*

C11 — Dependency isolation: virtualenv → Docker

Without isolation, every project on your machine shares one set of packages. Project A needs `pydantic 1.x`, Project B needs `2.x` — they cannot coexist. You break one by fixing the other. That's **dependency hell**.

A **virtual environment** (`.venv/`) is a private folder with its own interpreter and packages. Three things it protects: 1. **Package conflicts between projects** (the main event — venv isolates `site-packages`) 2. **The system Python**, which macOS/Linux use for OS tooling — polluting it breaks system tools 3. **Reproducibility** — without isolation you can't tell what your project *needs* vs what's incidentally installed, so you can't produce a trustworthy dependency list → unreproducible builds → "works on my machine"

> **The same instinct at a bigger scope is Docker.** Isolate dependencies so it runs the same everywhere — at the language level that's a virtualenv, at the OS level that's a container. Remember this in v0.4.

C12 — `.python-version` ≠ `requires-python`

Two different mechanisms, often confused:

	What it says	Who reads it	Shape
`.python-version`	"Use *exactly* this interpreter"	`uv` / `pyenv`, when building `.venv`	A **pin**: `3.12`
`requires-python` (pyproject)	"This project *works on* these versions"	Dependency resolvers, and installers	A **constraint**: `>=3.12`

The first controls *your* environment. The second shapes *resolution* — it's how a resolver knows not to hand you a package that dropped 3.12 support. You need both.

Why pinning matters at all — the three concrete failure modes it kills: 1. **Stdlib behaviour changes** between minor versions 2. **C-extension ABI mismatch** — a wheel built for 3.12 physically will not load on 3.14 3. **Different dependency resolution** — the same install can pick *different package versions* per Python version

Together those are the entire content of the phrase *"works on my machine."*

Also: boring is a virtue in production. We pinned 3.12 despite 3.14 being installed. You don't run bleeding-edge language versions on a project whose dependencies you don't control — you'd spend evenings on someone's incompatible C extension instead of learning architecture.

C13 — Repo boundaries: one repo = one deployable unit

Learned by getting it wrong: `git init` had landed at `projects/`, so the repo contained study notes *and* product code. Three reasons that's broken:

1. **A repo should be one deployable unit.** In v0.4 you build a Docker image from it — your study notes don't belong in the image. 2. **Your portfolio link** should open OmniAssist, not a folder of planning markdown. 3. **CI triggers on the whole repo** — editing a plan doc would fire the pipeline for nothing.

Also: the project name is not cosmetic. It becomes the import path, the package name, the GitHub URL, and the Docker image tag. Fix it on day one; unwinding it in v0.4 is miserable.

C14 — Presence validation ≠ value protection (`SecretStr`)

Making a key **required** (C4) and keeping it **out of logs** are different problems. A plain `str` key is invisible to git but fully visible to `repr()`, `str()`, tracebacks, framework error pages, and any observability tool that serialises objects.

> **Secrets rarely leak because someone committed them. They leak because something *printed* them.**

`SecretStr` renders as `SecretStr('')` and requires `.get_secret_value()` to read. Accidental exposure becomes impossible; deliberate access still works. Verified empirically: `'gsk_' in repr(settings)` went `True` → `False`.

C15 — Validate values, not just presence (`Literal`)

`llm_provider: str` accepts `"bananacloud"`. `app_env: str` accepts `"prodution"` — which in v0.4 would silently take the *non-production* branch **in production**. A typo that validates is worse than one that crashes, because the failure surfaces far from its cause.

`Literal["groq", "anthropic"]` rejects it at startup, naming the permitted values. **Real payoff:** `LLM_PROVIDER=grok` — a typo actually made repeatedly in this project's own planning — is now

impossible to deploy. *Encode the mistakes you personally make into the type system.*

C16 — Formatting ≠ linting

Two different jobs, both in CI:

Tool	Job	Caught here
`ruff format`	Layout — whitespace, line breaks, quotes	stray blank lines
`ruff check`	Convention & correctness — import order, unused vars, bugs	`I001` import order

`ruff format` reported "already formatted" while `ruff check` still failed. Passing one says nothing about the other. Import order convention: **stdlib → third-party → local**, alphabetical within groups.

C17 — Git tracks files, not directories

An empty `tests/` directory simply does not exist to git. Commit, clone elsewhere, and the folder is gone. Convention: an empty `.gitkeep` file to hold the directory open. (`.gitkeep` is not a git feature — purely a naming convention.)

C18 — Commit messages: Conventional Commits, and *why* not *how*

`feat:` / `fix:` / `chore:` prefixes are machine-readable and later drive changelog generation and semantic versioning. The **body** should explain *what changed and why* — the diff already shows *how*. Six months on, the body is the only record of why `SecretStr` is there.

C19 — Verify behaviour, not exit codes

`git check-ignore -v .env.example` exits **0** when *any* pattern matches — **including a negation** (`!.env.example`). Branching on that exit code produced a false "wrongly ignored" alarm. The definitive test was behavioural: does `git add --dry-run` succeed, and does the file appear in `git status`? *Don't trust a tool's exit code whose semantics you haven't checked.*

C20 — Dependency Inversion, and why `Protocol` over `ABC`

> **High-level code must not depend on low-level code. Both depend on an abstraction.**

The trap: `from groq import Groq` inside `services/` welds business logic to one vendor. Every service imports it; swapping providers touches all of them; testing needs a live key.

The fix: `services/ → LLMClient (interface) ← GroqClient`. The arrow from the vendor points **up** at your contract — that's the "inversion."

	`ABC`	`Protocol` ← chosen
Conformance	must **inherit**	just **has the methods**
Typing	nominal	structural (checked duck typing)
Test double must inherit?	yes	**no**

Decisive reason: `FakeLLMClient` satisfies the contract *without importing or inheriting anything from production code*, and mypy still verifies it. **Proven:** one `talk(client: LLMClient)` function drove a live Groq client and a keyless fake.

C21 — The composition root

Exactly one place is allowed to know both the global config **and** the concrete implementations: the factory. Everything downstream receives an `LLMClient` and never learns which one.

Two deliberate details in `factory.py`:

- **Returns `-> LLMClient`, not `-> GroqClient`.** Annotate the concrete type and callers start reaching for vendor-specific attributes; the abstraction leaks within a week.
- **The vendor import sits inside the function.** Importing the factory doesn't pull `groq` into memory; a Groq-only deployment never loads the Anthropic SDK.

C22 — Static typing catches what passing tests do not

The live call returned `"OK"` — green, working, shipped. mypy then found `message.content` is `str | None` while `chat()` promised `-> str`.

Failure mode if unfixed: `chat()` returns `None`; three layers up something calls `.strip()`; `AttributeError` in a file unrelated to the cause. **Bugs that surface far from their origin are the expensive kind.** The happy path is common, which is exactly why tests alone miss this.

Corollary — not every type error is your bug. mypy also flagged `Settings()` for a "missing argument" it can't know is populated from `.env` at runtime. Correct fix: enable `plugins = ["pydantic.mypy"]` (verified: 3 errors → 2). Wrong fix: `# type: ignore`, which would also silence real errors.

C23 — The adapter boundary translates types *and* errors

Two leaks the adapter must stop:

Types. Your `Message` is `dict[str, str]`; the SDK wants `ChatCompletionUserMessageParam`. `cast()` at that seam is legitimate — translating is the adapter's whole job. The alternative leaks vendor TypedDicts into `services/`. *A cast at a boundary is fine; a cast inside business logic is a smell.*

Errors. Services must never catch `groq.RateLimitError`. The adapter raises a vendor-neutral `LLMError`. **A vendor leaks upward through its exception types just as easily as through its imports.**

C24 — How to read an unfamiliar API (the FDE skill)

Six questions to answer from the docs — *copying exact names, never guessing*: **auth** · **exact call path** · **request shape** · **response extraction path** · **exception class names** · **streaming mechanics**.

Then **verify against the installed library, not the docs or your memory** — `inspect.signature`, `dir()`. Doing so surfaced two things the quickstart never mentioned: 1. **`max_retries=2` is the default** — one logical call can be three HTTP requests, tripling cost and burning rate limit during exactly the moments you're already throttled. *Never inherit a default you didn't choose.* 2. **14 exception classes exist**, including `RateLimitError` — which D11 guarantees you will hit on the free tier.

> **"It raises errors when something goes wrong" is never an acceptable answer about an API.** Retry logic, alerting and user-facing messages all branch on class names.

Also noted for Block 3: streaming uses `chunk.choices[0].delta.content` — **`delta`, not `message`.** Different shape from the non-streaming path.

C25 — A parameter that changes the return type should have been a separate function

`chat(messages, stream: bool)` would return `str | Iterator[str]` — forcing *every* caller to narrow a union, including the 90% who passed `stream=False` and know exactly what they're getting. `@overload` can paper over it, but that's machinery invented to solve a self-inflicted problem.

Also: flag arguments hide intent (`chat(msgs, True)` says nothing) and a Protocol declaring **two methods** forces every implementer — including the fake — to provide both. A bool can be silently ignored.

C26 — Streaming is a UX and reliability feature, not a performance one

Reason	Effect
Perceived latency	Total time is unchanged (sometimes marginally worse). Reading starts immediately.
Timeouts	Long generations exceed proxy/LB timeouts; flowing bytes keep the connection alive (bites in v0.4).
Cancellation	User stops a bad generation → stop paying for tokens (C10).

Measured: first token 0.58s vs total 0.86s. Small on Groq (very fast); on a slower provider generating 500 tokens the gap becomes ~0.4s vs ~8s. **The benefit scales with generation length.**

C27 — Generator laziness, and the eager/lazy split

A function containing `yield` does not execute when called — it returns a generator; the body runs only on iteration.

This bit for real: `self.calls.append(...)` inside the generator body meant the call was never recorded until something iterated. `stream_chat(msgs)` then `assert len(fake.calls) == 1` **failed**.

> **Pattern: if a generator function must do anything eagerly — validate arguments, record a call, acquire a resource — split it into a plain function that returns the generator.**

```
def stream_chat(self, messages):     # plain function — body runs on call
    self.calls.append(messages)
    return self._stream()

def _stream(self):                   # generator — runs on iteration
    ...
    yield piece
```

Same property in the real client, deliberately: `GroqClient.stream_chat` issues no HTTP request until iterated. Good (don't pay for an unconsumed stream) — but an `AuthenticationError` surfaces at the first `for` loop, not at the call site.

C28 — A test double that lies gives you confidence you haven't earned

The fake yielded `word + " "`, so `"".join(stream_chat(m))` was `'one two three '` while `chat(m)` returned `'one two three'`. Real provider chunks concatenate **exactly**.

> **Invariant the fake must uphold: `"".join(client.stream_chat(m)) == client.chat(m)`**

Why it matters: Block 4 accumulates streamed chunks into history. A test on the unfaithful fake stores a trailing space and **passes**; production stores something different. *A test that passes while the real path is broken is worse than no test.* Fix: yield fixed-size character slices — exact reconstruction by construction, and closer to real token boundaries than word-splitting.

C29 — The same value can mean different things in different contexts

`content` is `str | None` in both methods. The correct handling is **opposite**:

Context	Meaning of `None`	Response
`chat()` — the whole reply	Anomaly: model produced nothing	**raise `LLMError`**
`stream_chat()` — one chunk	Routine: first chunk carries the role, last carries a finish reason	**skip and continue**

Decide what a value *means in context* before deciding what to do with it. That judgement is most of what separates correct code from merely defensive code.

C30 — Server-Sent Events: the whole protocol, and its three traps

SSE is **an ordinary HTTP response that never ends**: `Content-Type: text/event-stream`, then `data: <payload>\n\n` per event. A **blank line terminates an event**. That's it.

Why SSE over WebSockets here: token streaming is one-directional. SSE is plain HTTP (proxies, LBs and CDNs pass it), browsers reconnect automatically, and there's no upgrade handshake. WebSockets buy bidirectionality we don't need and cost infrastructure config in v0.4. *Pick the least powerful tool that solves the problem — it has the fewest failure modes.*

Three traps, all hit or avoided in Block 4:

1. **Payloads must be JSON-encoded.** Model output is full of newlines. A raw `data: hello\nworld\n\n` becomes **two malformed events** — the client sees a truncated reply and blames the model. `json.dumps(chunk)` escapes the newline inside a quoted string so the frame stays one line. Seen live in our own output: `data: " \n"`. 2. **`[DONE]` sentinel.** SSE has no end-of-stream marker, so the client can't distinguish "finished" from "connection dropped." Convention borrowed from OpenAI's API. 3. **`X-Accel-Buffering: no`.** Without it nginx buffers the whole response and delivers it at the end — **streaming silently stops working only in production**, the worst place to find out.

Also: never buffer server-side. Collecting all chunks then returning them is a slow non-streaming endpoint with extra steps.

C31 — A health check must be cheap, or it becomes the load

It is tempting to have `/healthz` verify the LLM is reachable. Do the arithmetic first:

> A load balancer probes every **10 seconds = 8,640 requests/day**. The Groq free tier is ~**1,000/day**. > **The health check alone would exhaust the entire quota eight times over, serving zero users.**

This is C5 with a price tag. Split the two questions:

Probe	Question	On failure
Liveness (`/healthz`)	Is the process alive?	Restart the container
Readiness (`/readyz`, v0.4)	Can I serve traffic *right now*?	Remove from the LB — **don't** restart

C32 — Trim what you *send*; keep what you *store*

`trimmed = history[-max_history:]` is a **slice, not a mutation**. Verified: 12 messages stored, 4 sent. Trimming bounds the request payload; it is not forgetting.

Two things to know about the choice:

- **Message count is a proxy for token count.** The real limit is ~14,400 tokens/min (D11) and messages vary wildly in length. Proper token counting needs a tokenizer — deferred to v0.3 with observability. *Know you chose a proxy, and why.*
- **A naive window can start mid-exchange.** Our trimmed payload opened with an `assistant` message — from the model's view, it spoke first, unprompted. Same family as D14's dangling user turn: **don't send the model state that couldn't occur in a real conversation.**

C33 — Streamlit re-runs the entire script on every interaction

Every click, every message, every widget change re-executes the file from line 1.

	Consequence
Module-level code	**Runs again each time** — an API call there fires per click (C10, with a bill)
Local variables	**Wiped** — history vanishes every message
`st.session_state`	The only thing that survives; holds `conversation_id` and `messages`

Corollary: past messages must be **redrawn** on every run — Streamlit doesn't remember what it painted. Also `timeout=None` on the streaming HTTP call, since a default timeout kills long replies mid-flight.

C34 — Syntactically valid dead code is harder than a crash

The Streamlit page rendered a title and nothing else — **no error**. The entire `st.chat_input` block had been indented one level, nesting it inside a function that merely got *defined*. Valid Python, never executed.

> **Diagnostic: when a script "does nothing," list its module-level statements** (`ast.parse(...).body`). If the thing you expected to run isn't there, it's nested inside something.

A crash tells you where to look. Silent dead code tells you nothing — which is why this class of bug eats hours.

C35 — Fix the name, don't configure around the collision

`ui/app.py` and the `app/` package both resolve to a module named `app`; mypy refused to check either and suggested `--exclude`, `__init__.py`, or `--explicit-package-bases`.

All three suppress the symptom. Renaming to `ui/streamlit_app.py` removes the cause, and is a better name anyway. `--exclude ui` would have disabled type checking across a whole directory of real code — **a config flag that silences a checker is a liability you'll forget you added.**

C36 — `uv sync --locked` turns reproducibility into an enforced rule

The flag installs **exactly** `uv.lock` and **fails the build if the lock is out of date** with `pyproject.toml`.

Two guarantees that follow:

- CI cannot quietly resolve different versions than your laptop has
- Nobody can add a dependency without committing the lockfile

This is D2's payoff arriving: the reason for choosing `uv` was never speed, it was the lock. **A**

convention enforced by a machine is a rule; one enforced by discipline is a suggestion.

C37 — Tags are immutable; branches move

`v0.1` is a permanent pointer to one commit. `main` will keep moving; the tag won't.

Why it matters concretely:

- `git diff v0.1..HEAD` tells you exactly what changed since a known-good state — essential when a v0.2 migration breaks something
- It makes v0.2 an *evolution* of a shipped release rather than a rewrite (D1)
- In v0.4 the deploy pipeline deploys and rolls back to **tags — you cannot roll back to a branch**

C38 — Test behaviour, not implementation

```
assert len(fake.calls[-1]) == 3          # ✓ what the provider received
assert service._store["c1"] == [...]     # ✗ reaching into private state
```

The first survives the PostgreSQL migration; the second breaks the moment `_store` stops being a dict — and a "safety net" that breaks during the refactor it was built for is just noise you have to fix while already mid-surgery.

Corollary: **don't test the library.** Not that pydantic validates or that FastAPI routes — only your own logic (history accumulates, trimming caps the payload, the full conversation survives).

The trimming case is deliberately **two** tests, not one: the first asserts the cap, the second asserts the cap wasn't achieved by *deleting* data. Merged into a single test, you'd likely assert only the half you were thinking about.

C39 — Accessors must not hand out internal state

`get_history` returned `self._store.get(cid, [])` — **the live list**. Proven: a caller appended to it and corrupted the service's history from outside.

Why it's a migration landmine, not just poor style: when `_store` becomes a SQL query, `get_history` will build a *fresh list from rows* and mutation will do nothing. Any code that accidentally relies on the leak keeps working until the database lands, then fails in a way that looks unrelated to the migration.

> **Make the in-memory version behave the way the database version will, so the swap is invisible.** Today's shortcut is tomorrow's migration bug.

Fix: `return list(...)`.

C40 — Regression tests exist to stop a fixed bug coming back

`test_get_history_returns_a_copy` proves nothing about the feature — it exists solely so nobody reintroduces the leak. A bug found once is a bug worth pinning; the fix is cheap now and invisible later.

C41 — A half-declared package breaks static analysis

mypy: *"Source file found twice under different module names: `fakes` and `tests.fakes`."* With no `__init__.py`, `tests/fakes.py` was a top-level module `fakes`; the import `from tests.fakes`

`import ...` made it `tests.fakes` as well. One file, two identities.

mypy offered `--explicit-package-bases` and `MYPYPATH`. Both configure around it. The real problem was that `tests/` was being *used* as a package without being *declared* as one — `touch tests/__init__.py` fixed the cause. Same principle as C35.

(Shell aside: zsh does not treat `#` as a comment interactively by default, so a pasted trailing comment becomes pytest arguments. `setopt interactive_comments` fixes it.)

C42 — The Repository pattern, and the two-step refactor rule

An object that looks like an in-memory collection to its caller while hiding whether the data lives in RAM or Postgres. `ChatService` depends on a Protocol — `get_history(cid, limit)` and `add_message(cid, msg)` — and never learns which implementation it got. Swapping storage engines was **one line in the composition root**.

> **Never change the abstraction and the implementation in the same step.**

Step	Change	If a test fails
2.3	Protocol + in-memory impl; behaviour identical	the **refactor** is wrong
2.5	Postgres impl; interface unchanged	the **SQL** is wrong

Both at once and a red test tells you nothing about which half broke.

C43 — Let the database own correctness

Four places where the database is a better authority than application code:

- **`server_default=func.now()`, not `default=datetime.now`** — Python's version means three app servers with drifting clocks write inconsistent orderings, and it doesn't apply to inserts that bypass the ORM. One clock, always applied.
- **`DateTime(timezone=True)`** — a naive timestamp is a bug with a delayed fuse. Local Postgres runs `Asia/Kolkata`; a v0.4 deployment runs UTC.
- **`ondelete="CASCADE"`** — the DB removes orphans. Application code can be bypassed; a constraint cannot.
- **The foreign key surfaced a bug the dict had hidden:** `setdefault` created conversations implicitly, so `add_message` never had to think about it. Postgres refuses. **Constraints make impossible states impossible.**

C44 — An index is a data structure chosen for an access pattern

Every read is *"messages for this conversation, chronological, limited"*, so:
`Index("ix_messages_conversation_created", "conversation_id", "created_at").`

Without it Postgres scans every message in every conversation. At 50 messages, invisible; at 500,000, seconds per request. **Same reasoning as picking a hash map over a list** — this is where DSA stops being an exercise.

It only pays off because of the interface: `ORDER BY ... LIMIT 10` on an indexed column reads ~10 rows, while "load all, slice in Python" reads everything. Design the access pattern first; the index serves it.

C45 — Check-then-act is a race; make it atomic

```
conversation = session.get(Conversation, cid)    # read
if conversation is None:
    session.add(Conversation(id=cid))            # write
```

Two concurrent requests opening the same conversation both see `None`; the second `INSERT` raises a duplicate-key error. Invisible with one user, **guaranteed in v0.4** with multiple workers — surfacing as an unreproducible 500.

The fix is never "check more carefully", it's **one statement**: `INSERT ... ON CONFLICT DO NOTHING`. **Let the database arbitrate concurrency — it's built for it; your application code isn't.**

C46 — One Engine per process

A SQLAlchemy `Engine` owns a **connection pool**. Create one per request and you open a fresh pool every time, never reuse a connection, and exhaust Postgres's 100-connection default under trivial load. `lru_cache` it.

`pool_pre_ping=True` sends a cheap `SELECT 1` before lending a pooled connection — the difference between surviving a database restart and needing your own.

C47 — Migrations are code; autogenerate is a draft

`create_all()` can create tables, never alter them. Alembic makes the schema **versioned, diffable, reviewable in a PR, and reversible** — the database equivalent of `uv.lock`.

Autogenerate reliably detects new tables and columns. It is unreliable about **renames — it emits drop + add, which destroys data** — and about server defaults, constraint changes and custom types like `vector`.

> **A migration you haven't read is a production incident you've scheduled.**

Reversibility was *proven*, not assumed: `downgrade -1` removed the tables, `upgrade head` brought them back. In v0.4 that's the 2am rollback path.

C48 — Ordering needs a *total* order

In Postgres `now()` returns the **transaction start time** — rows written in one transaction share a timestamp and `ORDER BY created_at` cannot separate them. Conversations come back scrambled. `ORDER BY created_at, id` breaks ties deterministically.

Related subtlety: to fetch the *last* N you must query `DESC ... LIMIT n` (so the index does the work), then reverse in Python — the model needs chronological order.

C49 — Dead code keeps its dependencies alive and hides them from the linter

After swapping to Postgres, `routes/chat.py` kept `repository = InMemoryConversationRepository()` — never read, but executed on every import. Ruff did **not** report the import as unused, *because the dead line used it.* One piece of dead code concealed another.

C50 — Password storage: three separate requirements

Hash, not encryption. Encryption is reversible *by design* — there is a key, and whoever holds it gets plaintext: your backup, your logs, an attacker who steals the key alongside the database. A hash is one-way, **including for you**. And the people it protects most are your users, who reuse passwords

elsewhere.

Slow, not fast. SHA-256 *is* a hash and is wrong here, because it's designed to be fast — a GPU computes billions per second, so an attacker with your table brute-forces common passwords in minutes. You want a tunable work factor:

	one login	1 billion guesses
SHA-256	~0.000001 s	**minutes**
Argon2id (defaults)	~0.04 s	**centuries**

Same user experience; completely different attacker economics. **You aren't making it impossible, you're making it unaffordable.**

Salted. Without a per-user random value, identical passwords produce identical hashes — you can see which users share one, and precomputed rainbow tables work. Argon2 and bcrypt generate and embed the salt automatically.

The hash string carries its own recipe: `$argon2id$v=19$m=65536,t=3,p=4$<salt>$<hash>`. That's how cost parameters can be raised next year while old hashes still verify, and what makes `check_needs_rehash()` possible.

C51 — Sequential IDs leak information

An autoincrement primary key in a public URL tells an attacker three things for free: records are **enumerable** (`/users/1`, `/2`, `/3`…), the highest value is your **total user count**, and any ID reveals **signup order**. UUIDs leak none of it.

The rule is not "always UUID" — `MessageRow.id` is an integer because it never leaves the database. **Match the key type to the exposure.**

C52 — A JWT is signed, not encrypted

`header.payload.signature`, all base64. **Anyone holding the token can read the payload with no key** — verified by decoding one by hand. The signature proves *"this wasn't altered"*, never *"this is private."*

> **Never put anything in a JWT you wouldn't print on a postcard.**

And pin the algorithm. The classic attack is editing the header to `alg: none`, or swapping `RS256` for `HS256` so a *public* key is used as an HMAC secret. PyJWT requires an explicit `algorithms=[...]` list for exactly this reason. **Never let attacker-controlled input tell you how to verify it.**

`sub` holds the user **id**, not the email — emails change; a token's subject must be immutable.

C53 — Stateless auth is C2 one layer up

A server-side session means storing a session ID and querying it on every request — shared state. A JWT is self-contained, so **any worker can authenticate any request with no shared store and no database round-trip.**

Sessions would have reintroduced precisely what moving conversation history to Postgres removed. The trade-off is real: a JWT **cannot be revoked before it expires**, which is why access tokens are short-lived.

C54 — mypy treats `...` as a stub body

`def hash_password(password: str) -> str: ...` returns `None` and **mypy says nothing** — `...` is the convention for `.pyi` stubs and Protocol methods, so the return check is skipped. That's why `LLMClient.chat(...) -> str: ...` type-checks.

An entire unimplemented function passed type checking. The only signal was ruff reporting an unused import. **Your linter caught what your type checker structurally cannot** — another reason both are in CI.

C55 — Autogenerate diffs models against the database

`alembic revision --autogenerate` run *before* the model existed produced `def upgrade(): pass`. No model → no difference → nothing generated. It would have applied cleanly and created nothing.

A compact restatement of C47: **autogenerate is a draft produced from what exists, not a thing that knows your intent.** Reading the file is the whole safeguard.

C56 — Migration history is append-only *once it's shared*

Two migrations named "create users" (one empty) were collapsed into one: roll back, delete the file, re-point the next revision's `down_revision`, re-apply.

That rewrite was safe **only because nothing had been pushed and nobody else had migrated.** Once a migration is on `main` and someone's database has recorded it, the history is immutable — you fix forward with a new migration instead. **Know which side of that line you're on before you edit a revision file.**

C57 — User enumeration: identical errors are not enough

A login endpoint that distinguishes *"no such user"* from *"wrong password"* is a **free account-checking tool** for anyone with an email list — which matters enormously for a health, finance or dating service. So both failures return the same 401 and the same message.

But the message is not the only observable. An attacker doesn't read your error, they **time it**:

Path	Work done	Time
Email exists, password wrong	DB lookup + argon2 verify	~53 ms
Email unknown	DB lookup, return early	**~2 ms**

A 25× difference, measurable over a handful of requests, and the identical message is worthless.

Fix: always do the same work. Verify against a throwaway hash when the user is missing, so both paths cost the same. Measured after the fix: **53 ms vs 56 ms — indistinguishable.**

> **Security is about everything observable — timing, response size, which errors occur, how many queries ran — not only what you return.** This class of bug passes every test and every code review, and is found with a stopwatch.

Related: the dummy hash is computed **lazily** (`lru_cache`), not at module scope — importing a module should never burn 50 ms of CPU.

C58 — A response model is a filter, not documentation

`TokenResponse` declares exactly two fields, and FastAPI serialises **only** those. Even if a handler

accidentally returned a `User`, `password_hash` could not reach the wire.

Compare the alternative — returning a dict and trusting every current and future handler to omit the sensitive fields. **Make the leak structurally impossible rather than relying on everyone remembering.** Same instinct as `SecretStr` (C14) and `frozen=True` (C39).

C59 — A lazy security check is no security check

`stream_reply` was a generator, so the route's `try/except ConversationNotFoundError` wrapped a call that executed **nothing**. The ownership check only ran when FastAPI began streaming — by which point the status line and headers were already sent, and a 404 was physically impossible. The request crashed mid-stream instead of being rejected.

This is **C27 reappearing in a security-critical path.** In v0.1 the cost was a missing test assertion; here it was an authorisation check that could not reject.

The fix is the same eager/lazy split: `stream_reply` is a plain function that performs the check and *returns* a generator from a private `_stream()`.

What did not catch it: mypy clean, ruff clean, all five tests passing. Only exercising the real cross-user path did. Hence `test_ownership_is_checked_before_the_stream_is_consumed`, which calls `stream_reply` **without iterating it** — a regression test for laziness itself.

C60 — 404, not 403, for resources that aren't yours

403 means *"this exists and it isn't yours"* — which confirms the id is real and lets an attacker enumerate. 404 reveals only what the caller is entitled to know.

Both repositories implement this uniformly: reading another user's conversation returns `[]`, writing to it raises `ConversationNotFoundError`. Same family as C57's identical login errors — **never confirm the existence of something the caller has no right to see.**

C61 — Adding a NOT NULL column to a populated table

Autogenerate emitted `op.add_column(..., nullable=False)` against a table holding 4 rows, and Postgres refused: *"column user_id contains null values."* **Structurally correct, operationally impossible** — autogenerate diffs models, and knows nothing about data (C55).

In production this is **three deploys**, not one: 1. `ADD COLUMN … NULL` — old code keeps inserting fine 2. backfill 3. `SET NOT NULL`

The reason is rolling deploys: old and new code run simultaneously, and old code's inserts know nothing about the new column. Doing it in one step here was acceptable only because the rows were disposable local data — the same window as C56.

Bonus observation: the failure left no damage. Postgres has transactional DDL, so the migration rolled back atomically. MySQL would have left the column half-added and the revision unrecorded.

C62 — The upsert ownership trap

`INSERT … ON CONFLICT DO NOTHING` on the parent conversation looked safe. Add an owner column and it silently isn't: **User B posts to User A's conversation id, the conflict fires, `DO NOTHING` runs, and the message is inserted into A's conversation.** A cross-user *write*, which is worse than a read

leak.

The upsert must be followed by an ownership check in the same transaction. **When you add a column that carries authority, re-audit every statement that touches the row** — "do nothing on conflict" means "do nothing about the conflict", not "this is fine".

C63 — Auth in a re-run model: the gate and `st.stop()`

Streamlit has no routing. The script runs top to bottom on **every** interaction, so *"am I signed in?"* cannot be remembered — it must be re-derived each run:

```
if "token" not in st.session_state:
    render_auth()
    st.stop()        # halt here; nothing below runs
render_chat()
```

Without `st.stop()` the chat UI renders underneath the login form. `st.stop()` is how you write a guard clause when there are no routes to redirect to.

`st.form` matters for the same reason: a bare `text_input` re-runs the script on **every keystroke**. A form batches the inputs and submits once.

C64 — Store the token, never the password

The password goes into a form field, is posted once, and is never written to `session_state`. **You cannot leak what you do not keep.** The token is stored because every subsequent request needs it.

And handle expiry as a normal path, not an error. Tokens live 60 minutes; a tab left open will 401 on its next message. The client drops the token and re-renders the login screen rather than showing a traceback — the user sees a login form, which is the truth.

This is the full **auth flow**, not just an auth check: credentials → token → stored → attached to every request → expired → back to login. The same five stages appear in React in v0.4; only the syntax differs.

C65 — One `except` for a whole library's error family

`pypdf` raises fourteen distinct exception types, and every one of them inherits from `PyPdfError`. A single `except PyPdfError` therefore contains the entire library, and the caller is handed a project-defined `PdfExtractionError` instead.

The general rule: **check whether a library gives its exceptions a common base before enumerating them.** Most mature libraries do. Catching the base is not laziness — it is the difference between a boundary that holds and one that leaks a new exception type the next time the library is upgraded.

C66 — Silent success on useless input is worse than an error

A scanned PDF parses perfectly and yields zero text. Indexing it "succeeds": the upload returns 200, nothing is stored, and the user discovers three questions later that the assistant knows nothing about their document.

The failure has to surface **at the moment the user can still act on it**. Hence the explicit rejection with an OCR hint. Note the asymmetry that makes this correct rather than merely strict: an empty *page* is normal and is skipped; an empty *document* is rejected. A 40-page report with a scanned cover

still indexes its other 39 pages.

C67 — Chunking is the retrieval unit

Embedding a whole document produces one vector that is the *average* of everything the document says — and the average of fifty pages means nothing. Ask "what is the refund window?" and it will not match, because the document is mostly about other things.

The unit you store is the unit you get back. You do not want the document that mentions refunds; you want the paragraph that states the window. Overlap exists for the same reason at a smaller scale: a cut that lands mid-sentence leaves neither chunk able to answer, so every idea must appear whole in at least one chunk.

C68 — Derive the cursor from where you actually stopped

The chunker's first version advanced with `start += size - overlap` while the boundary search independently pulled `end` *backwards*. The two were computed from different premises, and whenever `end` moved further back than the stride, the text between them was covered by no chunk at all.

Measured: **32 of 45 characters silently dropped.** No exception, no warning. The fix is one line — `start = end - overlap` — and the principle generalises far beyond chunking: **when a loop adjusts its endpoint, the next iteration must start from the adjusted value, never from the value you assumed it would take.**

Also note what caught it. `ruff`, `mypy` and every mechanical test passed; the test that found it was *"does any input text fail to appear in the output"* — a **conservation check** rather than a behaviour check. Worth asking of any transform: what must be preserved, and does a test assert it?

C69 — A guard checked once cannot see what the loop does later

`overlap >= size` is rejected at the door. It still permits `size=1000, overlap=900`, and once the boundary window pulls `end` back to `start + 800`, `end - overlap` lands *behind* `start` — an infinite loop that no test catches, because a hanging test produces no failure, just a stalled CI job.

Entry validation covers the inputs; it cannot cover a value the loop computes later. Make progress structural (`max(end - overlap, start + 1)`) rather than relying on a precondition to imply it.

C70 — Bound the search for a "nicer" cut

Searching the whole window for a boundary means one early space can end a chunk after seven characters. Long unbroken runs are ordinary in real documents — URLs, hashes, base64 blobs, CJK text without spaces.

Restricting the search to the last fifth gives a cheap guarantee: a boundary is taken only when it is *nearly* where the hard cut would have been. **A clean hard cut beats a degenerate chunk**, and preference order (paragraph → line → sentence → space, first hit wins) beats "whichever marker appears latest".

C71 — Keyword-only parameters make a mistake unspellable

`chunk_text(body, 150, 1000)` type-checks perfectly — both arguments are `int` — and silently produces garbage. A `*` in the signature forces `chunk_text(body, size=1000, overlap=150)` at every call site.

Reach for this whenever **two adjacent parameters share a type and transposing them is not an error, only a wrong answer.** The type checker cannot help; the signature can.

C72 — Embeddings are not interchangeable the way LLM providers are

Swapping Groq for Anthropic is harmless: old conversations still read fine. A vector, by contrast, is only meaningful against the model that produced it.

Two separate failures follow. **Dimensions differ** — 384 for `bge-small`, 768 for Gemini — so the `vector(384)` column breaks outright. Worse, even at matching widths **the semantic space differs**: the two models place the same sentence in unrelated coordinates, so similarity search returns noise with no error at all.

This is why `dimensions` and `model_id` are on the protocol. Dimensions let the schema be derived rather than guessed; `model_id` is stored per row so stale vectors can be *detected* after a provider change. **Swapping the LLM is a config change; swapping the embedder invalidates the index.**

C73 — Queries and documents are embedded differently

`bge` models expect an instruction prefix on queries (*"Represent this sentence for searching relevant passages:"*) and nothing on passages. Embed a query like a document and retrieval quality drops measurably, with no error.

Two methods — `embed_query` and `embed_documents` — rather than one `embed()` make the mistake impossible to express. The batching asymmetry falls out of the same split: a document upload is hundreds of chunks (one round trip, not hundreds), a user question is always exactly one string.

C74 — Import cost is a design decision

`from app.embeddings.local import LocalEmbedder` sits *inside* `get_embedder()`, not at module top. Verified: importing the factory loads nothing heavy, while importing `local` pulls in `fastembed` and `onnxruntime`.

Without that, every importer of the factory — a test, a route, `main.py` at startup — pays for ONNX and tokenizers. Same discipline as `get_settings()` (C-series, lazy config): **importing a module must have no side effects and no meaningful cost.** The related guarantee is that no test constructs `LocalEmbedder`, so CI never downloads the 130 MB model.

C75 — A type annotation as a conformance proof

`embedder: Embedder = FakeEmbedder()` is a one-line test that mypy checks at build time: if the protocol gains a method and the fake does not implement it, type-checking fails before a single test runs.

This is the structural-typing payoff (the `Protocol`-over-`ABC` choice, applied for the fifth time): the fake inherits from nothing, yet conformance is still *proved* rather than hoped for.

REFERENCE — LLM API pricing (2026-08-02)

Anthropic (authoritative):

Model	Model ID	Context	Input /1M	Output /1M
Claude Opus 5	`claude-opus-5`	1M	$5.00	$25.00

Claude Sonnet 5	`claude-sonnet-5`	1M	$3.00 ($2 intro to 2026-08-31)	$15.00 ($10 intro)
Claude Haiku 4.5	`claude-haiku-4-5`	200K	$1.00	$5.00

Cross-provider snapshot — *third-party aggregators, verify before committing money*:

Tier	Model	Input /1M	Output /1M
Frontier	Claude Opus 5 · GPT-5.5	$5.00 · $5.00	$25.00 · $30.00
Frontier	Claude Sonnet 5 · GPT-5.4 · Gemini 3.1 Pro · Grok 4.5	$3.00 · $2.50 · $2.00 · $2.00	$15.00 · $15.00 · $12.00 · $6.00
Budget	Claude Haiku 4.5 · Llama 3.3 70B (Groq) · DeepSeek V4 Pro	$1.00 · $0.59 · $0.44	$5.00 · $0.79 · $0.87
Ultra-budget	Grok 4.1 Fast · DeepSeek V4 Flash · Mistral Small 3.2 · GPT-4.1-nano	$0.20 · $0.14 · $0.10 · $0.10	$0.50 · $0.28 · $0.30 · $0.40

Free tiers: Gemini **1,500 req/day, no card, no expiry** · **Groq ~1,000 req/day, no card** ⬅ *ours* · Cerebras 1M tok/day · xAI $25 credits + up to $150/mo **in exchange for data sharing** · OpenAI $5/3mo · **Anthropic: none**

Three traps spotted while comparing: 1. ***"Free" always has a price — find it.*** xAI's generous tier is paid for with your conversation data. 2. **Grok doubles its rate above 200K tokens** — a pricing cliff sitting exactly where conversation history grows unboundedly (C10). *Pricing structure is an architectural input, not trivia.* 3. **Never build on an announced-EOL model** (Gemini 2.5 Flash-Lite retires 2026-10-16) — a self-inflicted migration.

Anthropic API gotchas (for when we add it): model IDs are complete as written — **never append a date suffix** · on Opus 5 thinking is **on by default** and `max_tokens` caps thinking **plus** response text together · `temperature/top_p/top_k` are **rejected (400)** — steer with prompting · stream for long outputs or you'll hit SDK HTTP timeouts.

SELF-CHECK HISTORY

2026-08-02 — v0.1 design quiz: 3/3

Q	Verdict	Sharpening applied
What happens to history if FastAPI restarts?		Missed that externalized state also buys **horizontal scalability** → C2
Why fail at startup, not first request?		Said "know if the API is working" — that's a **health check**, not config validation → C5
Why does the UI call FastAPI, not the LLM?		Correct for v0.4's browser; for v0.1's server-side Streamlit the real reason is the **single choke point** → C6

2026-08-02 — Block 1 Step 1 quiz: 2/2

Q	Verdict	Sharpening applied
Why pin the Python version?	Strong	Named reproducibility; added the 3 concrete failure modes + the `.python-version` vs `requires-python` distinction → C12
What breaks without a virtualenv?	Right instinct	It's mostly *packages*, not Python; plus system-Python pollution and unreproducible dependency lists → C11

2026-08-02 — Block 1 adversarial code review of `app/config.py`: 3 findings, 2 real defects

#	Severity	Finding	Outcome
1	Security	API key leaked via `repr()` / `str()` / tracebacks	Fixed with `SecretStr` → C14
2	Correctness	Invalid values accepted (`bananacloud`, `prodution`)	Fixed with `Literal` → C15
3	Style	Inconsistent blank lines + unsorted imports	Fixed via `ruff format` + `ruff check --fix` → C16

Final state: 6/6 verification checks pass — lint clean, format clean, three distinct invalid configs rejected at startup, happy path loads, zero key leakage.

2026-08-02 — Block 2 API-reference reading: 5/6

Correct on auth, call path, message shape, response extraction, streaming flag. Weak on **errors** — "it raises exceptions" is not actionable; the answer needed class names. Introspection then found `max_retries=2` silently on by default, which the docs did not surface.

2026-08-02 — Block 2 mypy review: 3 findings

#	Type	Finding	Outcome	
1	False positive	`Settings()` "missing argument" — mypy can't see `.env`	Enabled `pydantic.mypy` plugin → C22	
2	Structural	`dict[str,str]` vs SDK TypedDicts	`cast` at the adapter seam → C23	
3	**Real bug**	`content` is `str \`	None, `signature promised str`	Raise `LLMError` → C22/C23

Final: mypy clean, ruff clean, live call returns `OK`, fake works with no `.env` and no key.

2026-08-02 — Block 3 review: 2 findings, both real

#	Finding	Outcome
1	Fake's stream didn't reconstruct its own `chat()` (trailing space)	Fixed-size chunking → C28
2	`self.calls` never recorded — eager work sat inside a generator body	Eager/lazy split → C27

Design question answered correctly: separate `stream_chat()` over a `stream: bool` flag → C25.

Block 4 review — 2 findings

Finding	Outcome
Trimmed window can open with an `assistant` message (state that can't occur in a real conversation)	Logged for v0.2 → C32
First chunk is `""` — passes the `is not None` guard and emits a useless SSE frame	Logged → C30

Design questions answered 4/4, including the interrupted-stream policy (→ D14).

Block 5 review — 1 finding

Finding	Outcome

Whole chat block indented inside `stream_reply()` — valid syntax, never executed, no error shown	Dedented; AST diagnostic learned → C34

Plus a module-name collision caught by mypy → C35 / D15.

Block 6 — CI verified

`ruff format --check`, `ruff check` and `mypy` all pass **with no `.env` and no API key present** — D5 proven, not assumed. `uv sync --locked` confirms the lockfile is in sync. Two green CI runs (PR + main), ~35s each.

BLOCK PROGRESS — v0.1

Block	Status
1 — Repo skeleton + config & secrets	**COMPLETE** (2026-08-02) — 8/8 steps · commit `6e40a75` · github.com/vikasgautam2003/OmniAssist
2 — LLM client (D8 interface + GroqClient + factory + fake)	**COMPLETE** (2026-08-02)
3 — Streaming	**COMPLETE** (2026-08-02)
4 — FastAPI + SSE + history	**COMPLETE**
5 — Streamlit UI	**COMPLETE**
6 — CI + README + tag `v0.1`	**COMPLETE**

CHANGE LOG

Date	What
2026-08-02	`FLAGSHIP_PROJECT.md` — CI added to v0.1 best practices & stack; recorded CI-moves-to-v0.1 decision + the no-live-key constraint
2026-08-02	`FLAGSHIP_PROJECT.md` — v0.1 block list expanded to 6 blocks
2026-08-02	`FLAGSHIP_PROJECT.md` — stack switched to provider-agnostic LLM layer (Groq default); Groq-free-tier decision recorded
2026-08-02	`LEARN_SHEET.md` created, then lost in a folder cleanup, then rebuilt in full — **now correctly located at `projects/omniassist/`**
2026-08-02	Project scaffolded: `uv init . --python 3.12`, renamed `ai` → `omniassist`, `pyproject.toml` name fixed, git repo re-rooted at the project (D12, C13)
2026-08-02	**Block 1 COMPLETE** — `.gitignore`, `.env/.env.example`, `app/config.py` (fail-fast + `SecretStr` + `Literal`), `tests/.gitkeep`, genesis commit `6e40a75`, pushed to `github.com/vikasgautam2003/OmniAssist` (private)
2026-08-02	Security audit on committed tree: `.env` absent, no `gsk_` key anywhere in git history, `.venv` excluded, `uv.lock` + `.env.example` committed — **5/5 clean**
2026-08-02	`~/Downloads/OmniAssist_Project_Synopsis.docx` generated in the college template format (5 sections, 15 references, 2,799 words)
2026-08-02	**Block 2 COMPLETE** — `app/clients/{base,groq_client,factory}.py` + `tests/fakes.py`; `LLMClient` Protocol, `LLMError`, composition root, keyless fake; mypy + pydantic plugin configured; concepts C20–C24

2026-08-02	**Block 3 COMPLETE** — `stream_chat()` on the Protocol, `GroqClient` (stream = True, `delta.content`, None-skipped), faithful chunking fake with eager/lazy split; concepts C25–C29
2026-09-22	**Block 4 COMPLETE** — `POST /chat/{id}` SSE endpoint, `GET /healthz`, `ChatService` with history + trimming; concepts C30–C32, decision D14
2026-09-22	**Block 5 COMPLETE** — `ui/streamlit_app.py` chat UI consuming SSE; concepts C33–C35, decision D15
2026-09-22	**Block 6 COMPLETE** — GitHub Actions CI (format/lint/types, no API key), README; concepts C36–C37
2026-09-22	**v0.1 SHIPPED** — 6/6 blocks, CI green, tagged `v0.1`
2026-09-26	**v0.2 Block 1 COMPLETE** — pytest configured, 5 tests on `ChatService` running with no key; `get_history` returns a copy; `self._client` made private; `tests/__init__.py` added; pytest wired into CI. Concepts C38–C41, decision D16
2026-10-03	**v0.2 Block 2 COMPLETE** — PostgreSQL 17 + pgvector, SQLAlchemy models, Alembic migration (reversibility verified), `PostgresConversationRepository` with atomic upsert, repository Protocol, `app/domain.py`. Cross-process persistence proven. Concepts C42–C49, decisions D17–D19
2026-10-04	**v0.2 Block 3 (auth) in progress** — argon2id password hashing, `users` table (UUID PK, unique email), JWT mint/verify with pinned algorithm, `User` domain type + `UserRepository` with `EmailAlreadyExistsError`. Concepts C50–C56, decisions D20–D23
2026-10-04	**Step 3.3c** — `POST /auth/signup` (201/409) and `/auth/login` (200/401) with email normalised once at the Pydantic boundary, identical errors for unknown-vs-wrong, and a constant-time failure path verified by measurement (53 ms vs 56 ms). Concepts C57–C58, decisions D24–D25
2026-10-04	**Steps 3.4–3.5** — `get_current_user` dependency (401 for every failure, user looked up not trusted), `conversations.user_id` FK + migration, ownership enforced in the `WHERE` clause, `/chat` now requires auth and returns 404 for another user's conversation. 8 tests including cross-user isolation. Concepts C59–C62, decision D26
2026-10-04	**Step 3.6 — Block 3 COMPLETE.** Streamlit auth gate: login/signup tabs, token in `session_state`, `Authorization: Bearer` on chat, 401-on-expiry returns to login, logout and new-conversation controls. API contract verified for all six status codes the UI branches on. Concepts C63–C64
2026-10-05	**Step 4.1** — `app/services/pdf.py`: text extraction behind a vendor-neutral `PdfExtractionError`; one `except PyPdfError` contains all fourteen library error types; a document with no text layer is rejected with an OCR hint rather than indexed silently. Hand-built PDF fixture so tests need no `reportlab`. 6 tests. Concepts C65–C66
2026-10-11	**Step 4.2** — `app/services/chunking.py`: overlapping chunks with boundary preference (paragraph → line → sentence → space) bounded to the last fifth of the window. Review found **silent data loss** — 32 of 45 characters dropped — caused by a fixed stride ignoring the adjusted end; fixed by deriving `start` from `end` with a progress clamp. 8 tests including a conservation check. Concepts C67–C71, decisions D29–D30
2026-10-11	**Step 4.3** — `app/embeddings/`: `Embedder` protocol exposing `model_id` and `dimensions`, `LocalEmbedder` on `fastembed/bge-small-en-v1.5` (384 dims), `FakeEmbedder` for tests, factory with a lazy inner import verified not to load `onnxruntime`. 6 tests; no model download in CI. Concepts C72–C75, decisions D27–D28