

```

    2 0.000026      LiteonTe_a5:4f:69      LiteonTe_d0:e3:6d      ARP      42      192.168.43.44 is at 74:df:bf:a5:4f:69
Frame 2: 42 bytes on wire (336 bits), 42 bytes captured (336 bits)
Encapsulation type: Ethernet (1)
Arrival Time: Aug 24, 2018 03:34:27.609139000 IST
[Time shift for this packet: 0.000000000 seconds]
Epoch Time: 1535061867.609139000 seconds
[Time delta from previous captured frame: 0.000026000 seconds]
[Time delta from previous displayed frame: 0.000026000 seconds]
[Time since reference or first frame: 0.000026000 seconds]
Frame Number: 2
Frame Length: 42 bytes (336 bits)
Capture Length: 42 bytes (336 bits)
[Frame is marked: True]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:arp]
[Coloring Rule Name: ARP]
[Coloring Rule String: arp]
Ethernet II, Src: LiteonTe_a5:4f:69 (74:df:bf:a5:4f:69), Dst: LiteonTe_d0:e3:6d (f8:28:19:d0:e3:6d)
Destination: LiteonTe_d0:e3:6d (f8:28:19:d0:e3:6d)
    Address: LiteonTe_d0:e3:6d (f8:28:19:d0:e3:6d)
        ....0. .... = LG bit: Globally unique address (factory default)
        ....0. .... = IG bit: Individual address (unicast)
Source: LiteonTe_a5:4f:69 (74:df:bf:a5:4f:69)
    Address: LiteonTe_a5:4f:69 (74:df:bf:a5:4f:69)
        ....0. .... = LG bit: Globally unique address (factory default)
        ....0. .... = IG bit: Individual address (unicast)
Type: ARP (0x0806)
Address Resolution Protocol (reply)
Hardware type: Ethernet (1)
Protocol type: IPv4 (0x0800)
Hardware size: 6
Protocol size: 4
Opcode: reply (2)
Sender MAC address: LiteonTe_a5:4f:69 (74:df:bf:a5:4f:69)
Sender IP address: 192.168.43.44
Target MAC address: LiteonTe_d0:e3:6d (f8:28:19:d0:e3:6d)
Target IP address: 192.168.43.11
```