

```
Frame 186: 490 bytes on wire (3920 bits), 490 bytes captured (3920 bits) on interface 0
Interface id: 0 (enp2s0)
Encapsulation type: Ethernet (1)
Arrival Time: Aug 20, 2018 02:39:42.595559043 IST
[Time shift for this packet: 0.000000000 seconds]
Epoch Time: 1534712982.595559043 seconds
[Time delta from previous captured frame: 0.000295889 seconds]
[Time delta from previous displayed frame: 4.381893251 seconds]
[Time since reference or first frame: 7.834254635 seconds]
Frame Number: 186
Frame Length: 490 bytes (3920 bits)
Capture Length: 490 bytes (3920 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:ip:tcp:http]
[Coloring Rule Name: HTTP]
[Coloring Rule String: http || tcp.port == 80 || http2]
Ethernet II, Src: HewlettP_2d:7f:92 (a0:8c:fd:2d:7f:92), Dst: Cisco_af:0c:44 (a0:3d:6f:af:0c:44)
Destination: Cisco_af:0c:44 (a0:3d:6f:af:0c:44)
Address: Cisco_af:0c:44 (a0:3d:6f:af:0c:44)
.... ..0. .... = LG bit: Globally unique address (factory default)
.... ..0. .... = IG bit: Individual address (unicast)
Source: HewlettP_2d:7f:92 (a0:8c:fd:2d:7f:92)
Address: HewlettP_2d:7f:92 (a0:8c:fd:2d:7f:92)
.... ..0. .... = LG bit: Globally unique address (factory default)
.... ..0. .... = IG bit: Individual address (unicast)
Type: IPv4 (0x0800)
Internet Protocol Version 4, Src: 10.10.60.30, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 40762, Dst Port: 80, Seq: 1, Ack: 1, Len: 424
Hypertext Transfer Protocol
```