INLUME INNOVATIONS

THE INTERIOR COLLECTION

A new light.

A new perspective.

Lighting that transforms the way a space feels.



INTERIOR LIGHTING

32 PRODUCTS | 5W TO 40W

DOWNLIGHTS / CYLINDER LIGHTS / ARCHITECTURAL LIGHTS

www.inlumeinnovations.com

8368690828

Round downlights

DOWNLIGHT 6W

6W



PRODUCT PROFILE

Power rating	**6W**
Collection	**Round downlights**

DOWN LIGHT ROUND 8W

8W

MODEL RD-01



PRODUCT PROFILE

Power rating	**8W**
Collection	**Round downlights**

Round downlights

DOWN LIGHT ROUND 12W

12W

MODEL RD-02



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1560 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D130 x H40 mm
Net weight	215 g
Driver	36V / 300 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

DOWN LIGHT ROUND 20W

20W

MODEL RD-03



PRODUCT PROFILE

Power rating	**20W**
Collection	**Round downlights**

Square downlights

DOWN LIGHT SQUARE 6W

6W

MODEL SQ-01



TECHNICAL DETAILS

Input voltage	90-300V
Light output	780 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	110 x 110 x 40 mm
Net weight	170 g
Driver	36V / 160 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

DOWN LIGHT SQUARE 12W

12W

MODEL SQ-02



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1560 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	130 x 130 x 40 mm
Net weight	265 g
Driver	36V / 300 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Interior lighting collection

DOWN LIGHT SQUARE 18W

18W

MODEL SQ-03



TECHNICAL DETAILS

Input voltage	90-300V
Light output	2340 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	180 x 180 x 40 mm
Net weight	545 g
Driver	36V / 500 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

DOWN LIGHT FIXED 10W

10W

MODEL DF-01



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1300 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D52 x H27 mm
Net weight	140 g
Driver	36V / 270 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Fixed downlights

DOWN LIGHT FIXED 20W

20W

MODEL DF-02



TECHNICAL DETAILS

Input voltage	90-300V
Light output	2600 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D71 x H42 mm
Net weight	210 g
Driver	36V / 500 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

DOWN LIGHT FIXED 30W

30W

MODEL DF-03



TECHNICAL DETAILS

Input voltage	90-300V
Light output	3900 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D94 x H53 mm
Net weight	330 g
Driver	36V / 800 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Interior lighting collection

DOWN LIGHT FIXED 40W

40W

MODEL DF-04



TECHNICAL DETAILS

Input voltage	90-300V
Light output	5200 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D113 x H58 mm
Net weight	440 g
Driver	36V / 1100 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

DOWN LIGHT TILTING 10W

10W

MODEL DT-01



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1300 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D52 x H27 mm
Net weight	170 g
Driver	36V / 270 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Tilting downlights

DOWN LIGHT TILTING 20W

20W

MODEL DT-02



TECHNICAL DETAILS

Input voltage	90-300V
Light output	2600 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D71 x H41 mm
Net weight	240 g
Driver	36V / 500 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

DOWN LIGHT TILTING 30W

30W

MODEL DT-03



TECHNICAL DETAILS

Input voltage	90-300V
Light output	3900 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D94 x H53 mm
Net weight	390 g
Driver	36V / 800 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Interior lighting collection

DOWN LIGHT TILTING 40W

40W

MODEL DT-04



TECHNICAL DETAILS

Input voltage	90-300V
Light output	5200 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D113 x H58 mm
Net weight	500 g
Driver	36V / 1100 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

PLASTIC DOWNLIGHT ROUND 6W

6W

MODEL PDR-01



TECHNICAL DETAILS

Input voltage	90-300V
Light output	780 lm
Efficacy	130 lm/W
Dimensions	D120 x H40 mm
Net weight	90 g
Driver	36V / 160 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Plastic round downlights

PLASTIC DOWNLIGHT ROUND 12W

12W

MODEL PDR-02



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1560 lm
Efficacy	130 lm/W
Dimensions	D140 x H40 mm
Net weight	130 g
Driver	36V / 300 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

PLASTIC DOWNLIGHT ROUND 18W

18W

MODEL PDR-03



TECHNICAL DETAILS

Input voltage	90-300V
Light output	2340 lm
Efficacy	130 lm/W
Dimensions	D170 x H40 mm
Net weight	185 g
Driver	36V / 500 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Plastic square downlights

PLASTIC DOWNLIGHT SQUARE 6W

6W

MODEL PDS-01



TECHNICAL DETAILS

Input voltage	90-300V
Light output	780 lm
Efficacy	130 lm/W
Dimensions	120 x 120 x 40 mm
Net weight	115 g
Driver	36V / 160 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

PLASTIC DOWNLIGHT SQUARE 12W

12W

MODEL PDS-02



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1560 lm
Efficacy	130 lm/W
Dimensions	140 x 140 x 40 mm
Net weight	165 g
Driver	36V / 300 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Interior lighting collection

PLASTIC DOWNLIGHT SQUARE 18W

18W

MODEL PDS-03



TECHNICAL DETAILS

Input voltage	90-300V
Light output	2340 lm
Efficacy	130 lm/W
Dimensions	170 x 170 x 40 mm
Net weight	220 g
Driver	36V / 480 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

CYLINDER 10W

10W

MODEL BMC01



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1300 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D50 x L150 mm
Net weight	250 g
Driver	36V / 270 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Cylinder lights

CYLINDER 20W

20W

MODEL BMC02



TECHNICAL DETAILS

Input voltage	90-300V
Light output	2600 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D70 x L150 mm
Net weight	320 g
Driver	36V / 500 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

CYLINDER 30W

30W

MODEL BMC03



TECHNICAL DETAILS

Input voltage	90-300V
Light output	3900 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D90 x L150 mm
Net weight	535 g
Driver	36V / 800 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Interior lighting collection

CYLINDER 40W

40W

MODEL BMC04



TECHNICAL DETAILS

Input voltage	90-300V
Light output	5200 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	D110 x L150 mm
Net weight	700 g
Driver	36V / 1000 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

UP DOWN -K LIGHT

5+5W

MODEL K



PRODUCT PROFILE

Power rating	**5+5W**
Collection	**Architectural lighting**

Architectural lighting

ONE WAY UP/DOWN -HALF K LIGHT

5W

MODEL HK



PRODUCT PROFILE

Power rating	**5W**
Collection	**Architectural lighting**

FOOT LIGHT

5W

MODEL FOOT



TECHNICAL DETAILS

Input voltage	90-300V
Light output	650 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	75 x 75 x 40 mm
Net weight	170 g
Driver	36V / 130 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Architectural lighting

2 WAY LIGHT

6W

MODEL BM2WAY



TECHNICAL DETAILS

Input voltage	90-300V
Light output	780 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	80 x 60 x 40 mm
Net weight	140 g
Driver	36V / 160 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

4 WAY LIGHT

12W

MODEL BM4WAY



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1560 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	100 x 80 x 40 mm
Net weight	290 g
Driver	36V / 300 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

Architectural lighting

6 WAY LIGHT

18W

MODEL BM6WAY



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1690 lm
Body	Die-cast aluminium
Dimensions	160 x 80 x 40 mm
Net weight	305 g
Driver	36V / 500 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option

WALL LIGHT

12W

MODEL BMW01



TECHNICAL DETAILS

Input voltage	90-300V
Light output	1560 lm
Efficacy	130 lm/W
Body	Die-cast aluminium
Dimensions	60 x 60 x 50 mm
Net weight	285 g
Driver	36V / 300 mA
Rated life	50,000 hours
Installation	Tool-less

Colour options: 2800 / 4000 / 5700 / 6200K
RGB option