INLUME INNOVATIONS

SOLAR LIGHTING / PRODUCT CATALOGUE

# LIGHT THAT LIVES OUTDOORS.



## SOLAR STREET LIGHTS

Integrated lighting for pathways and outdoor spaces.

**www.inlumeinnovations.com**

Application illustration

# FIND YOUR MODEL

Four configurations. One integrated solar lighting range.

| Specification | 1 panel | 2 panels | 3 panels | 4 panels |
|---|---|---|---|---|
| **Luminous flux*** | 300 lm | 500 lm | 650 lm | 800 lm |
| **Battery capacity** | 5,000 mAh | 8,000 mAh | 12,000 mAh | 15,000 mAh |
| **Net weight** | 1,030 g | 1,430 g | 2,100 g | 2,260 g |
| **Product page** | 03 | 04 | 05 | 06 |

*Luminous flux stated at full battery.

## FEATURES ACROSS THE RANGE

**AUTOMATIC DAYLIGHT CONTROL**
Automatic switch-off during daytime.

**RADAR SENSING**
10% brightness when idle.

**REMOTE OPERATION**
2 / 3 / 4 hour timers and multi-level brightness.

**INTEGRATED CONSTRUCTION**
ABS shell and tempered-glass solar panel.

Full specifications and product views follow on pages 03-06.

GSTIN: 09CXKPD4992D1Z8 inlumeinnovations@gmail.com +91 8368690828

# SOLAR STREET LIGHT

Solar street light / 1 light panel

**KEY HIGHLIGHTS**

**300 lm**

Luminous flux at full battery

**5,000 mAh**

LiFePO4 battery · 3.2 V

Integrated solar street light



LIGHT & REMOTE SOLAR PANEL

**DAYLIGHT CONTROL**

Automatic daytime switch-off

**TIMER SETTINGS**

2 / 3 / 4 hours

**RADAR SENSING**

10% brightness when idle

**BRIGHTNESS CONTROL**

Levels 1-8 / multi-level

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **LED source** | 5730 - 48 pcs × 1 / 7500 K |
| **Lamp dimensions** | L390 × W194 × H53 mm |
| **Solar panel** | Monocrystalline silicon / 6 V / L300 × W186 mm |
| **Battery** | Lithium iron phosphate / 3.2 V, 5000 mAh / protected |
| **Charging time** | 5-10 hours |
| **Discharge time** | 7-12 hours in radar sensing mode |
| **Remote control distance** | 10 metres in a straight line |
| **Mounting hole** | Ø42-50 mm / 54 mm depth |
| **Ingress protection** | IP65 - solar panel side only |
| **Materials** | ABS plastic shell / tempered-glass solar panel |
| **Net weight** | 1030 g |

GSTIN: 09CXKPD4992D1Z8 inlumeinnovations@gmail.com +91 8368690828

# SOLAR STREET LIGHT

Solar street light / 2 light panels

KEY HIGHLIGHTS

**500 lm**

Luminous flux at full battery

**8,000 mAh**

LiFePO4 battery · 3.2 V

Integrated solar street light



LIGHT & REMOTE SOLAR PANEL

**DAYLIGHT CONTROL**

Automatic daytime switch-off

**TIMER SETTINGS**

2 / 3 / 4 hours

**RADAR SENSING**

10% brightness when idle

**BRIGHTNESS CONTROL**

Levels 1-8 / multi-level

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **LED source** | 5730 - 48 pcs × 2 / 7500 K |
| **Lamp dimensions** | L484 × W219 × H53 mm |
| **Solar panel** | Monocrystalline silicon / 6 V / L398 × W212 mm |
| **Battery** | Lithium iron phosphate / 3.2 V, 8000 mAh / protected |
| **Charging time** | 5-10 hours |
| **Discharge time** | 7-12 hours in radar sensing mode |
| **Remote control distance** | 10 metres in a straight line |
| **Mounting hole** | Ø42-50 mm / 54 mm depth |
| **Ingress protection** | IP65 - solar panel side only |
| **Materials** | ABS plastic shell / tempered-glass solar panel |
| **Net weight** | 1430 g |

GSTIN: 09CXKPD4992D1Z8 inlumeinnovations@gmail.com +91 8368690828

# SOLAR STREET LIGHT

Solar street light / 3 light panels

KEY HIGHLIGHTS

**650 lm**

Luminous flux at full battery

**12,000 mAh**

LiFePO4 battery · 3.2 V

Integrated solar street light



LIGHT & REMOTE SOLAR PANEL

**DAYLIGHT CONTROL**

Automatic daytime switch-off

**TIMER SETTINGS**

2 / 3 / 4 hours

**RADAR SENSING**

10% brightness when idle

**BRIGHTNESS CONTROL**

Levels 1-8 / multi-level

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **LED source** | 5730 - 48 pcs × 3 / 7500 K |
| **Lamp dimensions** | L622 × W239 × H53 mm |
| **Solar panel** | Monocrystalline silicon / 6 V / L508 × W230 mm |
| **Battery** | Lithium iron phosphate / 3.2 V, 12000 mAh / protected |
| **Charging time** | 5-10 hours |
| **Discharge time** | 7-12 hours in radar sensing mode |
| **Remote control distance** | 10 metres in a straight line |
| **Mounting hole** | Ø42-50 mm / 80 mm depth |
| **Ingress protection** | IP65 - solar panel side only |
| **Materials** | ABS plastic shell / tempered-glass solar panel |
| **Net weight** | 2100 g |

GSTIN: 09CXKPD4992D1Z8 inlumeinnovations@gmail.com +91 8368690828

# SOLAR STREET LIGHT

Solar street light / 4 light panels

KEY HIGHLIGHTS

**800 lm**

Luminous flux at full battery

**15,000 mAh**

LiFePO4 battery · 3.2 V

Integrated solar street light



LIGHT & REMOTE SOLAR PANEL

**DAYLIGHT CONTROL**

Automatic daytime switch-off

**TIMER SETTINGS**

2 / 3 / 4 hours

**RADAR SENSING**

10% brightness when idle

**BRIGHTNESS CONTROL**

Levels 1-8 / multi-level

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **LED source** | 5730 - 48 pcs × 4 / 7500 K |
| **Lamp dimensions** | L724 × W239 × H53 mm |
| **Solar panel** | Monocrystalline silicon / 6 V / L608 × W230 mm |
| **Battery** | Lithium iron phosphate / 3.2 V, 15000 mAh / protected |
| **Charging time** | 5-10 hours |
| **Discharge time** | 7-12 hours in radar sensing mode |
| **Remote control distance** | 10 metres in a straight line |
| **Mounting hole** | Ø42-50 mm / 80 mm depth |
| **Ingress protection** | IP65 - solar panel side only |
| **Materials** | ABS plastic shell / tempered-glass solar panel |
| **Net weight** | 2260 g |

# LET US LIGHT YOUR NEXT SPACE.

Explore solar lighting with INLUME INNOVATIONS.

**PRODUCT & BUSINESS ENQUIRIES**

Connect with us for pricing, availability and model selection.


**PHONE / WHATSAPP**

**+91 8368690828**

**EMAIL**

**inlumeinnovations@gmail.com**

**WEBSITE**

**www.inlumeinnovations.com**

**GSTIN**

**09CXKPD4992D1Z8**


## Our journey begins with light.

Solar lighting / Solar Lighting