
PRODUCT
CATALOGUE
BRIGHTER SPACES.
BETTER TOMORROWS.
RESIDENTIAL
COMMERCIAL
INFRASTRUCTURE
INDUSTRIAL


AC STREET LIGHT
RELIABLE I EFFICIENT I DURABLE
FOR BRIGHTER, SAFER SPACES


INLUME INNOVATIONS
Led Street Light 50W
INLUME INNOVATIONS
Led Street Light 100W
24W
LED STREET LIGHT
(220V-AC)
Inbuilt 6kva Driver
Led lumen -
140 to 170 Lumen/Watt
Color temp -
5500K to 6500K
Body - Aluminum
IP66
36W
LED STREET LIGHT
(220V-AC)
Inbuilt 6kva Driver
Led lumen -
140 to 170 Lumen/Watt
Color temp -
5500K to 6500K
Body - Aluminum
IP66
50W
LED STREET LIGHT
(220V-AC)
Inbuilt 6kva Driver
Led lumen -
140 to 170 Lumen/Watt
Color temp -
5500K to 6500K
Body - Aluminum
IP66
100W
LED STREET LIGHT
(220V-AC)
Inbuilt 6kva Driver
Led lumen -
140 to 170 Lumen/Watt
Color temp -
5500K to 6500K
Body - Aluminum
IP66



01

50W LED FLOOD LIGHT

- 440V - AC
- Inbuilt 6kva Circuit
- Lance Model DOB
- Color Temperature 5500K to 6500K
- Body - Aluminum
- IP66



02

100W LED FLOOD LIGHT

- 440V - AC
- Inbuilt 6kva Circuit
- Lance Model DOB
- Color Temperature 5500K to 6500K
- Body - Aluminum
- IP66



03

150W LED FLOOD LIGHT

- 440V - AC
- Inbuilt 6kva Circuit
- Lance Model DOB
- Color Temperature 5500K to 6500K
- Body - Aluminum
- IP66



04

200W LED FLOOD LIGHT

- 440V - AC
- Inbuilt 6kva Circuit
- Lance Model DOB
- Color Temperature 5500K to 6500K
- Body - Aluminum
- IP66





LED HIGH-WAY LIGHT

High performance lighting for
safer, brighter and more efficient roads.



100W
LED HIGH-WAY LIGHT

- Inbuilt 6kva Driver
- Lance Model DOB
- Fiber Frame
- Color Temperature – 5500K to 6500K
- Body – Aluminum
- IP66



150W
LED HIGH-WAY LIGHT

- Inbuilt 6kva Driver
- Lance Model DOB
- Fiber Frame
- Color Temperature – 5500K to 6500K
- Body – Aluminum
- IP66



200W
LED HIGH-WAY LIGHT

- Inbuilt 6kva Driver
- Lance Model DOB
- Fiber Frame
- Color Temperature – 5500K to 6500K
- Body – Aluminum
- IP66

High Brightness

Energy Efficient

Durable Aluminum Body

Weather Resistant (IP66)



01 30W LED FLOOD LIGHT (220V-AC)

- Inbuilt 6kva Circuit
- Lance Model DOB
- Multi-Color
- Body - Aluminum
- IP66



02 50W LED FLOOD LIGHT (220V-AC)

- Inbuilt 6kva Circuit
- Lance Model DOB
- Multi-Color
- Body - Aluminum
- IP66



03 100W LED FLOOD LIGHT (220V-AC)

- Inbuilt 6kva Circuit
- Lance Model DOB
- Multi-Color
- Body - Aluminum
- IP66



WELL GLASS LIGHT

ROBUST | EFFICIENT | DEPENDABLE



PRODUCT SPECIFICATIONS

Luminous Flux	140 lm/W
Correlated Color Temperature	3K, 4K, 6K
Luminous Efficacy (rated)	110 lm/W
Color Rendering Index (CRI)	>80
Optic Type Beam Angle	120° degree(s)
Optical Cover Type	Polycarbonate cover
Luminaire Light Beam Spread	120°
Surge Protection	6kV
Protection	Short Circuit, Open Circuit, Over Voltage, Under Voltage Protection
Input Voltage	80V to 120V AC
Line Frequency	50 Hz to 60 Hz
Power Factor (Fraction)	0.95
Power Consumption Tolerance	+/-10%

HIGH PERFORMANCE

ENERGY EFFICIENT

DURABLE DESIGN



HIGH EFFICACY LED TECHNOLOGY



POLYCARBONATE COVER



RUGGED CONSTRUCTION