



EAMCET CODE : NGIT

NEIL GOGTE INSTITUTE OF TECHNOLOGY

A Unit of Keshav Memorial Technical Educational Society (KMTES)

(Approved by AICTE, New Delhi & Affiliated to Osmania University, Hyderabad)

PRACTICAL RECORD BOOK

**D.No. 10TC-111, Kachavanisingaram (V), Uppal,
Hyderabad - 500 088, Telangana Ph : +91 40-2988 8262**

website : www.ngit.ac.in

Name :

Roll No. : Course.....

Branch / Sec. : Year..... Sem.....

Name of the Lab :



NEIL GOGTE INSTITUTE OF TECHNOLOGY

A Unit of Keshav Memorial Technical Educational Society (KMTES)

(Approved by AICTE, New Delhi & Affiliated to Osmania University, Hyderabad)
D.No. 10TC-111, Kachavanisingaram (V), Uppal, Hyderabad - 500 088, Telangana

Certificate

Department : _____

Certified that this is a bonafide record of practical work done by
Mr. / Miss _____ of
B.E. _____ Branch _____ Section _____ Semester.
bearing with Hall ticket No _____ during the
academic year _____ in the _____ Laboratory

Signature of Faculty

Head of the Dept

Record submitted for the Practical Examination held on.....

Internal Examiner

External Examiner

INDEX

Sl. No.	Name of the Experiment	Date of Experiment	Date of Submission	Page Number	Grade	Faculty Signature
1.						
2.						
3.						
4.						
5.						
6.						
7.						
8.						
9.						
10.						
11.						
12.						
13.						
14.						
15.						
16.						
17.						

PROGRAM 1:Python and MATLAB/GNU OCTAVE installation and IDE Setup

Python Installation & IDE Setup

a. Installing Python

1. Download Python:
 - Go to the official [Python website](https://www.python.org/).
 - Download the latest stable version for your operating system (Windows, macOS, or Linux).
2. Install Python:
 - Run the installer.
 - On Windows, ensure you select the option "Add Python to PATH" during installation (very important).
 - Follow the installation prompts for your operating system.
3. Verify Installation:
 - Open a terminal (Command Prompt on Windows or Terminal on macOS/Linux).
 - Type `python--version` (or `python3--version` on macOS/Linux) to confirm the installation.

b. Installing an IDE for Python: Visual Studio Code (VS Code):

- Download VS Code: Go to [VS Code Download](https://code.visualstudio.com/).
- Install: Follow the prompts based on your operating system.
- Python Extension: After installation, open VS Code and go to the Extensions Marketplace (or press `Ctrl+Shift+X`), search for the Python extension by Microsoft, and install it.
- Interpreter Setup: Ensure you select the correct Python interpreter by opening the Command Palette (`Ctrl+Shift+P`), typing `Python: Select Interpreter`, and choosing the one you just installed.

MATLAB Installation & IDE Setup-Most basic MATLAB syntax and built-in functions are supported by open source GNU OCTAVE. So GNU Octave is used in place of MATLAB: GNU OCTAVE INSTALLATION Windows

- Go to the official Octave website:
<https://www.gnu.org/software/octave/download.html>
- Under the Windows section, click the download link for the latest version.
- Once downloaded, run the installer (.exe file).
- Follow the installation prompts (keep default settings unless needed).
- After installation, launch Octave from the Start menu.

Verify Installation After installing, open a terminal or command prompt and type: `octave --version`, If Octave is installed correctly, it will display the installed version.

PROGRAM 2: Writing simple Python and MATLAB Programs

Simple Python Programs RUN USING VSCODE IDE

Hello,World!

```
#A simple program to print "Hello,World!" print("Hello, World!")
```

OUTPUT: Hello,World!

Sum of Two Numbers

```
#A simple program to calculate the sum of two numbers
```

```
num1 = 5
```

```
num2=10
```

```
sum=num1+num2
```

```
print(f"The sum of {num1} and {num2} is {sum}.")
```

OUTPUT: The sum of 5 and 10 is 15.

Even or Odd Number

```
#A simple program to check if a number is even or odd
```

```
num = int(input("Enter a number: "))
```

```
if num%2==0:
```

```
    print(f"{num} is an even number.")
```

```
else:
```

```
    print(f"{num} is an odd number.")
```

OUTPUT: Enter a number: 5

5 is an odd number

Factorial of a Number

```
#A program to find the factorial of a number
```

```
num= int(input("Enter a number to find its factorial:"))
```

```
factorial = 1
```

```
for i in range(1,num+1):
```

```
    factorial *= i
```

```
print(f"The factorial of {num} is {factorial}.")
```

OUTPUT: Enter a number to find its factorial: 5

The factorial of 5 is 120.

Fibonacci Sequence

```
#A program to print the Fibonacci sequence up to n terms
```

```
n=int(input("Enter the number of terms in the Fibonacci sequence:"))
```

```
a, b = 0, 1
```

```
print("Fibonacci sequence:")
```

```
for _ in range(n):
```

```
    print(a,end="")
```

```
    a, b = b, a + b
```

OUTPUT: Enter the number of terms in the Fibonacci sequence: 9

Fibonacci sequence: 0 1 1 2 3 5 8 13 21

Simple MATLAB Programs can be executed using GNU OCTAVE.

Open a new file and enter the below script and run it and the output will be displayed in the command window.

Hello,World!

%A simple program to display"Hello,World!"

disp('Hello, World!')

OUTPUT:Hello, World!

Sum of Two Numbers

%A program to calculate the sum of two numbers

num1 = 5;

num2=10;

sum=num1+ num2;

fprintf('The sum of %d and %d is %d.\n',num1,num2,sum);

OUTPUT: The sum of 5 and 10 is 15.

Even or Odd Number

%A program to check if a number is even or odd

num = input('Enter a number: ');

if mod(num,2)==0

 fprintf('%d is an even number.\n',num);

else

 fprintf('%d is an odd number.\n',num);

end

OUTPUT: 'Enter a number: 5

5 is an odd number

Factorial of a Number

%A program to find the factorial of a number

num=input('Enter a number to find its factorial:');

factorial = 1;

fori=1:num

 factorial=factorial* i;

end

fprintf('The factorial of %d is %d.\n',num,factorial);

OUTPUT: Enter a number to find its factorial: 5

The factorial of 5 is 120.

Fibonacci Sequence

%A program to print the Fibonacci sequence up to n terms

```
n=input('Enter the number of terms in the Fibonacci sequence:');
```

```
a=0;
```

```
b=1;
```

```
fprintf('Fibonacci sequence:\n'); for
```

```
i = 1:n
```

```
    fprintf('%d',a);
```

```
    temp = a + b;
```

```
    a=b;
```

```
    b=temp;
```

```
end
```

```
fprintf('\n');
```

OUTPUT: Enter the number of terms in the Fibonacci sequence: 8

Fibonacci sequence: 0 1 1 2 3 5 8 13

PROGRAM 3: Implementing control structures and functions

Python Program Using if-else(Conditional Statement)

GradeEvaluation : This program takes a student's score as input and evaluates the grade based on the score.

#A program to evaluate a student's grade based on score

```
score = int(input("Enter the score (0-100): "))
```

```
if score >= 90:
```

```
    print("Grade:A")
```

```
elif score >= 80:
```

```
    print("Grade:B")
```

```
elif score >= 70:
```

```
    print("Grade:C")
```

```
elif score >= 60:
```

```
    print("Grade:D")
```

```
else:
```

```
    print("Grade:F")
```

OUTPUT: Enter the score (0-100): 90

Grade: A

Python Program Using for Loop : Multiplication Table

#A program to print the multiplication table of a number

```
num=int(input("Enter a number to generate its multiplication table:"))
```

```
print(f"Multiplication table of {num}:")
```

```
for i in range(1, 11):
```

```
    print(f"{num} x {i} = {num*i}")
```

OUTPUT: Enter a number to generate its multiplication table: 9

Multiplication table of 9:

9 x 1 = 9

9 x 2 = 18

9 x 3 = 27

9 x 4 = 36

9 x 5 = 45

9 x 6 = 54

9 x 7 = 63

9 x 8 = 72

9 x 9 = 81

9 x 10 = 90

Python Program Using while Loop : This program counts down from a given number to zero using a while loop.

```
#A program to count down from a given number
num=int(input("Enter a number to count down: "))
```

```
whilenum>=0:
    print(num)
    num -= 1
```

Enter a number to countdown: 9

9
8
7
6
5
4
3
2
1
0

Python Program Using Nested Loops : Multiplication Table(Nested Loops)

This program prints the multiplication table in a grid format using nested loops.

```
num = int(input("Enter a number to generate its multiplication table: "))
```

```
# Using nested for loops to generate the multiplication table
```

```
print(f"\nMultiplication Table of {num}:\n")
```

```
for i in range(1, 11): # Outer loop for numbers 1 to 10
```

```
    for j in range(1, 11): # Inner loop for numbers 1 to 10
```

```
        result = i * j
```

```
        print(f"{i} x {j} = {result}")
```

```
        print("-" * 20) # Separating each row for better readability
```

OUPUT: Enter a number to generate its multiplication table: 5

Multiplication Table of 5:

1 x 1 = 1

1 x 2 = 2

1 x 3 = 3

1 x 4 = 4

1 x 5 = 5

1 x 6 = 6

1 x 7 = 7

1 x 8 = 8
1 x 9 = 9
1 x 10 = 10

2 x 1 = 2
2 x 2 = 4
2 x 3 = 6
2 x 4 = 8
2 x 5 = 10
2 x 6 = 12
2 x 7 = 14
2 x 8 = 16
2 x 9 = 18
2 x 10 = 20

...

MATLAB program that demonstrates the use of if-else conditional statements

% Check if the number is positive, negative, or zero

num = input('Enter a number: ');

if num > 0

 disp('The number is positive.');

elseif num < 0

 disp('The number is negative.');

else

 disp('The number is zero.');

end

OUTPUT: Enter a number: 5

 The number is positive.

MATLAB program that demonstrates the use of a while loop.

In this example, the program will print numbers from 1 to 10

counter = 1;

% While loop to print numbers from 1 to 10

while counter <= 10

 disp(counter);

 counter = counter + 1;

% Increment the counter by 1

end

OUTPUT:

1

2

3

4

5
6
7
8
9
10

MATLAB program that generates a multiplication table using nested loops:

```
num = input('Enter a number to generate its multiplication table: ');  
% Using nested loops to generate the multiplication table  
fprintf('\nMultiplication Table of %d:\n', num);  
fori = 1:10 % Outer loop for numbers 1 to 10  
    forj = 1:10 % Inner loop for numbers 1 to 10  
        result = i * j;  
        fprintf('%d x %d = %d\n', i, j, result);  
    % Print the result  
end  
% Separator for better readability  
end  
OUPUT:
```

Enter a number to generate its multiplication table: 5

1 x 1 = 1
1 x 2 = 2
1 x 3 = 3
1 x 4 = 4
1 x 5 = 5
1 x 6 = 6
1 x 7 = 7
1 x 8 = 8
1 x 9 = 9
1 x 10 = 10

2 x 1 = 2
2 x 2 = 4
2 x 3 = 6
2 x 4 = 8
2 x 5 = 10
2 x 6 = 12
2 x 7 = 14
2 x 8 = 16
2 x 9 = 18
2 x 10 = 20

...

Implementing Functions in Python

Basic Function Without Parameters

Hello,World!Function: This function simply prints"Hello,World!"when called.

#A simple function that prints Hello,World!

```
def greet():  
    print("Hello,World!")  
  
    #Calling the function  
    greet()
```

OUTPUT: Hello, World!

Function with Parameters : Addition Function: This function takes two numbers as parameters and returns their sum.

#A function that adds two numbers

```
def add(a, b):  
    result=a+b  
    return result
```

#Calling the function with arguments

```
num1 = 5  
num2=10  
print(f"The sum of {num1} and {num2} is: {add(num1,num2)}")
```

OUTPUT: The sum of 5 and 10 is: 15

Function with Multiple Return Values: Basic Math Operations

This function performs multiple operations(addition,subtraction,multiplication)on two numbers and returns the results.

#A function that returns multiple values(sum,difference,andproduct)

```
def basic_operations(a, b):  
    sum_result=a+b  
    difference=a-b  
    product = a * b  
    return sum_result,difference,product
```

#Calling the function and unpacking the returned values

```
a=8  
b=4  
sum_res,diff,prod=basic_operations(a,b)
```

```
print(f"Sum: {sum_res}")
```

```
print(f"Difference:{diff}")
```

```
print(f"Product: {prod}")
```

OUTPUT: Sum: 12

Difference: 4

Product: 32

Function with Recursion: Factorial Using Recursion

#A function to calculate the factorial of a number using recursion

```
def factorial(n):  
    if n==0 or n==1: #Basecase  
        return 1  
    else:  
        return n*factorial(n-1)
```

#Calling the function

```
num = 5  
print(f"The factorial of {num} is: {factorial(num)}")
```

OUTPUT: The factorial of 5 is: 120

Implementing Functions in MATLAB

Function to Calculate the Square of a Number

% square Number function: This function returns the square of a number

```
function result = squareNumber(num)  
    result = num^2; % Square the input number  
end
```

% Main script that calls the square Number function

```
% Ask the user for a number  
num = input('Enter a number to calculate its square: ');
```

```
% Call the function and display the result  
result = squareNumber(num);  
fprintf('The square of %.2f is %.2f.\n', num, result);
```

OUTPUT: Enter a number to calculate its square: 5
The square of 5.00 is 25.00.

Function to Calculate Factorial of a Number

% factorial Number function: This function calculates the factorial of a number

```
function result = factorialNumber(num)  
    result = 1; % Initialize result as 1  
    for i = 1:num  
        result = result * i; % Multiply result by each number up to num  
    end  
end
```

```
% Main script that calls the factorialNumber function
```

```
% Ask the user for a number
```

```
num = input('Enter a number to calculate its factorial: ');
```

```
% Call the function and display the result
```

```
result = factorialNumber(num);
```

```
fprintf('The factorial of %d is %d.\n', num, result);
```

OUTPUT: Enter a number to calculate its factorial: 5

The factorial of 5 is 120.

Function to Find the Largest of Three Numbers

```
% find Largest function: Returns the largest of three numbers
```

```
function largest = findLargest(a, b, c)
```

```
    if a >= b && a >= c
```

```
        largest = a;
```

```
    elseif b >= a && b >= c
```

```
        largest = b;
```

```
    else
```

```
        largest = c;
```

```
    end
```

```
end
```

```
% Main script that calls the findLargest function
```

```
% Ask the user for three numbers
```

```
a = input('Enter the first number: ');
```

```
b = input('Enter the second number: ');
```

```
c = input('Enter the third number: ');
```

```
% Call the function and display the result
```

```
largest = findLargest(a, b, c);
```

```
fprintf('The largest number among %.2f, %.2f, and %.2f is %.2f.\n', a, b, c, largest);
```

Enter the first number: 5

Enter the second number: 3

Enter the third number: 8

The largest number among 5.00, 3.00, and 8.00 is 8.00.

PROGRAM 4 : Implementing Data Structures in Python and MATLAB

Data Structures in Python

Lists(Array-like Structure) : This program demonstrate to create, update, and manipulate lists.

```
#Create a list
fruits=['apple','banana','cherry']

#Add an item to the list
fruits.append('orange')

#Insert an item at a specific position
fruits.insert(1, 'kiwi')

#Remove an item from the list
fruits.remove('banana')

#Accessing elements
print(f"The first fruit is:{fruits[0]}")

#Slicing the list
print(f"Fruits from index 1 to 2:{fruits[1:3]}")

#Loop through the list
for fruit in fruits:
    print(fruit)
```

OUTPUT:

```
The first fruit is: apple
Fruits from index 1 to 2: ['kiwi', 'cherry']
apple
kiwi
cherry
orange
```


Stack(LIFO:Last In,First Out): Stack Implementation Using a List

class Stack:

```
def __init__(self): # Fixed: __init__ should be used
    self.stack = []
```

```
def push(self, item):
    self.stack.append(item)
```

```
def pop(self):
    if self.is_empty():
        return "Stack is empty"
    return self.stack.pop()
```

```
def peek(self):
    if self.is_empty():
        return "Stack is empty"
    return self.stack[-1]
```

```
def is_empty(self):
    return len(self.stack) == 0
```

```
def size(self):
    return len(self.stack)
```

Using the Stack

```
my_stack = Stack()
```

```
my_stack.push(10)
```

```
my_stack.push(20)
```

```
my_stack.push(30)
```

```
print(f"Top of the stack: {my_stack.peek()}") # The top of the stack should be 30
```

```
print(f"Stack size: {my_stack.size()}") # The size should be 3
```

```
print(f"Popped item: {my_stack.pop()}") # It will pop 30
```

```
print(f"Stack size after pop: {my_stack.size()}") # The size will now be 2
```

OUTPUT: Top of the stack: 30

Stack size: 3

Popped item: 30

Stack size after pop: 2

Queue(FIFO:First In,First Out)

```
class Queue:
def __init__(self):
    self.queue = [] # Initialize an empty list to represent the queue

def enqueue(self, item):
    """Add an item to the end of the queue."""
    self.queue.append(item)

def dequeue(self):
    """Remove and return the item from the front of the queue."""
    if self.is_empty():
        return "Queue is empty"
    return self.queue.pop(0) # Remove and return the first item in the list

def peek(self):
    """Return the front item without removing it."""
    if self.is_empty():
        return "Queue is empty"
    return self.queue[0]

def is_empty(self):
    """Check if the queue is empty."""
    return len(self.queue) == 0

def size(self):
    """Return the number of items in the queue."""
    return len(self.queue)

# Using the Queue
my_queue = Queue()
# Enqueue some items
my_queue.enqueue(10)
my_queue.enqueue(20)
my_queue.enqueue(30)
```

```
print(f"Front of the queue: {my_queue.peek()}") # The front item should be 10
print(f"Queue size: {my_queue.size()}") # The size should be 3
print(f"Dequeued item: {my_queue.dequeue()}") # It will dequeue 10
print(f"Queue size after dequeue: {my_queue.size()}") # The size will now be 2
print(f"Front of the queue after dequeue: {my_queue.peek()}") # Now it should
be 20
```

OUTPUT:

```
Front of the queue: 10
Queue size: 3
Dequeued item: 10
Queue size after dequeue: 2
Front of the queue after dequeue: 20
```

Dictionary (HashMap) Program in Python : In Python, dictionaries are used to store key-value pairs, and they behave like hash maps in other programming languages. A dictionary in Python is an unordered collection of items, where each item consists of a key and a corresponding value.

Here's a simple Python program that demonstrates how to use a dictionary (hash map) for storing, retrieving, updating, and deleting key-value pairs:

```
# Create a dictionary
my_dict = {
    'name': 'John',
    'age': 25,
    'city': 'New York'
}

# Accessing values using keys
print(f"Name: {my_dict['name']}")
print(f"Age: {my_dict['age']}")
print(f"City: {my_dict['city']}")

# Adding a new key-value pair to the dictionary
```

```

my_dict['job'] = 'Engineer'

# Updating an existing key-value pair
my_dict['age'] = 26

# Display the updated dictionary
print(f"Updated Dictionary: {my_dict}")

# Checking if a key exists in the dictionary
if 'name' in my_dict:
    print(f"Name exists in dictionary: {my_dict['name']}")

# Removing a key-value pair from the dictionary using 'del'
del my_dict['city']

# Using the pop() method to remove a key-value pair
job = my_dict.pop('job')

# Display the removed item
print(f"Removed job: {job}")

# Display the final state of the dictionary
print(f"Final Dictionary: {my_dict}")

# Getting all keys and values
print(f"Keys: {my_dict.keys()}")
print(f"Values: {my_dict.values()}")

OUTPUT:
Name: John
Age: 25
City: New York
Updated Dictionary: {'name': 'John', 'age': 26, 'city': 'New York', 'job': 'Engineer'}
Name exists in dictionary: John

```

Removed job: Engineer

Final Dictionary: {'name': 'John', 'age': 26, 'city': 'New York'}

Keys: dict_keys(['name', 'age', 'city'])

Values: dict_values(['John', 26, 'New York'])

Data Structures in MATLAB

ARRAYS

% Create an initial array

```
myArray = [10, 20, 30, 40, 50];
```

% Accessing elements

```
firstElement = myArray(1); % First element
```

```
disp(['First Element: ', num2str(firstElement)]);
```

```
thirdElement = myArray(3); % Third element
```

```
disp(['Third Element: ', num2str(thirdElement)]);
```

% Modifying elements

```
myArray(2) = 25; % Update the second element
```

```
disp('Updated Array:');
```

```
disp(myArray); % Output: [10, 25, 30, 40, 50]
```

% Adding elements

```
myArray = [myArray, 60]; % Append 60 to the array
```

```
disp('Array after Adding 60:');
```

```
disp(myArray); % Output: [10, 25, 30, 40, 50, 60]
```

% Removing elements

```
myArray(2) = []; % Remove the second element (25)
```

```
disp('Array after Removing Second Element:');
```

```
disp(myArray); % Output: [10, 30, 40, 50, 60]
```

% Slicing arrays

```
subArray = myArray(2:4); % Extract elements 2 to 4
```

```

disp('Sliced SubArray (2 to 4):');
disp(subArray); % Output: [30, 40, 50]

% Checking if an element exists
exists = ismember(40, myArray); % Check if 40 is in the array
disp(['Does 40 exist in the array? ', num2str(exists)]); % Output: true

% Length of the array
arrayLength = length(myArray);
disp(['Length of Array: ', num2str(arrayLength)]);

% Looping through the array
disp('Looping through array elements:');
for i = 1:length(myArray)
    disp(myArray(i));
end

```

OUTPUT:

First Element: 10

Third Element: 30

Updated Array:

10 25 30 40 50

Array after Adding 60:

10 25 30 40 50 60

Array after Removing Second Element:

10 30 40 50 60

Sliced SubArray (2 to 4):

30 40 50

Does 40 exist in the array? 1

Length of Array: 5

Looping through array elements:

10

30

40

50

STACK Implementation in MATLAB

```

classdef Stack
properties
    stack = []; % Initialize an empty array for the stack
end

methods
    % Push an item onto the stack
    function push(obj, item)
        obj.stack = [obj.stack, item]; % Append item to the end of the stack
    end

    % Pop an item from the stack
    function item = pop(obj)
        if ~obj.isEmpty() % Check if the stack is empty
            item = obj.stack(end); % Get the last element
            obj.stack(end) = []; % Remove the last element
        else
            item = 'Stack is empty'; % Return a message if stack is empty
        end
    end

    % Peek at the top item of the stack
    function item = peek(obj)
        if ~obj.isEmpty() % Check if the stack is empty
            item = obj.stack(end); % Return the top item (last element)
        else
            item = 'Stack is empty'; % Return a message if stack is empty
        end
    end

    % Check if the stack is empty

```

```

function isEmpty = isEmpty(obj)
    isEmpty = isempty(obj.stack); % True if stack is empty, false otherwise
end

% Get the size of the stack (number of elements)
function size = size(obj)
    size = length(obj.stack); % Return the number of elements in the stack
end
end
end

```

Example Usage of the Stack Class

```

% Create a Stack object
myStack = Stack();

% Push elements onto the stack
myStack.push(10);
myStack.push(20);
myStack.push(30);

% Display the top element
disp(['Top element: ', num2str(myStack.peak())]); % Output: Top element: 30

% Display the size of the stack
disp(['Stack size: ', num2str(myStack.size())]); % Output: Stack size: 3

% Pop the top element
disp(['Popped element: ', num2str(myStack.pop())]); % Output: Popped
element: 30

% Display the size of the stack after popping
disp(['Stack size after pop: ', num2str(myStack.size())]); % Output: Stack size
after pop: 2

```



```

% Check if the stack is empty
disp(['Is the stack empty? ', num2str(myStack.isEmpty())]); % Output: Is the
stack empty? 0 (false)

% Pop all elements
disp(['Popped element: ', num2str(myStack.pop())]); % Output: Popped
element: 20
disp(['Popped element: ', num2str(myStack.pop())]); % Output: Popped
element: 10

% Check if the stack is empty
disp(['Is the stack empty now? ', num2str(myStack.isEmpty())]); % Output: Is the
stack empty now? 1 (true)

% Try popping from an empty stack
disp(['Popped element: ', myStack.pop()]); % Output: Popped element: Stack is
empty
    OUTPUT:
        Top element: 30
        Stack size: 3
        Popped element: 30
        Stack size after pop: 2
        Is the stack empty? 0
        Popped element: 20
        Popped element: 10
        Is the stack empty now? 1
        Popped element: Stack is empty

```

Queue Implementation in MATLAB

```
classdef Queue
    properties
        queue = []; % Initialize an empty array for the queue
    end

    methods
        % Enqueue an item into the queue (add to the end)
        function enqueue(obj, item)
            obj.queue = [obj.queue, item]; % Append item to the end of the
queue
        end

        % Dequeue an item from the queue (remove from the front)
        function item = dequeue(obj)
            if ~obj.isEmpty() % Check if the queue is empty
                item = obj.queue(1); % Get the first element
                obj.queue(1) = []; % Remove the first element
            else
                item = 'Queue is empty'; % Return a message if the queue is empty
            end
        end

        % Peek at the front item of the queue (without removing it)
        function item = peek(obj)
            if ~obj.isEmpty() % Check if the queue is empty
                item = obj.queue(1); % Return the front item
            else
                item = 'Queue is empty'; % Return a message if the queue is empty
            end
        end

        % Check if the queue is empty
        function isEmpty = isEmpty(obj)
```

```

        isEmpty = isempty(obj.queue); % True if the queue is empty, false
otherwise
    end

    % Get the size of the queue (number of elements)
    function size = size(obj)
        size = length(obj.queue); % Return the number of elements in the
queue
    end
end
end
end

```

Example Usage of the Queue Class

```

% Create a Queue object
myQueue = Queue();

% Enqueue elements into the queue
myQueue.enqueue(10);
myQueue.enqueue(20);
myQueue.enqueue(30);

% Display the front element
disp(['Front element: ', num2str(myQueue.peak())]); % Output: Front
element: 10

% Display the size of the queue
disp(['Queue size: ', num2str(myQueue.size())]); % Output: Queue size: 3

% Dequeue the front element
disp(['Dequeued element: ', num2str(myQueue.dequeue())]); % Output:
Dequeued element: 10

% Display the size of the queue after dequeuing
disp(['Queue size after dequeue: ', num2str(myQueue.size())]); % Output:
Queue size after dequeue: 2

```

```

% Check if the queue is empty
disp(['Is the queue empty? ', num2str(myQueue.isEmpty())]); % Output: Is
the queue empty? 0 (false)

% Dequeue all elements
disp(['Dequeued element: ', num2str(myQueue.dequeue())]); % Output:
Dequeued element: 20
disp(['Dequeued element: ', num2str(myQueue.dequeue())]); % Output:
Dequeued element: 30

% Check if the queue is empty
disp(['Is the queue empty now? ', num2str(myQueue.isEmpty())]); % Output:
Is the queue empty now? 1 (true)

% Try dequeuing from an empty queue
disp(['Dequeued element: ', myQueue.dequeue()]); % Output: Dequeued
element: Queue is empty
OUTPUT:
Front element: 10
Queue size: 3
Dequeued element: 10
Queue size after dequeue: 2
Is the queue empty? 0
Dequeued element: 20
Dequeued element: 30
Is the queue empty now? 1
Dequeued element: Queue is empty

```

PROGRAM 5: Writing and Testing Search and Sort Algorithms

Search Algorithms in python

Linear Search and Binary Search Algorithm

```
def linear_search(arr, target):
    for index, element in enumerate(arr):
        if element == target:
            return index # Return the index if the element is found
    return -1 # Return -1 if the element is not found

def binary_search(arr, target):
    left, right = 0, len(arr) - 1
    while left <= right:
        mid = (left + right) // 2 # Find the middle element
        if arr[mid] == target: # If the target is found
            return mid
        elif arr[mid] < target: # If the target is in the right half
            left = mid + 1
        else: # If the target is in the left half
            right = mid - 1

    return -1 # Return -1 if the element is not found

Testing the Search Algorithms
# Sample array (unsorted for linear search)
arr_unsorted = [10, 3, 5, 8, 7, 1, 9, 2]
# Sample array (sorted for binary search)
arr_sorted = sorted(arr_unsorted) # Sorting the array for binary search
target = 5

# Test Linear Search
linear_result = linear_search(arr_unsorted, target)
if linear_result != -1:
    print(f"Linear Search: Target {target} found at index {linear_result}")
else:
    print(f"Linear Search: Target {target} not found")
```

```
# Test Binary Search
binary_result = binary_search(arr_sorted, target)
if binary_result != -1:
    print(f"Binary Search: Target {target} found at index {binary_result}")
else:
    print(f"Binary Search: Target {target} not found")
```

OUTPUT:

Linear Search: Target 5 found at index 2

Binary Search: Target 5 found at index 2

Search Algorithms in MATLAB

Linear Search in MATLAB

```
function index = linearSearch(arr, target)
    % Linear Search Algorithm
    % Returns the index of the target element if found, else returns -1
    index = -1; % Initialize index as -1 (not found)

    for i = 1:length(arr)
        if arr(i) == target
            index = i; % Return the index (1-based) if element is found
            return;
        end
    end
end
```

Binary Search in MATLAB

```
function index = binarySearch(arr, target)
    % Binary Search Algorithm (requires sorted array)
    % Returns the index of the target element if found, else returns -1

    left = 1; % Starting index
    right = length(arr); % Ending index
```

```

while left <= right
    mid = floor((left + right) / 2); % Find the middle index

    if arr(mid) == target
        index = mid; % Return the index (1-based) if the element is found
        return;
    elseif arr(mid) < target
        left = mid + 1; % If the target is larger, search in the right half
    else
        right = mid - 1; % If the target is smaller, search in the left half
    end
end

```

```

    index = -1; % Return -1 if the element is not found
end

```

Testing the Search Algorithms in MATLAB

```

% Sample array for Linear Search (unsorted)

```

```

arr_unsorted = [10, 3, 5, 8, 7, 1, 9, 2];

```

```

% Sample array for Binary Search (sorted)

```

```

arr_sorted = sort(arr_unsorted); % Sort the array for binary search

```

```

target = 5;

```

```

% Test Linear Search

```

```

linear_result = linearSearch(arr_unsorted, target);

```

```

if linear_result ~= -1

```

```

    disp(['Linear Search: Target ', num2str(target), ' found at index ',
num2str(linear_result)]);

```

```

else

```

```

    disp(['Linear Search: Target ', num2str(target), ' not found']);

```

```

end

```

```

% Test Binary Search

```

```

binary_result = binarySearch(arr_sorted, target);
if binary_result ~= -1
    disp(['Binary Search: Target ', num2str(target), ' found at index ',
num2str(binary_result)]);
else
    disp(['Binary Search: Target ', num2str(target), ' not found']);
end

```

OUTPUT:

Linear Search: Target 5 found at index 3

Binary Search: Target 5 found at index 3

SORTING ALGORITHMS IN PYTHON

Bubble Sort

```

def bubble_sort(arr):
    n = len(arr)
    for i in range(n):
        # Flag to check if any swapping happened in this pass
        swapped = False
        for j in range(0, n-i-1):
            if arr[j] > arr[j+1]:
                arr[j], arr[j+1] = arr[j+1], arr[j] # Swap the elements
                swapped = True
        # If no elements were swapped, the list is already sorted
        if not swapped:
            break
    return arr

arr = [10, 3, 5, 8, 7, 1, 9, 2]
print("Original Array:", arr)
# Test Bubble Sort
bubble_sorted = bubble_sort(arr.copy())
print("Sorted using Bubble Sort:", bubble_sorted)
Original Array: [10, 3, 5, 8, 7, 1, 9, 2]
Sorted using Bubble Sort: [1, 2, 3, 5, 7, 8, 9, 10]

```


Bubble Sort Algorithm in MATLAB

```
function sorted_array = bubbleSort(arr)
    n = length(arr); % Get the number of elements in the array
    for i = 1:n
        swapped = false; % Flag to check if any swapping happens
        for j = 1:n-i
            if arr(j) > arr(j+1)
                % Swap elements if they are in the wrong order
                temp = arr(j);
                arr(j) = arr(j+1);
                arr(j+1) = temp;
                swapped = true; % Mark that a swap has happened
            end
        end
        % If no elements were swapped, the array is already sorted
        if ~swapped
            break;
        end
    end
    sorted_array = arr; % Return the sorted array
end

% Example unsorted array
arr = [10, 3, 5, 8, 7, 1, 9, 2];
disp('Original Array:');
disp(arr);

% Call the bubbleSort function
sorted_arr = bubbleSort(arr);
disp('Sorted Array:');
disp(sorted_arr);

OUTPUT:
Original Array:
    10     3     5     8     7     1     9     2
Sorted Array:
     1     2     3     5     7     8     9    10
```

PROGRAM 6 : Analyzing Algorithm Complexity in Practical Problems

Bubble Sort Time Complexity in python

```
import time
# Bubble Sort function
def bubble_sort(arr):
    n = len(arr)
    for i in range(n):
        swapped = False # Flag to check if any swap was made during this pass
        for j in range(n-i-1): # The last i elements are already sorted
            if arr[j] > arr[j+1]:
                # Swap elements if they are in the wrong order
                arr[j], arr[j+1] = arr[j+1], arr[j]
                swapped = True
        if not swapped:
            break # No swaps were made, array is already sorted
    return arr
# Example array
arr = [64, 34, 25, 12, 22, 11, 90]
# Record the start time
start_time = time.time()
# Call the bubble_sort function
sorted_arr = bubble_sort(arr)
# Record the end time
end_time = time.time()
# Calculate the time taken to sort the array
elapsed_time = end_time - start_time
# Output the results
print("Original array:", [64, 34, 25, 12, 22, 11, 90])
print("Sorted array:", sorted_arr)
print(f"Time taken to sort the array: {elapsed_time:.6f} seconds")
OUTPUT:
Original array: [64, 34, 25, 12, 22, 11, 90]
Sorted array: [11, 12, 22, 25, 34, 64, 90]
Time taken to sort the array: 0.000004 seconds
```

PROGRAM 7 : Implementing Numerical Methods in Python and MATLAB

Implementing Numerical Methods in Python

Bisection Method (Root Finding): Let's solve $f(x) = x^2 - 4$

```
def bisection_method(f, a, b, tol=1e-5, max_iter=100):
    if f(a) * f(b) > 0:
        print("The function must have opposite signs at the endpoints a and b.")
        return None
    iter_count = 0
    while (b - a) / 2 > tol:
        c = (a + b) / 2
        if f(c) == 0: # Root is found
            return c
        elif f(c) * f(a) < 0:
            b = c
        else:
            a = c
        iter_count += 1
    if iter_count > max_iter:
        print("Maximum iterations reached.")
        break
    return (a + b) / 2 # Return midpoint as root approximation
# Example function: f(x) = x^2 - 4
def func(x):
    return x**2 - 4
# Applying bisection method
root = bisection_method(func, 0, 3)
print(f"Root: {root}")
OUTPUT: Root: 2.000000238418579
```

Newton-Raphson Method (Root Finding)

```
def newton_raphson_method(f, f_prime, x0, tol=1e-5, max_iter=100):
    x = x0
    iter_count = 0
    while abs(f(x)) > tol:
```

```

    x = x - f(x) / f_prime(x)
    iter_count += 1
    if iter_count > max_iter:
        print("Maximum iterations reached.")
        break
    return x
# Example function: f(x) = x^2 - 4, f'(x) = 2x
def func(x):
    return x**2 - 4
def func_prime(x):
    return 2*x
# Applying Newton-Raphson method
root = newton_raphson_method(func, func_prime, 3)
print(f"Root: {root}")
OUTPUT: Root: 2.0000000000000002

```

Trapezoidal Rule (Numerical Integration)

Let's approximate the integral of $f(x) = x^2$ from $a=0$ to $b=2$ using the Trapezoidal Rule with $n=1000$ subintervals.

```

def trapezoidal_rule(f, a, b, n):
    h = (b - a) / n
    integral = 0.5 * (f(a) + f(b)) # First and last terms
    for i in range(1, n):
        integral += f(a + i * h) # Middle terms
    return integral * h
# Example function: f(x) = x^2
def func(x):
    return x**2

```

Applying the Trapezoidal Rule

```
result = trapezoidal_rule(func, 0, 2, 1000)
```

```
print(f"Integral result: {result}")
```

OUTPUT: Integral result: 2.666667

Implementing Numerical Methods in MATLAB

Bisection Method (Root Finding)

```
function root = bisection_method(f, a, b, tol, max_iter)
    if f(a) * f(b) > 0
        disp('The function must have opposite signs at the endpoints a and b.');
```

return;

```
    end
    iter_count = 0;
    while (b - a) / 2 > tol
        c = (a + b) / 2;
        if f(c) == 0
            root = c; % Root found
            return;
        elseif f(c) * f(a) < 0
            b = c;
        else
            a = c;
        end
        iter_count = iter_count + 1;
        if iter_count > max_iter
            disp('Maximum iterations reached.');
```

break;

```
    end
    end
    root = (a + b) / 2; % Midpoint is the approximate root
end
```

```
% Example function:  $f(x) = x^2 - 4$ 
f = @(x) x^2 - 4;
% Using the bisection method
root = bisection_method(f, 0, 3, 1e-5, 100);
disp(['Root: ', num2str(root)]);
OUTPUT: Root: 2
```

Newton-Raphson Method (Root Finding)

```
function root = newton_raphson_method(f, f_prime, x0, tol, max_iter)
    x = x0;
    iter_count = 0;
    while abs(f(x)) > tol
        x = x - f(x) / f_prime(x);
        iter_count = iter_count + 1;

        if iter_count > max_iter
            disp('Maximum iterations reached. ');
            break;
        end
    end

    root = x;
end

% Example function:  $f(x) = x^2 - 4$ ,  $f'(x) = 2x$ 
f = @(x) x^2 - 4;
f_prime = @(x) 2*x;
% Using the Newton-Raphson method
root = newton_raphson_method(f, f_prime, 3, 1e-5, 100);
disp(['Root: ', num2str(root)]);
OUTPUT: Root: 2
```

Trapezoidal Rule (Numerical Integration)

```
function integral = trapezoidal_rule(f, a, b, n)
    h = (b - a) / n; % Step size
```

```

integral = 0.5 * (f(a) + f(b)); % First and last terms
for i = 1:n-1
    integral = integral + f(a + i * h); % Middle terms
end
integral = integral * h; % Final result
end
% Example function: f(x) = x^2
f = @(x) x^2;
% Using the Trapezoidal Rule
result = trapezoidal_rule(f, 0, 2, 1000);
disp(['Integral result: ', num2str(result)]);
OUTPUT: Integral result: 2.6667

```

PROGRAM 8 : Performing Matrix Operations and Solving Linear Systems

In Python, matrix operations and solving linear systems can be easily performed using the numpy library. First, ensure that you have numpy installed: `pip install numpy`

Matrix Operations in Python (using numpy):

```
import numpy as np
```

```
# Define matrices
```

```
A = np.array([[1, 2], [3, 4]])
```

```
B = np.array([[5, 6], [7, 8]])
```

```
# Matrix Addition
```

```
C_add = A + B
```

```
print("Matrix Addition:\n", C_add)
```

```
# Matrix Subtraction
```

```
C_sub = A - B
```

```
print("Matrix Subtraction:\n", C_sub)
```

```
# Matrix Multiplication (Dot Product)
```

```
C_mult = np.dot(A, B)
```

```
print("Matrix Multiplication (A * B):\n", C_mult)
```

```
# Matrix Transpose
```

```
C_transpose = A.T
```

```
print("Matrix Transpose of A:\n", C_transpose)
```

```
# Matrix Inversion
```

```
A_inv = np.linalg.inv(A)
```

```
print("Matrix Inverse of A:\n", A_inv)
```


OUTPUT:

Matrix Addition:

[[6 8]

[10 12]]

Matrix Subtraction:

[[-4 -4]

[-4 -4]]

Matrix Multiplication (A * B):

[[19 22]

[43 50]]

Matrix Transpose of A:

[[1 3]

[2 4]]

Matrix Inverse of A:

[[-2. 1.]

[1.5 -0.5]]

Solving Linear Systems: To solve a system of linear equations, we can use `numpy.linalg.solve()`, which is a convenient way to solve the equation $Ax = b$ for x , where A is the coefficient matrix and b is the right-hand side vector.

Consider the system of linear equations:

$$2x + y = 5$$

$$x + 2y = 6$$

This system can be represented in matrix form as:

$$A = \begin{bmatrix} 2 & 1 \\ 1 & 2 \end{bmatrix}$$

```

b = [5, 6]

import numpy as np

# Coefficient matrix (A)
A = np.array([[2, 1], [1, 2]])

# Right-hand side (b)
b = np.array([5, 6])

# Solve for x (where Ax = b)
x = np.linalg.solve(A, b)

print("Solution (x, y):", x)

```

OUTPUT: Solution (x, y): [1. 3.]

Determinant and Rank of a Matrix: ou can also compute the determinant and rank of a matrix using `numpy.linalg.det()` and `numpy.linalg.matrix_rank()`.

```

# Determinant of matrix A
det_A = np.linalg.det(A)

print("Determinant of A:", det_A)

# Rank of matrix A
rank_A = np.linalg.matrix_rank(A)

print("Rank of A:", rank_A)

```

OUTPUT: Determinant of A: 3.0000000000000004

Rank of A: 2

Eigenvalues and Eigenvectors

```

# Eigenvalues and Eigenvectors of A
eigenvalues, eigenvectors = np.linalg.eig(A)

```

```
print("Eigenvalues:", eigenvalues)
print("Eigenvectors:\n", eigenvectors)
```

OUTPUT: Eigenvalues: [5. -0.]

Eigenvectors:

```
[[ 0.70710678 -0.70710678]
```

```
[ 0.70710678  0.70710678]]
```

PROGRAM 9 : Case Studies and Applications in Engineering

Scientific programming is crucial in engineering to model complex systems, simulate physical processes, solve differential equations, optimize designs, and analyze large datasets. Below are some examples of **scientific programming applications** in engineering, along with the case studies illustrating their use.

Finite Element Analysis (FEA) for Structural Engineering

Problem: Structural Integrity of a Beam Under Load

Application: Finite Element Analysis (FEA) is used to simulate the behavior of a structure (like a beam) under different loads and conditions. The goal is to determine stress, strain, and displacement patterns in the structure.

Steps Involved:

1. **Problem Definition:** Model the beam as a collection of elements (nodes and finite elements).
2. **Mesh Generation:** Divide the beam into smaller elements (discretization).
3. **Material Properties:** Define material properties like Young's modulus, Poisson's ratio, and density.
4. **Boundary Conditions:** Apply boundary conditions (fixed or free ends, loads).
5. **Solver:** Use numerical solvers (like Gaussian elimination) to solve the system of equations that govern the system's behavior.
6. **Post-Processing:** Visualize the displacement, stress, and strain distributions.

Scientific Programming Tools:

- **Languages:** Python, MATLAB, C++
- **Libraries:** FEniCS (Python), ABAQUS, ANSYS

Computational Fluid Dynamics (CFD) for Flow Simulation

Problem: Fluid Flow Over an Airfoil

Application: Computational Fluid Dynamics (CFD) is used to analyze the behavior of fluid flows around objects (e.g., airfoils, pipes). For this example, the flow over an airfoil needs to be simulated to evaluate its lift and drag forces.

Steps Involved:

1. **Geometry Creation:** Model the airfoil geometry.
2. **Mesh Generation:** Discretize the geometry into cells (e.g., using a structured or unstructured grid).
3. **Governing Equations:** Solve the Navier-Stokes equations for fluid dynamics.

4. **Boundary Conditions:** Set inlet, outlet, and wall boundary conditions for the flow.
5. **Solver:** Use numerical solvers to compute velocity, pressure, and other parameters at each cell.
6. **Post-Processing:** Visualize the velocity field, pressure distribution, and forces acting on the airfoil.

Scientific Programming Tools:

- **Languages:** Python, MATLAB, C++
- **Libraries:** OpenFOAM, CFDTool (MATLAB), PyFoam (Python)

Control Systems Design for a Mechanical System

Problem: Designing a PID Controller for a Motor Speed Control System

Application: In mechanical engineering, controlling the speed of a motor is a common problem. The task is to design a PID controller that ensures the motor speed follows a desired reference value while minimizing the error.

Steps Involved:

1. **Modeling the System:** Create a mathematical model for the motor (e.g., transfer function or state-space model).
2. **Controller Design:** Design a PID controller (Proportional-Integral-Derivative controller) to regulate motor speed.
3. **Simulation:** Simulate the system response to step or ramp inputs, and evaluate performance.
4. **Tuning the PID Parameters:** Adjust the PID parameters (K_p , K_i , K_d) to minimize overshoot and settling time.

Scientific Programming Tools:

- **Languages:** Python, MATLAB, Simulink
- **Libraries:** control (Python), scipy.signal (Python), Simulink (MATLAB)

Signal Processing: Filtering and Spectral Analysis

Problem: Design of a Digital Filter for Signal Processing

Application: Digital signal processing (DSP) involves filtering signals to remove noise or unwanted frequencies. A **low-pass filter** can be designed to allow only signals with frequencies lower than a cutoff frequency to pass through, while higher frequencies are attenuated.

Steps Involved:

1. **Filter Design:** Design a digital low-pass filter using the **Butterworth** or **Chebyshev** method.
2. **Frequency Response Analysis:** Analyze the frequency response of the filter to ensure it meets the desired specifications (e.g., cutoff frequency, passband ripple).
3. **Simulation:** Apply the filter to a noisy signal and check the output.

Scientific Programming Tools:

- **Languages:** Python, MATLAB
- **Libraries:** scipy.signal (Python), Signal Processing Toolbox (MATLAB)

Power Systems: Load Flow Analysis

Problem: Power Flow in an Electrical Grid

Application: In electrical power systems, load flow analysis (also known as **power flow analysis**) is used to determine the voltage, current, power, and impedance at different points in the network. This helps in understanding how power is distributed and how the system behaves under different load conditions.

Steps Involved:

1. **Power Flow Model:** Represent the electrical network as a system of equations based on Kirchhoff's laws.
2. **Solve Power Flow Equations:** Use iterative methods (like **Gauss-Seidel** or **Newton-Raphson**) to solve the system.
3. **Analysis:** Analyze the voltage levels, power losses, and stability of the grid.

Scientific Programming Tools:

- **Languages:** Python, MATLAB
- **Libraries:** numpy, scipy (Python), Power System Toolbox (MATLAB)

PROGRAM 10 : Data Manipulation and Analysis using Pandas and MATLAB

Data Manipulation and Analysis using Pandas

```
import pandas as pd
```

```
# --- 1. Create a DataFrame from a Dictionary ---
```

```
data = {
```

```
    'Name': ['Alice', 'Bob', 'Charlie', 'David'],
```

```
    'Age': [25, 30, 35, 40],
```

```
    'City': ['New York', 'Los Angeles', 'Chicago', 'Houston']
```

```
}
```

```
# Creating a DataFrame
```

```
df = pd.DataFrame(data)
```

```
# Display the DataFrame
```

```
print("Initial DataFrame:")
```

```
print(df)
```

```
print("\n")
```

```
# --- 2. Reading Data from a CSV File (Simulated by creating a DataFrame) ---
```

```
# Assuming you have a CSV file (Here we're simulating it by creating a  
DataFrame directly)
```

```
# --- 3. Selecting and Indexing Data ---
```

```
# Accessing a specific column
```

```
print("Accessing the 'Name' column:")
```

```
print(df['Name'])
```

```
print("\n")
```

```

# Accessing multiple columns

print("Accessing 'Name' and 'Age' columns:")

print(df[['Name', 'Age']])

print("\n")

# Accessing a specific row by index

print("Accessing the row at index 2 (Charlie):")

print(df.loc[2])

print("\n")

# Accessing the second row (position-based)

print("Accessing the second row (position 1):")

print(df.iloc[1])

print("\n")

# --- 4. Data Cleaning ---

# Create a DataFrame with missing data

data_with_nan = {

    'Name': ['Alice', 'Bob', 'Charlie', None],

    'Age': [25, None, 35, 40],

    'City': ['New York', 'Los Angeles', 'Chicago', 'Houston']

}

df_nan = pd.DataFrame(data_with_nan)

# Fill missing values

df_nan['Name'].fillna('Unknown', inplace=True)

df_nan['Age'].fillna(0, inplace=True)

```



```

print("DataFrame after handling missing values:")

print(df_nan)

print("\n")

# --- 5. Dropping Duplicates ---

data_duplicates = {
    'Name': ['Alice', 'Bob', 'Charlie', 'Alice'],
    'Age': [25, 30, 35, 25],
    'City': ['New York', 'Los Angeles', 'Chicago', 'New York']
}

df_duplicates = pd.DataFrame(data_duplicates)

# Drop duplicate rows

df_unique = df_duplicates.drop_duplicates()

print("DataFrame after dropping duplicates:")

print(df_unique)

print("\n")

# --- 6. Data Transformation ---

# Adding a new column based on existing data

df['Age in 5 Years'] = df['Age'] + 5

print("DataFrame with a new column 'Age in 5 Years':")

print(df)

print("\n")

# Apply a function to the 'Age' column to increment it

df['Age'] = df['Age'].apply(lambda x: x + 1)

```

```

print("DataFrame after applying a function to increment the 'Age' column:")

print(df)

print("\n")

# --- 7. Grouping Data ---

# Group by 'City' and calculate the average age
grouped_df = df.groupby('City')['Age'].mean()

print("Average Age by City:")

print(grouped_df)

print("\n")

# --- 8. Merging DataFrames ---

# Create another DataFrame for merging
data2 = {
    'Name': ['Alice', 'Bob', 'Charlie', 'David'],
    'Salary': [50000, 60000, 70000, 80000]
}

df2 = pd.DataFrame(data2)

# Merge the two DataFrames on the 'Name' column
merged_df = pd.merge(df, df2, on='Name')

print("Merged DataFrame:")

print(merged_df)

print("\n")

# --- 9. Saving DataFrame to a CSV File ---

# Save the DataFrame to a CSV file (uncomment to run this part)

```

```
# df.to_csv('output.csv', index=False)
```

OUTPUT:

Initial DataFrame:

	Name	Age	City
0	Alice	25	New York
1	Bob	30	Los Angeles
2	Charlie	35	Chicago
3	David	40	Houston

Accessing the 'Name' column:

0	Alice
1	Bob
2	Charlie
3	David

Name: Name, dtype: object

Accessing 'Name' and 'Age' columns:

	Name	Age
0	Alice	25
1	Bob	30
2	Charlie	35
3	David	40

Accessing the row at index 2 (Charlie):

Name	Charlie
Age	35
City	Chicago

Name: 2, dtype: object

Accessing the second row (position 1):

Name	Bob
Age	30
City	Los Angeles

Name: 1, dtype: object

DataFrame after handling missing values:

	Name	Age	City
0	Alice	25	New York
1	Bob	0	Los Angeles
2	Charlie	35	Chicago
3	Unknown	40	Houston

DataFrame after dropping duplicates:

	Name	Age	City
0	Alice	25	New York
1	Bob	30	Los Angeles
2	Charlie	35	Chicago

DataFrame with a new column 'Age in 5 Years':

	Name	Age	City	Age in 5 Years
0	Alice	25	New York	30
1	Bob	30	Los Angeles	35
2	Charlie	35	Chicago	40
3	David	40	Houston	45

DataFrame after applying a function to increment the 'Age' column:

	Name	Age	City	Age in 5 Years
0	Alice	26	New York	30
1	Bob	31	Los Angeles	35
2	Charlie	36	Chicago	40
3	David	41	Houston	45

Average Age by City:

City	Average Age
Chicago	36.0
Houston	41.0
Los Angeles	31.0

New York 26.0

Name: Age, dtype: float64

Merged DataFrame:

	Name	Age	City	Age in 5 Years	Salary
0	Alice	26	New York	30	50000
1	Bob	31	Los Angeles	35	60000
2	Charlie	36	Chicago	40	70000
3	David	41	Houston	45	80000

Data Manipulation and Analysis using MATLAB

% 1. Creating Arrays and Data Structures

% Creating a numeric array

A = [1, 2, 3, 4, 5]; % Row vector

B = [1; 2; 3; 4; 5]; % Column vector

% Creating a matrix (2D array)

C = [1, 2, 3; 4, 5, 6; 7, 8, 9];

% Display the matrices

disp('Row vector A:');

disp(A);

disp('Column vector B:');

disp(B);

disp('Matrix C:');

disp(C);

% 2. Creating a Table

Names = {'Alice', 'Bob', 'Charlie', 'David'};

Ages = [25, 30, 35, 40];

Cities = {'New York', 'Los Angeles', 'Chicago', 'Houston'};

```
T = table(Names', Ages', Cities');  
disp('Table of people data:');  
disp(T);
```

% 3. Accessing Data from Arrays and Tables

```
% Accessing individual elements in arrays
```

```
first_value = A(1); % First element of A
```

```
second_row_first_column = C(2, 1); % Element in second row, first column of  
C
```

```
disp('First value of A:');  
disp(first_value);
```

```
disp('Element at position (2,1) in C:');  
disp(second_row_first_column);
```

```
% Accessing table columns by name
```

```
names_col = T.Names;
```

```
ages_col = T.Ages;
```

```
% Accessing specific row and column in the table
```

```
first_person = T(1, :); % First row of the table
```

```
disp('Names column from the table:');  
disp(names_col);
```

```
disp('First person from the table:');  
disp(first_person);
```

% 4. Handling Missing Data

```
% Creating a table with missing data
```

```

Age = [25, NaN, 35, 40];
City = {'New York', 'Los Angeles', 'Chicago', 'Houston'};

T_with_missing = table(Age', City');
disp('Table with missing data:');
disp(T_with_missing);

% Replace NaN with a specific value (e.g., 0)
T_with_missing.Age(isnan(T_with_missing.Age)) = 0;

disp('Table after replacing NaN with 0:');
disp(T_with_missing);

% 5. Creating a New Column in the Table

% Adding a new column 'Age_in_5_years' to the table
T_with_missing.Age_in_5_years = T_with_missing.Age + 5;

disp('Table with new column "Age_in_5_years":');
disp(T_with_missing);

% 6. Basic Statistical Operations

% Calculating basic statistics for the Age column
mean_age = mean(T_with_missing.Age);
std_age = std(T_with_missing.Age);
min_age = min(T_with_missing.Age);
max_age = max(T_with_missing.Age);

disp(['Mean age: ', num2str(mean_age)]);
disp(['Standard deviation of age: ', num2str(std_age)]);
disp(['Minimum age: ', num2str(min_age)]);
disp(['Maximum age: ', num2str(max_age)]);

```

% 7. Saving Data to a CSV File

```
writetable(T_with_missing, 'people_data.csv');  
disp('Data saved to people_data.csv');
```

OUTPUT: Row vector A:

1 2 3 4 5

Column vector B:

1
2
3
4
5

Matrix C:

1 2 3
4 5 6
7 8 9

Table of people data:

Names	Ages	Cities
'Alice'	25	'New York'
'Bob'	30	'Los Angeles'
'Charlie'	35	'Chicago'
'David'	40	'Houston'

First value of A:

1

Element at position (2,1) in C:

4

Names column from the table:

'Alice' 'Bob' 'Charlie' 'David'

First person from the table:

Names: 'Alice' Ages: 25 Cities: 'New York'

Table with missing data:

Age	City
25	'New York'
NaN	'Los Angeles'
35	'Chicago'
40	'Houston'

Table after replacing NaN with 0:

Age	City
25	'New York'
0	'Los Angeles'
35	'Chicago'
40	'Houston'

Table with new column "Age_in_5_years":

Age	City	Age_in_5_years
25	'New York'	30
0	'Los Angeles'	5
35	'Chicago'	40
40	'Houston'	45

Mean age: 25

Standard deviation of age: 17.677

Minimum age: 0

Maximum age: 40

Data saved to people_data.csv

PROGRAM 11 : Creating Various Plots(Line,Scatter,Bar,Histogram)

```
import matplotlib.pyplot as plt
import numpy as np
```

```
# Data for plotting
```

```
x = np.linspace(0, 10, 100) # 100 points between 0 and 10
```

```
y = np.sin(x) # Sine of x
```

```
y2 = np.cos(x) # Cosine of x
```

```
categories = ['A', 'B', 'C', 'D']
```

```
values = [10, 20, 15, 30]
```

```
# 1. Line Plot
```

```
plt.figure(figsize=(10, 6)) # Set the figure size
```

```
plt.plot(x, y, label='sin(x)', color='blue') # Line plot for sin(x)
```

```
plt.plot(x, y2, label='cos(x)', color='red') # Line plot for cos(x)
```

```
plt.title('Line Plot Example')
```


```
plt.xlabel('X values')
```

```
plt.ylabel('Y values')
```

```
plt.legend() # Show legend
```


```
plt.grid(True) # Display grid
```

```
plt.show()
```




2. Scatter Plot

```
plt.figure(figsize=(10, 6))  
plt.scatter(x, y, label='sin(x)', color='green') # Scatter plot for sin(x)  
plt.scatter(x, y2, label='cos(x)', color='purple') # Scatter plot for cos(x)  
plt.title('Scatter Plot Example')  
plt.xlabel('X values')  
plt.ylabel('Y values')  
plt.legend()  
plt.show()
```



3. Bar Plot

```
plt.figure(figsize=(10, 6))  
plt.bar(categories, values, color='orange') # Bar plot  
plt.title('Bar Plot Example')  
plt.xlabel('Categories')  
plt.ylabel('Values')  
plt.show()
```



4. Histogram

```
data = np.random.randn(1000) # Generate 1000 random numbers from  
normal distribution
```

```
plt.figure(figsize=(10, 6))
```


```
plt.hist(data, bins=30, color='cyan', edgecolor='black') # Histogram
```

```
plt.title('Histogram Example')
```

```
plt.xlabel('Data Values')
```

```
plt.ylabel('Frequency')
```

```
plt.show()
```



PROGRAM 12 : Customizing and Interpreting Plots for Engineering Data

```
import matplotlib.pyplot as plt
import numpy as np

# Example 1: Temperature vs. Time (Line Plot)
time = np.linspace(0, 24, 100) # Time from 0 to 24 hours
temperature = 20 + 5 * np.sin(2 * np.pi * time / 24) # Simulated temperature
variation

plt.figure(figsize=(10, 6))
plt.plot(time, temperature, label='Temperature', color='blue', linestyle='-',
marker='o', markersize=5)
plt.title('Temperature Variation Over 24 Hours', fontsize=14)
plt.xlabel('Time (hours)', fontsize=12)
plt.ylabel('Temperature (°C)', fontsize=12)
plt.grid(True)
plt.legend(loc='upper right')
plt.tight_layout()
plt.show()

# Example 2: Signal Plot (Sine Wave)
frequency = 50 # Frequency of the signal in Hz
sampling_rate = 1000 # Samples per second
t = np.linspace(0, 1, sampling_rate) # Time vector for 1 second
signal = np.sin(2 * np.pi * frequency * t) # Sine wave signal

plt.figure(figsize=(10, 6))
plt.plot(t, signal, label='Signal', color='red', linestyle='-', linewidth=1.5)
plt.title('Sine Wave Signal (50 Hz)', fontsize=14)
plt.xlabel('Time (seconds)', fontsize=12)
plt.ylabel('Amplitude', fontsize=12)
plt.grid(True, which='both', linestyle='--', color='gray')
plt.legend(loc='upper right')
```

```

plt.tight_layout()
plt.show()


# Example 3: Histogram of Voltage Measurements
voltage_measurements = np.random.normal(loc=230, scale=10, size=1000) #
Simulated voltage data around 230V



plt.figure(figsize=(10, 6))
plt.hist(voltage_measurements, bins=30, color='green', edgecolor='black',
alpha=0.7)
plt.title('Histogram of Voltage Measurements', fontsize=14)
plt.xlabel('Voltage (V)', fontsize=12)
plt.ylabel('Frequency', fontsize=12)
plt.grid(True, linestyle='--')
plt.tight_layout()
plt.show()

# Example 4: Electrical Power vs. Resistance (Ohm's Law Plot)
voltage = 10 # Voltage in volts
resistance = np.linspace(1, 100, 100) # Resistance from 1 ohm to 100 ohms
current = voltage / resistance # Current using Ohm's Law ( $I = V/R$ )
power = voltage * current # Power using  $P = VI$ 

plt.figure(figsize=(10, 6))
plt.plot(resistance, power, label='Power vs. Resistance', color='purple',
linestyle='-', marker='x')
plt.title('Power vs. Resistance (Ohm's Law)', fontsize=14)
plt.xlabel('Resistance (Ohms)', fontsize=12)
plt.ylabel('Power (Watts)', fontsize=12)
plt.grid(True, linestyle='-.', color='orange')
plt.legend(loc='upper right')
plt.tight_layout()
plt.show()

```





PROGRAM 13 : Implementing Basic Machine Learning Algorithms in Python

Implementing basic machine learning algorithms in Python is essential to understand how machine learning models work. Here, we'll implement some of the most common algorithms: **Linear Regression**, **Logistic Regression**, **K-Nearest Neighbors (KNN)**, and **Decision Trees**. We will also demonstrate how to evaluate these models using a sample dataset. To implement these algorithms, we will use libraries such as scikit-learn, numpy, and matplotlib.

1. Linear Regression Example (Supervised Learning)

Linear regression is a fundamental machine learning algorithm used for predicting a continuous value based on the input features.

```
import numpy as np
import matplotlib.pyplot as plt
from sklearn.linear_model import LinearRegression
from sklearn.model_selection import train_test_split
from sklearn.metrics import mean_squared_error

# Generate some synthetic data (y = 2x + 1)
X = np.random.rand(100, 1) * 10 # 100 random values for X (from 0 to 10)
y = 2 * X + 1 + np.random.randn(100, 1) # y = 2x + 1 with some noise

# Split data into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42)

# Initialize Linear Regression model
model = LinearRegression()


# Train the model
model.fit(X_train, y_train)

# Make predictions
y_pred = model.predict(X_test)
```

```
# Evaluate the model
mse = mean_squared_error(y_test, y_pred)
print(f"Mean Squared Error: {mse}")

# Plotting the results
plt.scatter(X_test, y_test, color='blue', label='Actual data')
plt.plot(X_test, y_pred, color='red', linewidth=2, label='Predicted line')
plt.xlabel('X')
plt.ylabel('y')
plt.title('Linear Regression')
plt.legend()
plt.show()
```

Mean Squared Error: 0.6742030217027715



Logistic Regression Example (Supervised Learning)

Logistic regression is used for binary classification tasks, where the goal is to predict the probability of a class (e.g., 0 or 1).

```
from sklearn.datasets import load_iris
from sklearn.linear_model import LogisticRegression
```

```

from sklearn.model_selection import train_test_split
from sklearn.metrics import accuracy_score, confusion_matrix

# Load the Iris dataset
iris = load_iris()
X = iris.data
y = iris.target

# We will use only two classes (binary classification for simplicity)
X = X[y != 2]
y = y[y != 2]

# Split data into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3,
random_state=42)

# Initialize Logistic Regression model
log_reg = LogisticRegression()

# Train the model
log_reg.fit(X_train, y_train)

# Make predictions
y_pred = log_reg.predict(X_test)

# Evaluate the model
accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy}")
print(f"Confusion Matrix:\n{confusion_matrix(y_test, y_pred)}")

Accuracy: 1.0
Confusion Matrix:
[[17  0]
 [ 0 13]]

```

K-Nearest Neighbors (KNN) Example (Supervised Learning)

K-Nearest Neighbors (KNN) is a simple and intuitive algorithm used for both classification and regression tasks. In this example, we'll use it for classification.

```
from sklearn.neighbors import KNeighborsClassifier
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split
from sklearn.metrics import accuracy_score

# Load the Iris dataset
iris = load_iris()
X = iris.data
y = iris.target

# Split data into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3,
random_state=42)

# Initialize KNN model with 3 neighbors
knn = KNeighborsClassifier(n_neighbors=3)

# Train the model
knn.fit(X_train, y_train)

# Make predictions
y_pred = knn.predict(X_test)

# Evaluate the model
accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy}")

Accuracy: 1.0
```

Decision Tree Classifier Example (Supervised Learning)

Decision Trees are used for classification and regression tasks. Here, we'll implement it for classification.

```
from sklearn.tree import DecisionTreeClassifier
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split
from sklearn.metrics import accuracy_score

# Load the Iris dataset
iris = load_iris()
X = iris.data
y = iris.target

# Split data into training and testing sets
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3,
random_state=42)

# Initialize Decision Tree model
dt = DecisionTreeClassifier()

# Train the model
dt.fit(X_train, y_train)

# Make predictions
y_pred = dt.predict(X_test)

# Evaluate the model
accuracy = accuracy_score(y_test, y_pred)
print(f"Accuracy: {accuracy}")

Accuracy: 1.0
```

PROGRAM 14 : Exploring IoT and Big Data Tools

Exploring **IoT (Internet of Things)** and **Big Data Tools** can provide insight into how these technologies work and how they are applied to real-world scenarios. Both IoT and Big Data are critical components of modern computing, enabling industries to collect, process, and analyze vast amounts of data in real-time for better decision-making and automation.

Common IoT Applications:

- **Smart Homes:** Devices like smart thermostats (e.g., Nest), smart lights, and voice assistants (e.g., Amazon Alexa, Google Assistant).
- **Wearables:** Devices like Fitbit or smartwatches that collect health and fitness data.
- **Healthcare:** Remote monitoring systems, wearables for health tracking, and hospital equipment.
- **Agriculture:** Smart farming using IoT-enabled sensors for soil moisture, temperature, and weather conditions.
- **Industry 4.0:** Industrial IoT (IIoT) sensors and systems that monitor production lines, machinery, and energy consumption.

IoT Tools

Several platforms and tools are available to work with IoT systems. These tools facilitate the deployment, management, and integration of IoT devices.

IoT Platforms and Development Tools

- **Arduino:** An open-source electronics platform used for building IoT devices. It consists of a microcontroller board and software development environment.
- **Raspberry Pi:** A small single-board computer that can be used for building IoT projects.
- **ThingSpeak:** An IoT platform for connecting IoT devices, collecting data, and visualizing it in real-time.
- **AWS IoT:** Amazon Web Services offers a suite of tools (including AWS IoT Core) to securely connect IoT devices to the cloud and perform data analytics.
- **Google Cloud IoT:** A fully managed suite of tools for building IoT applications using Google's cloud infrastructure.
- **Microsoft Azure IoT Hub:** A platform for managing and securing IoT devices, ingesting data, and running analytics.

IoT Protocols

- **MQTT (Message Queuing Telemetry Transport):** A lightweight messaging protocol designed for low-bandwidth, high-latency networks. MQTT is often used for IoT communications.
- **CoAP (Constrained Application Protocol):** Another lightweight protocol designed for constrained devices and low-power, low-bandwidth networks.
- **HTTP/HTTPS:** Common protocols for IoT communication but less efficient in terms of bandwidth compared to MQTT and CoAP.
- **LoRaWAN (Long Range Wide Area Network):** A wireless protocol for long-range, low-power communications for IoT devices.

Big Data Tools :

Big Data refers to datasets that are too large or complex to be handled by traditional data processing systems. Big Data typically encompasses data that is **high-volume**, **high-velocity**, and **high-variety**. It can include everything from social media posts, sensor data from IoT devices, financial transactions, and medical records, to data generated by online activities, etc.

Big Data Storage Tools

- **Hadoop:** An open-source framework that stores and processes large datasets in a distributed computing environment. It includes components like **HDFS** (Hadoop Distributed File System) and **MapReduce** (for distributed processing).
- **Apache HBase:** A distributed, column-oriented NoSQL database that runs on top of HDFS and is used for real-time read/write access to large datasets.
- **Amazon S3 (Simple Storage Service):** A scalable storage service for storing any amount of data, often used for Big Data storage.
- **Google Cloud Storage:** Similar to Amazon S3, Google Cloud Storage offers scalable storage services for Big Data.

Big Data Processing Frameworks

- **Apache Spark:** A powerful open-source engine for large-scale data processing. Spark can perform both batch and real-time processing and is much faster than traditional MapReduce-based systems.
- **Apache Flink:** A framework for distributed stream processing that allows you to process data in real-time.
- **Apache Kafka:** A distributed event streaming platform used for building real-time data pipelines and streaming applications.

Big Data Analytics Tools

- **Apache Hive:** A data warehouse system built on top of Hadoop for querying and managing large datasets.
- **Apache Pig:** A platform for analyzing large datasets that provide a high-level scripting language.
- **PrestoDB:** A distributed SQL query engine designed for running interactive analytic queries on large datasets.
- **Tableau:** A powerful data visualization tool that helps in creating interactive and shareable dashboards to analyze Big Data.
- **Power BI:** Microsoft's business analytics service that allows for data visualization and sharing insights from Big Data.

Data Processing Languages

- **SQL:** Traditional query language for managing structured data.
- **Python:** Popular for Big Data analytics due to libraries like **Pandas**, **Dask**, **NumPy**, and **PySpark**.
- **R:** A language for statistical computing and graphics, widely used for data analysis.
- **Scala:** Often used in conjunction with Spark for processing large datasets.

IoT + Big Data Integration

The integration of IoT and Big Data plays a significant role in industries like manufacturing, healthcare, and smart cities, where IoT devices collect massive amounts of data that need to be processed and analyzed for real-time decision-making. Here are some ways these technologies work together:

- **Data Collection via IoT Devices:** Sensors and IoT devices collect real-time data (e.g., from manufacturing machines, smart home devices, or wearable health devices).
- **Data Streaming and Processing:** The data is sent to cloud platforms (e.g., AWS IoT, Google Cloud IoT) or to Big Data platforms like Apache Kafka or Apache Flink for real-time processing.
- **Big Data Storage:** The processed data is stored in Big Data platforms such as Hadoop, HBase, or NoSQL databases like MongoDB.
- **Analytics and Insights:** Advanced analytics using tools like Apache Spark, Presto, or machine learning models to gain insights from the data. These insights are then used for decision-making, predictive maintenance, or anomaly detection.

PROGRAM 15 : Working on Individual/Group Projects

PROGRAM 16 : Preparing Project Reports and Presentations

PROGRAM 17 : Final Projection Presentation

Working on individual or group projects using scientific programming can be both rewarding and challenging. It provides an opportunity to apply mathematical and computational techniques to solve real-world problems. These projects often involve using programming languages such as **Python**, **MATLAB**, **R**, or other domain-specific languages that facilitate mathematical modeling, data analysis, and simulation. Below are some general steps and considerations for working on these types of projects.

1. Defining the Project

Whether you're working alone or in a group, the first step is defining the project's scope and objectives clearly. This is where you decide the problem you are trying to solve, which data or systems you need to work with, and what tools and methods you will use.

Key steps for defining the project:

- **Identify the Problem:** What specific problem do you want to solve? Is it related to physics, engineering, machine learning, or data analysis? For example, in electronics, you might simulate an electrical circuit, while in data science, you might analyze trends in a dataset.
- **Set Clear Goals:** What do you aim to achieve? For example, is it a simulation, optimization, or model-building task? Define the key deliverables and milestones for the project.
- **Choose Tools and Libraries:** Depending on the problem, you might need specific scientific libraries or tools. For example, you might use:
 - **Python:** Libraries like NumPy, SciPy, Matplotlib, Pandas, TensorFlow, PyTorch, etc.
 - **MATLAB:** Built-in functions and toolboxes like Simulink, Optimization Toolbox, etc.
 - **R:** Libraries like ggplot2, dplyr, and caret for statistical analysis and visualization.
- **Team Organization (for Group Projects):** If you're working in a group, decide on roles and responsibilities. For example, one person might be in charge of coding, another for data collection, and another for visualization and reporting.

2. Data Collection & Preparation

For many scientific programming projects, the first step is collecting and preparing

data. Data might come from sensors, databases, simulations, or online resources.

Steps to follow:

- **Data Collection:** Ensure the data you're collecting is reliable and relevant to your problem. For instance, if you're working on environmental modeling, you might collect data from sensors or databases related to temperature, humidity, air quality, etc.
- **Data Cleaning:** Raw data often needs preprocessing. This includes removing outliers, filling missing values, normalizing, and transforming the data into a usable format.
- **Data Storage:** Organize your data properly in files (CSV, JSON, etc.) or databases (SQL, NoSQL).

3. Algorithm Development

Once you have your data, the next step is to develop algorithms to analyze, process, or model the data. This could involve implementing numerical methods, optimization techniques, machine learning models, etc.

Examples of algorithms:

- **Numerical Methods:**
 - Solving linear systems of equations (using Gaussian elimination, LU decomposition).
 - Optimization techniques (gradient descent, Newton-Raphson method).
 - Interpolation and integration (e.g., Newton's interpolating polynomial or Simpson's rule for numerical integration).
- **Machine Learning:**
 - Supervised Learning: Implement regression (linear regression, decision trees) or classification (SVM, KNN, neural networks).
 - Unsupervised Learning: Clustering algorithms like k-means, hierarchical clustering, or dimensionality reduction techniques like PCA.
- **Simulation:**
 - For example, simulating a physical process like projectile motion or circuit behavior (using methods such as Monte Carlo simulations or finite element analysis).

4. Visualization

Visualization helps you interpret the results of your calculations. Scientific

programming projects often require you to plot graphs, charts, or 3D visualizations.

Libraries for visualization:

- **Python:**
 - **Matplotlib:** For creating 2D graphs and plots.
 - **Seaborn:** Built on top of Matplotlib for advanced statistical plotting.
 - **Plotly:** For interactive visualizations.
 - **Mayavi/Plotly:** For 3D visualizations.
- **MATLAB:**
 - Built-in functions such as plot, surf, mesh, etc., allow for 2D and 3D plotting.

5. Testing and Validation

Once the algorithm is implemented, you must test and validate it to ensure it works as expected. This involves:

- **Unit Testing:** Testing individual parts of the code to check their correctness.
- **Integration Testing:** Verifying if different parts of the system work well together.
- **Validation:** Comparing your results with real-world data or known benchmarks.

6. Documentation and Reporting

For both individual and group projects, proper documentation is crucial. This includes:

- **Code Documentation:** Use comments and docstrings to explain the functionality of your code.
- **Reports:** If this is a larger project, you might be asked to submit a report that explains:
 - Problem statement
 - Methods used
 - Results and interpretation
 - Conclusions and recommendations

LaTeX or Markdown can be useful for writing professional reports, and libraries like **Jupyter Notebooks** (Python) are great for combining code, text, and visualizations in one place.

7. Collaboration (for Group Projects)

If you're working in a group, it is essential to use collaboration tools and version control systems.

Tools for Collaboration:

- **Git/GitHub:** Version control for tracking changes and collaboration. Git allows multiple people to work on the same project simultaneously.
- **Slack/Teams:** Communication platforms for quick collaboration.
- **Trello/Asana:** Project management tools to track tasks and progress.

Whether working on an individual or group project, scientific programming allows you to apply mathematical models and data analysis techniques to solve problems in diverse fields such as physics, engineering, and data science. The key to success in such projects is:

1. Clearly defining the problem.
2. Choosing the right tools and libraries.
3. Ensuring proper testing and validation.
4. Collaborating efficiently if working in a team.
5. Documenting and reporting your results.

These steps will help ensure that your scientific programming project is well-executed and produces meaningful, interpretable results.