

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 10.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 24.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 24.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 13.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 13.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 7.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 28.5 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 21.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 22.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 3.5 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 13.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 14.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 12.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 2.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 7.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 9.8 in the documented measurement context. The value must not be interpreted

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 18.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 28.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 6.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 13.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 19.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 10.0 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 4.5 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 2.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 7.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 11.6 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 2.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 9.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 13.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 28.4 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 21.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 8.2 in the documented measurement context. The value must not be interpreted

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 6.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 28.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 27.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 20.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 11.2 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 15.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 23.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 28.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 25.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 19.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 23.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 10.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 3.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 18.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 25.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 26.3 in the documented measurement context. The value must not be interpreted

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 5.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 22.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 14.1 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 17.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 28.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 7.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 17.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 2.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 16.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 8.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 18.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 24.0 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 22.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 8.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 24.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 18.0 in the documented measurement context. The value must not be interpreted



ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 23.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 16.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 12.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 23.4 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 16.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 2.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 27.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 5.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 7.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 27.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 27.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 24.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 5.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 24.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 21.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 28.1 in the documented measurement context. The value must not be interpreted

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 3.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 11.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 11.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 27.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 22.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 5.4 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 10.3 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 4.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 25.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 14.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 25.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 24.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 9.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 17.8 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 10.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 6.3 in the documented measurement context. The value must not be interpreted

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 11.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 5.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 22.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 13.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 21.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 7.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 6.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 28.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 16.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 8.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 14.4 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 7.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 15.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 20.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 13.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 10.5 in the documented measurement context. The value must not be interpreted independently

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 21.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 14.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 19.2 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 10.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 20.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 10.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 25.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 2.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 25.9 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 26.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 6.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 24.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 7.7 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 28.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 20.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 3.8 in the documented measurement context. The value must not be interpreted



ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 2.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 7.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 13.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 5.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 26.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 18.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 18.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 12.9 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 14.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 17.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 16.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 8.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 18.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 5.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 28.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 11.5 in the documented measurement context. The value must not be interpreted

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 5.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 14.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 16.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 13.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 22.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 10.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 24.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 26.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 20.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 5.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 17.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 8.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 4.3 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 28.6 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 23.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 22.6 in the documented measurement context. The value must not be interpreted independently

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 26.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 7.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 5.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 6.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 4.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 4.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 19.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 15.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 18.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 26.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 20.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 28.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 10.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 15.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 9.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 12.0 in the documented measurement context. The value must not be interpreted

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 16.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 13.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 7.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 16.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 9.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 5.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 2.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 17.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 26.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 20.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 17.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 10.0 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 11.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 5.9 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 24.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 9.8 in the documented measurement context. The value must not be interpreted



ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 7.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 22.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 11.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 21.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 10.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 15.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 22.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 8.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 14.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 26.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 20.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 13.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 17.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 15.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 4.0 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 18.1 in the documented measurement context. The value must not be interpreted



ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 4.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 21.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 21.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 21.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 2.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 24.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 25.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 10.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 25.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 21.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 27.9 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 26.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 9.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 18.4 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 15.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 25.2 in the documented measurement context. The value must not be interpreted

ARCHIVE
SCANNED

ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 14.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 28.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 5.1 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 28.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 26.8 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 7.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 26.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 14.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 9.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 21.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 17.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 14.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 18.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 9.0 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 16.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 17.6 in the documented measurement context. The value must not be interpreted



ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 6.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 2.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 4.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 25.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 22.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 26.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 3.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 20.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 8.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 12.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 19.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 9.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 16.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 8.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 12.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 13.5 in the documented measurement context. The value must not be interpreted



ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 12.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 16.5 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 21.9 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 8.6 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 20.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 8.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 8.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 17.3 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 9.3 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 12.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 11.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 23.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 20.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 26.8 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 2.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 18.6 in the documented measurement context. The value must not be interpreted



ARCHIVE | IMAGE-ONLY SOURCE | ZX-440

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 24.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 19.7 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 28.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 7.1 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 26.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed utilization indicator was 21.2 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 25.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed error rate indicator was 6.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 25.4 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 5.5 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed pressure indicator was 24.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed latency indicator was 19.4 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed throughput indicator was 23.0 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed availability indicator was 2.6 in the documented measurement context. The value must not be interpreted

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed risk indicator was 25.7 in the documented measurement context. The value must not be interpreted independently

Scanned historical field record. This controlled record for ZX-440 describes operational evidence collected under the applicable process and version. The observed variance indicator was 27.8 in the documented measurement context. The value must not be interpreted

