

SAHYADRI PETROCHEMICALS LTD.

Refinery Division, Vadodara, Gujarat

Classification: INTERNAL

Doc No: SPL-CDU1-DS-1101A

Rev: 3 Date: 12-Jan-2024

Page 1 of 1

EQUIPMENT DATASHEET

Crude Charge Pump P-1101A | Crude Distillation Unit CDU-1

This datasheet defines the design and construction particulars of Crude Charge Pump **P-1101A**, serving the Crude Distillation Unit (CDU-1). Refer to P&ID drawing **PID-CDU1-002** and motor **M-1101A**.

1. Identification & Service

Tag Number	P-1101A	Service	Crude charge to CDU-1
P&ID; Ref.	PID-CDU1-002	Driver	Motor M-1101A, 160 kW
Pump Type	Centrifugal, API 610 BB2	Standby	P-1101B (identical)
Manufacturer	Deccan Flow Systems Pvt. Ltd.	Model	DFS-CC-250

2. Design / Operating Data

Parameter	Design	Normal Operating	Units
Capacity	320	300	m3/hr
Differential Head	210	205	m
Pumping Temperature	165	150	deg C
Suction Pressure	3.5	3.2	kg/cm2 g
Fluid	Crude oil (sour)	-	-
Rated Speed	2965	2965	rpm

3. Sealing & Auxiliary

Mechanical Seal	Deccan Type DFS-3300, single cartridge
Seal Flush Plan	API Plan 52 (unpressurised buffer + external reservoir)
Shaft Alignment Spec	Per OEM manual DFS-OM-250 (laser alignment mandatory)
Bearing Lubrication	Oil bath, ISO VG 68

Prepared by: R. Deshmukh (Rotating Equipment Engineer) | Approved by: S. Iyer (Reliability Lead)