

WEEK-9 [Immella Vikram, 2520090118]

BOOKFLOW LIBRARY SYSTEM

Transactional Microservice using Spring Boot, Spring Data JPA and PostgreSQL

To develop a transactional BookFlow Library microservice using Spring Boot, Spring Data JPA and PostgreSQL for managing book inventory and borrowing orders, with FastAPI Gateway integration.

Database – bookflow creation in Postgresql

```
postgres=# CREATE DATABASE bookflow;
CREATE DATABASE
postgres=# \c bookflow
You are now connected to database "bookflow" as user "postgres".
bookflow=# \dt
Did not find any tables.
```

Tables Inserted

```
bookflow=# \dt
List of tables
Schema | Name      | Type  | Owner
-----+-----+-----+-----
public | inventory | table | postgres
public | orders    | table | postgres
(2 rows)
```

Initial Inventory Data in PostgreSQL

```
bookflow=# INSERT INTO inventory
bookflow-# (book_id, total_stock, available_stock)
bookflow-# VALUES
bookflow-# (101, 5, 5),
bookflow-# (102, 3, 3),
bookflow-# (103, 2, 0);
INSERT 0 3
bookflow=# SELECT * FROM inventory;
 book_id | available_stock | total_stock
-----+-----+-----
    101 |          5      |          5
    102 |          3      |          3
    103 |          0      |          2
(3 rows)
```

GET Inventory for Book 101

```
2026-10-01T12:02:30.250+05:30 INFO 23396 --- [demo] [nio-8080-exec-1] o.s.web.servlet.DispatcherServlet : Completed initialization in 1 ms
Hibernate:
    select
        i1_0.book_id,
        i1_0.available_stock,
        i1_0.total_stock
    from
        inventory i1_0
    where
        i1_0.book_id=?
```

localhost:8080/inventory/101

Pretty print ☒

```
{
  "bookId": 101,
  "totalStock": 5,
  "availableStock": 5
}
```

Successful Book Borrowing — POST /orders

POST http://localhost:8080/orders

Docs Params Authorization Headers 8 Body Scripts Settings

☐ none ☐ form-data ☐ x-www-form-urlencoded ☒ raw ☐ binary ☐ G

```
1 {
2   "userId": 501,
3   "bookId": 101
4 }
```

Body Cookies Headers 5 Test Results

{ } JSON Preview Visualize

```
1 {
2   "id": 1,
3   "userId": 501,
4   "bookId": 101,
5   "status": "BORROWED"
6 }
```

GET /inventory/101 — Inventory After Book Borrowing

```

Hibernate:
  select
    i1_0.book_id,
    i1_0.available_stock,
    i1_0.total_stock
  from
    inventory i1_0
  where
    i1_0.book_id=?

```

localhost:8080/inventory/101

Pretty print ☒

```

{
  "bookId": 101,
  "totalStock": 5,
  "availableStock": 4
}

```

PostgreSQL Database — Inventory and Order Records After Borrowing

```

bookflow=# SELECT * FROM inventory;
 book_id | available_stock | total_stock
-----+-----+-----
    101 |          5 |          5
    102 |          3 |          3
    103 |          0 |          2
(3 rows)

```

```

bookflow=# SELECT * FROM inventory;
 book_id | available_stock | total_stock
-----+-----+-----
    102 |          3 |          3
    103 |          0 |          2
    101 |          4 |          5
(3 rows)


```

```

bookflow=# SELECT * FROM orders;
 id | book_id | status  | user_id
-----+-----+-----+-----
   1 |    101 | BORROWED |    501
(1 row)


```

POST /orders — Out-of-Stock Book Returns 409 Conflict



FastAPI Gateway — /gateway/orders Successfully Forwards Request to Spring Boot

INFO: 127.0.0.1:64794 - "POST /gateway/orders HTTP/1.1" 200 OK



PostgreSQL — Final Inventory and Order Records

```
bookflow=# SELECT * FROM inventory;
```

book_id	available_stock	total_stock
102	3	3
103	0	2
101	3	5

(3 rows)

```
bookflow=# SELECT * FROM orders;
```

id	book_id	status	user_id
1	101	BORROWED	501
2	101	BORROWED	501

(2 rows)

Folder Structure: bookflow-transaction/

```

|
├── pom.xml
|
└── src/
    ├── main/
    │   ├── java/
    │   │   ├── com/
    │   │   │   ├── bookflow/
    │   │   │   │   ├── transaction/
    │   │   │   │   │   ├── BookflowTransactionApplication.java
    │   │   │   │   │   └──
    │   │   │   │   └── controller/
    │   │   │   │       ├── OrderController.java
    │   │   │   │       └── InventoryController.java
    │   │   │   └──
    │   │   └── entity/
    │   │       ├── Inventory.java
    │   │       └── Order.java
    │   └──
    └──

```

```

|      |
|      |└─ repository/
|      |  |└─ InventoryRepository.java
|      |  └─ OrderRepository.java
|      |
|      |└─ service/
|      |  |└─ InventoryService.java
|      |  └─ OrderService.java
|      |
|      |└─ dto/
|      |  └─ OrderRequest.java
|      |
|      └─ exception/
|          |└─ BookOutOfStockException.java
|          └─ GlobalExceptionHandler.java
|
└─ resources/
    └─ application.yml

```

Codes:

□ pom.xml

```

<?xml version="1.0" encoding="UTF-8"?> <project
xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">

    <modelVersion>4.0.0</modelVersion>

    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>3.5.5</version>
        <relativePath/>
    </parent>

    <groupId>com.bookflow</groupId>

```

```

<artifactId>bookflow-transaction</artifactId>
<version>0.0.1-SNAPSHOT</version>
<name>bookflow-transaction</name>
<description>BookFlow Transactional Microservice</description>
<properties>
    <java.version>17</java.version>
</properties>

<dependencies>

    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-web</artifactId>
    </dependency>

    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-data-jpa</artifactId>
    </dependency>

    <dependency>
        <groupId>org.postgresql</groupId>
        <artifactId>postgresql</artifactId>
        <scope>runtime</scope>
    </dependency>

    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-validation</artifactId>
    </dependency>

    <dependency>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-test</artifactId>
        <scope>test</scope>
    </dependency>

</dependencies>

<build>
    <plugins>
        <plugin>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-maven-plugin</artifactId>
            <configuration>
                <mainClass>com.bookflow.transaction.BookflowTransactionApplication</ma
inClass>
            </configuration>
        </plugin>
    </plugins>
</build>

```

```

        </plugins>
    </build>

</project>

```

□ application.yml

```

spring:
datasource:
    url: jdbc:postgresql://localhost:5432/bookflow
username: postgres      password: UR_PASSWORD
    jpa:
hibernate:
    ddl-auto: update
show-sql: true
properties:
hibernate:
    format_sql: true
server:
port: 8080

```

□ BookflowTransactionApplication.java

```

package com.bookflow.transaction;

import org.springframework.boot.SpringApplication; import
org.springframework.boot.autoconfigure.SpringBootApplication;
@SpringBootApplication public class
BookflowTransactionApplication {

    public static void main(String[] args) {
        SpringApplication.run(BookflowTransactionApplication.class, args);
    } }

```

□ Inventory.java

```

package com.bookflow.transaction.entity;
import jakarta.persistence.Entity; import
jakarta.persistence.Id; import
jakarta.persistence.Table; import
jakarta.validation.constraints.Min;

@Entity
@Table(name = "inventory") public
class Inventory {

```

```

        @Id        private
Long bookId;

        @Min(value = 0, message = "Total stock cannot be negative")
private Integer totalStock;

        @Min(value = 0, message = "Available stock cannot be negative")
private Integer availableStock;
        public Inventory()
{
        }
        public Inventory(Long bookId, Integer totalStock, Integer
availableStock)
{
        this.bookId = bookId;
this.totalStock = totalStock;
this.availableStock = availableStock;
        }
        public Long getBookId() {
return bookId;
        }
        public void setBookId(Long
bookId) {
        this.bookId = bookId;
        }
        public Integer
getTotalStock() {
        return
totalStock;
        }
        public void setTotalStock(Integer
totalStock) {
        this.totalStock = totalStock;
        }

        public Integer getAvailableStock() {
return availableStock;
        }
        public void setAvailableStock(Integer
availableStock) {
        this.availableStock =
availableStock;
        } }

```

□ Order.java

```

package com.bookflow.transaction.entity;
import jakarta.persistence.Entity; import
jakarta.persistence.GeneratedValue; import
jakarta.persistence.GenerationType; import
jakarta.persistence.Id; import
jakarta.persistence.Table;

```

```

@Entity
@Table(name = "orders") public
class Order {

```

```

        @Id

```

```

    @GeneratedValue(strategy = GenerationType.IDENTITY)
    private Long id;
    private Long userId;
    private Long bookId;
    private String status;

    public Order() {
    }
    public Order(Long userId, Long bookId, String status) {
    this.userId = userId;        this.bookId = bookId;
    this.status = status;
    }
    public Long getId() {
    return id;
    }    public void setId(Long
id) {        this.id = id;
    }

    public Long getUserId()
    {
        return userId;
    }

    public void setUserId(Long userId) {
    this.userId = userId;
    }    public Long
getBookId() {        return
bookId;
    }    public void setBookId(Long
bookId) {        this.bookId = bookId;
    }    public String
getStatus() {        return
status;
    }    public void setStatus(String
status) {        this.status = status;
    } }

```

□ InventoryRepository.java

```

package com.bookflow.transaction.repository;

import com.bookflow.transaction.entity.Inventory;
import org.springframework.data.jpa.repository.JpaRepository;
    public interface InventoryRepository extends JpaRepository<Inventory, Long>
    { }

```

□ OrderRepository.java

```

package com.bookflow.transaction.repository;

import com.bookflow.transaction.entity.Order; import
org.springframework.data.jpa.repository.JpaRepository;
public interface OrderRepository extends JpaRepository<Order, Long>
{
}

```

□ OrderRequest.java

```

package com.bookflow.transaction.dto;
import
jakarta.validation.constraints.NotNull;
public class OrderRequest
{

    @NotNull
    private Long userId;

    @NotNull
    private Long bookId;
    public Long getUserId()
{
    return userId;
}
    public void setUserId(Long
userId) {
    this.userId = userId;
}
    public Long
getBookId() {
    return
bookId;
}
    public void setBookId(Long
bookId) {
    this.bookId = bookId;
} }

```

□ InventoryService.java

```

package com.bookflow.transaction.service;

import com.bookflow.transaction.entity.Inventory; import
com.bookflow.transaction.repository.InventoryRepository; import
org.springframework.stereotype.Service;
@Service public class
InventoryService {

    private final InventoryRepository inventoryRepository;
    public InventoryService(InventoryRepository inventoryRepository)
{
    this.inventoryRepository = inventoryRepository;
}
}

```

```

        public Inventory getInventory(Long bookId) {
        return inventoryRepository.findById(bookId)
            .orElseThrow(() -> new RuntimeException("Book not found"));
        }
    }
}

```

□ OrderService.java

```

package com.bookflow.transaction.service;
import com.bookflow.transaction.dto.OrderRequest; import
com.bookflow.transaction.entity.Inventory; import
com.bookflow.transaction.entity.Order; import
com.bookflow.transaction.exception.BookOutOfStockException;
import com.bookflow.transaction.repository.InventoryRepository;
import com.bookflow.transaction.repository.OrderRepository;
import org.springframework.stereotype.Service; import
org.springframework.transaction.annotation.Transactional;
@Service public class
OrderService {
    private final InventoryRepository
inventoryRepository;    private final OrderRepository
orderRepository;

    public OrderService(
        InventoryRepository inventoryRepository,
        OrderRepository orderRepository) {        this.inventoryRepository
= inventoryRepository;        this.orderRepository =
orderRepository;
    }

    @Transactional
    public Order borrowBook(OrderRequest request) {

        Inventory inventory =
inventoryRepository.findById(request.getBookId())
            .orElseThrow(() -> new RuntimeException("Book not found"));
        if (inventory.getAvailableStock() <= 0)
        {
            throw new BookOutOfStockException(
                "Book " + request.getBookId() + " is out of stock");
        }
        inventory.setAvailableStock(
inventory.getAvailableStock() - 1);

        inventoryRepository.save(inventory);
        Order order = new Order(
            request.getUserId(),
            request.getBookId(),
            "BORROWED");
    }
}

```

```

        return
orderRepository.save(order);
    } }

```

□ InventoryController.java

```

package com.bookflow.transaction.controller;
import com.bookflow.transaction.entity.Inventory; import
com.bookflow.transaction.service.InventoryService; import
org.springframework.web.bind.annotation.*;

@RestController
@RequestMapping("/inventory") public
class InventoryController {
    private final InventoryService
inventoryService;
    public InventoryController(InventoryService inventoryService)
{
        this.inventoryService = inventoryService;
    }

    @GetMapping("/{bookId}")    public Inventory
getInventory(@PathVariable Long bookId) {        return
inventoryService.getInventory(bookId);
    } }

```

□ OrderController.java

```

package com.bookflow.transaction.controller;

import com.bookflow.transaction.dto.OrderRequest;
import com.bookflow.transaction.entity.Order; import
com.bookflow.transaction.service.OrderService; import
jakarta.validation.Valid; import
org.springframework.http.HttpStatus; import
org.springframework.web.bind.annotation.*;

@RestController
@RequestMapping("/orders") public
class OrderController {
    private final OrderService
orderService;

    public OrderController(OrderService orderService) {
        this.orderService = orderService;
    }

    @PostMapping

```

```

        @ResponseStatus(HttpStatus.CREATED)    public Order
borrowBook(@Valid @RequestBody OrderRequest request) {    return
orderService.borrowBook(request);
    } }

```

- BookOutOfStockException.java

```

package com.bookflow.transaction.exception;
public class BookOutOfStockException extends RuntimeException
{
    public BookOutOfStockException(String message)
{
        super(message);
    } }

```

- GlobalExceptionHandler.java

```

package com.bookflow.transaction.exception;
import org.springframework.http.HttpStatus;
import org.springframework.web.bind.annotation.*;

import java.util.Map;
@RestControllerAdvice public class
GlobalExceptionHandler {

    @ExceptionHandler(BookOutOfStockException.class)
    @ResponseStatus(HttpStatus.CONFLICT)
    public Map<String, Object> handleOutOfStock(
        BookOutOfStockException ex) {
        return
Map.of(
            "status", 409,
            "error", "OUT_OF_STOCK",
            "message", ex.getMessage()
        );
    }
}

```

□ gateway.py — FastAPI gateway

```

from fastapi import FastAPI
import httpx  app =
FastAPI()

SPRING_SERVICE = "http://localhost:8080"

@app.post("/gateway/orders") async def
create_order(order: dict):    async with
httpx.AsyncClient() as client:
response = await client.post(

```

```
f"{SPRING_SERVICE}/orders",  
json=order      )      return  
response.json()
```