Is Graph Bipartite

Saturday, 10 July 2021 9:54 AM

If we can make two set of vertices so that no edge is present within the same set. then graph is called Bipartite Graph.

graph ①





graph ②



Set A Set B



↳ Not a Bipartite graph.

graph ③



This graph is Bipartite

Set A Set B.



Hint → Acyclic graph is always Bipartite graph.



Acyclic graph - always Bipartite.

☆ cyclic → Bipartite → True / False.

- Acyclic → Bipartite
- cyclic → even length → Bipartite
- cyclic → odd length → Not a Bipartite graph









BFS Pair → src, discovery time / level



loop of all the vertex



get
remove
mark
add
Neighbour.



False

return False.

odd length cycle

visited

continue

array of Integer

-1

Discovery level





Spread of Injection

Saturday, 10 July 2021 9:55 AM

7
8
0 1 10
1 2 10
2 3 10
0 3 10
3 4 10
4 5 10
5 6 10
4 6 10

6 → Infected
3 Covid

time



No. of people = 4

rate of infection spreading.



Rotting Oranges

Saturday, 10 July 2021 11:59 AM



at t=0

rotted oranges = 2

fresh oranges = 1

Empty cell = 0



n



Steps:

(1) Count of total fresh orange.

(2) BFS, marking - rotted;
↳ count − −;

BFS with all rotted oranges.

(3) level (maximise.)

(4) out of while loop ⇒ if count = 0] return level;
↳ return (−1);

2 → rotted orange

1 → fresh orange

0 → Empty cell

	0	1	2	3	4	5
0	2	1	1	1	0	1
1	1	1	1	0	0	1
2	1	0	1	1	1	1
3	1	1	1	1	1	0
4	1	1	1	2	1	0
5	2	1	1	1	1	1
6	1	1	1	0	0	0
7	1	1	1	1	0	2



(1) Iterate on data, find cord of fresh oranges and add element in queue which are rotten.



fresh orange = 34 + 4

= 38

(1) get front cell

(2) mark - discover time

(3) make freshorange --

(4) add neighbours

37
36
35
34 33 32 31 ⟶

count → 0] all the oranges are rotted

count → ≥0] → fresh oranges is cover with Empty cell

Fire in the City →



0 → water

1 → wooden House

2 → Fired Catched in house

Time Required to completely burn the city. if not possible then return -1 (rotten oranges)

time of burning of every house:-

t+0. burn at time = t =)

Shortest Path in Weights (Dijkstra's Algorithms)

Saturday, 10 July 2021 9:55 AM

B.F.S.

① get tremove

② mark

③ work

④ Add neighbours.

Shortest path in terms of Edge

BFS

P.S → ~~Queue~~ Priority Queue (Min)

src, psf, wsf

src = 0

0, 0, 0

1, 01, 10

3, 03, 40 continue

2, 012, 20

3, 0123, 30

4, 01234, 32

5, 012345, 35

6, 0123456, 40 continue

6, 0123456, 38

Shortest path in terms of weight

↓

Dijkstra's



0 via 0 @ 0

1 via 01 @ 10

2 via 012 @ 20

3 via 0123 @ 30

4 via 01234 @ 32

5 via 012345 @ 35

6 via 0123456 @ 38

Minimum Wired Required to connect all PCs

Saturday, 10 July 2021 9:55 AM

graph → connected, → resultant graph is acyclic

n vertices → (n-1) Edges in final result

Prims Algorithm

Help to find

Minimum Spanning Tree

S1	S2	wire required
0	1	10
1	2	50
0	3	30
3	2	5
3	4	2
4	6	3
6	5	3
4	5	8



connect all the server in min. wire.



Minimum → Min.

Spanning → possibility

Tree → connected and Acyclic



Graph is Tree

connected & Acyclic] → tree



connected & Acyclic



Spanning tree



Min = 49







Spanning Tree

4x8=12









graph → connected

src, Parent, wt

get + remove

mark

work - addEdge

Add neighbors

P.S → Priority Queue.

wt







How prims Algorithms (MST. minimum spanning tree) is different from Dijkstras Algo.

→ Dijkstra find min path (in terms of weight) from a single source to single dest

→ Prims find min path sum to connect all all the vertex.



Dijkstra → 0 - 1 → 40

Prims - → 0 - 2 - 3 - 4 - 1

0 - 1 ✗

Iterative DFS

Saturday, 10 July 2021 2:24 PM

Home work

D.F.S

1. Try to solve by state Method, which is already done in tree.

Reverse order D.F.S

2. Try using BFS algorithm, just replace Queue from Stack.

- order of computation
- Evaluate Division