FIG. 7 Shadow Outcome Scoring & Bounded Context Projections

(a) Zeus Judge: 8-Gate Shadow Abstention (src/judge.rs)

1. Artifact Load	≤64 KiB, O_NOFOLLOW, regular	InvalidModel
2. Schema & Weights	job_limits_v1, |w| ≤ 100	InvalidModel
3. Domain Binding	SHA-256(ctx,model,proto,ver)	DomainMismatch
4. Verifier Presence	External verifier configured	NoVerifier
5. Support Box	8-D features x_i ∈ [min, max]	OutsideSupport
6. Sample Floor	Both heads samples ≥ 30	InsufficientSamples
7. Output Range	log1p_tok, log1p_sec ∈ [0, 30]	InvalidPrediction
8. Margin Gate	|p_direct − p_parallel| ≥ 0.05	Ambiguous

OUTPUT: Decision::Rank { preferred } (probability_status = "uncalibrated")
Persists shadow-decision.json & shadow-outcome.json; never alters UCB1 routing.

(b) Deterministic Memory & Handoff Bounds

1. TRANSCRIPT COMPACTION (src/agent.rs)

Triggered past compaction_threshold_bytes (default 1 MiB) or overflow:



Replaces summarization LLMs: model can re-read any elided file; audit event emitted.

2. WORKER HANDOFF PROJECTION (src/output.rs)

Full worker outputs always persist to events.jsonl; integrator sees ≤ 8192 B/worker:



JSON PROJECTED PAYLOAD:
{index, audit_event, tool_calls, original_bytes, omitted_bytes, text}
Caps 12-worker aggregation at ~96 KiB instead of blowing 4 MiB context limits.

Source: src/judge.rs (Shadow Judge), src/agent.rs (PROTECT_LAST_TOOL_RESULTS=4), src/output.rs (worker_handoff).