

Office Interior: Fitout Specifications

Please note – All fitouts will be Combination of First & Second Generation

PRESENTATION OVERVIEW

Cabin Furniture

Meeting Room Tables

All Chair Types

Walls and Partitions

Ceilings and Lighting

Carpets and Flooring

Frosting and Blinds

Other

WORKSTATIONS

LINEAR / L-SHAPED WORKSTATIONS

- Tabletop: 25mm Pre-Laminated particle board confirming to E1
 Grade finished with 2mm PVC edge binding Color White or
 Off-white
- Vertical raceway system with Grommet hole
 Laminate Leg Finish: White MS powder coated
- Power Socket: 2 UPS sockets, 1data,1 voice
- Workstation sizes: 4'x2'(Standard)
- Under structure Supported on MS Powder Coated Frame.







CABIN

(1+2 SEATER)

- Main Table : 5' L X 2.5' D X 2'6" HT (1500L X 700D
 X750HT)
- Side Storage With Pneumatic Ha Top: 3'6" L X 1'6" D X
 2'6" HT (1050L X 450D X 750HT)
- Table-Top 25mm PLB Table Top with 2mm pvc edge banding on all exposed edges and Aluminum Flip Up Box with soft closure and provision to mount Color White or Off-white
- Switches and sockets considered or power and data management.
- Under structure Supported on MS Powder Coated
 Frame
- Storages are made of 25mm thick openable shutters,
 Recessed handle and lock considered. Finish Top: White
 to Off White



MEETING

4-PAX MEETINGS

- Main Table: 3' D X 2'6" HT (900D X750HT) 25mm PLB
 Table-Top with 2mm PVC edge banding on all exposed edges and
- Aluminum Flip Up Box with 1 data, 1 voice, and 2 international switch socket
- Under structure Supported on MS Powder Coated
 Frame
- Finish: White or Off-White






MEETING

6 PAX MEETING ROOMS

- Main Table: 7' L X 3'6" D X 2'6" HT (2100L X 1050D X 750HT) -25mm PLB Table-Top with 2mm PVC edge banding on all exposed edges and 2 Nos Aluminum Flip Up Box with 1 data, and 3 switch socket
- Under structure Supported on MS Powder
 Coated Frame
- Finish: White or Off White






CHAIRS

- Frame in Moulded Nylon PP with Mesh
 Ergonomic Mesh Seat
- Mesh Back with Adjustable Arms and PP Pad with Aluminum & Nylon Base
- Synchronized Mechanism & Gas Lift. 3D
 Armrest

Conference Room & Cabin Chair



Workstation & Visitor Chair



07

PEDESTALS

- Size 1'4" W x 1'6" D x 2'1.6" HT (400W x 450D x 640HT)
- Pedestal Particle Board Mobile Pedestal With regular cylindrical lock & key recessed handles.
- Finish: Grey & White Particle Board




PARTITIONS

- Providing and fixing modular full height glass
 45X25 Section partition system with Silver or
 black frames, including glass to glass
- I, T, L joint and gasket with 10mm clear toughened glass.
- 45mm x 25mm profile
- Wooden door of 30-35 mm on Aluminum Frame in grey/Black powder coated section







WOODEN DOORS

• VARIOUS TYPES AS SHOWN





GYPSUM PARTITIONS

 Providing & fixing both side Gypsum partition having framework made in size of 50 x 50, 16-gauge GI frames at approx. 400 to 600 centers both ways with slab and floor members 50 x 25 inclusive of additional members for skirting, switch boxes, white marker boards, doors, windows also include glass wools inside partitions wools, making opening and cutting for switches points, doors etc.





CEILING

OPEN







GRID CEILING

In Cabins

- Providing & fixing in position false ceiling in Grid 600 x 600 mm x 15/16 mm with suspenders wherever required. Making necessary framework for A.C. ducting, grill cutouts for diffusers/grill and light fittings, fire sprinklers and smoke detectors, as per approved specifications by architect (Channels with blackline grooves).
- Acoustic Performance 0.5NRC
- Make Techno Acoustic





LIGHTS

- Panel Light Size 2'-0" L X 2'-0"
- Open Ceiling lights will be 4 ft / 8 ft x
 100 mm wide linear lights.
- Wattage: 36W
- Mouting type: Recessed
- Colour Temperature: 6000K
- CRI:70- 100
- Diffuser type: Sheet Diffuser Ballast:
 High frequency Electronic ballast
- Illuminance: Direct type Luminous
 Efficacy: 30 Havells Fixture body
 material: Aluminum
- extrusionand CRCA, Black Powder coated



FLOORING

CARPET


 Semi-Nylon tiled carpet flooring of approved make and of approved shade as per manufacture specification including the supply and installation for the same

• Gauge: 1/12"

• Backing: PVC with Reinforced Fiberglass

• Thickness: approx. 6.5mm

• Tile Size: 500mmX500mm



BLINDS

- Top Tube: Made of extruded aluminum 38mm dia. with wall thickness of 1.2mm with spline adoptable to accommodate clutch as manufacturer's approved make.
- Shade Orientation: Regular roll, shade cloth falls at window side of roller.
- Configuration: Single band Fabric shade: White
- Fabric Composition: 30% Polyester, 70% Vinyl on Polyester
- Openness factor/ Light transmission: 3% Thickness: ISO
 2286: 0.55- 0.65 mm ± 5%
- Shade will be as per landlord fit-out guidelines



THANK YOU

REDBRICK OFFICES LIMITED

PHONE NUMBER

1800 120 9088

EMAIL ADDRESS

hello@redbrickoffices.com