SIMATS ENGINEERING

# SIMATS Online Programming Lab

## C PROGRAMMING

B.Vikranth naik
192413027C

**QUESTIONS** 8 / 8 completed

Swap 2 No's

## SWAP 2 NO'S

C Program to Swap Two Numbers.
Swapping two numbers in C programming means swapping the values of two variables.
For example, there are two variables m & n. Value of m is “2” & value of n is “3”.
Before Swapping: m value = 2; n value = 3
After Swapping: m value = 3; n value = 2

Problem Description
Write a C program that swaps the values of two variables based on user input.

**Testcases:**
6,6
a,b
-5,-6

**PROGRAM EDITOR**

C | Run | Save

```c
#include <stdio.h>

int main() {
    int m, n, temp;

    printf("Enter the value of m: ");
    scanf("%d", &m);
    printf("Enter the value of n: ");
    scanf("%d", &n);

    printf("Before Swapping: m value = %d; n value = %d\n", m, n);

    temp = m;
    m = n;
    n = temp;

    printf("After Swapping: m value = %d; n value = %d\n", m, n);

    return 0;
}
```

**OUTPUT**

```
Enter the value of m: Enter the value of n: Before Swapping:
m value = 7; n value = 9
After Swapping: m value = 9; n value = 7
```

**INPUT**

```
7 9
```

© 2026 **SIMATS Online Lab**. All rights reserved.