

ACTIONS	
sa	add — takes a textobject , then a target: <code>saiw</code>)
sa	in visual mode: surrounds the selection
sd	delete surrounding
sr	replace surrounding (old target, then new)
sf	find right edge
sF	find left edge
sh	highlight surrounding briefly
.	everything dot-repeats

TARGETS	
) [} >	the bracket, tight
([{ <	the bracket, padded with spaces
b	any bracket: ([{
q	any quote: ' " `
t	tag — prompts for the name on replace/add
f	function call — prompts for the name
?	prompt for left + right yourself
other	the character itself: _ *

EXAMPLES	
saiw)	word → (word)
saiw(	word → (word)
sa\$"	to end of line, in double quotes
sdq	"word" → word
sr'"	'word' → "word"
sr)tdiv<	(x) → x
sdf	fn(x) → x
srfllog<	fn(x) → log(x)
saiw?***<	word → **word**
sdt	drop the surrounding tag

WHICH ONE, WHEN THERE ARE SEVERAL	
2sd)	count: the 2nd surrounding outwards
sdn)	next — the one after the cursor
sdL)	last — the one before the cursor
2sfnt	combine: 2nd next tag, find its right edge
srLn)	prefix order is action, count, n/l, target

GOTCHAS	
20	n_lines: search gives up beyond 20 lines
V sa	linewise selection puts surroundings on own lines
sa	normal mode needs a textobject; visual does not
f	matches <code>name(...)</code> , incl. dots: <code>a.b(x)</code>
t	self-nested <code><a><a></code> won't match

ALSO MINE	
<leader>c	GitPermalink — link to the line on GitLab
<leader>	space