

HELMET: HOW TO EVALUATE LONG-CONTEXT LANGUAGE MODELS EFFECTIVELY AND THOROUGHLY

Howard Yen^P Tianyu Gao^P Minmin Houⁱ Ke Dingⁱ
 Daniel Fleischerⁱ Peter Izsakⁱ Moshe Wasserblatⁱ Danqi Chen^P
^PPrinceton Language and Intelligence, Princeton University ⁱIntel
 {hyen, tianyu, danqi}@cs.princeton.edu
<https://princeton-nlp.github.io/HELMET>

ABSTRACT

Many benchmarks exist for evaluating long-context language models (LCLMs), yet developers often rely on synthetic tasks such as needle-in-a-haystack (NIAH) or an arbitrary subset of tasks. However, it remains unclear whether these benchmarks reflect the diverse downstream applications of LCLMs, and such inconsistencies further complicate model comparison. We investigate the underlying reasons behind these practices and find that existing benchmarks often provide noisy signals due to limited coverage of applications, insufficient context lengths, unreliable metrics, and incompatibility with base models. In this work, we introduce **HELMET** (How to Evaluate Long-context Models Effectively and Thoroughly), a comprehensive benchmark encompassing seven diverse, application-centric categories. We also address several issues in previous benchmarks by adding controllable lengths up to 128K tokens, model-based evaluation for reliable metrics, and few-shot prompting for robustly evaluating base models. Consequently, we demonstrate that HELMET offers more reliable and consistent rankings of frontier LCLMs. Through a comprehensive study of 59 LCLMs, we find that (1) synthetic tasks like NIAH do not reliably predict downstream performance; (2) the diverse categories in HELMET exhibit distinct trends and low correlations with each other; and (3) while most LCLMs achieve perfect NIAH scores, open-source models significantly lag behind closed ones when tasks require full-context reasoning or following complex instructions—the gap widens as length increases. Finally, we recommend using our RAG tasks for fast model development, as they are easy to run and better predict other downstream performance; ultimately, we advocate for a holistic evaluation across diverse tasks.¹

1 INTRODUCTION

Long-context language models (LCLMs) unlock a myriad of applications, from summarizing long documents to learning new tasks on the fly with thousands of examples. Many recent benchmarks have sought to evaluate language models’ long-context abilities (Zhang et al., 2024b; An et al., 2024; Shaham et al., 2023; Bai et al., 2024, *inter alia*). However, recent developments in long-context processing (Chen et al., 2023; Xiong et al., 2023; Peng et al., 2024; Fu et al., 2024) still rely either on perplexity or on synthetic needle-in-a-haystack tasks (NIAH; Kamradt, 2024; Hsieh et al., 2024). Frontier LCLMs (Dubey et al., 2024; Team et al., 2024c; OpenAI, 2023; Team

Table 1: Most LCLMs evaluate on synthetic (Syn.) tasks. ^b: base models. ∞ : ∞ BENCH.

Model	Syn. PPL	∞		ZEROSCROLLS						RAG ICL	
		QA	All	NQA	QS	QL	SQ	All			
Gemini-1.5	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✓
GPT-4	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Claude-3.5	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Llama-3.1	✓	✗	✓	✗	✗	✓	✓	✓	✗	✗	✗
Phi-3	✓	✗	✗	✗	✗	✓	✗	✓	✗	✗	✗
Jamba-1.5	✓	✗	✓	✗	✗	✗	✗	✗	✗	✗	✗
Qwen2	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗	✗
Command R	✓	✗	✗	✗	✗	✗	✗	✗	✗	✓	✗
Xiong et al.	✗	✗	✗	✗	✓	✓	✓	✓	✓	✗	✗
Chen et al. ^b	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗
Peng et al. ^b	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗	✗
Fu et al. ^b	✓	✓	✓	✗	✗	✗	✗	✗	✗	✗	✗

¹Our data and code are available at <https://github.com/princeton-nlp/HELMET>.




Figure 1: Long-context benchmark results of frontier LCLMs (Llama-3.1 8B/70B, GPT-4o-mini, GPT-4o-08-06, and Gemini-1.5 Flash/Pro) at 128K input length. NIAH is saturated for almost all models; RULER (Hsieh et al., 2024) and ∞ BENCH (Zhang et al., 2024b) show unexpected trends for Llama-3.1 (Dubey et al., 2024). In contrast, HELMET demonstrates more consistent rankings of these frontier models.

et al., 2024a) also mostly report NIAH, sometimes with arbitrary subsets of other datasets, as shown in Table 1. Such inconsistencies complicate comparisons between different models. It is also unclear whether synthetic NIAH tasks or the few chosen datasets offer a holistic picture of models’ long-context abilities and their performance in real-world applications.

Why don’t model developers agree on these evaluations? We take a closer look and find that existing benchmarks suffer from many critical design flaws, including:

- **Insufficient coverage of downstream tasks:** Existing benchmarks either focus on synthetic tasks (Hsieh et al., 2024) or include only simple question answering (Zhang et al., 2024b). Other works study particular aspects of LCLMs, such as summarization (Chang et al., 2024), in-context learning (Li et al., 2024c), and retrieval-augmented generation (RAG; Lee et al., 2024), but they do not provide a holistic evaluation of LCLMs.
- **Inadequate lengths:** Most natural language datasets in existing benchmarks (Shaham et al., 2023; An et al., 2024; Table 4) are too short to effectively test frontier long-context abilities (usually $\geq 128K$).
- **Unreliable metrics:** For commonly used long-document QA and summarization tasks, most existing benchmarks still rely on metrics like ROUGE (Lin, 2004), which are often noisy and unreliable (Goyal et al., 2023; Deutsch et al., 2022; Chang et al., 2024).
- **Incompatibility with base models:** Many LCLM developments focus on base models without instruction tuning, but most existing benchmarks require models to be instruction-tuned—hence developers can only rely on synthetic tasks or perplexity.

Consequently, existing benchmarks are either not applicable to long-context works (inadequate lengths or incompatibility) or provide highly noisy signals (insufficient coverage or unreliable metrics). We summarize the shortcomings of existing benchmarks in Table 2. For the three benchmarks that support a 128K² context length (NIAH, RULER, and ∞ BENCH), we use them to evaluate six frontier models and report the numbers in Figure 1. We see that NIAH does not reflect differences across models; RULER and ∞ BENCH show unexpected trends—on RULER, Gemini Flash outperforms Gemini Pro; on ∞ BENCH, the 70B Llama model underperforms compared to the 8B one. This raises concerns about the reliability of the benchmarks and how they can differentiate long-context models, which likely contributes to the lack of use of these benchmarks in model development.

To address these challenges, we present **HELMET** (How to Evaluate Long-context Models Effectively and Thoroughly). We curate a *diverse* set of application-centric long-context tasks across seven categories. Beyond widely adopted categories like *synthetic recall*, *long-document question answering* (QA), and *summarization*, we also add *many-shot in-context learning* (ICL), *retrieval-augmented generation* (RAG), *passage re-ranking*, and *generation with citations* (Gao et al., 2023). We further address the shortcomings of existing benchmarks: (1) we ensure all datasets support input lengths of 128K tokens and are easily extendable to longer contexts (§2.1); (2) we introduce reference-based model evaluation for QA and summarization and show that it significantly improves over n-gram overlap metrics (§2.2); (3) we refine the prompts and in-context demonstrations used for all tasks, reducing evaluation noise caused by different output formats and allowing base models to

²Throughout the paper, we use binary prefixes K= 2^{10} .

Table 2: Comparison of long-context benchmarks: ZeroSCROLLS (Shaham et al., 2023), LongBench (Bai et al., 2024), L-Eval (An et al., 2024), RULER (Hsieh et al., 2024), ∞ BENCH (Zhang et al., 2024b), and our HELMET. L : input tokens. † : All datasets have $L < 128K$ except one dataset. ‡ : L-Eval uses LLMs to compute reference-free, pairwise win-rates; we design reference-based model evaluation for specific tasks.

	Type of tasks							Benchmark features		
	Cite	RAG	Re-rank	Long-QA	Summ	ICL	Synthetic Recall	Robust Eval.	$L \geq 128k$	Controllable L
ZeroSCROLLS	\times	\times	\times	\checkmark	\checkmark	\times	\times	\times	\times^\dagger	\times
LongBench	\times	\checkmark	\times	\checkmark	\checkmark	\checkmark	\checkmark	\times	\times^\dagger	\times
L-Eval	\times	\checkmark	\times	\checkmark	\checkmark	\times	\times	\checkmark^\ddagger	\times^\dagger	\times
RULER	\times	\times	\times	\times	\times	\times	\checkmark	\checkmark	\checkmark	\checkmark
∞ BENCH	\times	\times	\times	\checkmark	\checkmark	\times	\checkmark	\times	\checkmark	\checkmark
HELMET (Ours)	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark

be evaluated robustly across most categories (§2.3). Together, HELMET enables a holistic evaluation of long-context capabilities and provides more reliable signals for model development. Figure 1 demonstrates that HELMET can clearly differentiate models with varying capabilities and reflect comparisons consistent with human perception. More discussion on HELMET’s improvements over previous benchmarks and direct comparisons can be found in §A.

To understand the progress of LCLMs and how different long-context capabilities correlate with one another, we evaluate a comprehensive list of 59 LCLMs of various architectures, scales, and training approaches. Our analysis reveals that (1) synthetic tasks poorly indicate ownstream performance (§3.1), (2) different categories in HELMET show distinct trends (§3.2), and (3) open-source models significantly lag behind closed ones on tasks that require reasoning over long contexts or following complex instructions—the gap further widens as context length increases (§3.3). Finally, we find that the RAG category strikes a good balance between ease of use, stronger correlation with downstream tasks, and compatibility with base models. Ultimately, it is imperative to evaluate LCLMs across a diverse spectrum of categories. We hope that our insights provide a more effective way to evaluate LCLMs for future model development and benchmarking.

2 OUR BENCHMARK: HELMET

In this work, we seek to overcome the shortcomings of existing benchmarks by meeting the following desiderata: (1) diverse coverage across different tasks and capabilities of LCLMs, (2) controllable context lengths that support more than 128K input tokens, and (3) reliable evaluation for both base and instruction-tuned models. In this section, we describe the datasets used in HELMET and how they improve upon existing evaluation benchmarks in terms of settings and metrics. An overview of HELMET is shown in Table 3.

2.1 REALISTIC AND DIVERSE LONG-CONTEXT APPLICATIONS

Retrieval-augmented generation (RAG). We use open-domain question answering (ODQA)—which requires retrieving from a knowledge corpus and then generating correct answers (Chen et al., 2017)—as a representation of retrieval-augmented generation (RAG) applications. We utilize Natural Questions (NQ; Kwiatkowski et al., 2019), TriviaQA (TQA; Joshi et al., 2017), HotpotQA (Yang et al., 2018), and PopQA (Mallen et al., 2023). We use the gold passage (the passage with the answer) from Petroni et al. (2021), or otherwise select any passage that contains the answer.

Given an input length L , we first determine the number of passages k that can fit within L tokens, then retrieve k passages³ from the corpus⁴ that *do not contain the answer* as *distractors*. This differs from previous works that *randomly sample passages* from the corpus (Lee et al., 2024) and is more

³We use [Alibaba-NLP/gte-large-en-v1.5](#) for retrieval (Zhang et al., 2024a).

⁴We use Wikipedia 2019-8-01 dump, split into 100-word passages (Petroni et al., 2021).

Table 3: Overview of evaluation datasets. We select datasets that cover various important long-context capabilities. SubEM: substring exact match.

Category	Dataset	Metrics	Description
Retrieval-augmented generation	Natural Questions	SubEM	Factoid question answering
	TriviaQA	SubEM	Trivia question answering
	PopQA	SubEM	Long-tail entity question answering
	HotpotQA	SubEM	Multi-hop question answering
Generation with citations	ALCE ASQA	Recall, Cite	Answer ambiguous questions with citations
	ALCE Qampari	Recall, Cite	Answer factoid questions with citations
Passage re-ranking	MS MARCO	NDCG@10	Rerank passage for a query
Many-shot in-context learning	TREC Coarse	Accuracy	Question type classification, 6 labels
	TREC Fine	Accuracy	Question type classification, 50 labels
	NLU	Accuracy	Task intent classification, 68 labels
	BANKING77	Accuracy	Banking intent classification, 77 labels
	CLINC150	Accuracy	Intent classification, 151 labels
Long-document QA	NarrativeQA	Model-based	Book and movie script QA
	∞ BENCH QA	ROUGE F1	Novel QA with entity replacement
	∞ BENCH MC	Accuracy	Novel multiple-choice QA with entity replacement
Summarization	∞ BENCH Sum	Model-based	Novel summarization with entity replacement
	Multi-LexSum	Model-based	Summarizing multiple legal documents
Synthetic recall	JSON KV	SubEM	Retrieve a key in JSON dictionary
	RULER MK Needle	SubEM	Retrieve the needle (a number) within noisy needles
	RULER MK UUID	SubEM	Retrieve the needle (a UUID) within noisy needles
	RULER MV	SubEM	Retrieve multiple values for one needle (key)

realistic and challenging. For NQ, TQA, and PopQA, we take the top $k - 1$ distractors and insert the gold passage at six evenly distributed positions following Liu et al. (2023). For HotpotQA, which requires two gold passages, we combine them and the top $k - 2$ distractors and randomly shuffle them into three permutations. We use substring exact match (SubEM; whether the answer is included in the output), following previous work (Asai et al., 2024a). See §B.1 for more details.

Generation with citations (Cite). We leverage ALCE (Gao et al., 2023) to evaluate LCLMs on a realistic application of answering questions while providing correct attributions (Bohnet et al., 2022). Given multi-faceted questions and relevant passages, models are required to generate a long-text answer and cite supporting passage IDs at the end of each sentence. This tests models’ ability to utilize the passages in the context and also to follow the instructions about citation formats. We use the ASQA (Stelmakh et al., 2022) and QAMPARI (Rubin et al., 2022) subsets from ALCE. For an input length L , we first determine the number of passages k , and use the top k retrieved passages from Wikipedia as contexts. The model’s outputs are evaluated on correctness and citation quality, and we report the average across all metrics. See §B.2 for more details.

Passage re-ranking (Re-rank). Re-ranking retrieved passages based on their relevance to the query is an important application of LCLMs (Sun et al., 2023). The task requires the model to retrieve relevant information, compare, and reason over different parts of the contexts. We use the MS MARCO dataset (Bajaj et al., 2018), where each instance contains a query and passages retrieved by BM25 (Robertson & Zaragoza, 2009) from the Internet. Each passage has annotations of a relevance label—perfect, highly relevant, or not relevant. We determine the number of passages k from the input length L , and randomly sample k passages with balanced labels for each test query. The model is prompted with the query and the shuffled k passages and is instructed to output the top-10 document IDs ranked by relevance. We report NDCG@10. Details are in §B.3.

Many-shot in-context learning (ICL). In-context learning (ICL) is a key ability that enables LLMs to adapt to new tasks on the fly (Brown et al., 2020). Recent studies (Ratner et al., 2023; Xu et al., 2024; Li et al., 2024c; Bertsch et al., 2024) explore performing many-shot ICL (with thousands of examples) with LCLMs. Following Bertsch et al. (2024), we focus on datasets with large label spaces: TREC-coarse, TREC-fine (Li & Roth, 2002), BANKING77 (Casaneve et al., 2020), CLINC150 (Larson et al., 2019), and NLU (Liu et al., 2019). We adjust the number of shots to control the input length L , and the number of examples in each class is balanced. We report accuracy on the test set.

One *difference* from previous works is that we map original natural language labels (e.g., *location*) into numbered labels (i.e., *0*, *1*) to test how well a model can learn new tasks instead of relying on its pre-trained priors (Wei et al., 2023; Pan et al., 2023; Min et al., 2022). More details are in §B.4.

Long-document question answering (LongQA). We use NarrativeQA (Kočíský et al., 2018) and the English book QA and multiple choice (MC) subsets from ∞ BENCH (Zhang et al., 2024b) for evaluating long-document QA. We select those tasks for their abundant context lengths (Table 4). We truncate the document from the end based on L . We use ROUGE F1 for ∞ BENCH QA (answers are mostly entity names) and accuracy for ∞ BENCH MC. For NarrativeQA, where the answers can be long text and open-ended, we design and use a model-based evaluation (§2.2).

Summarization (Summ). Summarization tests LCLMs’ ability to synthesize information across the contexts. We choose Multi-LexSum (legal document summarization) and the English summarization task from ∞ BENCH (novel summarization) for their extensive lengths (Table 4). We truncate the document from the end based on the evaluation length L . We use our model-based evaluation (§2.2) for both datasets instead of the commonly used ROUGE, as it better reflects human judgment.

Synthetic recall. Synthetic recall tasks, such as needle-in-a-haystack (NIAH), stress test models’ ability to recall relevant information (the “needle”) from long contexts. They have gained popularity for being easy to use (as they can test any arbitrary length) and easy to control (can placing the “needle” at any position). For this category, we select multiple synthetic recall tasks from RULER (an extended version of NIAH; Hsieh et al., 2024) and also add a JSON KV retrieval task (Liu et al., 2023), which we find more challenging. We intentionally select the synthetic tasks that correlate well with application-driven tasks; in-depth discussions are in §3.1. Following previous works, we report the percentage of the ground truth answers that are substrings in the generation (SubEM). Refer to §B.5 for more details.

Table 4: Dataset lengths.

Datasets	Medium	Max
ZeroSCROLLS		
QASPER	6K	12K
GovReport	12K	33K
QuALITY	9K	11K
SQuALITY	8K	10K
HELMET		
NarrativeQA	73K	518K
∞ BENCH QA	191K	835K
∞ BENCH MC	167K	835K
∞ BENCH Sum	154K	835K
Multi-LexSum	90K	5M

2.2 RELIABLE EVALUATION METRICS

Existing long-context benchmarks (Zhang et al., 2024b; Shaham et al., 2023) largely rely on n-gram overlap metrics like ROUGE (Lin, 2004), which have been shown to correlate poorly with human judgment for tasks with long outputs, such as summarization (Goyal et al., 2023; Deutsch et al., 2022; Krishna et al., 2023). L-Eval (An et al., 2024) uses LLMs to score reference-free “win rates,” which neglect the available answer annotations and always require evaluating model pairs. Instead, we design a *reference-based model evaluation* method for long-document QA and summarization that is more reliable and easy to use.

Question answering. In NarrativeQA, we prompt GPT-4o⁵ with the question, the ground truth, and the model output to check for fluency and correctness. The fluency score is either 0 (incoherent or repetitive) or 1 (fluent), and the correctness score takes on the value of 0 (incorrect), 1 (partly correct), 2 (correct but not fully relevant), and 3 (correct and relevant). We take the product of the two as the final score, normalizing it to a range of $[0, 100]$.

Summarization. Following previous works (Kamoi et al., 2023; Zhang & Bansal, 2021), we first decompose the gold summary into atomic claims and use GPT-4o to check if each claim is supported by the generation (recall) and if each sentence in the generation is supported by the reference summary (precision). We then compute the F1 score from the recall and precision scores. Additionally, we ask GPT-4o to evaluate fluency (0 or 1) and take its product with the F1 score as the final score. In each step, we prompt GPT-4o with handwritten examples.

⁵GPT-4o-2024-05-13

	Multi-LexSum										InfBench Sum									
	ROUGE ?					Ours ?					ROUGE ?					Ours ?				
GPT-4o-08	22.2	22.7	23.5	23.6	23.8	43.0	47.9	51.8	51.3	53.5	15.9	16.7	17.0	17.3	17.0	13.6	20.7	26.0	28.9	32.9
Gemini-1.5-Pro	23.5	24.3	24.7	24.9	25.1	42.8	45.0	47.9	52.4	58.3	14.9	15.6	16.2	17.2	17.0	17.2	20.5	24.8	31.2	34.5
Claude-3.5-Sonnet	22.5	20.7	20.4	20.2	19.8	43.8	41.8	41.8	42.1	44.0	14.2	16.0	16.9	14.6	14.5	14.1	25.9	31.2	29.1	29.2
Llama-3.2-1B-Inst	21.1	22.0	22.2	22.2	22.0	15.2	16.8	20.8	18.5	15.1	14.1	15.5	15.8	16.5	16.4	0.9	1.9	2.4	2.7	3.1
Llama-3.2-3B-Inst	20.9	20.3	21.6	22.8	23.3	33.1	34.2	35.1	39.1	39.7	15.5	16.1	16.5	16.3	16.4	4.1	8.2	11.9	11.4	12.1
Llama-3.1-8B-Inst	24.5	24.6	23.5	23.8	24.7	38.8	39.3	42.7	39.4	38.8	15.5	16.2	16.4	16.9	17.3	3.7	9.2	12.3	13.9	15.3
Llama-3.1-70B-Inst	23.3	23.4	23.7	23.8	23.6	41.4	45.9	47.5	44.3	43.9	15.9	16.5	16.9	17.0	17.7	10.8	16.8	20.8	21.5	19.3
Mistral-7B-Inst-v0.1	23.1	22.1	22.3	21.4	21.2	25.5	21.2	17.8	19.1	15.9	11.5	12.3	12.6	12.6	12.4	1.5	3.1	2.5	2.9	2.5
Mistral-7B-Inst-v0.3	21.9	22.6	23.2	20.0	15.6	33.3	33.3	32.3	19.8	10.0	14.4	15.0	15.0	13.7	11.9	9.2	10.2	11.0	1.8	0.2
	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K

Figure 2: Comparison between ROUGE-L F1 and our model-based evaluation metric on summarization tasks. Our metric shows more consistent trends: it reflects the performance gain on GPT-4o with increased input length, while ROUGE remains almost the same; our metric also clearly differentiates models while ROUGE shows little distinction.

Empirically, our reference-based model evaluation reflects more consistent trends, as shown in Figure 2: (1) Llama-3.1-8B-Inst achieves similar ROUGE scores to GPT-4o, while our evaluation reveals a significant gap. (2) Our metric better identifies incoherent generations and shows lower performance for models with smaller context windows, such as the Mistral models. (3) Our metric exhibits a substantially more positive trend for GPT-4o as input length increases, whereas ROUGE-L remains within a 2-point absolute difference. We further validate the model-based evaluation through human studies, which suggest our new metrics strongly correlate with human judgments: for example, on ∞ BENCH Sum, our metric reaches a human-model agreement of Cohen’s $\kappa = 0.91$ for summary precision and $\kappa = 0.76$ for recall. More details on the human studies are in §B.

2.3 ROBUST PROMPTING AND CONTROLLED EVALUATION SETTINGS

Robust prompting reduces noise and enables evaluation on base models. Many long-context benchmarks require models to follow instructions and only support evaluating instruction-tuned models (Zhang et al., 2024b; Shaham et al., 2023). However, many model developments do not incorporate instruction tuning (Chen et al., 2023; Fu et al., 2024), leaving these models reliant on perplexity-based evaluation or synthetic tasks. To support long-context research efforts, we design our benchmark so that at least a subset of the datasets accommodates evaluating base models.

Existing benchmarks mostly use zero-shot prompting (Shaham et al., 2023; Zhang et al., 2024b), which leads to inconsistent output formats, especially for base models. For example, the model may output a long answer in RAG when a short answer is required. We add two-shot demonstrations in the prompt for all tasks to address this problem.⁶ For long-document QA and summarization, we replace the original document with a placeholder phrase to reduce the number of input tokens in the ICL example. As shown in Table 8, both base and instruction-tuned models significantly benefit from the demonstrations.

Furthermore, we employ the length-instruction-enhanced evaluation from L-Eval for long-generation tasks (i.e., summarization), which has been shown to have substantially more consistent and reliable evaluations (An et al., 2024). As a result, we find that our reproduction of previous datasets, such as ∞ BENCH QA tasks, better reflects the capabilities of LCLMs, as shown in Table 7. The use of demonstrations and improved instructions more accurately depicts how models perform in real applications.

Controlled input length and difficulty. An important dimension to consider when evaluating LCLMs is the input length L , as longer inputs can provide more information while challenging the model’s ability to process distracting contexts. As we discussed in §2.1, we can control the input length L for each task by either adjusting the number of retrieved passages, the number of demonstrations, or truncating the document text to fit within the specified lengths. This allows us to study model performance at or beyond the length of current frontier LCLMs ($\geq 128K$).

⁶Except for ICL (the number of shots varies) and RULER (we follow the original formatting).

As shown in Figure 1 and 2, HELMET provides rankings more consistent with human perception of model performance. The diverse tasks, controllable lengths, and robust evaluation metrics and prompting enable a thorough examination of LCLMs across multiple dimensions.

3 ANALYSIS

We evaluate 59 LCLMs with HELMET. To our best knowledge, this is the most thorough and controlled comparison of long-context models on diverse applications. These models cover closed-source models, such as GPT-4, Claude, and Gemini, as well as open-source model families, such as Llama (Dubey et al., 2024), Mistral (Jiang et al., 2023), Phi (Abdin et al., 2024), and Qwen (Qwen et al., 2025). We also consider models that use different architectures—full-attention transformers (Vaswani et al., 2017), sliding-window attention (Beltagy et al., 2020), and hybrid models with SSM modules (Dao & Gu, 2024). We also benchmark position extrapolation models such as YaRN (Peng et al., 2024) and LongRoPE (Ding et al., 2024). We list all the models evaluated in Table 15. We evaluate each model at input lengths: $L \in \{8K, 16K, 32K, 64K, 128K\}$, where L is the number of Llama-2 tokens (Touvron et al., 2023), and use greedy decoding for all models to ensure consistency. We randomly sample 100 to 600 examples from each dataset; more details are in §D.

3.1 SIMPLE SYNTHETIC TASKS ARE POOR PREDICTORS OF REAL-WORLD PERFORMANCE

Many model developers rely on simple synthetic tasks, such as NIAH, for evaluating long-context language models, but it is unclear if these tasks accurately represent real-world performance. To this end, we calculate Spearman’s rank correlation ρ between synthetic and real-world tasks for 35 instruction-tuned models. First, Figure 3 shows that none of the synthetic tasks achieves an average correlation higher than 0.8. We also make the following observations.

Not all synthetic tasks are created equal. The original NIAH, which places a needle in the middle of unrelated essays and asks the model to retrieve it, exhibits weak correlation with real-world tasks: all correlations are ≤ 0.8 . Similarly, the popular RULER average score—which includes not only NIAH variants but also synthetic aggregation, multi-hop tracing, and QA—does not yield strong correlations (all < 0.85).

We take a closer look at different RULER tasks and find that harder recall-type tasks are more reflective of real-world categories—for example, RULER MK, which places distracting needles around the target needle. Despite the overall low correlation, we believe these tasks can still serve as a useful sanity check during model development. We compile several such RULER tasks, along with JSON KV, to form the HELMET synthetic recall set (more discussions in §E.1).

Tasks with noisier, more distracting contexts better differentiate models. To understand why synthetic tasks exhibit weak correlation with real-world tasks, we plot the performance of different models on NIAH, RULER MK (one of our recall tasks), and HotpotQA (one of our RAG tasks) in Figure 4. We use ∞ BENCH QA as a representative real-world task. We find that most models achieve either perfect or near-zero performance on the original NIAH, leaving few data points in the middle and resulting in poor separability between models. In contrast, RULER MK, which introduces more distracting contexts, better distributes model performance between 0% and 100%, leading to clearer differentiation.

RAG is a better proxy for real-world tasks. Finally, we find that RAG datasets, such as HotpotQA, consistently achieve higher correlation with other real-world tasks. Figure 4 also shows that HotpotQA exhibits an almost linear relationship with the QA dataset. Similar to synthetic tasks, RAG

NIAH	0.44	0.71	0.75	0.76	0.72	0.68
RULER MK	0.48	0.73	0.84	0.79	0.87	0.74
RULER MV	0.61	0.71	0.77	0.83	0.79	0.74
RULER All	0.51	0.77	0.85	0.79	0.83	0.75
Recall	0.61	0.74	0.85	0.82	0.85	0.77
RAG	0.5	0.72	0.85	0.92	0.89	0.78
	ICL	Cite	Re-rank	LongQA	Summ	Avg.

Figure 3: Spearman’s rank correlation at 128K input length, calculated across 35 instruction-tuned models.




Figure 4: Distribution of instruction-tuned models’ performance on ∞ BENCH QA with respect to NIAH, RULER MK, and HotpotQA.

tasks are easy to control and assess models’ recall abilities. However, since all passages are retrieved and relevant to the query, RAG contexts are more distracting and therefore harder to saturate.

3.2 DIVERSE LCLM APPLICATIONS CALL FOR DIVERSE EVALUATION

In long-context language modeling, realistic tasks are often only used in isolation (Karpinska et al., 2024; Li et al., 2024c; Dubey et al., 2024), which limits the understanding of LCLMs in a broader context. In this work, we cross-examine model performance over a wide range of real tasks, and find that different categories do not consistently correlate with each other, as shown in Figure 5.

show moderate correlation due to their shared retrieval component. However, the added complexity of generating citations in ALCE results in lower correlation with other categories. Naturally, RAG and passage re-ranking moderately correlate due to the shared retrieval component. As shown in Figure 9, generating correct answers and producing valid citations are not strongly correlated, suggesting that instruction following and recalling facts within long contexts are distinct capabilities.

Furthermore, some categories—generation with citations and in-context learning—do not correlate well with other categories. Intuitively, summarization tests for the model’s ability to aggregate information across the entire input, while ICL evaluates its ability to learn new tasks from many examples. Such capabilities are orthogonal to recall facts in long contexts. Such capabilities are orthogonal to recalling facts in long contexts. Therefore, model developers should evaluate across these distinct axes to form a more holistic understanding of a model’s capabilities (see additional analysis in §E.2).

Recall	1	0.88	0.74	0.85	0.82	0.85	0.61
RAG	0.88	1	0.72	0.85	0.92	0.89	0.5
Cite	0.74	0.72	1	0.84	0.72	0.82	0.34
Re-rank	0.85	0.85	0.84	1	0.87	0.89	0.36
LongQA	0.82	0.92	0.72	0.87	1	0.85	0.51
Summ	0.85	0.89	0.82	0.89	0.85	1	0.38
ICL	0.61	0.5	0.34	0.36	0.51	0.38	1
	Recall	RAG	Cite	Re-rank	LongQA	Summ	ICL

Figure 5: Spearman rank correlation between different categories at $L = 128K$.

3.3 MODEL PERFORMANCE ACROSS TASKS AND LENGTHS

We show the performance of instruction-tuned models on HELMET at five different lengths in Figure 6, and the full results are illustrated in Figure 10. We analyze the model performance across two critical dimensions of long-context language modeling: *task complexity* and *input length*.

Open-source models lag behind closed-source models on complex tasks. First, we consider the performance of frontier LCLMs at the longest input length of 128K tokens. We find that the closed-source models—notably GPT-4o-08 and Gemini-1.5-Pro—stand out as the strongest LCLMs. Other than ICL, the closed-source models outperform the open-source models on all tasks. The gap is relatively small on synthetic recall and LongQA, where the task is to retrieve information from the context. There is a stark contrast in the generation with citations and re-ranking performance, where the closed-source models are 30 to 40 absolute points better than the best open-source models.

	Recall					RAG					Cite					Re-rank				
GPT-4	99.5	99.8	97.6	91.2	73.5	75.1	73.5	70.9	68.1	64.7	44.0	42.7	26.1	3.1	1.2	87.8	78.1	54.7	25.8	9.6
GPT-4o-05	93.2	92.2	91.2	90.1	82.4	72.5	72.4	72.6	72.7	70.4	44.2	43.7	42.3	42.4	40.4	86.3	77.9	67.7	57.7	47.7
GPT-4o-08	100.0	100.0	100.0	100.0	99.9	73.9	74.0	72.4	71.5	70.2	45.4	46.7	45.4	45.4	44.3	86.9	80.5	68.5	58.4	50.0
GPT-4o-mini	99.8	99.8	99.1	96.1	89.6	72.6	72.1	70.0	68.7	68.0	36.1	33.7	30.0	27.1	24.3	80.8	71.1	58.8	42.0	31.2
Claude-3.5-Sonnet	99.5	96.6	96.2	97.2	94.7	55.4	35.8	33.4	32.5	38.1	34.8	32.2	28.3	26.3	18.7	75.2	41.0	34.8	17.9	7.2
Gemini-1.5-Flash	93.5	93.8	93.7	93.2	91.2	71.9	70.5	69.2	68.0	66.5	48.7	49.4	48.1	40.2	31.7	87.8	80.8	74.0	61.2	50.8
Gemini-1.5-Pro	87.5	87.3	96.3	87.2	91.0	73.6	73.4	72.3	71.8	71.1	47.2	45.9	44.8	46.2	43.6	87.6	84.1	76.5	68.4	59.7
Llama-3.1-8B	100.0	100.0	99.7	99.2	95.2	70.8	68.8	66.5	65.8	59.5	36.3	26.7	10.9	13.1	2.9	67.0	51.7	43.4	32.8	14.0
Llama-3.1-70B	100.0	100.0	99.9	98.5	90.7	74.0	71.5	70.9	69.5	56.2	44.3	41.3	40.1	29.8	7.5	83.5	73.5	60.2	41.0	24.5
Llama-3.3-70B	100.0	100.0	99.6	98.5	81.8	74.4	72.7	70.3	69.2	55.1	40.4	38.6	35.7	31.0	10.9	84.8	76.7	65.0	42.3	26.2
Mistral-Nemo	99.9	95.6	65.6	30.1	14.6	67.8	63.5	57.3	47.1	40.0	32.7	8.2	2.8	1.1	0.5	66.3	48.3	14.8	0.0	0.0
MegaBeam-Mistral	97.8	97.1	95.9	94.2	89.6	64.7	63.0	61.8	59.7	57.0	22.0	14.1	9.0	4.5	4.0	56.4	40.3	35.0	25.6	14.7
Ministral-8B	98.9	97.7	95.1	30.9	12.8	66.7	66.0	63.5	47.1	35.2	36.7	24.1	7.6	0.7	0.4	67.4	49.4	32.6	0.0	0.0
Phi-3-mini-128k	97.8	96.8	95.1	95.4	50.1	62.5	61.4	59.4	56.3	46.7	23.3	18.5	10.1	2.1	0.6	53.1	33.1	23.5	14.0	5.8
Phi-3-small-128k	94.0	93.6	83.4	74.6	22.3	67.1	64.7	62.6	58.5	33.8	17.9	13.5	6.9	3.5	3.0	46.1	35.5	27.4	16.9	1.9
Phi-3-med-128k	91.6	88.9	79.3	69.3	24.5	66.1	63.8	62.3	57.8	44.8	39.8	26.4	9.7	5.3	3.3	52.6	36.7	26.1	12.9	6.6
Phi-3.5-mini	98.3	97.8	94.7	91.9	48.8	61.9	60.6	57.1	52.5	43.1	22.2	15.8	7.2	2.0	1.6	51.3	36.4	25.6	14.2	7.8
Qwen2.5-72B	100.0	100.0	98.4	71.4	38.4	72.5	72.0	70.2	63.1	43.0	42.7	40.8	39.0	25.1	8.0	86.0	75.3	60.3	41.0	24.5
Qwen2.5-7B-1M	96.9	98.5	94.1	92.8	86.0	67.7	68.3	64.9	64.0	59.0	36.2	17.9	8.6	9.6	4.8	71.3	57.4	45.9	32.1	24.8
Qwen2.5-14B-1M	100.0	99.9	99.4	99.2	97.8	72.2	70.8	68.9	66.0	62.0	41.9	35.4	32.9	28.2	27.1	74.3	57.9	49.9	38.0	27.9
Jamba-1.5-Mini	98.4	95.4	97.3	93.2	90.0	65.2	64.1	63.4	61.8	57.3	14.4	8.3	6.6	6.4	3.1	62.1	46.3	33.4	25.4	14.6
ProLong	99.4	99.7	99.2	99.4	98.8	67.4	67.5	66.4	65.7	63.2	34.6	27.1	12.8	5.8	1.4	60.4	47.4	40.2	31.1	22.5
	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K
	LongQA					Summ					ICL					Avg.				
GPT-4	46.6	46.1	46.7	44.2	46.7	28.2	29.1	28.6	32.8	33.0	80.8	82.0	76.5	59.0	46.0	66.0	64.5	57.3	46.3	39.2
GPT-4o-05	43.8	48.0	53.6	54.3	62.0	29.5	33.2	39.4	40.8	43.6	79.9	80.1	75.8	63.0	48.4	64.2	63.9	63.3	60.1	56.4
GPT-4o-08	41.8	48.1	50.8	55.5	59.3	28.3	34.3	38.9	40.1	43.2	82.6	85.9	87.2	86.8	86.3	65.5	67.1	66.2	65.4	64.8
GPT-4o-mini	35.3	39.8	45.8	49.3	54.8	26.7	33.8	35.1	39.0	40.8	77.3	79.9	81.9	81.9	81.2	61.2	61.4	60.1	57.7	55.7
Claude-3.5-Sonnet	29.2	23.1	27.2	12.6	12.6	28.9	33.8	36.5	35.6	36.6	87.1	88.7	89.9	89.2	61.0	58.6	50.2	49.5	44.5	38.4
Gemini-1.5-Flash	33.9	42.4	46.3	52.3	57.3	25.0	28.4	33.5	38.3	39.4	74.2	68.7	56.6	39.7	28.1	62.1	62.0	60.2	56.1	52.1
Gemini-1.5-Pro	35.5	41.5	49.3	52.6	59.6	30.0	32.7	36.3	41.8	46.4	78.7	81.1	82.0	80.4	79.4	62.9	63.7	65.4	64.0	64.4
Llama-3.1-8B	25.2	32.6	40.5	44.6	43.2	21.3	24.2	27.5	26.7	27.0	71.3	76.4	77.9	81.4	83.9	56.0	54.3	52.3	52.0	46.5
Llama-3.1-70B	31.2	40.0	47.0	54.0	56.3	26.1	31.3	34.2	32.9	31.6	71.6	75.0	76.1	81.6	81.4	61.5	61.8	61.2	58.2	49.7
Llama-3.3-70B	34.7	41.8	49.8	52.2	52.0	24.9	30.0	33.4	32.9	33.3	70.2	75.0	76.3	82.1	77.8	61.3	62.1	61.4	58.3	48.2
Mistral-Nemo	31.0	33.4	27.3	21.4	22.5	25.3	19.8	20.8	19.3	18.5	68.6	76.0	80.2	82.2	84.0	55.9	49.2	38.4	28.7	25.7
MegaBeam-Mistral	20.7	30.7	32.2	34.9	37.3	20.3	22.6	24.1	29.0	28.9	72.1	76.4	80.6	83.8	86.2	50.6	49.2	48.4	47.4	45.4
Ministral-8B	28.8	33.4	34.9	23.7	25.0	22.7	25.6	23.1	14.4	11.5	71.3	74.8	77.3	82.8	84.4	56.1	53.0	47.7	28.5	24.2
Phi-3-mini-128k	28.2	31.4	32.9	33.9	29.9	19.1	21.7	24.0	25.0	23.7	65.6	69.6	73.7	76.2	78.7	49.9	47.5	45.5	43.3	33.6
Phi-3-small-128k	25.0	28.5	36.0	41.8	27.5	18.6	20.3	24.8	24.4	6.6	67.8	74.1	79.1	82.3	79.6	48.1	47.2	45.7	43.2	24.9
Phi-3-med-128k	22.7	21.2	19.1	18.4	26.9	21.4	23.3	23.0	27.6	24.8	62.6	65.5	67.8	73.0	73.2	51.0	46.5	41.0	37.7	29.1
Phi-3.5-mini	24.7	26.4	29.3	30.6	28.5	19.6	21.1	22.9	24.9	26.3	63.8	70.2	75.2	78.0	79.5	48.8	46.9	44.6	42.0	33.6
Qwen2.5-72B	36.2	40.5	44.4	41.5	38.9	28.2	33.9	38.8	34.1	31.4	78.4	80.4	81.8	83.6	83.2	63.4	63.3	61.8	51.4	38.2
Qwen2.5-7B-1M	28.8	36.7	37.9	36.5	38.6	22.9	25.0	27.5	27.9	28.9	70.8	69.2	57.2	49.4	47.1	56.4	53.3	48.0	44.6	41.3
Qwen2.5-14B-1M	31.0	38.1	39.7	44.1	47.8	27.3	32.1	34.3	35.3	38.6	79.8	84.7	88.2	89.6	90.5	60.9	59.9	59.0	57.2	56.0
Jamba-1.5-Mini	35.9	40.0	48.1	51.0	54.2	17.1	17.3	17.3	17.7	18.1	81.0	85.0	87.9	89.7	91.0	53.4	50.9	50.6	49.3	46.9
ProLong	28.3	36.9	37.6	40.8	43.9	21.7	22.3	22.2	26.0	29.2	69.1	75.1	78.9	83.2	86.5	54.4	53.7	51.1	50.3	49.4
	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K

Figure 6: Results of HELMET. All models are instruction-tuned and have a claimed context window of 128K tokens or more.

Performance degradation with longer inputs is category-dependent. Most frontier models largely retain performance on recall and RAG with longer inputs; however, even the best models experience significant degradation as context length increases on tasks like re-ranking and generation with citations. As illustrated in Figure 7, performance degradation at longer lengths becomes more pronounced as task complexity increases from left to right. On generation with citations, open-source models completely collapse at 128K, while GPT-4o remains relatively stable. This underscores the importance of evaluating models on more complex long-context applications.

No clear winner across all categories. As we observe from the previous sections, the different categories do not always correlate with each other. This is evident in the varying top-performing models across categories: for instance, GPT-4o excels in recall and generation with citations, while Gemini performs better in passage re-ranking and long-document QA. Furthermore, many open-source models outperform closed-source models on ICL, potentially because heavy instruction tuning negatively impacts ICL. We provide qualitative examples in Table 19. Thus, evaluating models across multiple axes is essential. In the appendix, we also present additional analysis, such as the performance of positional extrapolation methods (§E.3), the lost-in-the-middle phenomenon (§E.4), and the performance of Claude (§E.6).

	NIAH					RAG					Re-rank					Cite				
GPT-4o-08	100.0	100.0	100.0	100.0	100.0	73.9	74.0	72.4	71.5	70.2	86.9	80.5	68.5	58.4	50.0	45.4	46.7	45.4	45.4	44.3
Gemini-1.5-Pro	96.8	98.0	96.0	34.0	36.2	73.6	73.4	72.3	71.8	71.1	87.6	84.1	76.5	68.4	59.7	47.2	45.9	44.8	46.2	43.6
Llama-3.1-8B-Inst	100.0	100.0	100.0	100.0	100.0	70.8	68.8	66.5	65.8	59.5	67.0	51.7	43.4	32.8	14.0	36.3	26.7	10.9	13.1	2.9
Llama-3.1-70B-Inst	100.0	100.0	100.0	100.0	100.0	74.0	71.5	70.9	69.5	56.2	83.5	73.5	60.2	41.0	24.5	44.3	41.3	40.1	29.8	7.5
Jamba-1.5-Mini	100.0	100.0	100.0	100.0	100.0	65.2	64.1	63.4	61.8	57.3	62.1	46.3	33.4	25.4	14.6	14.4	8.3	6.6	6.4	3.1
Qwen2-7B-Inst	100.0	100.0	100.0	100.0	100.0	58.5	57.3	54.0	51.1	47.4	47.9	28.2	19.5	8.6	5.9	15.5	7.4	3.6	3.5	2.4
Qwen2-57B-Inst	100.0	100.0	100.0	87.0	36.0	65.4	66.2	62.2	54.7	12.7	53.3	38.9	22.3	6.5	0.0	36.0	11.3	4.1	3.9	1.1
	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K

Figure 7: Results of selected instruct models on various lengths and increasing complexity of tasks. Notably, Qwen2 relies on position extrapolation, while other open-models are trained at or greater than 128K context window.

4 RELATED WORKS

Long-context language models. Frontier models such as GPT-4 (OpenAI, 2023), Gemini (Team et al., 2024b), and Claude claim to have expanded their context window beyond 100K tokens. In the open-source community, there are also efforts to train models with longer input lengths (Dubey et al., 2024; Fu et al., 2024; AI et al., 2024; Gao et al., 2024), explore position extrapolation techniques (Peng et al., 2024; Chen et al., 2023; Ding et al., 2024), and experiment with efficient architectures (Beltagy et al., 2020; Bertsch et al., 2023; Gu & Dao, 2024; Dao & Gu, 2024; Yen et al., 2024; Lieber et al., 2024, *inter alia*).

Synthetic tasks. Synthetic tasks are often used to evaluate LCLMs since they can be procedurally generated, enabling arbitrarily long input lengths and controlled “needle” placement (Tay et al., 2021; Liu et al., 2023). In particular, Needle-in-a-Haystack (NIAH; Kamradt, 2024) inserts a “needle” at specific depths of a long essay (i.e., the haystack) and asks the model to recall the fact. Recent works have expanded upon it and designed new procedures to test different aspects of LCLMs (Hsieh et al., 2024; Li et al., 2024b; Levy et al., 2024; Arora et al., 2023; Laban et al., 2024; Goldman et al., 2024, *inter alia*). However, they do not study how results on synthetic tasks transfer to real applications. In contrast, we evaluate both synthetic and downstream tasks and investigate how they correlate with each other.

Long-context benchmarks. As discussed in the main paper, existing benchmarks either are limit to relatively short context lengths (Shaham et al., 2022; 2023; Li et al., 2024a; An et al., 2024; Bai et al., 2024; Dong et al., 2024; Kwan et al., 2024) or lack rigorous evaluation methods (Zhang et al., 2024b; Yuan et al., 2024). Many works instead focus on specific domains, such as question answering (Wang et al., 2024b; Karpinska et al., 2024; Wang et al., 2024a;c), in-context learning (Li et al., 2024c; Bertsch et al., 2024; Xu et al., 2024; Anil et al., 2024; Agarwal et al., 2024), summarization (Chang et al., 2024; Kim et al., 2024; Shen et al., 2022), or RAG (Lee et al., 2024). In this work, we construct a comprehensive benchmark that tests across diverse downstream tasks at long input lengths and also present a unified comparison and analysis across 59 LCLMs.

5 CONCLUSION

In this work, we first identify the shortcomings of long-context evaluation settings and existing benchmarks—over-reliance on synthetic tasks, limited coverage of realistic applications, and unreliable metrics among others. We seek to address these issues by constructing HELMET, an application-centric benchmark with diverse domains and reliable evaluation settings. We then present a comprehensive evaluation of 59 frontier LCLMs across multiple dimensions, including different tasks, input lengths, and model types. Our analysis shows that synthetic tasks poorly predict downstream performance and that different categories exhibit distinct capabilities and trends. Thus, evaluating models on a diverse set of real-world tasks is essential. Furthermore, open-source models still lag behind closed-source models on complex tasks at longer lengths. Finally, we hope that our benchmark and comprehensive evaluation serve as a valuable resource for future research in long-context language modeling.

REPRODUCIBILITY STATEMENT

We have publicly released all of our code and data to ensure reproducibility. Experimental settings are outlined in the main text (§3) and the appendix (§D), and we will provide additional details and instructions in the code repository. Furthermore, we plan on releasing the model generated outputs and statistics to enable further analysis and comparison.

ACKNOWLEDGMENTS

We would like to acknowledge Mengzhou Xia, Howard Chen, Xi Ye, Yinghui He, Lucy He, Alexander Wettig, Sadhika Malladi, and other members of Princeton Language and Intelligence for their helpful feedback and discussion. We also thank Adithya Bhaskar and Joie Zhang for helping with validating the model-based evaluation. Tianyu Gao is supported by an IBM PhD Fellowship. This work is gratefully supported by an NSF CAREER award (IIS-2239290), a grant from Intel, and the Microsoft Accelerate Foundation Models Research (AFMR) grant program.

REFERENCES

- Marah Abdin, Jyoti Aneja, Hany Awadalla, Ahmed Awadallah, Ammar Ahmad Awan, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Jianmin Bao, Harkirat Behl, Alon Benhaim, Misha Bilenko, Johan Bjorck, Sébastien Bubeck, Martin Cai, Qin Cai, Vishrav Chaudhary, Dong Chen, Dongdong Chen, Weizhu Chen, Yen-Chun Chen, Yi-Ling Chen, Hao Cheng, Parul Chopra, Xiyang Dai, Matthew Dixon, Ronen Eldan, Victor Fragoso, Jianfeng Gao, Mei Gao, Min Gao, Amit Garg, Allie Del Giorno, Abhishek Goswami, Suriya Gunasekar, Emman Haider, Junheng Hao, Russell J. Hewett, Wenxiang Hu, Jamie Huynh, Dan Iter, Sam Ade Jacobs, Mojan Javaheripi, Xin Jin, Nikos Karampatziakis, Piero Kauffmann, Mahoud Khademi, Dongwoo Kim, Young Jin Kim, Lev Kurilenko, James R. Lee, Yin Tat Lee, Yuanzhi Li, Yunsheng Li, Chen Liang, Lars Liden, Xihui Lin, Zeqi Lin, Ce Liu, Liyuan Liu, Mengchen Liu, Weishung Liu, Xiaodong Liu, Chong Luo, Piyush Madan, Ali Mahmoudzadeh, David Majercak, Matt Mazzola, Caio César Teodoro Mendes, Arindam Mitra, Hardik Modi, Anh Nguyen, Brandon Norick, Barun Patra, Daniel Perez-Becker, Thomas Portet, Reid Pryzant, Heyang Qin, Marko Radmilac, Liliang Ren, Gustavo de Rosa, Corby Rosset, Sambudha Roy, Olatunji Ruwase, Olli Saarikivi, Amin Saied, Adil Salim, Michael Santacrose, Shital Shah, Ning Shang, Hiteshi Sharma, Yelong Shen, Swadheen Shukla, Xia Song, Masahiro Tanaka, Andrea Tupini, Praneetha Vaddamanu, Chunyu Wang, Guanhua Wang, Lijuan Wang, Shuohang Wang, Xin Wang, Yu Wang, Rachel Ward, Wen Wen, Philipp Witte, Haiping Wu, Xiaoxia Wu, Michael Wyatt, Bin Xiao, Can Xu, Jiahang Xu, Weijian Xu, Jilong Xue, Sonali Yadav, Fan Yang, Jianwei Yang, Yifan Yang, Ziyi Yang, Donghan Yu, Lu Yuan, Chenruidong Zhang, Cyril Zhang, Jianwen Zhang, Li Lyna Zhang, Yi Zhang, Yue Zhang, Yunan Zhang, and Xiren Zhou. Phi-3 technical report: A highly capable language model locally on your phone, 2024. URL <https://arxiv.org/abs/2404.14219>.
- Rishabh Agarwal, Avi Singh, Lei M. Zhang, Bernd Bohnet, Luis Rosias, Stephanie Chan, Biao Zhang, Ankesh Anand, Zaheer Abbas, Azade Nova, John D. Co-Reyes, Eric Chu, Feryal Behbahani, Aleksandra Faust, and Hugo Larochelle. Many-shot in-context learning, 2024. URL <https://arxiv.org/abs/2404.11018>.
01. AI, :, Alex Young, Bei Chen, Chao Li, Chengen Huang, Ge Zhang, Guanwei Zhang, Heng Li, Jiangcheng Zhu, Jianqun Chen, Jing Chang, Kaidong Yu, Peng Liu, Qiang Liu, Shawn Yue, Senbin Yang, Shiming Yang, Tao Yu, Wen Xie, Wenhao Huang, Xiaohui Hu, Xiaoyi Ren, Xinyao Niu, Pengcheng Nie, Yuchi Xu, Yudong Liu, Yue Wang, Yuxuan Cai, Zhenyu Gu, Zhiyuan Liu, and Zonghong Dai. Yi: Open foundation models by 01.ai, 2024.
- Chenxin An, Shansan Gong, Ming Zhong, Xingjian Zhao, Mukai Li, Jun Zhang, Lingpeng Kong, and Xipeng Qiu. L-eval: Instituting standardized evaluation for long context language models. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 14388–14411, Bangkok, Thailand, August 2024. Association for Computational Linguistics. URL <https://aclanthology.org/2024.acl-long.776>.
- Cem Anil, Esin Durmus, Mrinank Sharma, Joe Benton, Sandipan Kundu, Joshua Batson, Nina Rimskey, Meg Tong, Jesse Mu, Daniel Ford, et al. Many-shot jailbreaking. *Anthropic, April*, 2024.

- Simran Arora, Sabri Eyuboglu, Aman Timalsina, Isys Johnson, Michael Poli, James Zou, Atri Rudra, and Christopher Ré. Zoology: Measuring and improving recall in efficient language models, 2023.
- Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. Self-RAG: Learning to retrieve, generate, and critique through self-reflection. In *The Twelfth International Conference on Learning Representations*, 2024a. URL <https://openreview.net/forum?id=hSyW5go0v8>.
- Akari Asai, Zexuan Zhong, Danqi Chen, Pang Wei Koh, Luke Zettlemoyer, Hannaneh Hajishirzi, and Wen tau Yih. Reliable, adaptable, and attributable language models with retrieval, 2024b. URL <https://arxiv.org/abs/2403.03187>.
- Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, Yuxiao Dong, Jie Tang, and Juanzi Li. LongBench: A bilingual, multitask benchmark for long context understanding. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 3119–3137, Bangkok, Thailand, August 2024. Association for Computational Linguistics. URL <https://aclanthology.org/2024.acl-long.172>.
- Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, Mir Rosenberg, Xia Song, Alina Stoica, Saurabh Tiwary, and Tong Wang. Ms marco: A human generated machine reading comprehension dataset, 2018. URL <https://arxiv.org/abs/1611.09268>.
- Iz Beltagy, Matthew E. Peters, and Arman Cohan. Longformer: The long-document Transformer. *arXiv:2004.05150*, 2020. URL <https://arxiv.org/abs/2004.05150>.
- Amanda Bertsch, Uri Alon, Graham Neubig, and Matthew R. Gormley. Unlimiformer: Long-range transformers with unlimited length input. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. URL <https://openreview.net/forum?id=1JWUJWLCJo>.
- Amanda Bertsch, Maor Ivgi, Uri Alon, Jonathan Berant, Matthew R. Gormley, and Graham Neubig. In-context learning with long-context models: An in-depth exploration. In *First Workshop on Long-Context Foundation Models @ ICML 2024*, 2024. URL <https://openreview.net/forum?id=4KAmc7vUbq>.
- Bernd Bohnet, Vinh Q Tran, Pat Verga, Roei Aharoni, Daniel Andor, Livio Baldini Soares, Jacob Eisenstein, Kuzman Ganchev, Jonathan Herzig, Kai Hui, et al. Attributed question answering: Evaluation and modeling for attributed large language models. *arXiv preprint arXiv:2212.08037*, 2022. URL <https://arxiv.org/pdf/2212.08037.pdf>.
- Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020. URL <https://papers.nips.cc/paper/2020/hash/1457c0d6bfc4967418bfb8ac142f64a-Abstract.html>.
- Iñigo Casanueva, Tadas Temčinas, Daniela Gerz, Matthew Henderson, and Ivan Vulić. Efficient intent detection with dual sentence encoders. In Tsung-Hsien Wen, Asli Celikyilmaz, Zhou Yu, Alexandros Papangelis, Mihail Eric, Anuj Kumar, Iñigo Casanueva, and Rushin Shah (eds.), *Proceedings of the 2nd Workshop on Natural Language Processing for Conversational AI*, pp. 38–45, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.nlp4convai-1.5. URL <https://aclanthology.org/2020.nlp4convai-1.5>.
- Yapei Chang, Kyle Lo, Tanya Goyal, and Mohit Iyyer. Boookscore: A systematic exploration of book-length summarization in the era of LLMs. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=7Ttk3RzDeu>.

- Danqi Chen, Adam Fisch, Jason Weston, and Antoine Bordes. Reading Wikipedia to answer open-domain questions. In Regina Barzilay and Min-Yen Kan (eds.), *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1870–1879, Vancouver, Canada, July 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1171. URL <https://aclanthology.org/P17-1171>.
- Shouyuan Chen, Sherman Wong, Liangjian Chen, and Yuandong Tian. Extending context window of large language models via positional interpolation, 2023.
- Nick Craswell, Bhaskar Mitra, Emine Yilmaz, Daniel Campos, and Ellen M. Voorhees. Overview of the trec 2019 deep learning track, 2020. URL <https://arxiv.org/abs/2003.07820>.
- Tri Dao. Flashattention-2: Faster attention with better parallelism and work partitioning, 2023. URL <https://arxiv.org/abs/2307.08691>.
- Tri Dao and Albert Gu. Transformers are ssms: Generalized models and efficient algorithms through structured state space duality, 2024. URL <https://arxiv.org/abs/2405.21060>.
- Daniel Deutsch, Rotem Dror, and Dan Roth. Re-examining system-level correlations of automatic summarization evaluation metrics. In Marine Carpuat, Marie-Catherine de Marneffe, and Ivan Vladimir Meza Ruiz (eds.), *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 6038–6052, Seattle, United States, July 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.naacl-main.442. URL <https://aclanthology.org/2022.naacl-main.442>.
- Yiran Ding, Li Lyna Zhang, Chengruidong Zhang, Yuanyuan Xu, Ning Shang, Jiahang Xu, Fan Yang, and Mao Yang. Longrope: Extending llm context window beyond 2 million tokens, 2024. URL <https://arxiv.org/abs/2402.13753>.
- Zican Dong, Tianyi Tang, Junyi Li, Wayne Xin Zhao, and Ji-Rong Wen. BAMBOO: A comprehensive benchmark for evaluating long text modeling capacities of large language models. In Nicoletta Calzolari, Min-Yen Kan, Veronique Hoste, Alessandro Lenci, Sakriani Sakti, and Nianwen Xue (eds.), *Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024)*, pp. 2086–2099, Torino, Italia, May 2024. ELRA and ICCL. URL <https://aclanthology.org/2024.lrec-main.188>.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Lauren Rantala-Yeary, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Man-nat Singh, Manohar Paluri, Marcin Kardas, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong,

Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujjwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaoqing Ellen Tan, Xinfeng Xie, Xuchao Jia, Xuwei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aaron Grattafiori, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alex Vaughan, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Franco, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Changan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, Danny Wyatt, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Firat Ozgenel, Francesco Caggioni, Francisco Guzmán, Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Govind Thattai, Grant Herman, Grigory Sizov, Guangyi, Zhang, Guna Lakshminarayanan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Karthik Prasad, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kun Huang, Kunal Chawla, Kushal Lakhotia, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Maria Tsimpoukelli, Martynas Mankus, Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Maya Lathi, Meghan Keenally, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikolay Pavlovich Laptev, Ning Dong, Ning Zhang, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Rohan Maheswari, Russ Howes, Ruty Rinott, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Kohler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vitor Albiero, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu

- Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaofang Wang, Xiaojian Wu, Xiaolan Wang, Xide Xia, Xilun Wu, Xinbo Gao, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yuchen Hao, Yundi Qian, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, and Zhiwei Zhao. The llama 3 herd of models, 2024. URL <https://arxiv.org/abs/2407.21783>.
- Yao Fu, Rameswar Panda, Xinyao Niu, Xiang Yue, Hannaneh Hajishirzi, Yoon Kim, and Hao Peng. Data engineering for scaling language models to 128k context, 2024.
- Tianyu Gao, Howard Yen, Jiatong Yu, and Danqi Chen. Enabling large language models to generate text with citations. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 6465–6488, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.398. URL <https://aclanthology.org/2023.emnlp-main.398>.
- Tianyu Gao, Alexander Wettig, Howard Yen, and Danqi Chen. How to train long-context language models (effectively), 2024. URL <https://arxiv.org/abs/2410.02660>.
- Omer Goldman, Alon Jacovi, Aviv Slobodkin, Aviya Maimon, Ido Dagan, and Reut Tsarfaty. Is it really long context if all you need is retrieval? towards genuinely difficult long context nlp, 2024. URL <https://arxiv.org/abs/2407.00402>.
- Tanya Goyal, Junyi Jessy Li, and Greg Durrett. News Summarization and Evaluation in the Era of GPT-3, 2023. URL <https://arxiv.org/abs/2209.12356>.
- Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. In *First Conference on Language Modeling*, 2024. URL <https://openreview.net/forum?id=tEYskw1VY2>.
- Cheng-Ping Hsieh, Simeng Sun, Samuel Krman, Shantanu Acharya, Dima Rekesh, Fei Jia, and Boris Ginsburg. RULER: What’s the real context size of your long-context language models? In *First Conference on Language Modeling*, 2024. URL <https://openreview.net/forum?id=kIoBbc76Sy>.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, L  lio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timoth  e Lacroix, and William El Sayed. Mistral 7b, 2023.
- Mandar Joshi, Eunsol Choi, Daniel Weld, and Luke Zettlemoyer. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In Regina Barzilay and Min-Yen Kan (eds.), *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1601–1611, Vancouver, Canada, July 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1147. URL <https://aclanthology.org/P17-1147>.
- Ryo Kamoi, Tanya Goyal, Juan Diego Rodriguez, and Greg Durrett. WiCE: Real-World Entailment for Claims in Wikipedia. *arXiv preprint arXiv:2303.01432*, 2023. URL <https://arxiv.org/abs/2303.01432>.
- Garrett Kamradt. Needle in a haystack - pressure testing llms, 2024. URL https://github.com/gkamradt/LLMTest_NeedleInAHaystack.
- Marzena Karpinska, Katherine Thai, Kyle Lo, Tanya Goyal, and Mohit Iyyer. One thousand and one pairs: A “novel” challenge for long-context language models, 2024. URL <https://arxiv.org/abs/2406.16264>.
- Yekyung Kim, Yapei Chang, Marzena Karpinska, Aparna Garimella, Varun Manjunatha, Kyle Lo, Tanya Goyal, and Mohit Iyyer. FABLES: Evaluating faithfulness and content selection in book-length summarization. In *First Conference on Language Modeling*, 2024. URL <https://openreview.net/forum?id=YfHxQSoaWU>.

- Tomáš Kočiský, Jonathan Schwarz, Phil Blunsom, Chris Dyer, Karl Moritz Hermann, Gábor Melis, and Edward Grefenstette. The NarrativeQA reading comprehension challenge. *Transactions of the Association for Computational Linguistics*, 6:317–328, 2018. doi: 10.1162/tacl.a.00023. URL <https://aclanthology.org/Q18-1023>.
- Kalpesh Krishna, Erin Bransom, Bailey Kuehl, Mohit Iyyer, Pradeep Dasigi, Arman Cohan, and Kyle Lo. LongEval: Guidelines for human evaluation of faithfulness in long-form summarization. In Andreas Vlachos and Isabelle Augenstein (eds.), *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pp. 1650–1669, Dubrovnik, Croatia, May 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.eacl-main.121. URL <https://aclanthology.org/2023.eacl-main.121/>.
- Wai-Chung Kwan, Xingshan Zeng, Yufei Wang, Yusen Sun, Liangyou Li, Yuxin Jiang, Lifeng Shang, Qun Liu, and Kam-Fai Wong. M4LE: A multi-ability multi-range multi-task multi-domain long-context evaluation benchmark for large language models. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15568–15592, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.832. URL <https://aclanthology.org/2024.acl-long.832/>.
- Tom Kwiakowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:452–466, 2019. doi: 10.1162/tacl.a.00276. URL <https://aclanthology.org/Q19-1026>.
- Philippe Laban, Alexander R. Fabbri, Caiming Xiong, and Chien-Sheng Wu. Summary of a haystack: A challenge to long-context llms and rag systems, 2024. URL <https://arxiv.org/abs/2407.01370>.
- Stefan Larson, Anish Mahendran, Joseph J. Peper, Christopher Clarke, Andrew Lee, Parker Hill, Jonathan K. Kummerfeld, Kevin Leach, Michael A. Laurenzano, Lingjia Tang, and Jason Mars. An evaluation dataset for intent classification and out-of-scope prediction. In Kentaro Inui, Jing Jiang, Vincent Ng, and Xiaojun Wan (eds.), *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 1311–1316, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1131. URL <https://aclanthology.org/D19-1131>.
- Jinhyuk Lee, Anthony Chen, Zhuyun Dai, Dheeru Dua, Devendra Singh Sachan, Michael Boratko, Yi Luan, Sébastien M. R. Arnold, Vincent Perot, Siddharth Dalmia, Hexiang Hu, Xudong Lin, Panupong Pasupat, Aida Amini, Jeremy R. Cole, Sebastian Riedel, Iftekhar Naim, Ming-Wei Chang, and Kelvin Guu. Can long-context language models subsume retrieval, rag, sql, and more?, 2024. URL <https://arxiv.org/abs/2406.13121>.
- Mosh Levy, Alon Jacoby, and Yoav Goldberg. Same task, more tokens: the impact of input length on the reasoning performance of large language models. In *Association for Computational Linguistics (ACL)*, 2024.
- Jiaqi Li, Mengmeng Wang, Zilong Zheng, and Muhan Zhang. LooGLE: Can long-context language models understand long contexts? In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 16304–16333, Bangkok, Thailand, August 2024a. Association for Computational Linguistics. URL <https://aclanthology.org/2024.acl-long.859>.
- Mo Li, Songyang Zhang, Yunxin Liu, and Kai Chen. Needlebench: Can llms do retrieval and reasoning in 1 million context window?, 2024b. URL <https://arxiv.org/abs/2407.11963>.
- Tianle Li, Ge Zhang, Quy Duc Do, Xiang Yue, and Wenhui Chen. Long-context llms struggle with long in-context learning. *CoRR*, abs/2404.02060, 2024c. URL <https://doi.org/10.48550/arXiv.2404.02060>.

- Xin Li and Dan Roth. Learning question classifiers. In *COLING 2002: The 19th International Conference on Computational Linguistics*, 2002. URL <https://aclanthology.org/C02-1150>.
- Opher Lieber, Barak Lenz, Hofit Bata, Gal Cohen, Jhonathan Osin, Itay Dalmedigos, Erez Safahi, Shaked Meirum, Yonatan Belinkov, Shai Shalev-Shwartz, Omri Abend, Raz Alon, Tomer Asida, Amir Bergman, Roman Glozman, Michael Gokhman, Avashalom Manevich, Nir Ratner, Noam Rozen, Erez Shwartz, Mor Zusman, and Yoav Shoham. Jamba: A hybrid transformer-mamba language model, 2024. URL <https://arxiv.org/abs/2403.19887>.
- Chin-Yew Lin. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, Barcelona, Spain, July 2004. Association for Computational Linguistics. URL <https://aclanthology.org/W04-1013>.
- Nelson F. Liu, Kevin Lin, John Hewitt, Ashwin Paranjape, Michele Bevilacqua, Fabio Petroni, and Percy Liang. Lost in the middle: How language models use long contexts. *Transactions of the Association for Computational Linguistics*, 12:157–173, 2023. URL <https://api.semanticscholar.org/CorpusID:259360665>.
- Xingkun Liu, Arash Eshghi, Pawel Swietojanski, and Verena Rieser. Benchmarking natural language understanding services for building conversational agents. *ArXiv*, abs/1903.05566, 2019. URL <https://api.semanticscholar.org/CorpusID:76660838>.
- Alex Mallen, Akari Asai, Victor Zhong, Rajarshi Das, Daniel Khashabi, and Hannaneh Hajishirzi. When not to trust language models: Investigating effectiveness of parametric and non-parametric memories. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (eds.), *Association for Computational Linguistics (ACL)*, pp. 9802–9822, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.546. URL <https://aclanthology.org/2023.acl-long.546>.
- Sewon Min, Xinxu Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. Rethinking the role of demonstrations: What makes in-context learning work? In Yoav Goldberg, Zornitsa Kozareva, and Yue Zhang (eds.), *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 11048–11064, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.759. URL <https://aclanthology.org/2022.emnlp-main.759>.
- Jianmo Ni, Chen Qu, Jing Lu, Zhuyun Dai, Gustavo Hernandez Abrego, Ji Ma, Vincent Zhao, Yi Luan, Keith Hall, Ming-Wei Chang, and Yinfei Yang. Large dual encoders are generalizable retrievers. In *Empirical Methods in Natural Language Processing (EMNLP)*, pp. 9844–9855, 2022. URL <https://aclanthology.org/2022.emnlp-main.669>.
- OpenAI. GPT-4 Technical Report, 2023.
- Jane Pan, Tianyu Gao, Howard Chen, and Danqi Chen. What in-context learning “learns” in-context: Disentangling task recognition and task learning. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (eds.), *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 8298–8319, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-acl.527. URL <https://aclanthology.org/2023.findings-acl.527>.
- Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. YaRN: Efficient context window extension of large language models. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=wHBfxhZulu>.
- Fabio Petroni, Aleksandra Piktus, Angela Fan, Patrick Lewis, Majid Yazdani, Nicola De Cao, James Thorne, Yacine Jernite, Vladimir Karpukhin, Jean Maillard, Vassilis Plachouras, Tim Rocktäschel, and Sebastian Riedel. KILT: a benchmark for knowledge intensive language tasks. In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pp. 2523–2544, Online, June 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.naacl-main.200. URL <https://aclanthology.org/2021.naacl-main.200>.

- Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tianyi Tang, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report, 2025. URL <https://arxiv.org/abs/2412.15115>.
- Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. SQuAD: 100,000+ questions for machine comprehension of text. In *Empirical Methods in Natural Language Processing (EMNLP)*, 2016. URL <https://aclanthology.org/D16-1264/>.
- Nir Ratner, Yoav Levine, Yonatan Belinkov, Ori Ram, Inbal Magar, Omri Abend, Ehud Karpas, Amnon Shashua, Kevin Leyton-Brown, and Yoav Shoham. Parallel context windows for large language models. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (eds.), *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 6383–6402, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.352. URL <https://aclanthology.org/2023.acl-long.352>.
- Stephen Robertson and Hugo Zaragoza. The probabilistic relevance framework: Bm25 and beyond. *Found. Trends Inf. Retr.*, 3(4):333–389, apr 2009. ISSN 1554-0669. doi: 10.1561/15000000019. URL <https://doi.org/10.1561/15000000019>.
- Samuel Joseph Amouyal Ohad Rubin, Ori Yoran, Tomer Wolfson, Jonathan Herzig, and Jonathan Berant. QAMPARI: An Open-domain Question Answering Benchmark for Questions with Many Answers from Multiple Paragraphs. *arXiv preprint arXiv:2205.12665*, 2022. URL <https://arxiv.org/abs/2205.12665>.
- Uri Shaham, Elad Segal, Maor Ivgi, Avia Efrat, Ori Yoran, Adi Haviv, Ankit Gupta, Wenhan Xiong, Mor Geva, Jonathan Berant, and Omer Levy. SCROLLS: Standardized Comparison over long language sequences. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 12007–12021, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. URL <https://aclanthology.org/2022.emnlp-main.823>.
- Uri Shaham, Maor Ivgi, Avia Efrat, Jonathan Berant, and Omer Levy. ZeroSCROLLS: A zero-shot benchmark for long text understanding. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 7977–7989, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.536. URL <https://aclanthology.org/2023.findings-emnlp.536>.
- Zejiang Shen, Kyle Lo, Lauren Yu, Nathan Dahlberg, Margo Schlanger, and Doug Downey. Multi-lexsum: Real-world summaries of civil rights lawsuits at multiple granularities. In *Thirty-sixth Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2022. URL <https://openreview.net/forum?id=z1d8fUiS8Cr>.
- Ivan Stelmakh, Yi Luan, Bhuwan Dhingra, and Ming-Wei Chang. ASQA: Factoid questions meet long-form answers. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pp. 8273–8288, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.566. URL <https://aclanthology.org/2022.emnlp-main.566>.
- Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. Roformer: Enhanced transformer with rotary position embedding, 2021. URL <https://arxiv.org/abs/2104.09864>.
- Weiwei Sun, Lingyong Yan, Xinyu Ma, Shuaiqiang Wang, Pengjie Ren, Zhumin Chen, Dawei Yin, and Zhaochun Ren. Is ChatGPT good at search? investigating large language models as re-ranking agents. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 14918–14937, Singapore, December

2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.923. URL <https://aclanthology.org/2023.emnlp-main.923>.

Yi Tay, Mostafa Dehghani, Samira Abnar, Yikang Shen, Dara Bahri, Philip Pham, Jinfeng Rao, Liu Yang, Sebastian Ruder, and Donald Metzler. Long range arena : A benchmark for efficient transformers. In *International Conference on Learning Representations*, 2021. URL <https://openreview.net/forum?id=qVyeW-grC2k>.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M. Dai, Anja Hauth, Katie Millican, David Silver, Melvin Johnson, Ioannis Antonoglou, Julian Schrittwieser, Amelia Glaese, Jilin Chen, Emily Pitler, Timothy Lillcrap, Angeliki Lazaridou, Orhan Firat, James Molloy, Michael Isard, Paul R. Barham, Tom Hennigan, Benjamin Lee, Fabio Viola, Malcolm Reynolds, Yuanzhong Xu, Ryan Doherty, Eli Collins, Clemens Meyer, Eliza Rutherford, Erica Moreira, Kareem Ayoub, Megha Goel, Jack Krawczyk, Cosmo Du, Ed Chi, Heng-Tze Cheng, Eric Ni, Purvi Shah, Patrick Kane, Betty Chan, Manaal Faruqui, Aliaksei Severyn, Hanzhao Lin, YaGuang Li, Yong Cheng, Abe Ittycheriah, Mahdis Mahdieh, Mia Chen, Pei Sun, Dustin Tran, Sumit Bagri, Balaji Lakshminarayanan, Jeremiah Liu, Andras Orban, Fabian Gra, Hao Zhou, Xinying Song, Aurelien Boffy, Harish Ganapathy, Steven Zheng, HyunJeong Choe, goston Weisz, Tao Zhu, Yifeng Lu, Siddharth Gopal, Jarrod Kahn, Maciej Kula, Jeff Pitman, Rushin Shah, Emanuel Taropa, Majd Al Merey, Martin Baeuml, Zhifeng Chen, Laurent El Shafey, Yujing Zhang, Olcan Sercinoglu, George Tucker, Enrique Piqueras, Maxim Krikun, Iain Barr, Nikolay Savinov, Ivo Danihelka, Becca Roelofs, Anas White, Anders Andreassen, Tamara von Glehn, Lakshman Yagati, Mehran Kazemi, Lucas Gonzalez, Misha Khalman, Jakub Sygnowski, Alexandre Frechette, Charlotte Smith, Laura Culp, Lev Proleev, Yi Luan, Xi Chen, James Lottes, Nathan Schucher, Federico Lebron, Alban Rustemi, Natalie Clay, Phil Crone, Tomas Kocisky, Jeffrey Zhao, Bartek Perz, Dian Yu, Heidi Howard, Adam Bloniarz, Jack W. Rae, Han Lu, Laurent Sifre, Marcello Maggioni, Fred Alcober, Dan Garrette, Megan Barnes, Shantanu Thakoor, Jacob Austin, Gabriel Barth-Maroon, William Wong, Rishabh Joshi, Rahma Chaabouni, Deeni Fatiha, Arun Ahuja, Gaurav Singh Tomar, Evan Senter, Martin Chadwick, Ilya Kornakov, Nithya Attaluri, Iaki Iturrate, Ruibo Liu, Yunxuan Li, Sarah Cogan, Jeremy Chen, Chao Jia, Chenjie Gu, Qiao Zhang, Jordan Grimstad, Ale Jakse Hartman, Xavier Garcia, Thanumalayan Sankaranarayanan Pillai, Jacob Devlin, Michael Laskin, Diego de Las Casas, Dasha Valter, Connie Tao, Lorenzo Blanco, Adri Puigdomnech Badia, David Reitter, Mianna Chen, Jenny Brennan, Clara Rivera, Sergey Brin, Shariq Iqbal, Gabriela Surita, Jane Labanowski, Abhi Rao, Stephanie Winkler, Emilio Parisotto, Yiming Gu, Kate Olszewska, Ravi Addanki, Antoine Miech, Annie Louis, Denis Teplyashin, Geoff Brown, Elliot Catt, Jan Bala-guer, Jackie Xiang, Pidong Wang, Zoe Ashwood, Anton Briukhov, Albert Webson, Sanjay Ganapathy, Smit Sanghavi, Ajay Kannan, Ming-Wei Chang, Axel Stjerngren, Josip Djolonga, Yuting Sun, Ankur Bapna, Matthew Aitchison, Pedram Pejman, Henryk Michalewski, Tianhe Yu, Cindy Wang, Juliette Love, Junwhan Ahn, Dawn Bloxwich, Kehang Han, Peter Humphreys, Thibault Sellam, James Bradbury, Varun Godbole, Sina Samangooei, Bogdan Damoc, Alex Kaskasoli, Sbastien M. R. Arnold, Vijay Vasudevan, Shubham Agrawal, Jason Riesa, Dmitry Lepikhin, Richard Tanburn, Srivatsan Srinivasan, Hyeontaek Lim, Sarah Hodgkinson, Pranav Shyam, Johan Ferret, Steven Hand, Ankush Garg, Tom Le Paine, Jian Li, Yujia Li, Minh Giang, Alexander Neitz, Zaheer Abbas, Sarah York, Machel Reid, Elizabeth Cole, Aakanksha Chowdhery, Dipan-jan Das, Dominika Rogoziska, Vitaliy Nikolaev, Pablo Sprechmann, Zachary Nado, Lukas Zilka, Flavien Prost, Luheng He, Marianne Monteiro, Gaurav Mishra, Chris Welty, Josh Newlan, Dawei Jia, Miltiadis Allamanis, Clara Huiyi Hu, Raoul de Liedekerke, Justin Gilmer, Carl Saroufim, Shruti Rijhwani, Shaobo Hou, Disha Shrivastava, Anirudh Baddepudi, Alex Goldin, Adnan Ozturel, Albin Cassirer, Yunhan Xu, Daniel Sohn, Devendra Sachan, Reinald Kim Amplayo, Craig Swanson, Dessie Petrova, Shashi Narayan, Arthur Guez, Siddhartha Brahma, Jessica Landon, Miteyan Patel, Ruizhe Zhao, Kevin Vilella, Luyu Wang, Wenhao Jia, Matthew Rahtz, Mai Gimnez, Legg Yeung, James Keeling, Petko Georgiev, Diana Mincu, Boxi Wu, Salem Haykal, Rachel Saputro, Kiran Vodrahalli, James Qin, Zeynep Cankara, Abhanshu Sharma, Nick Fernando, Will Hawkins, Behnam Neyshabur, Solomon Kim, Adrian Hutter, Priyanka Agrawal, Alex Castro-Ros, George van den Driessche, Tao Wang, Fan Yang, Shuo yin Chang, Paul Komarek, Ross McIlroy, Mario Lui, Guodong Zhang, Wael Farhan, Michael Sharman, Paul Natsev, Paul Michel, Yamini Bansal, Siyuan Qiao, Kris Cao, Siamak Shakeri, Christina Butterfield, Justin Chung, Paul Kishan Rubenstein, Shivani Agrawal, Arthur Mensch, Kedar Soparkar, Karel Lenc,

Timothy Chung, Aedan Pope, Loren Maggiore, Jackie Kay, Priya Jhakra, Shibo Wang, Joshua Maynez, Mary Phuong, Taylor Tobin, Andrea Tacchetti, Maja Trebacz, Kevin Robinson, Yash Katariya, Sebastian Riedel, Paige Bailey, Kefan Xiao, Nimesh Ghelani, Lora Aroyo, Ambrose Slone, Neil Houlsby, Xuehan Xiong, Zhen Yang, Elena Gribovskaya, Jonas Adler, Mateo Wirth, Lisa Lee, Music Li, Thais Kagohara, Jay Pavagadhi, Sophie Bridgers, Anna Bortsova, Sanjay Ghemawat, Zafarali Ahmed, Tianqi Liu, Richard Powell, Vijay Bolina, Mariko Iinuma, Polina Zablotskaia, James Besley, Da-Woon Chung, Timothy Dozat, Ramona Comanescu, Xiance Si, Jeremy Greer, Guolong Su, Martin Polacek, Raphaël Lopez Kaufman, Simon Tokumine, Hexiang Hu, Elena Buchatskaya, Yingjie Miao, Mohamed Elhawaty, Aditya Siddhant, Nenad Tomašev, Jinwei Xing, Christina Greer, Helen Miller, Shereen Ashraf, Aurko Roy, Zizhao Zhang, Ada Ma, Angelos Filos, Milos Besta, Rory Blevins, Ted Klimentko, Chih-Kuan Yeh, Soravit Changpinyo, Jiaqi Mu, Oscar Chang, Mantas Pajarskas, Carrie Muir, Vered Cohen, Charline Le Lan, Krishna Haridasan, Amit Marathe, Steven Hansen, Sholto Douglas, Rajkumar Samuel, Mingqiu Wang, Sophia Austin, Chang Lan, Jiepu Jiang, Justin Chiu, Jaime Alonso Lorenzo, Lars Lowe Sjöstrand, Sébastien Cevey, Zach Gleicher, Thi Avrahami, Anudhyan Boral, Hansa Srinivasan, Vittorio Selo, Rhys May, Konstantinos Aisopos, Léonard Hussenot, Livio Baldini Soares, Kate Baumli, Michael B. Chang, Adrià Recasens, Ben Caine, Alexander Pritzel, Filip Pavetic, Fabio Pardo, Anita Gergely, Justin Frye, Vinay Ramasesh, Dan Horgan, Kartikeya Badola, Nora Kassner, Subhrajit Roy, Ethan Dyer, Víctor Campos Campos, Alex Tomala, Yunhao Tang, Dalia El Badawy, Elspeth White, Basil Mustafa, Oran Lang, Abhishek Jindal, Sharad Vikram, Zhitao Gong, Sergi Caelles, Ross Hemsley, Gregory Thornton, Fangxiaoyu Feng, Wojciech Stokowiec, Ce Zheng, Phoebe Thacker, Çağlar Ünlü, Zhishuai Zhang, Mohammad Saleh, James Svensson, Max Bileschi, Piyush Patil, Ankesh Anand, Roman Ring, Katerina Tsihlias, Arpi Vezer, Marco Selvi, Toby Shevlane, Mikel Rodriguez, Tom Kwiatkowski, Samira Daruki, Keran Rong, Allan Dafoe, Nicholas FitzGerald, Keren Gu-Lemberg, Mina Khan, Lisa Anne Hendricks, Marie Pella, Vladimir Feinberg, James Cobon-Kerr, Tara Sainath, Maribeth Rauh, Sayed Hadi Hashemi, Richard Ives, Yana Hasson, Eric Noland, Yuan Cao, Nathan Byrd, Le Hou, Qingze Wang, Thibault Sottiaux, Michela Paganini, Jean-Baptiste Lespiau, Alexandre Moufarek, Samer Hassan, Kaushik Shivakumar, Joost van Amersfoort, Amol Mandhane, Pratik Joshi, Anirudh Goyal, Matthew Tung, Andrew Brock, Hannah Sheahan, Vedant Misra, Cheng Li, Nemanja Rakićević, Mostafa Dehghani, Fangyu Liu, Sid Mittal, Junhyuk Oh, Seb Noury, Eren Sezener, Fantine Huot, Matthew Lamm, Nicola De Cao, Charlie Chen, Sidharth Mudgal, Romina Stella, Kevin Brooks, Gautam Vasudevan, Chenxi Liu, Mainak Chaitin, Nivedita Melinkeri, Aaron Cohen, Venus Wang, Kristie Seymore, Sergey Zubkov, Rahul Goel, Summer Yue, Sai Krishnakumaran, Brian Albert, Nate Hurley, Motoki Sano, Anhad Mohananey, Jonah Joughin, Egor Filonov, Tomasz Kepa, Yomna Eldawy, Jiawern Lim, Rahul Rishi, Shirin Badiezadegan, Taylor Bos, Jerry Chang, Sanil Jain, Sri Gayatri Sundara Padmanabhan, Subha Puttagunta, Kalpesh Krishna, Leslie Baker, Norbert Kalb, Vamsi Bedapudi, Adam Kurzrok, Shuntong Lei, Anthony Yu, Oren Litvin, Xiang Zhou, Zhichun Wu, Sam Sobell, Andrea Siciliano, Alan Papir, Robby Neale, Jonas Bragagnolo, Tej Toor, Tina Chen, Valentin Anklin, Feiran Wang, Richie Feng, Milad Gholami, Kevin Ling, Lijuan Liu, Jules Walter, Hamid Moghaddam, Arun Kishore, Jakub Adamek, Tyler Mercado, Jonathan Mallinson, Siddhanta Wandekar, Stephen Cagle, Eran Ofek, Guillermo Garrido, Clemens Lombriser, Maksim Mukha, Botu Sun, Hafeezul Rahman Mohammad, Josip Matak, Yadi Qian, Vikas Peswani, Pawel Janus, Quan Yuan, Leif Schelin, Oana David, Ankur Garg, Yifan He, Oleksii Duzhyi, Anton Ålgmyr, Timothée Lottaz, Qi Li, Vikas Yadav, Luyao Xu, Alex Chinien, Rakesh Shivanna, Aleksandr Chuklin, Josie Li, Carrie Spadine, Travis Wolfe, Kareem Mohamed, Subhabrata Das, Zihang Dai, Kyle He, Daniel von Dincklage, Shyam Upadhyay, Akanksha Maurya, Luyan Chi, Sebastian Krause, Khalid Salama, Pam G Rabinovitch, Pavan Kumar Reddy M, Aarush Selvan, Mikhail Dekhtarev, Golnaz Ghiasi, Erdem Guven, Himanshu Gupta, Boyi Liu, Deepak Sharma, Idan Heimlich Shtacher, Shachi Paul, Oscar Akerlund, François-Xavier Aubet, Terry Huang, Chen Zhu, Eric Zhu, Elco Teixeira, Matthew Fritze, Francesco Bertolini, Liana-Eleonora Marinescu, Martin Bølle, Dominik Paulus, Khyatti Gupta, Tejas Latkar, Max Chang, Jason Sanders, Roopa Wilson, Xuwei Wu, Yi-Xuan Tan, Lam Nguyen Thiet, Tulsee Doshi, Sid Lall, Swaroop Mishra, Wanming Chen, Thang Luong, Seth Benjamin, Jasmine Lee, Ewa Andrejczuk, Dominik Rabiej, Vipul Ranjan, Krzysztof Styrz, Pengcheng Yin, Jon Simon, Malcolm Rose Harriott, Mudit Bansal, Alexei Robsky, Geoff Bacon, David Greene, Daniil Mirylenka, Chen Zhou, Obaid Sarvana, Abhimanyu Goyal, Samuel Andermatt, Patrick Siegler, Ben Horn, Assaf Israel, Francesco Pongetti, Chih-Wei "Louis" Chen, Marco Selvatici, Pedro Silva, Kathie Wang, Jackson Tolins, Kelvin Guu, Roey Yogeve, Xiaochen Cai, Alessandro Agostini, Maulik

Shah, Hung Nguyen, Noah Ó Donnaile, Sébastien Pereira, Linda Friso, Adam Stambler, Adam Kurzrok, Chenkai Kuang, Yan Romanikhin, Mark Geller, ZJ Yan, Kane Jang, Cheng-Chun Lee, Wojciech Fica, Eric Malmi, Qijun Tan, Dan Banica, Daniel Balle, Ryan Pham, Yanping Huang, Diana Avram, Hongzhi Shi, Jasjot Singh, Chris Hidey, Niharika Ahuja, Pranab Saxena, Dan Doo-ley, Srividya Pranavi Potharaju, Eileen O'Neill, Anand Gokulchandran, Ryan Foley, Kai Zhao, Mike Dusenberry, Yuan Liu, Pulkit Mehta, Ragha Kotikalapudi, Chalence Safranek-Shrader, Andrew Goodman, Joshua Kessinger, Eran Globen, Prateek Kolhar, Chris Gorgolewski, Ali Ibrahim, Yang Song, Ali Eichenbaum, Thomas Brovelli, Sahitya Potluri, Preethi Lahoti, Cip Baetu, Ali Ghorbani, Charles Chen, Andy Crawford, Shalini Pal, Mukund Sridhar, Petru Gurita, Asier Mujika, Igor Petrovski, Pierre-Louis Cedoz, Chenmei Li, Shiyuan Chen, Niccolò Dal Santo, Siddharth Goyal, Jitesh Punjabi, Karthik Kappaganthu, Chester Kwak, Pallavi LV, Sarmishta Velury, Himadri Choudhury, Jamie Hall, Premal Shah, Ricardo Figueira, Matt Thomas, Minjie Lu, Ting Zhou, Chintu Kumar, Thomas Jurdi, Sharat Chikkerur, Yenai Ma, Adams Yu, Soo Kwak, Victor Åhdel, Sujevan Rajayogam, Travis Choma, Fei Liu, Aditya Barua, Colin Ji, Ji Ho Park, Vincent Hellendoorn, Alex Bailey, Taylan Bilal, Huanjie Zhou, Mehrdad Khatir, Charles Sutton, Wojciech Rzadkowski, Fiona Macintosh, Konstantin Shagin, Paul Medina, Chen Liang, Jinjing Zhou, Pararth Shah, Yingying Bi, Attila Dankovics, Shipra Banga, Sabine Lehmann, Marissa Bredezen, Zifan Lin, John Eric Hoffmann, Jonathan Lai, Raynald Chung, Kai Yang, Nihal Balani, Arthur Bražinskis, Andrei Sozanschi, Matthew Hayes, Héctor Fernández Alcalde, Peter Makarov, Will Chen, Antonio Stella, Liselotte Snijders, Michael Mandl, Ante Kärrman, Paweł Nowak, Xinyi Wu, Alex Dyck, Krishnan Vaidyanathan, Raghavender R, Jessica Mallet, Mitch Rudominer, Eric Johnston, Sushil Mittal, Akhil Udathu, Janara Christensen, Vishal Verma, Zach Irving, Andreas Santucci, Gamaleldin Elsayed, Elnaz Davoodi, Marin Georgiev, Ian Tenney, Nan Hua, Geoffrey Cideron, Edouard Leurent, Mahmoud Alnahlawi, Ionut Georgescu, Nan Wei, Ivy Zheng, Dylan Scandinaro, Heinrich Jiang, Jasper Snoek, Mukund Sundararajan, Xuezhi Wang, Zack Ontiveros, Itay Karo, Jeremy Cole, Vinu Rajashekhar, Lara Tumeh, Eyal Ben-David, Rishub Jain, Jonathan Uesato, Romina Datta, Oskar Bunyan, Shimu Wu, John Zhang, Piotr Stanczyk, Ye Zhang, David Steiner, Subhajit Naskar, Michael Azzam, Matthew Johnson, Adam Paszke, Chung-Cheng Chiu, Jaume Sanchez Elias, Afroz Mohiuddin, Faizan Muhammad, Jin Miao, Andrew Lee, Nino Vieillard, Jane Park, Jiageng Zhang, Jeff Stanway, Drew Garmon, Abhijit Karmarkar, Zhe Dong, Jong Lee, Aviral Kumar, Luowei Zhou, Jonathan Evens, William Isaac, Geoffrey Irving, Edward Loper, Michael Fink, Isha Arkatkar, Nanxin Chen, Izhak Shafran, Ivan Ptrychenko, Zhe Chen, John-son Jia, Anselm Levskaya, Zhenkai Zhu, Peter Grabowski, Yu Mao, Alberto Magni, Kaisheng Yao, Javier Snaider, Norman Casagrande, Evan Palmer, Paul Suganthan, Alfonso Castaño, Irene Giannoumis, Wooyeol Kim, Mikołaj Rybiński, Ashwin Sreevatsa, Jennifer Prendki, David Soergel, Adrian Goedeckemeyer, Willi Gierke, Mohsen Jafari, Meenu Gaba, Jeremy Wiesner, Diana Gage Wright, Yawen Wei, Harsha Vashisht, Yana Kulizhskaya, Jay Hoover, Maigo Le, Lu Li, Chimezie Iwuanyanwu, Lu Liu, Kevin Ramirez, Andrey Khorlin, Albert Cui, Tian LIN, Marcus Wu, Ricardo Aguilar, Keith Pallo, Abhishek Chakladar, Ginger Perng, Elena Allica Abellan, Mingyang Zhang, Ishita Dasgupta, Nate Kushman, Ivo Penchev, Alena Repina, Xihui Wu, Tom van der Weide, Priya Ponnappalli, Caroline Kaplan, Jiri Simsa, Shuangfeng Li, Olivier Dousse, Fan Yang, Jeff Piper, Nathan Ie, Rama Pasumarthi, Nathan Lintz, Anitha Vijayakumar, Daniel Andor, Pedro Valenzuela, Minnie Lui, Cosmin Paduraru, Daiyi Peng, Katherine Lee, Shuyuan Zhang, Somer Greene, Duc Dung Nguyen, Paula Kurylowicz, Cassidy Hardin, Lucas Dixon, Lili Janzer, Kiam Choo, Ziqiang Feng, Biao Zhang, Achintya Singhal, Dayou Du, Dan McKinnon, Natasha Antropova, Tolga Bolukbasi, Orgad Keller, David Reid, Daniel Finchelstein, Maria Abi Raad, Remi Crocker, Peter Hawkins, Robert Dadashi, Colin Gaffney, Ken Franko, Anna Bulanov, Rémi Leblond, Shirley Chung, Harry Askham, Luis C. Cobo, Kelvin Xu, Felix Fischer, Jun Xu, Christina Sorokin, Chris Alberti, Chu-Cheng Lin, Colin Evans, Alek Dimitriev, Hannah Forbes, Dylan Banarse, Zora Tung, Mark Omernick, Colton Bishop, Rachel Sterneck, Rohan Jain, Jiawei Xia, Ehsan Amid, Francesco Piccinno, Xingyu Wang, Praseem Banzal, Daniel J. Mankowitz, Alex Polozov, Victoria Krakovna, Sasha Brown, MohammadHossein Bateni, Dennis Duan, Vlad Firoiu, Meghana Thotakuri, Tom Natan, Matthieu Geist, Ser tan Girgin, Hui Li, Jiayu Ye, Ofir Roval, Reiko Tojo, Michael Kwong, James Lee-Thorp, Christopher Yew, Danila Sinopalnikov, Sabela Ramos, John Mellor, Abhishek Sharma, Kathy Wu, David Miller, Nicolas Sonnerat, Denis Vnukov, Rory Greig, Jennifer Beattie, Emily Caveness, Libin Bai, Julian Eisenschlos, Alex Korchemniy, Tomy Tsai, Mimi Jasarevic, Weize Kong, Phuong Dao, Zeyu Zheng, Frederick Liu, Fan Yang, Rui Zhu, Tian Huey Teh, Jason Sanmiya, Evgeny Gladchenko, Nejc Trdin, Daniel Toyama, Evan Rosen, Sasan Tavakkol, Linting Xue, Chen Elkind, Oliver

Woodman, John Carpenter, George Papamakarios, Rupert Kemp, Sushant Kafle, Tanya Grunina, Rishika Sinha, Alice Talbert, Diane Wu, Denese Owusu-Afriyie, Cosmo Du, Chloe Thornton, Jordi Pont-Tuset, Pradyumna Narayana, Jing Li, Saaber Fatehi, John Wieting, Omar Ajmeri, Benigno Uribe, Yeongil Ko, Laura Knight, Amélie Héliou, Ning Niu, Shane Gu, Chenxi Pang, Yeqing Li, Nir Levine, Ariel Stolovich, Rebeca Santamaria-Fernandez, Sonam Goenka, Wenny Yustalim, Robin Strudel, Ali Elqursh, Charlie Deck, Hyo Lee, Zonglin Li, Kyle Levin, Raphael Hoffmann, Dan Holtmann-Rice, Olivier Bachem, Sho Arora, Christy Koh, Soheil Hassas Yeganeh, Siim Pöder, Mukarram Tariq, Yanhua Sun, Lucian Ionita, Mojtaba Seyedhosseini, Pouya Tafti, Zhiyu Liu, Anmol Gulati, Jasmine Liu, Xinyu Ye, Bart Chrzaszcz, Lily Wang, Nikhil Sethi, Tianrun Li, Ben Brown, Shreya Singh, Wei Fan, Aaron Parisi, Joe Stanton, Vinod Koverkathu, Christopher A. Choquette-Choo, Yunjie Li, TJ Lu, Abe Ittycheriah, Prakash Shroff, Mani Varadarajan, Sanaz Bahargam, Rob Willoughby, David Gaddy, Guillaume Desjardins, Marco Cornero, Brona Robenek, Bhavishya Mittal, Ben Albrecht, Ashish Shenoy, Fedor Moiseev, Henrik Jacobsson, Alireza Ghaffarkhah, Morgane Rivière, Alanna Walton, Clément Crepy, Alicia Parrish, Zongwei Zhou, Clement Farabet, Carey Radebaugh, Praveen Srinivasan, Claudia van der Salm, Andreas Fidl, Salvatore Scellato, Eri Latorre-Chimoto, Hanna Klimczak-Plucińska, David Bridson, Dario de Cesare, Tom Hudson, Piermaria Mendolicchio, Lexi Walker, Alex Morris, Matthew Mauger, Alexey Guseynov, Alison Reid, Seth Odoom, Lucia Loher, Victor Cotruta, Madhavi Yenugula, Dominik Grewe, Anastasia Petrushkina, Tom Duerig, Antonio Sanchez, Steve Yadlowsky, Amy Shen, Amir Globerson, Lynette Webb, Sahil Dua, Dong Li, Surya Bhupatiraju, Dan Hurt, Haroon Qureshi, Ananth Agarwal, Tomer Shani, Matan Eyal, Anuj Khare, Shreyas Ram-mohan Belle, Lei Wang, Chetan Tekur, Mihir Sanjay Kale, Jinliang Wei, Ruoxin Sang, Brennan Saeta, Tyler Liechty, Yi Sun, Yao Zhao, Stephan Lee, Pandu Nayak, Doug Fritz, Manish Reddy Vuyyuru, John Aslanides, Nidhi Vyas, Martin Wicke, Xiao Ma, Evgenii Eltyshov, Nina Martin, Hardie Cate, James Manyika, Keyvan Amiri, Yelin Kim, Xi Xiong, Kai Kang, Florian Luisier, Nilesh Tripuraneni, David Madras, Mandy Guo, Austin Waters, Oliver Wang, Joshua Ainslie, Jason Baldridge, Han Zhang, Garima Pruthi, Jakob Bauer, Feng Yang, Riham Mansour, Jason Gelman, Yang Xu, George Polovets, Ji Liu, Honglong Cai, Warren Chen, XiangHai Sheng, Emily Xue, Sherjil Ozair, Christof Angermueller, Xiaowei Li, Anoop Sinha, Weiren Wang, Julia Wiesinger, Emmanouil Koukoumidis, Yuan Tian, Anand Iyer, Madhu Gurumurthy, Mark Goldenson, Parashar Shah, MK Blake, Hongkun Yu, Anthony Urbanowicz, Jennimaria Palomaki, Chrisantha Fernando, Ken Durden, Harsh Mehta, Nikola Momchev, Elahe Rahimtoroghi, Maria Georgaki, Amit Raul, Sebastian Ruder, Morgan Redshaw, Jinhyuk Lee, Denny Zhou, Komal Jalan, Dinghua Li, Blake Hechtman, Parker Schuh, Milad Nasr, Kieran Milan, Vladimir Mikulic, Juliana Franco, Tim Green, Nam Nguyen, Joe Kelley, Aroma Mahendru, Andrea Hu, Joshua Howland, Ben Vargas, Jeffrey Hui, Kshitij Bansal, Vikram Rao, Rakesh Ghiya, Emma Wang, Ke Ye, Jean Michel Sarr, Melanie Moranski Preston, Madeleine Elish, Steve Li, Aakash Kaku, Jigar Gupta, Ice Pasupat, Da-Cheng Juan, Milan Someswar, Tejvi M., Xinyun Chen, Aida Amini, Alex Fabrikant, Eric Chu, Xuanyi Dong, Amruta Muthal, Senaka Buthpitiya, Sarthak Jauhari, Nan Hua, Urvashi Khandelwal, Ayal Hitron, Jie Ren, Larissa Rinaldi, Shahar Drath, Avigail Dabush, Nan-Jiang Jiang, Harshal Godhia, Uli Sachs, Anthony Chen, Yicheng Fan, Hagai Taitelbaum, Hila Noga, Zhu Yun Dai, James Wang, Chen Liang, Jenny Hamer, Chun-Sung Ferng, Chenel Elkind, Avi Elkind, Aviel Atlas, Paulina Lee, Vít Listík, Mathias Carlen, Jan van de Kerkhof, Marcín Pikuś, Krunoslav Zaher, Paul Müller, Sasha Zykova, Richard Stefanec, Vitaly Gatsko, Christoph Hirsenschall, Ashwin Sethi, Xingyu Federico Xu, Chetan Ahuja, Beth Tsai, Anca Stefanoiu, Bo Feng, Keshav Dhandhanania, Manish Katyal, Akshay Gupta, Atharva Parulekar, Divya Pitta, Jing Zhao, Vivaan Bhatia, Yashodha Bhavnani, Omar Alhadlaq, Xiaolin Li, Peter Danenberg, Dennis Tu, Alex Pine, Vera Filippova, Abhipso Ghosh, Ben Limonchik, Bhargava Urala, Chaitanya Krishna Lanka, Derik Clive, Yi Sun, Edward Li, Hao Wu, Kevin Hongtongsak, Ianna Li, Kalind Thakkar, Kuanysh Omarov, Kushal Majmundar, Michael Alverson, Michael Kucharski, Mohak Patel, Mudit Jain, Maksim Zabelin, Paolo Pelagatti, Rohan Kohli, Saurabh Kumar, Joseph Kim, Swetha Sankar, Vineet Shah, Lakshmi Ramachandruni, Xiangkai Zeng, Ben Bariach, Laura Weidinger, Tu Vu, Alek Andreev, Antoine He, Kevin Hui, Sheleem Kashem, Amar Subramanya, Sissie Hsiao, Demis Hassabis, Koray Kavukcuoglu, Adam Sadovskiy, Quoc Le, Trevor Strohman, Yonghui Wu, Slav Petrov, Jeffrey Dean, and Oriol Vinyals. Gemini: A family of highly capable multimodal models, 2024a. URL <https://arxiv.org/abs/2312.11805>.

Gemini Team, Petko Georgiev, Ving Ian Lei, Ryan Burnell, Libin Bai, Anmol Gulati, Garrett Tanzer, Damien Vincent, Zhufeng Pan, Shibo Wang, Soroosh Mariooryad, Yifan Ding, Xinyang Geng,

Fred Alcober, Roy Frostig, Mark Omernick, Lexi Walker, Cosmin Paduraru, Christina Sorokin, Andrea Tacchetti, Colin Gaffney, Samira Daruki, Olcan Sercinoglu, Zach Gleicher, Juliette Love, Paul Voigtlaender, Rohan Jain, Gabriela Surita, Kareem Mohamed, Rory Blevins, Junwhan Ahn, Tao Zhu, Kornraphop Kawintiranon, Orhan Firat, Yiming Gu, Yujing Zhang, Matthew Rahtz, Manaal Faruqui, Natalie Clay, Justin Gilmer, JD Co-Reyes, Ivo Penchev, Rui Zhu, Nobuyuki Morioka, Kevin Hui, Krishna Haridasan, Victor Campos, Mahdis Mahdieh, Mandy Guo, Samer Hassan, Kevin Kilgour, Arpi Vezer, Heng-Tze Cheng, Raoul de Liedekerke, Siddharth Goyal, Paul Barham, DJ Strouse, Seb Noury, Jonas Adler, Mukund Sundararajan, Sharad Vikram, Dmitry Lepikhin, Michela Paganini, Xavier Garcia, Fan Yang, Dasha Valter, Maja Trebacz, Kiran V-drahalli, Chulayuth Asawaroengchai, Roman Ring, Norbert Kalb, Livio Baldini Soares, Siddhartha Brahma, David Steiner, Tianhe Yu, Fabian Mentzer, Antoine He, Lucas Gonzalez, Bibo Xu, Raphael Lopez Kaufman, Laurent El Shafey, Junhyuk Oh, Tom Hennigan, George van den Driessche, Seth Odoom, Mario Lucic, Becca Roelofs, Sid Lall, Amit Marathe, Betty Chan, Santiago Ontanon, Luheng He, Denis Teplyashin, Jonathan Lai, Phil Crone, Bogdan Damoc, Lewis Ho, Sebastian Riedel, Karel Lenc, Chih-Kuan Yeh, Aakanksha Chowdhery, Yang Xu, Mehran Kazemi, Ehsan Amid, Anastasia Petrushkina, Kevin Swersky, Ali Khodaei, Gowoon Chen, Chris Larkin, Mario Pinto, Geng Yan, Adria Puigdomenech Badia, Piyush Patil, Steven Hansen, Dave Orr, Sebastien M. R. Arnold, Jordan Grimstad, Andrew Dai, Sholto Douglas, Rishika Sinha, Vikas Yadav, Xi Chen, Elena Gribovskaya, Jacob Austin, Jeffrey Zhao, Kaushal Patel, Paul Komarek, Sophia Austin, Sebastian Borgeaud, Linda Friso, Abhimanyu Goyal, Ben Caine, Kris Cao, Da-Woon Chung, Matthew Lamm, Gabe Barth-Maron, Thais Kagohara, Kate Olszewska, Mia Chen, Kaushik Shivakumar, Rishabh Agarwal, Harshal Godhia, Ravi Rajwar, Javier Snaider, Xerxes Dotiwala, Yuan Liu, Aditya Barua, Victor Ungureanu, Yuan Zhang, Bat-Orgil Batsaikhan, Mateo Wirth, James Qin, Ivo Danihelka, Tulsee Doshi, Martin Chadwick, Jilin Chen, Sanil Jain, Quoc Le, Arjun Kar, Madhu Gurusurthy, Cheng Li, Ruoxin Sang, Fangyu Liu, Lampros Lam-prou, Rich Munoz, Nathan Lintz, Harsh Mehta, Heidi Howard, Malcolm Reynolds, Lora Aroyo, Quan Wang, Lorenzo Blanco, Albin Cassirer, Jordan Griffith, Dipanjan Das, Stephan Lee, Jakub Sygnowski, Zach Fisher, James Besley, Richard Powell, Zafarali Ahmed, Dominik Paulus, David Reitter, Zalan Borsos, Rishabh Joshi, Aedan Pope, Steven Hand, Vittorio Selo, Vihan Jain, Nikhil Sethi, Megha Goel, Takaki Makino, Rhys May, Zhen Yang, Johan Schalkwyk, Christina Butterfield, Anja Hauth, Alex Goldin, Will Hawkins, Evan Senter, Sergey Brin, Oliver Woodman, Marvin Ritter, Eric Noland, Minh Giang, Vijay Bolina, Lisa Lee, Tim Blyth, Ian Mackinnon, Machel Reid, Obaid Sarvana, David Silver, Alexander Chen, Lily Wang, Loren Maggiore, Oscar Chang, Nithya Attaluri, Gregory Thornton, Chung-Cheng Chiu, Oskar Bunyan, Nir Levine, Timothy Chung, Evgenii Eltyshv, Xiance Si, Timothy Lillicrap, Demetra Brady, Vaibhav Aggarwal, Boxi Wu, Yuanzhong Xu, Ross McIlroy, Kartikeya Badola, Paramjit Sandhu, Erica Moreira, Wojciech Stokowiec, Ross Hemsley, Dong Li, Alex Tudor, Pranav Shyam, Elahe Rahimtoroghi, Salem Haykal, Pablo Sprechmann, Xiang Zhou, Diana Mincu, Yujia Li, Ravi Addanki, Kalpesh Krishna, Xiao Wu, Alexandre Frechette, Matan Eyal, Allan Dafoe, Dave Lacey, Jay Whang, Thi Avrahami, Ye Zhang, Emanuel Taropa, Hanzhao Lin, Daniel Toyama, Eliza Rutherford, Motoki Sano, Hyun-Jeong Choe, Alex Tomala, Chalance Safranek-Shrader, Nora Kassner, Mantas Pajarskas, Matt Harvey, Sean Sechrist, Meire Fortunato, Christina Lyu, Gamaleldin Elsayed, Chenkai Kuang, James Lottes, Eric Chu, Chao Jia, Chih-Wei Chen, Peter Humphreys, Kate Baumli, Connie Tao, Rajkumar Samuel, Cicero Nogueira dos Santos, Anders Andreassen, Nemanja Rakićević, Dominik Grewe, Aviral Kumar, Stephanie Winkler, Jonathan Caton, Andrew Brock, Sid Dalmia, Hannah Sheahan, Iain Barr, Yingjie Miao, Paul Natsev, Jacob Devlin, Feryal Behbahani, Flavien Prost, Yanhua Sun, Artiom Myaskovsky, Thanumalayan Sankaranarayanan Pillai, Dan Hurt, Angeliki Lazaridou, Xi Xiong, Ce Zheng, Fabio Pardo, Xiaowei Li, Dan Horgan, Joe Stanton, Moran Ambar, Fei Xia, Alejandro Lince, Mingqiu Wang, Basil Mustafa, Albert Webson, Hyo Lee, Rohan Anil, Martin Wicke, Timothy Dozat, Abhishek Sinha, Enrique Piqueras, Elahe Dabir, Shyam Upadhyay, Anudhyan Boral, Lisa Anne Hendricks, Corey Fry, Josip Djolonga, Yi Su, Jake Walker, Jane Labanowski, Ronny Huang, Vedant Misra, Jeremy Chen, RJ Skerry-Ryan, Avi Singh, Shruti Rijhwani, Dian Yu, Alex Castro-Ros, Beer Changpinyo, Romina Datta, Sumit Bagri, Arnar Mar Hrafnkelsson, Marcello Maggioni, Daniel Zheng, Yury Sulsky, Shaobo Hou, Tom Le Paine, Antoine Yang, Jason Riesa, Dominika Rogozinska, Dror Marcus, Dalia El Badawy, Qiao Zhang, Luyu Wang, Helen Miller, Jeremy Greer, Lars Lowe Sjos, Azade Nova, Heiga Zen, Rahma Chaabouni, Mihaela Rosca, Jiepu Jiang, Charlie Chen, Ruibo Liu, Tara Sainath, Maxim Krikun, Alex Polozov, Jean-Baptiste Lespiau, Josh Newlan, Zeynep Cankara, Soo Kwak, Yunhan Xu, Phil Chen, Andy Coenen, Clemens Meyer, Katerina Tsihlias, Ada Ma, Juraj Gottweis,

Jinwei Xing, Chenjie Gu, Jin Miao, Christian Frank, Zeynep Cankara, Sanjay Ganapathy, Ishita Dasgupta, Steph Hughes-Fitt, Heng Chen, David Reid, Keran Rong, Hongmin Fan, Joost van Amersfoort, Vincent Zhuang, Aaron Cohen, Shixiang Shane Gu, Anhad Mohanane, Anastasija Ilic, Taylor Tobin, John Wieting, Anna Bortsova, Phoebe Thacker, Emma Wang, Emily Caveness, Justin Chiu, Eren Sezener, Alex Kaskasoli, Steven Baker, Katie Millican, Mohamed Elhawaty, Kostas Aisopos, Carl Lebsack, Nathan Byrd, Hanjun Dai, Wenhao Jia, Matthew Wiethoff, El-naz Davoodi, Albert Weston, Lakshman Yagati, Arun Ahuja, Isabel Gao, Golan Pundak, Susan Zhang, Michael Azzam, Khe Chai Sim, Sergi Caelles, James Keeling, Abhanshu Sharma, Andy Swing, YaGuang Li, Chenxi Liu, Carrie Grimes Bostock, Yamini Bansal, Zachary Nado, Ankesh Anand, Josh Lipschultz, Abhijit Karmarkar, Lev Proleev, Abe Ittycheriah, Soheil Hassas Yeganeh, George Polovets, Aleksandra Faust, Jiao Sun, Alban Rustemi, Pen Li, Rakesh Shivanna, Jeremiah Liu, Chris Welty, Federico Lebron, Anirudh Baddepudi, Sebastian Krause, Emilio Parisotto, Radu Soricut, Zheng Xu, Dawn Bloxwich, Melvin Johnson, Behnam Neyshabur, Justin Mao-Jones, Renshen Wang, Vinay Ramasesh, Zaheer Abbas, Arthur Guez, Constant Segal, Duc Dung Nguyen, James Svensson, Le Hou, Sarah York, Kieran Milan, Sophie Bridgers, Wiktor Gworek, Marco Tagliasacchi, James Lee-Thorp, Michael Chang, Alexey Guseynov, Ale Jakse Hartman, Michael Kwong, Ruizhe Zhao, Sheleem Kashem, Elizabeth Cole, Antoine Miech, Richard Tanburn, Mary Phuong, Filip Pavetic, Sebastien Cevey, Ramona Comanescu, Richard Ives, Sherry Yang, Cosmo Du, Bo Li, Zizhao Zhang, Mariko Inuma, Clara Huiyi Hu, Aurko Roy, Shaan Bijwadia, Zhenkai Zhu, Danilo Martins, Rachel Saputro, Anita Gergely, Steven Zheng, Dawei Jia, Ioannis Antonoglou, Adam Sadovsky, Shane Gu, Yingying Bi, Alek Andreev, Sina Samangooei, Mina Khan, Tomas Kocisky, Angelos Filos, Chintu Kumar, Colton Bishop, Adams Yu, Sarah Hodgkinson, Sid Mittal, Premal Shah, Alexandre Moufarek, Yong Cheng, Adam Blo-niarz, Jaehoon Lee, Pedram Pejman, Paul Michel, Stephen Spencer, Vladimir Feinberg, Xuehan Xiong, Nikolay Savinov, Charlotte Smith, Siamak Shakeri, Dustin Tran, Mary Chesus, Bernd Bohnet, George Tucker, Tamara von Glehn, Carrie Muir, Yiran Mao, Hideto Kazawa, Ambrose Slone, Kedar Soparkar, Disha Shrivastava, James Cobon-Kerr, Michael Sharman, Jay Pavagadhi, Carlos Araya, Karolis Misiunas, Nimesh Ghelani, Michael Laskin, David Barker, Qiuja Li, Anton Briukhov, Neil Houlsby, Mia Glaese, Balaji Lakshminarayanan, Nathan Schucher, Yunhao Tang, Eli Collins, Hyeontaek Lim, Fangxiaoyu Feng, Adria Recasens, Guangda Lai, Alberto Magni, Nicola De Cao, Aditya Siddhant, Zoe Ashwood, Jordi Orbay, Mostafa Dehghani, Jenny Brennan, Yifan He, Kelvin Xu, Yang Gao, Carl Saroufim, James Molloy, Xinyi Wu, Seb Arnold, Solomon Chang, Julian Schrittwieser, Elena Buchatskaya, Soroush Radpour, Martin Polacek, Skye Giordano, Ankur Bapna, Simon Tokumine, Vincent Hellendoorn, Thibault Sottiaux, Sarah Cogan, Aliaksei Severyn, Mohammad Saleh, Shantanu Thakoor, Laurent Shefey, Siyuan Qiao, Meenu Gaba, Shuo yiin Chang, Craig Swanson, Biao Zhang, Benjamin Lee, Paul Kishan Ruben-stein, Gan Song, Tom Kwiatkowski, Anna Koop, Ajay Kannan, David Kao, Parker Schuh, Axel Stjerngren, Golnaz Ghiasi, Gena Gibson, Luke Vilnis, Ye Yuan, Felipe Tiengo Ferreira, Aish-warya Kamath, Ted Klimenko, Ken Franko, Kefan Xiao, Indro Bhattacharya, Miteyan Patel, Rui Wang, Alex Morris, Robin Strudel, Vivek Sharma, Peter Choy, Sayed Hadi Hashemi, Jessica Landon, Mara Finkelstein, Priya Jhakra, Justin Frye, Megan Barnes, Matthew Mauger, Dennis Daun, Khuslen Baatarsukh, Matthew Tung, Wael Farhan, Henryk Michalewski, Fabio Viola, Fel-lix de Chaumont Quitry, Charline Le Lan, Tom Hudson, Qingze Wang, Felix Fischer, Ivy Zheng, Elspeth White, Anca Dragan, Jean baptiste Alayrac, Eric Ni, Alexander Pritzel, Adam Iwan-icki, Michael Isard, Anna Bulanova, Lukas Zilka, Ethan Dyer, Devendra Sachan, Srivatsan Srinivasan, Hannah Muckenhirn, Honglong Cai, Amol Mandhane, Mukarram Tariq, Jack W. Rae, Gary Wang, Kareem Ayoub, Nicholas FitzGerald, Yao Zhao, Woohyun Han, Chris Alberti, Dan Gar-rette, Kashyap Krishnakumar, Mai Gimenez, Anselm Levskaya, Daniel Sohn, Josip Matak, Inaki Iturrate, Michael B. Chang, Jackie Xiang, Yuan Cao, Nishant Ranka, Geoff Brown, Adrian Hut-ter, Vahab Mirrokni, Nanxin Chen, Kaisheng Yao, Zoltan Egyed, Francois Galilee, Tyler Liechty, Praveen Kallakuri, Evan Palmer, Sanjay Ghemawat, Jasmine Liu, David Tao, Chloe Thornton, Tim Green, Mimi Jasarevic, Sharon Lin, Victor Cotruta, Yi-Xuan Tan, Noah Fiedel, Hongkun Yu, Ed Chi, Alexander Neitz, Jens Heitkaemper, Anu Sinha, Denny Zhou, Yi Sun, Charbel Kaed, Brice Hulse, Swaroop Mishra, Maria Georgaki, Sneha Kudugunta, Clement Farabet, Izhak Shafran, Daniel Vlasic, Anton Tsitsulin, Rajagopal Ananthanarayanan, Alen Carin, Guolong Su, Pei Sun, Shashank V, Gabriel Carvajal, Josef Broder, Iulia Comsa, Alena Repina, William Wong, Warren Weilun Chen, Peter Hawkins, Egor Filonov, Lucia Loher, Christoph Hirnschall, Weiye Wang, Jingchen Ye, Andrea Burns, Hardie Cate, Diana Gage Wright, Federico Piccinini, Lei Zhang, Chu-Cheng Lin, Ionel Gog, Yana Kulizhskaya, Ashwin Sreevatsa, Shuang Song, Luis C.

Cobo, Anand Iyer, Chetan Tekur, Guillermo Garrido, Zhuyun Xiao, Rupert Kemp, Huaixiu Steven Zheng, Hui Li, Ananth Agarwal, Christel Ngani, Kati Goshvadi, Rebeca Santamaria-Fernandez, Wojciech Fica, Xinyun Chen, Chris Gorgolewski, Sean Sun, Roopal Garg, Xinyu Ye, S. M. Ali Eslami, Nan Hua, Jon Simon, Pratik Joshi, Yelin Kim, Ian Tenney, Sahitya Potluri, Lam Nguyen Thiet, Quan Yuan, Florian Luisier, Alexandra Chronopoulou, Salvatore Scellato, Praveen Srinivasan, Minmin Chen, Vinod Koverkathu, Valentin Dalibard, Yaming Xu, Brennan Saeta, Keith Anderson, Thibault Sellam, Nick Fernando, Fantine Huot, Junehyuk Jung, Mani Varadarajan, Michael Quinn, Amit Raul, Maigo Le, Ruslan Habalov, Jon Clark, Komal Jalan, Kalesha Bullard, Achintya Singhal, Thang Luong, Boyu Wang, Sujevan Rajayogam, Julian Eisenschlos, Johnson Jia, Daniel Finchelstein, Alex Yakubovich, Daniel Balle, Michael Fink, Sameer Agarwal, Jing Li, Dj Dvijotham, Shalini Pal, Kai Kang, Jaclyn Konzelmann, Jennifer Beattie, Olivier Dousse, Diane Wu, Remi Crocker, Chen Elkind, Siddhartha Reddy Jonnalagadda, Jong Lee, Dan Holtmann-Rice, Krystal Kallarackal, Rosanne Liu, Denis Vnukov, Neera Vats, Luca Invernizzi, Mohsen Jafari, Huanjie Zhou, Lilly Taylor, Jennifer Prendki, Marcus Wu, Tom Eccles, Tianqi Liu, Kavya Kopparapu, Francoise Beaufays, Christof Angermueller, Andreea Marzoca, Shourya Sarcar, Hilaral Dib, Jeff Stanway, Frank Perbet, Nejc Trdin, Rachel Sterneck, Andrey Khorlin, Dinghua Li, Xihui Wu, Sonam Goenka, David Madras, Sasha Goldshtein, Willi Gierke, Tong Zhou, Yaxin Liu, Yannie Liang, Anais White, Yunjie Li, Shreya Singh, Sanaz Bahargam, Mark Epstein, Sujoy Basu, Li Lao, Adnan Ozturk, Carl Crous, Alex Zhai, Han Lu, Zora Tung, Neeraj Gaur, Alanna Walton, Lucas Dixon, Ming Zhang, Amir Globerson, Grant Uy, Andrew Bolt, Olivia Wiles, Milad Nasr, Ilia Shumailov, Marco Selvi, Francesco Piccinno, Ricardo Aguilar, Sara McCarthy, Misha Khalman, Mrinal Shukla, Vlado Galic, John Carpenter, Kevin Vilella, Haibin Zhang, Harry Richardson, James Martens, Matko Bosnjak, Shreyas Rammohan Belle, Jeff Seibert, Mahmoud Alnahlawi, Brian McWilliams, Sankalp Singh, Annie Louis, Wen Ding, Dan Popovici, Lenin Simicich, Laura Knight, Pulkit Mehta, Nishesh Gupta, Chongyang Shi, Saaber Fatehi, Jovana Mitrovic, Alex Grills, Joseph Pagadora, Dessie Petrova, Danielle Eisenbud, Zhishuai Zhang, Damion Yates, Bhavishya Mittal, Nilesh Tripuraneni, Yannis Assael, Thomas Brovelli, Prateek Jain, Mihajlo Velimirovic, Canfer Akbulut, Jiaqi Mu, Wolfgang Macherey, Ravin Kumar, Jun Xu, Haroon Qureshi, Gheorghe Comanici, Jeremy Wiesner, Zhitao Gong, Anton Ruddock, Matthias Bauer, Nick Felt, Anirudh GP, Anurag Arnab, Dustin Zelle, Jonas Rothfuss, Bill Rosgen, Ashish Shenoy, Bryan Seybold, Xinjian Li, Jayaram Mudigonda, Goker Erdogan, Jiawei Xia, Jiri Simsa, Andrea Michi, Yi Yao, Christopher Yew, Steven Kan, Isaac Caswell, Carey Radebaugh, Andre Elisseeff, Pedro Valenzuela, Kay McKinney, Kim Paterson, Albert Cui, Eri Latorre-Chimoto, Solomon Kim, William Zeng, Ken Durden, Priya Ponnappalli, Tiberiu Sosea, Christopher A. Choquette-Choo, James Manyika, Brona Robenek, Harsha Vashisht, Sebastien Pereira, Hoi Lam, Marko Velic, Denese Owusu-Afriyie, Katherine Lee, Tolga Bolukbasi, Alicia Parrish, Shawn Lu, Jane Park, Balaji Venkatraman, Alice Talbert, Lambert Rosique, Yuchung Cheng, Andrei Sozanschi, Adam Paszke, Praveen Kumar, Jessica Austin, Lu Li, Khalid Salama, Wooyeol Kim, Nandita Dukkipati, Anthony Baryshnikov, Christos Kaplanis, XiangHai Sheng, Yuri Chervonyi, Caglar Unlu, Diego de Las Casas, Harry Askham, Kathryn Tunyasuvunakool, Felix Gimeno, Siim Poder, Chester Kwak, Matt Miecznikowski, Vahab Mirrokni, Alek Dimitriev, Aaron Parisi, Danyi Liu, Tomy Tsai, Toby Shevlane, Christina Kouridi, Drew Garmon, Adrian Goedeckemeyer, Adam R. Brown, Anitha Vijayakumar, Ali Elqursh, Sadegh Jazayeri, Jin Huang, Sara Mc Carthy, Jay Hoover, Lucy Kim, Sandeep Kumar, Wei Chen, Courtney Biles, Garrett Bingham, Evan Rosen, Lisa Wang, Qijun Tan, David Engel, Francesco Pongetti, Dario de Cesare, Dongseong Hwang, Lily Yu, Jennifer Pullman, Srini Narayanan, Kyle Levin, Siddharth Gopal, Megan Li, Asaf Aharoni, Trieu Trinh, Jessica Lo, Norman Casagrande, Roopali Vij, Loic Matthey, Bramandia Ramadhana, Austin Matthews, CJ Carey, Matthew Johnson, Kremena Goranova, Rohin Shah, Shereen Ashraf, Kingshuk Dasgupta, Rasmus Larsen, Yicheng Wang, Manish Reddy Vuyyuru, Chong Jiang, Joana Ijazi, Kazuki Osawa, Celine Smith, Ramya Sree Boppana, Taylan Bilal, Yuma Koizumi, Ying Xu, Yasemin Altun, Nir Shabat, Ben Bariach, Alex Korchemniy, Kiam Choo, Olaf Ronneberger, Chimezie Iwuanyanwu, Shubin Zhao, David Soergel, Cho-Jui Hsieh, Irene Cai, Shariq Iqbal, Martin Sundermeyer, Zhe Chen, Elie Bursztein, Chaitanya Malaviya, Fadi Biadisy, Prakash Shroff, Inderjit Dhillon, Tejasi Latkar, Chris Dyer, Hannah Forbes, Massimo Nicosia, Vitaly Nikolaev, Somer Greene, Marin Georgiev, Pidong Wang, Nina Martin, Hanie Sedghi, John Zhang, Praseem Banzal, Doug Fritz, Vikram Rao, Xuezhi Wang, Jiageng Zhang, Viorica Patraucean, Dayou Du, Igor Mordatch, Ivan Jurin, Lewis Liu, Ayush Dubey, Abhi Mohan, Janek Nowakowski, Vlad-Doru Ion, Nan Wei, Reiko Tojo, Maria Abi Raad, Drew A. Hudson, Vaishakh Keshava, Shubham Agrawal, Kevin Ramirez, Zhichun Wu, Hoang

- Nguyen, Ji Liu, Madhavi Sewak, Bryce Petrini, DongHyun Choi, Ivan Philips, Ziyue Wang, Ioana Bica, Ankush Garg, Jarek Wilkiewicz, Priyanka Agrawal, Xiaowei Li, Danhao Guo, Emily Xue, Naseer Shaik, Andrew Leach, Sadh MNM Khan, Julia Wiesinger, Sammy Jerome, Abhishek Chakladar, Alek Wenjiao Wang, Tina Ornduff, Folake Abu, Alireza Ghaffarkhah, Marcus Wainwright, Mario Cortes, Frederick Liu, Joshua Maynez, Andreas Terzis, Pouya Samangouei, Riham Mansour, Tomasz Kepa, François-Xavier Aubet, Anton Algymr, Dan Banica, Agoston Weisz, Andras Orban, Alexandre Senges, Ewa Andrejczuk, Mark Geller, Niccolo Dal Santo, Valentin Anklin, Majd Al Merey, Martin Baeuml, Trevor Strohmman, Junwen Bai, Slav Petrov, Yonghui Wu, Demis Hassabis, Koray Kavukcuoglu, Jeffrey Dean, and Oriol Vinyals. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context, 2024b. URL <https://arxiv.org/abs/2403.05530>.
- Jamba Team, Barak Lenz, Alan Arazi, Amir Bergman, Avshalom Manevich, Barak Peleg, Ben Aviram, Chen Almagor, Clara Fridman, Dan Padnos, Daniel Gissin, Daniel Jannai, Dor Muhlgay, Dor Zimberg, Edden M Gerber, Elad Dolev, Eran Krakovsky, Erez Safahi, Erez Schwartz, Gal Cohen, Gal Shachaf, Haim Rozenblum, Hofit Bata, Ido Blass, Inbal Magar, Itay Dalmedigos, Jhonathan Osin, Julie Fadlon, Maria Rozman, Matan Danos, Michael Gokhman, Mor Zisman, Naama Gidron, Nir Ratner, Noam Gat, Noam Rozen, Oded Fried, Ohad Leshno, Omer Antverg, Omri Abend, Opher Lieber, Or Dagan, Orit Cohavi, Raz Alon, Ro'i Belson, Roi Cohen, Rom Gilad, Roman Glozman, Shahar Lev, Shaked Meirom, Tal Delbari, Tal Ness, Tomer Asida, Tom Ben Gal, Tom Braude, Uriya Pumerantz, Yehoshua Cohen, Yonatan Belinkov, Yuval Globerson, Yuval Peleg Levy, and Yoav Shoham. Jamba-1.5: Hybrid transformer-mamba models at scale, 2024c. URL <https://arxiv.org/abs/2408.12570>.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurelien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. Llama 2: Open foundation and fine-tuned chat models, 2023.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in Neural Information Processing Systems (NIPS)*, 30, 2017. URL <https://papers.nips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-Abstract.html>.
- Chonghua Wang, Haodong Duan, Songyang Zhang, Dahua Lin, and Kai Chen. Ada-LEval: Evaluating long-context LLMs with length-adaptable benchmarks. In Kevin Duh, Helena Gomez, and Steven Bethard (eds.), *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 3712–3724, Mexico City, Mexico, June 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024.naacl-long.205. URL <https://aclanthology.org/2024.naacl-long.205>.
- Cunxiang Wang, Ruoxi Ning, Boqi Pan, Tonghui Wu, Qipeng Guo, Cheng Deng, Guangsheng Bao, Xiangkun Hu, Zheng Zhang, Qian Wang, and Yue Zhang. Novelqa: Benchmarking question answering on documents exceeding 200k tokens, 2024b. URL <https://arxiv.org/abs/2403.12766>.
- Minzheng Wang, Longze Chen, Fu Cheng, Shengyi Liao, Xinghua Zhang, Bingli Wu, Haiyang Yu, Nan Xu, Lei Zhang, Run Luo, Yunshui Li, Min Yang, Fei Huang, and Yongbin Li. Leave no document behind: Benchmarking long-context LLMs with extended multi-doc QA. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 5627–5646, Miami, Florida, USA, Novem-

- ber 2024c. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.322. URL <https://aclanthology.org/2024.emnlp-main.322/>.
- Jerry Wei, Jason Wei, Yi Tay, Dustin Tran, Albert Webson, Yifeng Lu, Xinyun Chen, Hanxiao Liu, Da Huang, Denny Zhou, and Tengyu Ma. Larger language models do in-context learning differently, 2023. URL <https://arxiv.org/abs/2303.03846>.
- Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Huggingface’s transformers: State-of-the-art natural language processing, 2020. URL <https://arxiv.org/abs/1910.03771>.
- Wenhan Xiong, Jingyu Liu, Igor Molybog, Hejia Zhang, Prajjwal Bhargava, Rui Hou, Louis Martin, Rashi Rungta, Karthik Abinav Sankararaman, Barlas Oguz, Madian Khabsa, Han Fang, Yashar Mehdad, Sharan Narang, Kshitiz Malik, Angela Fan, Shruti Bhosale, Sergey Edunov, Mike Lewis, Sinong Wang, and Hao Ma. Effective long-context scaling of foundation models, 2023.
- Xiaoyue Xu, Qinyuan Ye, and Xiang Ren. Stress-testing long-context language models with lifelong ICL and task haystack. In *First Workshop on Long-Context Foundation Models @ ICML 2024*, 2024. URL <https://openreview.net/forum?id=5ltgEKXnZt>.
- An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jialong Tang, Jialin Wang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Ma, Jianxin Yang, Jin Xu, Jingren Zhou, Jinze Bai, Jinzheng He, Junyang Lin, Kai Dang, Keming Lu, Keqin Chen, Kexin Yang, Mei Li, Mingfeng Xue, Na Ni, Pei Zhang, Peng Wang, Ru Peng, Rui Men, Ruize Gao, Runji Lin, Shijie Wang, Shuai Bai, Sinan Tan, Tianhang Zhu, Tianhao Li, Tianyu Liu, Wenbin Ge, Xiaodong Deng, Xiaohuan Zhou, Xingzhang Ren, Xinyu Zhang, Xipin Wei, Xuancheng Ren, Xuejing Liu, Yang Fan, Yang Yao, Yichang Zhang, Yu Wan, Yunfei Chu, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, Zhifang Guo, and Zhihao Fan. Qwen2 technical report, 2024. URL <https://arxiv.org/abs/2407.10671>.
- An Yang, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoyan Huang, Jiandong Jiang, Jianhong Tu, Jianwei Zhang, Jingren Zhou, Junyang Lin, Kai Dang, Kexin Yang, Le Yu, Mei Li, Minmin Sun, Qin Zhu, Rui Men, Tao He, Weijia Xu, Wenbiao Yin, Wenyuan Yu, Xiafei Qiu, Xingzhang Ren, Xinlong Yang, Yong Li, Zhiying Xu, and Zipeng Zhang. Qwen2.5-1m technical report, 2025. URL <https://arxiv.org/abs/2501.15383>.
- Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun’ichi Tsujii (eds.), *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2369–2380, Brussels, Belgium, October–November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1259. URL <https://aclanthology.org/D18-1259>.
- Howard Yen, Tianyu Gao, and Danqi Chen. Long-context language modeling with parallel context encoding. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2588–2610, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.142. URL <https://aclanthology.org/2024.acl-long.142>.
- Tao Yuan, Xuefei Ning, Dong Zhou, Zhijie Yang, Shiyao Li, Minghui Zhuang, Zheyue Tan, Zhuayu Yao, Dahua Lin, Boxun Li, Guohao Dai, Shengen Yan, and Yu Wang. Lv-eval: A balanced long-context benchmark with 5 length levels up to 256k, 2024. URL <https://arxiv.org/abs/2402.05136>.
- Shiyue Zhang and Mohit Bansal. Finding a balanced degree of automation for summary evaluation. In *Empirical Methods in Natural Language Processing (EMNLP)*, pp. 6617–6632, 2021. doi: 10.18653/v1/2021.emnlp-main.531. URL <https://aclanthology.org/2021.emnlp-main.531>.

Xin Zhang, Yanzhao Zhang, Dingkun Long, Wen Xie, Ziqi Dai, Jialong Tang, Huan Lin, Baosong Yang, Pengjun Xie, Fei Huang, Meishan Zhang, Wenjie Li, and Min Zhang. mgte: Generalized long-context text representation and reranking models for multilingual text retrieval, 2024a. URL <https://arxiv.org/abs/2407.19669>.

Xinrong Zhang, Yingfa Chen, Shengding Hu, Zihang Xu, Junhao Chen, Moo Khai Hao, Xu Han, Zhen Leng Thai, Shuo Wang, Zhiyuan Liu, and Maosong Sun. ∞ bench: Extending long context evaluation beyond 100k tokens, 2024b. URL <https://arxiv.org/abs/2402.13718>.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2023. URL <https://openreview.net/forum?id=ucCHPGDlao>.

A COMPARISON WITH OTHER BENCHMARKS

Due to the lack of large-scale human studies on long-context language models, discerning the true rankings of LCLMs remains challenging. Therefore, we rely on previous works and empirical observations to guide our expectations. Specifically, the Gemini 1.5 report demonstrates that larger models consistently outperform smaller ones at handling long contexts—both qualitatively and quantitatively across the Gemini, GPT, and Claude model families (Section 5.2, Tables 4 and 5 Team et al., 2024b). Although their evaluation suite is not publicly available, these results align with commonly observed patterns in language model performance. Given that obtaining ground truth rankings through human evaluation is prohibitively expensive and practically infeasible, relying on such well-established patterns is reasonable. In this section, we further examine HELMET’s improvements over existing benchmarks through direct comparisons of model rankings and performance, supported by careful ablation studies.

A.1 RESULTS

We build upon previous datasets and refine evaluation settings to better reflect model capabilities. Specifically, we evaluate models on ∞ BENCH, another benchmark that evaluates long-context at 128K tokens. The results reproduced from the original authors’ code are shown in Table 6. The numerical results for Figure 1 are presented in Table 5.

Upon closer inspection, we find that a set of open-sourced models’ ranking and performance on HELMET and ∞ BENCH in Table 9. In addition to the previously noted performance discrepancy between Llama-3.1-8B-Instruct and Llama-3.1-70B-Instruct, we observe that all Llama-3.2 models degenerate in performance on ∞ BENCH at input length 128K. However, on HELMET, the Llama-3.2 models, especially Llama-3.2-3B-Instruct, rank well against other open-source models. Upon qualitative examination, we find that the Llama 3.2 models are able to produce coherent and useful generation at long contexts with better prompting strategies from HELMET, such as adding in-context learning examples.

Our ablation study on few-shot demonstrations in Table 8 shows that 2-shot demonstrations substantially improve base model performance, better reflecting real-world usage patterns. As shown in Table 7, improved instructions and prompting enable smaller Llama-3.2 models to compete effectively with larger models. Thus, HELMET provides a better and more realistic reflection of how these models would be used in practice over previous benchmarks. These findings demonstrate that HELMET provides a more accurate and practical assessment of model capabilities compared to previous benchmarks.

Table 5: Results with 128k input length across different benchmarks.

Model	Claimed Length	NIAH	RULER	∞ BENCH	HELMET
GPT-4o-mini	128000	100.0	80.8	51.9	54.1
GPT-4o-08	128000	100.0	93.3	57.1	63.8
Gemini-1.5-Flash	1048576	100.0	86.6	50.8	50.7
Gemini-1.5-Pro	2097152	45.3	65.3	60.3	62.7
Llama-3.1-8B-Inst	131072	100.0	81.3	44.1	47.0
Llama-3.1-70B-Inst	131072	100.0	75.8	39.7	49.3

A.2 DISCUSSIONS

Many existing long-context language modeling benchmarks are studied in isolated settings, such as synthetic tasks (Hsieh et al., 2024; Li et al., 2024b; Levy et al., 2024; Laban et al., 2024), in-context learning (Anil et al., 2024; Bertsch et al., 2024; Li et al., 2024c; Agarwal et al., 2024), summarization (Chang et al., 2024; Kim et al., 2024), and retrieval-augmented settings (Lee et al., 2024). However, these works lack a unified evaluation across diverse downstream tasks.

There are also benchmarks that sought to unify different datasets, such as ∞ BENCH (Zhang et al., 2024b), LongBench (Bai et al., 2024), L-Eval (An et al., 2024), LV-Eval (Yuan et al., 2024), and

Table 6: Results on ∞ BENCH(Zhang et al., 2024b). We report numbers from running the original authors repo: <https://github.com/OpenBMB/InfiniteBench>. The original code did not support evaluation of the Gemini and Llama 3 models at the time of access, so we evaluate them by following the script and template for GPT-4 and open-source models, respectively. We exclude coding tasks from the evaluation suite since it is out of the scope for general long-context language modeling tasks.

Model	MC	QA	Sum	Diag	Calc	Find	Number	PassKey	KV	Avg.
GPT4	75.9	23.7	10.7	18.5	0.0	47.1	100.0	100.0	58.8	44.9
GPT-4o-05	88.2	37.9	23.7	28.5	0.0	58.6	100.0	100.0	94.2	55.4
GPT-4o-08	86.5	26.0	21.5	51.0	0.0	58.9	100.0	100.0	99.8	57.1
GPT-4o-mini	78.2	19.1	24.8	21.5	0.0	69.7	100.0	100.0	80.4	51.9
Gemini-1.5-Flash	76.0	42.1	30.0	55.8	0.0	47.4	100.0	100.0	31.4	50.8
Gemini-1.5-Pro	77.5	27.7	29.0	97.5	0.0	58.0	100.0	100.0	70.4	60.3
Llama-3.1-8B	56.8	8.8	14.3	0.5	0.0	22.0	99.7	100.0	18.8	33.0
Llama-3.1-8B-Inst	67.2	15.5	26.7	23.0	0.0	33.1	99.5	100.0	55.0	44.1
Llama-3.1-70B	66.4	9.2	17.5	8.5	0.0	32.3	100.0	100.0	13.4	35.1
Llama-3.1-70B-Inst	75.5	23.3	31.3	18.0	0.0	43.1	99.7	100.0	2.6	39.7
Llama-3.2-1B	2.2	1.4	8.6	4.5	0.0	0.0	1.5	0.0	0.0	2.0
Llama-3.2-1B-Instruct	3.5	1.4	12.5	5.5	0.0	0.0	0.0	0.0	0.0	2.4
Llama-3.2-3B	1.3	1.2	7.6	4.5	0.0	0.0	1.7	0.0	0.0	1.9
Llama-3.2-3B-Instruct	2.2	1.6	13.3	4.5	0.0	0.0	1.7	1.7	0.0	2.8

Table 7: We compare the results on ∞ BENCH multiple-choice (MC) and question answering (QA) tasks between the original authors and HELMET. In our implementation, we leverage refined prompts and carefully crafted parsing scripts to ensure robust and fair evaluation. For example, we find that Llama-3.2 models are actually much better long-context language models than ∞ BENCH would suggest.

Model	Claimed Length	Original		HELMET	
		MC	QA	MC	QA
GPT-4o-mini	128000	88.2	37.9	71.0	44.5
GPT-4o-05	128000	86.5	26.0	76.0	53.0
GPT-4o-08	128000	78.2	19.1	73.0	47.9
Gemini-1.5-Flash	1048576	76.0	42.1	79.1	51.7
Gemini-1.5-Pro	2097152	77.5	27.7	83.3	50.9
Llama-3.1-8B	131072	56.8	8.8	54.0	38.8
Llama-3.1-8B-Inst	131072	67.2	15.5	49.0	40.3
Llama-3.2-1B	131072	2.2	1.4	21.0	17.6
Llama-3.2-1B-Inst	131072	3.5	1.4	16.0	13.3
Llama-3.2-3B	131072	1.3	1.2	36.0	31.0
Llama-3.2-3B-Inst	131072	2.2	1.6	42.0	20.6

ZeroSCROLLS (Shaham et al., 2023). Many of these benchmarks are still limited by the context length, evaluation metrics, or both. Most similar to our work, ∞ BENCH(Zhang et al. (2024b)) also evaluates models at context lengths at 128K tokens. However, their evaluation settings are limited to a few domains—synthetic, QA, and summarization. Although they also evaluate coding tasks, the domain is limited to code-specialized models outside of the realm of general-purpose language models. Furthermore, their summarization evaluations lack robust evaluation and still rely on ROUGE scores. Similarly, LV-Eval (Yuan et al., 2024) evaluates long-context models across different lengths but is limited to the QA tasks. Furthermore, we are the first to evaluate existing LCLMs comprehensively—we evaluate 59 models of different sizes and architectures, which enables previously unavailable insights into the correlation across diverse tasks and the landscape of current models.

Table 8: We evaluate the performance of models on a subset of HELMET tasks with 0-shot and 2-shot demonstrations at 128k input length to understand the impact of ICL on model performance, averaged across three random seeds. The standard deviation across three runs are shown in the subscript. We observe that the performance is generally higher for 2-shot demonstrations compared to 0-shot demonstrations. Crucially, the 2-shot examples enable base models to achieve higher results that reflect the model’s long-context capabilities in realistic settings, such as for MSMARCO and JSON KV. ^bdenotes base models.

Model	JSON KV		NQ		MSMARCO		∞ BENCH MC		∞ BENCH QA	
	0 shot	2 shot	0 shot	2 shot	0 shot	2 shot	0 shot	2 shot	0 shot	2 shot
GPT-4o-mini	92.3 _{5.5}	93.7 _{2.1}	57.8 _{1.1}	60.4 _{2.6}	24.8 _{0.7}	31.4 _{1.1}	72.0 _{2.6}	69.3 _{4.7}	28.8 _{1.9}	47.1 _{4.4}
GPT-4o-05	99.3 _{0.6}	36.7 _{7.1}	59.4 _{4.0}	63.0 _{2.1}	42.7 _{0.9}	46.8 _{1.3}	73.7 _{0.6}	76.3 _{0.6}	49.1 _{1.9}	51.3 _{3.4}
GPT-4o-08	100.0 _{0.0}	100.0 _{0.0}	58.5 _{2.0}	61.9 _{4.5}	46.6 _{0.3}	48.7 _{1.0}	75.3 _{2.5}	72.7 _{0.6}	29.8 _{0.9}	48.6 _{1.5}
Gemini-1.5-Flash	98.3 _{0.6}	99.0 _{1.0}	53.7 _{5.9}	51.5 _{4.5}	44.9 _{3.0}	49.9 _{0.9}	73.9 _{2.3}	77.1 _{3.2}	48.2 _{4.7}	49.9 _{2.6}
Gemini-1.5-Pro	97.7 _{0.6}	93.7 _{2.3}	62.2 _{2.6}	59.2 _{2.7}	57.1 _{0.9}	58.4 _{0.3}	83.6 _{2.8}	83.3 _{0.7}	46.4 _{1.8}	47.2 _{3.2}
Llama-3.1-8B ^b	77.3 _{2.1}	98.0 _{1.0}	45.7 _{2.1}	44.9 _{3.9}	0.1 _{0.0}	7.5 _{0.5}	55.3 _{5.5}	53.3 _{8.0}	36.1 _{2.0}	36.6 _{2.1}
Llama-3.1-8B-Inst	96.0 _{1.0}	95.7 _{0.6}	48.4 _{1.3}	48.9 _{2.6}	5.4 _{0.0}	13.8 _{1.1}	49.7 _{2.1}	52.0 _{2.6}	29.1 _{2.0}	37.9 _{2.6}
Llama-3.2-1B ^b	34.0 _{3.5}	34.3 _{2.1}	25.1 _{0.7}	23.2 _{2.8}	0.3 _{0.0}	4.8 _{0.5}	23.0 _{2.6}	22.7 _{1.5}	18.9 _{2.5}	18.9 _{3.3}
Llama-3.2-1B-Inst	6.3 _{1.5}	9.3 _{3.2}	23.3 _{4.4}	22.9 _{1.4}	0.0 _{0.0}	0.5 _{0.3}	16.0 _{2.6}	16.3 _{2.5}	12.6 _{0.4}	12.7 _{0.5}
Llama-3.2-3B ^b	30.3 _{2.1}	54.0 _{8.9}	40.2 _{2.0}	42.3 _{4.1}	0.1 _{0.0}	6.0 _{1.3}	43.0 _{1.0}	40.7 _{7.2}	31.3 _{1.1}	31.6 _{2.2}
Llama-3.2-3B-Inst	31.3 _{2.3}	36.7 _{2.5}	44.2 _{2.5}	42.8 _{3.8}	0.2 _{0.0}	0.9 _{0.2}	36.0 _{2.0}	40.0 _{3.5}	17.8 _{1.2}	19.7 _{0.8}

Table 9: Comparison of model rankings on HELMET and ∞ BENCH.

Model	HELMET	Model	InfBench
Llama-3.1-70B-Inst	49.3	Llama-3.1-8B-Inst	46.7
Llama-3.1-8B-Inst	47.0	Llama-3.1-70B-Inst	43.7
Llama-3.1-70B	41.3	Yi-34B-200k	43.1
Yi-34B-200k	38.3	Llama-3.1-70B	38.6
Llama-3.2-3B-Inst	36.9	Yi-9B-200k	37.6
Llama-3.1-8B	35.6	Llama-3.1-8B	35.7
Yi-9B-200k	33.0	Yi-6B-200k	32.0
Llama-3.2-3B	31.9	Llama-3.2-3B-Inst	2.8
Yi-6B-200k	26.3	Llama-3.2-1B-Inst	2.6
Llama-3.2-1B-Inst	24.6	Llama-3.2-1B	2.0
Llama-3.2-1B	21.2	Llama-3.2-3B	1.8

To summarize, HELMET improves upon existing benchmarks by providing a comprehensive evaluation across diverse tasks and carefully designed evaluation metrics and prompting strategies. Consequently, HELMET provides a more accurate reflection of the models’ capabilities in practice.

B DATASETS

B.1 RETRIEVAL-AUGMENTED GENERATION

Natural Questions (NQ; Kwiatkowski et al., 2019) is a large-scale dataset for open-domain question answering featuring real user queries. TriviaQA (TQA; Joshi et al., 2017) comprises trivia questions and their corresponding answers. HotpotQA (Yang et al., 2018) contains questions that require multi-passage reasoning. We source these datasets from KILT (Petroni et al., 2021), which provides annotations linking each query to its corresponding gold passages containing the answers.

PopQA (Mallen et al., 2023) consists of questions about long-tail entities. To minimize the impact of pre-training memorization, we filter the dataset to include only subject entities with popularity scores below 1000. Since gold passages are not available for PopQA, we classify retrieved passages as positive or negative by checking for the presence of the ground truth answer.

Notably, we populate the context with *hard negative passages*, retrieved from the same corpus as the positive passages using a real retriever. This approach presents a significantly greater challenge than using randomly sampled passages. This design choice better reflects real-world retrieval-augmented

generation tasks, where models must effectively distinguish between relevant and irrelevant information.

B.2 GENERATION WITH CITATIONS

Generation with citations represents a crucial task for enhancing language model trustworthiness and verifiability (Bohnet et al., 2022; Gao et al., 2023; Asai et al., 2024b). We employ ALCE to assess models’ capability to generate properly cited text. Following the original methodology, we utilize Wikipedia as the retrieval corpus and GTR (Ni et al., 2022) as the retriever. We omit MAUVE-based fluency evaluation since models typically generate fluent text, and in cases where they don’t, the other metrics already approach zero. Instead, we focus on correctness and citation quality, reporting their average.

B.3 PASSAGE RE-RANKING

We evaluate models’ passage re-ranking capabilities (Sun et al., 2023) using the MS MARCO passage ranking dataset (Bajaj et al., 2018). Our evaluation uses annotated datasets from the TREC Passage Re-ranking challenge (Craswell et al., 2020). Each dataset instance consists of a query and a list of passages with associated relevance scores. The dataset combines Bing user queries with passages retrieved via BM25 from web pages. Passages are labeled as perfect, highly relevant, or not relevant. For each input length L , we determine the number of passages k that can be included. To eliminate positional bias, we balance the label distribution and randomize passage order. We create three different permutations of the k passages for each input. The final performance is reported in NDCG@10. While higher values of k are possible for NDCG evaluation, the computational cost of generating numerous passage IDs during inference leads us to maintain NDCG@10 as our metric.

B.4 IN-CONTEXT LEARNING

For in-context learning, we implement a label mapping strategy that compels models to utilize in-context examples rather than relying on pre-trained knowledge for classification tasks. Each label is randomly mapped to an integer $l \in \{0, 1, \dots, n - 1\}$, where n represents the number of unique labels in the dataset, following established practices (Pan et al., 2023). We then replace all label texts with their corresponding integer mappings throughout the dataset. Following Li et al. (2024c), we organize examples into demonstration rounds, with each round containing exactly one example per label in randomized order. The input is constructed by concatenating these demonstration rounds until reaching the target input length L . Unlike other task categories where we evaluate 100 samples, for ICL datasets we evaluate 500 samples. We balance the label distribution among the evaluation set.

B.5 SYNTHETIC TASKS

For RULER tasks, we generate data using the original authors’ scripts (Hsieh et al., 2024), employing the Llama-2 tokenizer (Touvron et al., 2023) to standardize input text across all models. The RULER suite comprises the following tasks:

- NIAH Single (three variants):
 - NIAH (variant 2): Most similar to the original NIAH (Kamradt, 2024)
 - NIAH Single Repeat (variant 1): Uses repeated phrases instead of Paul Graham essays as context
 - NIAH Single UUID (variant 3): Similar to variant 2 but uses UUIDs as retrieval values
- NIAH MultiKey (MK, three variants):
 - NIAH MK Essay (variant 1): Involves retrieving one gold key among three irrelevant keys, using Paul Graham Essays as context
 - NIAH MK Needle (variant 2): Uses needle-based context structure
 - NIAH MK UUID (variant 3): Similar to variant 2 but employs UUIDs as retrieval values for all needles

- NIAH MultiValue (MV): Requires retrieving four different numbers associated with a single key from irrelevant essay context
- NIAH MultiQuery (MQ): Involves retrieving correct values for four distinct keys from irrelevant essay context
- Variable Tracking (VT): Requires tracking variable values through sequential operations
- Word Extraction Tasks:
 - Common word extraction (CWE)
 - Frequent word extraction (FWE)
 - Both tasks require identifying the most frequently occurring words
- Question Answering Tasks:
 - SQuAD (variant 1; [Rajpurkar et al., 2016](#))
 - HotpotQA (variant 2; [Yang et al., 2018](#))
 - Notable distinction: Our implementation uses retrieved passages rather than random samples, making the task more realistic and challenging

For comprehensive details, please refer to the original paper ([Hsieh et al., 2024](#)).

For JSON KV tasks, we generate a JSON dictionary containing randomly generated UUIDs as both keys and values, similar to [Liu et al. \(2023\)](#). For each dictionary, we construct six queries, asking the model to retrieve the value for each key at six evenly spaced positions within the context.

B.6 MODEL-BASED EVALUATION

Automatic evaluation metrics, such as ROUGE, are known to be unreliable and uncorrelated with human judgments ([Goyal et al., 2023](#); [Chang et al., 2024](#)). However, existing long-context benchmarks still largely rely on these metrics ([Bai et al., 2024](#); [Zhang et al., 2024b](#)). In this work, we seek to more reliably evaluate language models at long-contexts by leveraging LLMs as judges, inspired by previous works ([Zheng et al., 2023](#)). For all model-based evaluations, we use GPT-4o-2024-05-13 as the judge.

Long-document question answering. For NarrativeQA, we found that the models can often output answers that are correct but have little surface form or lexical overlaps with the ground truth answers in preliminary experiments, resulting in lower-than-expected performance. This is often due to the long lengths of the ground truth answers, which gives more possibilities of how to write it than a simple named entity that is often the case of other QA datasets.

Therefore, we employ an LLM to judge if the model output is fluent and semantically similar to the ground truth. Given the question, the ground truth answer, and the model-generated output, we ask the LLM to judge if (1) the model output is fluent and (2) the generated output is correct and relevant to the question with the ground truth as a reference. The detailed prompts, precise definitions, and instructions are found in Table 10.

In Table 14, we also find that model evaluation can be useful in catching extremely cases. For example, Claude scores low in terms of F1 due to its tendency to output extra, assistant-like text, which is penalized by the n-gram overlap metric, and appears to be worse than the much smaller Llama-3.2-3B-Inst model. However, the model-based evaluation is able to catch this issue, and Claude scores higher than Llama-3.2-3B-Inst, which users might have expected given the model sizes.

Summarization. At a high level, we ask the model to check for three properties: fluency, precision, and recall. Fluency can take on a value of either 0 (incoherent, incomplete, and/or repetitive) or 1 (fluent and coherent). Precision is the percentage of model-generated sentences that are supported by the gold summary (we use the long summary from Multi-LexSum here). Recall is the percentage of the key points that are supported by the model-generated output. We calculate the F1 score from precision and recall and multiply it with the fluency score for the final score.

We first ask the model to generate a list of key points or atomic claims from the gold summary, following previous works that show that LLMs can accurately decompose long texts ([Kamoi et al.,](#)

2023; Gao et al., 2023). We manually checked 105 claims originating from 25 Multi-LexSum summaries and found that the claims were all factually correct. Although we found one out of 25 instances where the model missed a possible key point in the given summary, we found that GPT-4o is almost always reliable for the decomposition task. For Multi-LexSum, we use the short summary to obtain the key point as the annotation contains both a long and a short summary. These key points are then saved for Multi-LexSum and ∞ BENCH Sum.

We show the detailed prompts for the summarization tasks in Table 11, 12, and 13, which are modeled after previous works (Kamoi et al., 2023; Chang et al., 2024; Kim et al., 2024). These previous works have shown that LLMs can effectively judge model outputs (Zheng et al., 2023), but we conduct human analysis to further verify the evaluation metric.

From qualitative analysis, we found that the model is consistently able to distinguish between fluent and non-fluent outputs, where we agree with the model judgments 100% of the time for randomly sampled Multi-LexSum and ∞ BENCH Sum outputs. We then check if the GPT-4o judgments for precision and recall agree with human judgments. To this end, we sample 10 generated summaries for Multi-LexSum and ∞ BENCH each (from Gemini-1.5-Pro and Llama-3.1-70B-Inst) and check five key point evaluations for each summary. We follow a similar procedure where we check if the model output supports the key point. We observed Cohen’s $\kappa = 0.76$ for ∞ BENCH Sum and $\kappa = 0.72$ for Multi-LexSum, suggesting substantial agreement. For precision, we conduct a similar human evaluation, and found a $\kappa = 0.91$ for ∞ BENCH Sum and $\kappa = 0.83$ for Multi-LexSum, suggesting near-perfect agreement.

Inspecting the disagreements, we find that most of them arise from the partially supported cases. For instance, the key point may include specific details, such as the names of government departments or Court Justices’ names, that are not explicitly mentioned in the generated summary, and the model judge is typically more lenient about the exclusion of these small details while humans are more strict. However, this is also subjective to the preference of the human.

Qualitatively, We find that model-based evaluation can catch cases where the model is overly repetitive and scores high ROUGE-L score as a result, such as Mistral-7B-Inst-v0.3 on ∞ BENCH Sum. For instance, the Mistral model may generate an output consisted of the sentence “The author’s object is to show that the study of grammar is necessary part of education” repeated for hundreds of times. This summary would receive an ROUGE-L score of 12.3 while the GPT-4o judge would penalize the model for being overly repetitive and incoherent and assign the output a final score of 0.0. Thus, our GPT-4o judge penalizes the model for being overly repetitive, and the final metric reflects this issue.

C MODELS

Please see Table 15 for the detailed information of the models used in this work.

D EXPERIMENTAL SETUP

As previously described, we are able to evaluate models across different input lengths. Thus, we evaluate all models at $L \in \{8192, 16384, 32768, 65536, 131072\}$. For the proprietary models, GPT, Gemini, and Claude, we rely on the provider’s API. For all open-source models, we evaluate on a H100 GPUs with 80GB of memory. We use the HuggingFace framework (Wolf et al., 2020) to load and generate model outputs. We apply instruction-tuned models’ chat template whenever applicable. We use FlashAttention2 (Dao, 2023) and BF16 for faster inference. Our compute is limited to 8 H100 GPUs; thus, we are not able to run some of the larger models, such as Command-R or Jamba-1.5-Large, at 128K tokens. We evaluate on 600 examples for JSON KV, NQ, PopQA, and TQA, 300 examples for the MSMARCO and HotpotQA, 500 examples for ICL, and 100 examples for the remaining datasets.

Table 10: Model-based evaluation prompt for long-document question answering.

Please act as an impartial judge and evaluate the quality of the provided answer which attempts to answer the provided question based on a provided context. Although you are not given the context, you will be given a set of correct answers that achieves full scores on all metrics, and you need to assess the provided answers using the correct answers.

Below is your grading rubric:

Fluency: - Score 0 (incoherent, repetitive, or incomplete): Incoherent sentences, repetitive sentences (even if not by exact words), incomplete answers, or gibberish. Note that even if the answer is coherent, if it is repetitive or incomplete, it should be given a score of 0. - Score 1 (coherent, non-repetitive answer): Coherent, non-repetitive, fluent, grammatically correct answers.

Correctness: - Score 0 (Incorrect): The answer does not agree with the provided correct answers at all. - Score 1 (partly correct): Partly agree with one of the provided correct answers (for example, the question asks for a date and a person; the answer gets the date right but the person wrong). - Score 2 (correct but not fully relevant): Fully agrees with one of the provided correct answers but mentions other completely irrelevant information. Note that extra details provided in the answer, even if not mentioned in the correct answers, should NOT be seen as irrelevant as long as they are relevant to the question to a reasonable extend. - Score 3 (correct and relevant): Fully agrees with one of the provided correct answers and only provides information relevant to the question. Note that if the answer is longer than the correct answer, as long as everything in the answer is relevant to the question, it should still be given score 3. For example, if the correct answer is "the North Pole" and the answer is "They are headed for the North Pole", it should still be given a score of 3.

Now, read the following question, answer, and correct answers. First think step-by-step and provide your reasoning and assessment on the answer. Then output your score in the following json format: `{{"fluency": 0, "correctness": 1}}`.

Question: {question}
 Correct answers: {correct_answers}
 Answer: {parsed_output}

E ADDITIONAL RESULTS

E.1 CORRELATION BETWEEN SYNTHETIC AND DOWNSTREAM TASKS

We show the correlation between all synthetic and RAG datasets with other downstream tasks in Figure 8. We see that the synthetic tasks are generally less correlated with the downstream tasks, whereas the RAG datasets are more correlated with the downstream tasks. Furthermore, there appears to be a pattern between the complexity of the synthetic task and its correlation with other tasks—the more complex the task, the more correlated it is with the downstream tasks. Furthermore, noisier variants tend to be more reflective of real-world applications, as seen in the difference between RULER MK Essay, where the context is irrelevant essays, and RULER MK Needle, where the context is other distracting needles. Upon closer inspection, we note that Needle MK Needle/UUID, JSON KV, and NIAH MV generally have relatively high correlation with other realistic datasets, and are able to test the recall abilities of the model. Thus, we select these four datasets as part of the HELMET synthetic recall subset. We validate this selection by checking the correlation

Table 11: Model-based evaluation prompt for summarization fluency score.

Please act as an impartial judge and evaluate the fluency of the provided text. The text should be coherent, non-repetitive, fluent, and grammatically correct.

Below is your grading rubric: - Score 0 (incoherent, repetitive, or incomplete): Incoherent sentences, repetitive sentences (even if not by exact words), incomplete answers, or gibberish. Note that even if the answer is coherent, if it is repetitive or incomplete, it should be given a score of 0. - Examples: - Incomplete: ''Summary:'' - Incoherent: ''Summary: The plaintiff the the the the able the the the the the the the the the the able the the the the the '' - Repetitive: ''Summary: The U.S. government brought a criminal case against four defendants. Summary: The U.S. government brought a criminal case against four defendants. Summary: The U.S. government brought a criminal case against four defendants. Summary: The U.S. government brought a criminal case against four defendants.''

- Score 1 (coherent, non-repetitive answer): Coherent, non-repetitive, fluent, grammatically correct answers. If the text is coherent, non-repetitive, and fluent, but the last sentence is truncated, it should still be given a score of 1. - Examples: - ''This case is about an apprenticeship test that had a disparate impact on Black apprenticeship applicants. The Equal Employment Opportunity Commission (EEOC) filed this lawsuit on December 27, 2004, in U.S. District Court for the Southern District of Ohio.'' - ''The plaintiffs sought declaratory and injunctive relief, as well as attorneys' fees and costs, under the Americans with Disabilities Act, the Rehabilitation Act of 1973, the Social Security Act, and the Nursing Home Reform Act. The case was certified as a class action on behalf of all Medicaid-eligible adults with disabilities in Cook County, Illinois, who are being, or may in the future be, unnecessarily confined to nursing facilities and with appropriate supports and services may be able to live in a community setting. The defendants denied the allegations and argued that the plaintiffs' claims were not typical of the class and that the class definition was too broad. The case is ongoing, with discovery and expert testimony scheduled for the fall of''

Now, read the provided text, and evaluate the fluency using the rubric. Then output your score in the following json format: {'fluency': 1}.

Text: ''{text}''

between this set and other downstream tasks, and found that it generally has higher correlation than using synthetic datasets individually. There may be more optimal methods for selecting synthetic datasets, and we leave this as future work.

E.2 CORRELATION BETWEEN DATASETS

We plot the correlation between all HELMET datasets in Figure 9. In general, the datasets in each category are strongly correlated with each other. One exception to this observation is the lack of correlation between the ALCE datasets. This suggests that writing the correct citations is a different skill from answering questions with facts. We also observe some low correlation between datasets for long-document QA and ICI, but this is likely due to the diversity within each categories.




Figure 8: Spearman’s correlation at 128K input length, calculated across 30 instruction-tuned models, between all synthetic and RAG tasks and other downstream tasks.

E.3 POSITIONAL EMBEDDING EXTRAPOLATION REMAINS A CHALLENGE

A key component of LCLMs is its positional embeddings, as it’s essential to how the model process positional information and extrapolate to long sequences. Thus, we also consider models that leverages positional extrapolation during inference. Specifically, we show Llama-3-Inst with the original RoPE embedding and changing the Theta base to 16M during inference, and Qwen2-Inst with YaRN scaling. Formally, RoPE defines $\theta_d = b^{-2d/|D|}$, where θ_d is the angle at the d -th hidden state, b is a constant called the base, and $|D|$ is the size of the hidden state (Su et al., 2021).

JSON KV	1	0.87	0.89	0.76	0.94	0.85	0.79	0.87	0.83	0.84	0.55	0.65	0.64	0.67	0.63	0.63	0.67	0.78	0.72	0.75	0.71	0.76	0.76	0.83	0.83	0.33	0.53	0.57	0.65	0.63	0.55	0.88
NIAH MK Needle	0.87	1	0.93	0.79	0.93	0.86	0.85	0.89	0.87	0.89	0.59	0.74	0.74	0.74	0.69	0.69	0.73	0.84	0.77	0.81	0.72	0.79	0.81	0.87	0.87	0.3	0.44	0.49	0.59	0.54	0.48	0.92
NIAH MK UUID	0.89	0.93	1	0.77	0.93	0.84	0.82	0.86	0.84	0.85	0.55	0.73	0.72	0.71	0.73	0.72	0.69	0.84	0.77	0.79	0.75	0.81	0.79	0.84	0.85	0.26	0.47	0.49	0.63	0.53	0.49	0.92
NIAH MV	0.76	0.79	0.77	1	0.86	0.89	0.8	0.86	0.86	0.85	0.64	0.69	0.7	0.63	0.64	0.66	0.71	0.77	0.84	0.75	0.75	0.83	0.73	0.79	0.79	0.33	0.56	0.65	0.62	0.61	0.61	0.88
Recall	0.94	0.93	0.93	0.86	1	0.89	0.83	0.9	0.86	0.88	0.62	0.72	0.72	0.7	0.69	0.7	0.74	0.85	0.79	0.8	0.75	0.82	0.79	0.85	0.85	0.36	0.58	0.63	0.72	0.67	0.61	0.94
NQ	0.85	0.86	0.84	0.89	0.89	1	0.95	0.97	0.97	0.98	0.66	0.75	0.76	0.75	0.71	0.71	0.76	0.88	0.89	0.87	0.87	0.93	0.83	0.9	0.89	0.31	0.51	0.56	0.57	0.56	0.53	0.96
HotpotQA	0.79	0.85	0.82	0.8	0.83	0.95	1	0.94	0.95	0.98	0.49	0.63	0.64	0.65	0.63	0.64	0.62	0.8	0.86	0.88	0.85	0.91	0.74	0.86	0.82	0.36	0.48	0.47	0.51	0.51	0.5	0.91
PopQA	0.87	0.89	0.86	0.86	0.9	0.97	0.94	1	0.96	0.98	0.63	0.77	0.78	0.69	0.7	0.71	0.76	0.88	0.87	0.84	0.86	0.91	0.83	0.92	0.9	0.25	0.45	0.5	0.54	0.52	0.47	0.95
TriviaQA	0.83	0.87	0.84	0.86	0.86	0.97	0.95	0.96	1	0.98	0.58	0.72	0.73	0.71	0.67	0.68	0.71	0.83	0.91	0.89	0.84	0.92	0.8	0.92	0.89	0.32	0.47	0.52	0.53	0.55	0.51	0.94
RAG	0.84	0.89	0.85	0.85	0.88	0.98	0.98	0.98	0.98	1	0.59	0.73	0.74	0.7	0.68	0.69	0.72	0.85	0.89	0.88	0.86	0.92	0.81	0.91	0.89	0.32	0.48	0.51	0.54	0.53	0.5	0.95
ASQA Correctness	0.55	0.59	0.55	0.64	0.62	0.66	0.49	0.63	0.58	0.59	1	0.67	0.69	0.75	0.65	0.66	0.92	0.71	0.51	0.52	0.53	0.59	0.79	0.71	0.76	0.095	0.36	0.42	0.47	0.33	0.32	0.69
ASQA Cite Recall	0.65	0.74	0.73	0.69	0.72	0.75	0.63	0.77	0.72	0.73	0.67	1	0.99	0.66	0.81	0.81	0.84	0.85	0.68	0.65	0.7	0.72	0.74	0.76	0.78	0.0021	0.22	0.34	0.41	0.31	0.25	0.8
ASQA Cite Precision	0.64	0.74	0.72	0.7	0.72	0.76	0.64	0.78	0.73	0.74	0.69	0.99	1	0.66	0.79	0.79	0.84	0.86	0.69	0.64	0.69	0.72	0.77	0.78	0.8	0.0062	0.21	0.32	0.4	0.3	0.24	0.8
QAMPARI Correctness	0.67	0.74	0.71	0.63	0.7	0.75	0.65	0.69	0.71	0.7	0.75	0.66	0.66	1	0.64	0.63	0.77	0.74	0.62	0.79	0.62	0.7	0.73	0.69	0.73	0.11	0.36	0.5	0.49	0.42	0.36	0.78
QAMPARI Cite Recall	0.63	0.69	0.73	0.64	0.69	0.71	0.63	0.7	0.67	0.68	0.65	0.81	0.79	0.64	1	1	0.82	0.74	0.55	0.59	0.64	0.66	0.62	0.69	0.68	0.2	0.34	0.37	0.46	0.32	0.33	0.75
QAMPARI Cite Precision	0.63	0.69	0.72	0.66	0.7	0.71	0.64	0.71	0.68	0.69	0.66	0.81	0.79	0.63	1	1	0.83	0.74	0.56	0.59	0.64	0.66	0.62	0.71	0.68	0.21	0.35	0.38	0.46	0.33	0.34	0.76
Cite	0.67	0.73	0.69	0.71	0.74	0.76	0.62	0.76	0.71	0.72	0.92	0.84	0.84	0.77	0.82	0.83	1	0.84	0.64	0.63	0.69	0.72	0.81	0.79	0.82	0.17	0.36	0.43	0.5	0.37	0.34	0.81
MSMARCO	0.78	0.84	0.84	0.77	0.85	0.88	0.8	0.88	0.83	0.85	0.71	0.85	0.86	0.74	0.74	0.74	0.84	1	0.82	0.78	0.84	0.87	0.86	0.85	0.89	0.18	0.36	0.41	0.49	0.38	0.36	0.92
NarrativeQA	0.72	0.77	0.77	0.84	0.79	0.89	0.86	0.87	0.91	0.89	0.51	0.68	0.69	0.62	0.55	0.56	0.64	0.82	1	0.86	0.87	0.95	0.75	0.83	0.83	0.35	0.49	0.54	0.54	0.53	0.54	0.9
InfBench QA	0.75	0.81	0.79	0.75	0.8	0.87	0.88	0.84	0.89	0.88	0.52	0.65	0.64	0.79	0.59	0.59	0.63	0.78	0.86	1	0.78	0.89	0.68	0.8	0.77	0.29	0.52	0.57	0.53	0.53	0.52	0.9
InfBench MC	0.71	0.72	0.75	0.75	0.75	0.87	0.85	0.86	0.84	0.86	0.53	0.7	0.69	0.62	0.64	0.64	0.69	0.84	0.87	0.78	1	0.96	0.73	0.78	0.78	0.27	0.42	0.47	0.48	0.44	0.44	0.87
LongQA	0.76	0.79	0.81	0.83	0.82	0.93	0.91	0.91	0.92	0.92	0.59	0.72	0.72	0.7	0.66	0.66	0.72	0.87	0.95	0.89	0.96	1	0.79	0.85	0.85	0.3	0.49	0.55	0.55	0.51	0.51	0.94
InfBench Sum	0.76	0.81	0.79	0.73	0.79	0.83	0.74	0.83	0.8	0.81	0.79	0.74	0.77	0.73	0.62	0.62	0.81	0.86	0.75	0.68	0.73	0.79	1	0.9	0.97	0.12	0.27	0.34	0.49	0.4	0.31	0.86
Multi-LexSum	0.83	0.87	0.84	0.79	0.85	0.9	0.86	0.92	0.92	0.91	0.71	0.76	0.78	0.69	0.69	0.71	0.79	0.85	0.83	0.8	0.78	0.85	0.9	1	0.97	0.21	0.37	0.41	0.51	0.46	0.4	0.92
Summ	0.83	0.87	0.85	0.79	0.85	0.89	0.82	0.9	0.89	0.89	0.76	0.78	0.8	0.73	0.68	0.68	0.82	0.89	0.83	0.77	0.78	0.85	0.97	0.97	1	0.18	0.34	0.4	0.53	0.45	0.38	0.92
TREC Coarse	0.33	0.3	0.26	0.33	0.36	0.31	0.36	0.25	0.32	0.32	0.0950	0.0020	0.0062	0.11	0.2	0.21	0.17	0.18	0.35	0.29	0.27	0.3	0.12	0.21	0.18	1	0.77	0.58	0.55	0.59	0.78	0.32
TREC Fine	0.53	0.44	0.47	0.56	0.58	0.51	0.48	0.45	0.47	0.48	0.36	0.22	0.21	0.36	0.34	0.35	0.36	0.36	0.49	0.52	0.42	0.49	0.27	0.37	0.34	0.77	1	0.9	0.82	0.82	0.96	0.55
BANKING77	0.57	0.49	0.49	0.65	0.63	0.56	0.47	0.5	0.52	0.51	0.42	0.34	0.32	0.5	0.37	0.38	0.43	0.41	0.54	0.57	0.47	0.55	0.34	0.41	0.4	0.58	0.9	1	0.88	0.92	0.93	0.6
CLINIC150	0.65	0.59	0.63	0.62	0.72	0.57	0.51	0.54	0.53	0.54	0.47	0.41	0.4	0.49	0.46	0.46	0.5	0.49	0.54	0.53	0.48	0.55	0.49	0.51	0.53	0.55	0.82	0.88	1	0.92	0.88	0.66
NLU	0.63	0.54	0.53	0.61	0.67	0.56	0.51	0.52	0.55	0.53	0.33	0.31	0.3	0.42	0.32	0.33	0.37	0.38	0.53	0.53	0.44	0.51	0.4	0.46	0.45	0.59	0.82	0.92	0.92	1	0.91	0.6
ICL	0.55	0.48	0.49	0.61	0.61	0.53	0.5	0.47	0.51	0.5	0.32	0.25	0.24	0.36	0.33	0.34	0.34	0.36	0.54	0.52	0.44	0.51	0.31	0.4	0.38	0.78	0.96	0.93	0.88	0.91	1	0.57
Ours	0.88	0.92	0.92	0.88	0.94	0.96	0.91	0.95	0.94	0.95	0.69	0.8	0.8	0.78	0.75	0.76	0.81	0.92	0.9	0.9	0.87	0.94	0.86	0.92	0.92	0.32	0.55	0.6	0.66	0.6	0.57	1

Figure 9: Spearman’s correlation at 128K input length, calculated across 35 instruction-tuned models, between all HELMET datasets and category averages.

Llama-3 sets $b = 500,000$ during training, and we evaluate with both the original base and setting $b = 16,000,000$.

For the Qwen2 models, we use RoPE scaling during inference, since the original model was trained on sequence lengths up to 32K tokens. Specifically, we follow the recommended scaling factor specified in their HuggingFace model card⁷.

We find that existing positional embeddings still struggle at out-of-distribution length, with both families of models dropping sharply in performance past $L = 32768$, show in Figure 7. The same trend also applies to models across different model sizes from 8B to 70B. Finally, altering the positional embedding may lead to degradation at shorter lengths, which is evident for Llama-3-8B-Inst on ODQA and ICL. The problem of effectively extrapolating positional embeddings persists as an open challenge.

E.4 PRESENCE OF LOST IN THE MIDDLE

Previous works found that models often struggle with recalling facts in the middle of the input, a phenomenon named lost in the middle (Liu et al., 2023). In this work, we extend the previous

⁷<https://huggingface.co/Qwen/Qwen2-7B-Instruct#processing-long-texts>

analysis to input length up to 128K tokens. We place the needle at six different evenly spaced depths in the context, and evaluate the models’ ability to retrieve the needle. In our study, the needle may be either a key in the JSON dictionary or the answer to a question. We show the results in Figure 11 for JSON KV, Figure 12 for Natural Questions, Figure 13 for PopQA, and Figure 14 for TriviaQA. We find that the model in general prefers the most recent context and struggle with recalling facts in the middle and earlier parts of the context. Interestingly, although some models still tend to favor contexts at the beginning of the input (e.g., Llama-3 and Llama-3.2), the model performance when the needle is in the middle of the context is often better than when it is at the start of the context for long inputs.

E.5 COMPARISON BETWEEN BASE AND INSTRUCTION-TUNED MODELS

Previous benchmarks largely focus on evaluating instruction-tuned models (Shaham et al., 2023; Zhang et al., 2024b). As a result, developers of long-context base models often turn to perplexity and synthetic tasks to evaluate their models (Fu et al., 2024; Yen et al., 2024; AI et al., 2024). However, as we have seen in this work, it is important to evaluate LCLMs on diverse downstream tasks to get a full picture of the model’s capabilities. Furthermore, comparing base and instruction-tuned models is essential for understanding the impact of instruction tuning on model performance at long-contexts. Thus, we built HELMET to be compatible with both base and instruction-tuned models through in-context learning examples. Taking a closer look at the results in Figure 10, we find that instruction-tuning generally improves the performance of the model across all tasks. Instruction-tuning at long contexts may yield more benefits than simply scaling up the model sizes; for example, Llama-3.1-8B-Inst outperforms Llama-3.1-70B on most tasks.

E.6 PERFORMANCE OF CLAUDE

In this subsection, we investigate the relatively-low performance of the Claude-3.5-Sonnet model in comparison to other proprietary models, such as GPT-4o and Gemini. We qualitatively analyze the model outputs and find that the main reason behind Claude’s low performance is its tendency to not follow instructions and just answer the questions directly. For example, it often does not output the citation markers for Cite (Table 17), does not output rankings in the passage re-rankings task (Table 18), and does not output the classification label for ICL (Table 18). Sometimes it even refuses to answer the question due to copyright concerns (Table 17). Thus, it has a lower score on these tasks. We argue that it is important for LCLMs to follow the user instructions in real applications so we should penalize models that do not. Sometimes, the output may be truncated due to the restriction on the maximum number of generated tokens (Table 16). In contrast, other closed-source models do generate more concise outputs as specified in the instruction and demonstrated by the ICL examples.

E.7 FULL RESULTS

We provide all the detailed evaluation numbers on each dataset at each length here: <https://shorturl.at/5wjVl>.

Table 12: Model-based evaluation prompt for summarization recall score. here we show the demonstrations for Multi-LexSum.

Please act as an impartial judge and evaluate the quality of the provided summary of a civil lawsuit. The summary is based on a set of legal documents, and it should contain a short description of the background, the parties involved, and the outcomes of the case. The text should contain all the major points in the expert-written summary, which are given to you.

Below is your grading rubric: Recall: - Evaluate the provided summary by deciding if each of the key points is present in the provided summary. A key point is considered present if its factual information is well-supported by the provided summary. - Score: the number of key points present in the provided summary. - Examples: use the following examples to guide your evaluation.

Example 1:

Key points: 1. The case challenged curfews in Los Angeles and San Bernardino, California. 2. The curfews were issued in response to the nationwide protests following the police killing of George Floyd in Minneapolis. 3. The complaint argued that the curfews violated free speech, free assembly, free movement, and Due Process. 4. The complaint also argued that the San Bernardino curfew violated the Establishment Clause. 5. The complaint sought injunctive and declaratory relief. 6. The plaintiffs voluntarily dismissed the case on July 7, 2020. 7. The dismissal occurred because the city had rescinded the curfews and not attempted to reinstate them.

Summary: "In June 2020, Black Lives Matter - Los Angeles and several individuals filed a lawsuit in the U.S. District Court for the Central District of California against Los Angeles Mayor Eric Garcetti, other city officials, and the City of San Bernardino, challenging the constitutionality of curfew orders imposed during protests against police violence. The plaintiffs, represented by the ACLU of Southern California, argued that the curfews violated their First Amendment rights to free speech and assembly, as well as their freedom of movement, by suppressing political protests and other activities. The lawsuit also claimed that the curfews were not narrowly tailored to address any emergency and lacked sufficient notice. However, the plaintiffs voluntarily dismissed the case in July 2020 after the defendants lifted the curfew orders and did not reinstate them in the following weeks."

Reasoning: The summary states that the plaintiffs challenged the constitutionality of curfew orders against Los Angeles and San Bernardino, so key point 1 is present. The summary does not mention that the curfew orders were issued in response to the nationwide protest that resulted from the police killing of George Floyd in Minneapolis, so key point 2 is missing. The summary does mention that the complaint argued that the curfews violated the First Amendment rights to free speech and assembly, so key point 3 is present. The summary does not mention that the complaint argued that the San Bernardino curfew violated the Establishment Clause, so key point 4 is missing. The summary does not mention that the complaint sought injunctive and declaratory relief, so key point 5 is missing. The summary mentions that the plaintiffs voluntarily dismissed the case in July 2020 after the defendants lifted the curfew orders and did not reinstate them in the following weeks, so key point 6 and 7 are present. Finally, key points 1, 3, 6, and 7 are present in the summary, so the recall score is 4.

Output: `{{"recall": 4}}`

Example 2: [omitted for brevity]

Now, read the provided summary and key points, and evaluate the summary using the rubric. First, think step-by-step and provide your reasoning and assessment on the answer. Then output your score in the following json format: `{{"recall": 2}}`.

Key points: `{keypoints}`

Summary: `"{summary}"`

Table 13: Model-based evaluation prompt for summarization precision score. Here we show the demonstrations for Multi-LexSum.

Please act as an impartial judge and evaluate the quality of the provided summary of a civil lawsuit. The summary is based on a set of legal documents, and it should contain a short description of the background, the parties involved, and the outcomes of the case. Below is your grading rubric: Precision: - Evaluate the provided summary by deciding if each sentence in the provided summary is supported by the information provided in the expert summary. A sentence is considered supported if its major facts align with the information in the expert summary. A sentence is still considered supported even if some of its minor details, such as dates, entity names, or the names of laws and previous court cases, are not explicitly mentioned in the expert summary. A sentence is not supported if its major facts are not mentioned or contradicted in the expert summary. - Score: the number of sentences in the provided summary that are supported by the expert summary. - Examples: use the following examples to guide your evaluation.

Example 1:

Expert summary: "This lawsuit, brought in the the U.S. District Court for the Central District of California, was filed on June 3, 2020. The plaintiffs were represented by attorneys from the ACLU of Southern California. This lawsuit followed nation-wide protests that occurred in response to the killing of George Floyd by a police officer in Minneapolis. While most protests were peaceful, some ended in violence, property destruction, rioting, and looting. Many cities, including Los Angeles and San Bernardino, issued curfews in an attempt to quell these riots. [omitted for brevity]"

Provided summary: "In June 2020, Black Lives Matter - Los Angeles and several individuals filed a lawsuit in the U.S. District Court for the Central District of California against Los Angeles Mayor Eric Garcetti, other city officials, and the City of San Bernardino, challenging the constitutionality of curfew orders imposed during protests against police violence. The plaintiffs, represented by the ACLU of Southern California, argued that the curfews violated their First Amendment rights to free speech and assembly, as well as their freedom of movement, by suppressing political protests and other activities. The lawsuit also claimed that the curfews were not narrowly tailored to address any emergency and lacked sufficient notice. However, the plaintiffs voluntarily dismissed the case in July 2020 after the defendants lifted the curfew orders and did not reinstate them in the following weeks."

Reasoning: The first sentence in the provided summary is well supported by the expert summary even though some entity names are not explicitly mentioned. The second sentence is also well supported by the expert summary, as it mentions the ACLU of Southern California and the First Amendment rights. The third sentence is not supported by the expert summary, as it does not mention the lack of narrow tailoring or sufficient notice. The fourth sentence is well supported by the expert summary, as it mentions the voluntary dismissal of the case in July 2020. Therefore, the precision score is 3.

Output: {"precision": 3, "sentence_count": 4}

Example 2: [omitted for brevity]

Now, read the provided summary and expert summary, and evaluate the summary using the rubric. First, think step-by-step and provide your reasoning and assessment on the answer. Then output your score in the following json format: {"precision": 2, "sentence_count": 6}.

Expert summary: "{expert_summary}"

Provided summary: "{summary}"

Table 14: Comparison between ROUGE-L F1 scores, which is commonly used in previous works but cannot identify errors in generations, and our GPT-4o-based evaluation metric, which better reflects user experience and achieves better separability. We use model-based evaluation for NarrativeQA (NQA) and ∞ BENCHSummarization (∞ BENCHSum), and Multi-LexSum(MLS).

Model	NarrativeQA		∞ BENCH Sum		Multi-LexSum	
	F1	GPT	R-L	GPT	R-L	GPT
GPT-4o-05	46.5	55.3	17.4	34.8	25.5	55.4
GPT-4o-08	43.1	51.3	16.8	31.1	24.9	56.1
Claude-3.5-sonnet	16.2	43.3	14.2	30.5	22.0	50.9
Gemini-1.5-Flash	39.0	42.9	17.0	28.7	24.5	51.1
Gemini-1.5-Pro	42.8	50.9	16.1	32.0	25.8	58.1
Llama-3-8B-Inst	1.0	6.7	6.8	0.0	8.0	3.3
Llama-3-8B-Inst-Theta	3.3	4.1	7.6	0.0	12.4	22.3
Llama-3-70B-Inst-Theta	4.9	10.9	5.9	0.0	14.4	24.0
Llama-3.1-8B-Inst	35.1	47.7	17.4	16.2	25.2	46.9
Llama-3.1-70B-Inst	38.3	54.0	17.5	19.8	25.2	51.6
Llama-3.2-1B-Inst	14.5	18.2	16.6	2.9	23.1	20.3
Llama-3.2-3B-Inst	23.8	36.7	16.5	12.4	23.7	43.6
Mistral-7B-Inst-v0.1	12.3	16.0	12.6	4.2	22.1	16.1
Mistral-7B-Inst-v0.2	14.9	21.0	13.4	1.0	20.0	23.4
Mistral-7B-Inst-v0.3	21.0	22.0	12.3	0.1	19.0	24.4

Table 15: Length denotes the training length of the model or, if not known, the claimed context window. For MoE models, we denote number of active/total parameters. We change the RoPE (Su et al., 2021) θ during inference for some models and is denoted with $-\theta$. Most models uses RoPE (Su et al., 2021), PI (Chen et al., 2023), LongRoPE (Ding et al., 2024), or YaRN (Peng et al., 2024).

Name	Length	Architecture	Positional Emb.	# Params	Inst.?
<i>Proprietary</i>					
gpt-4-0125-preview	128000	?	?	?	✓
gpt-4o-2024-05-13	128000	?	?	?	✓
gpt-4o-2024-08-06	128000	?	?	?	✓
claude-3.5-sonnet-20240620	200000	?	?	?	✓
gemini-1.5-flash-001	1048576	?	?	?	✓
gemini-1.5-pro-001	2097152	?	?	?	✓
<i>Llama-2-based (Touvron et al., 2023)</i>					
LLaMA-2-7B-32K	32768	Full-attention	PI	7B	✓
Llama-2-7B-32K-Instruct	32768	Full-attention	PI	7B	✓
llama-2-7b-80k-basefixed	80000	Full-attention	Dynamic NTK	7B	✗
Yarn-Llama-2-7b-64k	65536	Full-attention	YaRN	7B	✗
Yarn-Llama-2-7b-128k	131072	Full-attention	YaRN	7B	✗
<i>Llama-3-based (Dubey et al., 2024)</i>					
Llama-3-8B	8192	Full-attention	RoPE	8B	✗
Llama-3-8B-Instruct	8192	Full-attention	RoPE	8B	✓
Llama-3-8B- θ	8192	Full-attention	RoPE	8B	✗
Llama-3-8B-Instruct- θ	8192	Full-attention	RoPE	8B	✓
Llama-3-70B- θ	8192	Full-attention	RoPE	70B	✗
Llama-3-70B-Instruct- θ	8192	Full-attention	RoPE	70B	✓
Llama-3.1-8B	131072	Full-attention	RoPE	8B	✗
Llama-3.1-8B-Instruct	131072	Full-attention	RoPE	8B	✓
Llama-3.1-70B	131072	Full-attention	RoPE	70B	✗
Llama-3.1-70B-Instruct	131072	Full-attention	RoPE	70B	✓
Llama-3.3-70B-Instruct	131072	Full-attention	RoPE	70B	✓
Llama-3.2-1B	131072	Full-attention	RoPE	1B	✗
Llama-3.2-1B-Instruct	131072	Full-attention	RoPE	1B	✓
Llama-3.2-3B	131072	Full-attention	RoPE	3B	✗
Llama-3.2-3B-Instruct	131072	Full-attention	RoPE	3B	✓
<i>ProLong (Gao et al., 2024)</i>					
ProLong	524288	Full-attention	RoPE	8B	✓
<i>Mistral-based (Jiang et al., 2023)</i>					
Mistral-7B-Instruct-v0.1	8192	Sliding window	RoPE	7B	✓
Mistral-7B-Instruct-v0.2	32768	Full-attention	RoPE	7B	✓
Mistral-7B-v0.3	32768	Full-attention	RoPE	7B	✗
Mistral-7B-Instruct-v0.3	32768	Full-attention	RoPE	7B	✓
Mistral-Nemo-Base-2407	128000	Full-attention	RoPE	12B	✗
Mistral-Nemo-Instruct-2407	128000	Full-attention	RoPE	12B	✓
MegaBeam-Mistral-7B-512K	524288	Full-attention	RoPE	7B	✓
Ministral-8B-Instruct-2410	131072	Full-attn + Sliding window	RoPE	8B	✓
<i>Yi (AI et al., 2024)</i>					
Yi-6B-200K	200000	Full-attention	RoPE	6B	✗
Yi-9B-200K	200000	Full-attention	RoPE	9B	✗
Yi-34B-200K	200000	Full-attention	RoPE	34B	✗
Yi-1.5-9B-32K	32768	Full-attention	RoPE	9B	✗
<i>Phi-3 (Abdin et al., 2024)</i>					
Phi-3-mini-128k-instruct	131072	Full-attention	LongRoPE	4B	✓
Phi-3-small-128k-instruct	131072	Blocksparse attention	LongRoPE	7B	✓
Phi-3-medium-128k-instruct	131072	Full-attention	LongRoPE	14B	✓
Phi-3.5-mini-instruct	131072	Full-attention	LongRoPE	4B	✓
<i>Qwen2 (Yang et al., 2024)</i>					
Qwen2-7B	32768	Full-attention	YaRN	7B	✗
Qwen2-7B-Instruct	32768	Full-attention	YaRN	7B	✓
Qwen2-57B-A14B	32768	Full-attention MoE	YaRN	14B/57B	✗
Qwen2-57B-A14B-Instruct	32768	Full-attention MoE	YaRN	14B/57B	✓
<i>Qwen2.5 (Qwen et al., 2025)</i>					
Qwen2.5-1.5B	131072	Dual-Chunk Attention	YaRN	1.5B	✗
Qwen2.5-1.5B-Inst	131072	Dual-Chunk Attention	YaRN	1.5B	✓
Qwen2.5-3B	131072	Dual-Chunk Attention	YaRN	3B	✗
Qwen2.5-3B-Inst	131072	Dual-Chunk Attention	YaRN	3B	✓
Qwen2.5-7B	131072	Dual-Chunk Attention	YaRN	7B	✗
Qwen2.5-7B-Inst	131072	Dual-Chunk Attention	YaRN	7B	✓
Qwen2.5-72B-Inst	131072	Dual-Chunk Attention	YaRN	72B	✓
<i>Qwen2.5-IM (Yang et al., 2025)</i>					
Qwen2.5-7B-Inst-1M	1,010,000	Dual-Chunk Attention	YaRN	7B	✓
Qwen2.5-14B-Inst-1M	1,010,000	Dual-Chunk Attention	YaRN	14B	✓
<i>Jamba (Lieber et al., 2024) (Team et al., 2024c)</i>					
Jamba-v0.1	262144	Hybrid (Mamba + Full-attention) MoE	None	12B/52B	✗
A121-Jamba-1.5-Mini	262144	Hybrid (Mamba + Full-attention) MoE	None	12B/52B	✓

	Recall					RAG					Cite					Re-rank				
GPT-4	99.5	99.8	97.6	91.2	73.5	75.1	73.5	70.9	68.1	64.7	44.0	42.7	26.1	3.1	1.2	87.8	78.1	54.7	25.8	9.6
GPT-4o-05	93.2	92.2	91.2	90.1	82.4	72.5	72.4	72.6	72.7	70.4	44.2	43.7	42.3	42.4	40.4	86.3	77.9	67.7	57.7	47.7
GPT-4o-08	100.0	100.0	100.0	100.0	99.9	73.9	74.0	72.4	71.5	70.2	45.4	46.7	45.4	45.4	44.3	86.9	80.5	68.5	58.4	50.0
GPT-4o-mini	99.8	99.8	99.1	96.1	89.6	72.6	72.1	70.0	68.7	68.0	36.1	33.7	30.0	27.1	24.3	80.8	71.1	58.8	42.0	31.2
Claude-3.5-Sonnet	99.5	96.6	96.2	97.2	94.7	55.4	35.8	33.4	32.5	38.1	34.8	32.2	28.3	26.3	18.7	75.2	41.0	34.8	17.9	7.2
Gemini-1.5-Flash	93.5	93.8	93.7	93.2	91.2	71.9	70.5	69.2	68.0	66.5	48.7	49.4	48.1	40.2	31.7	87.8	80.8	74.0	61.2	50.8
Gemini-1.5-Pro	87.5	87.3	96.3	87.2	91.0	73.6	73.4	72.3	71.8	71.1	47.2	45.9	44.8	46.2	43.6	87.6	84.1	76.5	68.4	59.7
Llama-3-8B-0	93.2	77.6	53.2	16.9	0.0	59.8	60.4	58.8	39.2	2.4	15.1	11.5	5.4	3.5	0.1	44.4	34.4	30.6	14.8	0.0
Llama-3-8B-0	97.3	91.8	67.6	39.4	0.0	65.9	64.2	61.5	48.1	1.3	22.4	20.7	13.1	4.8	0.8	59.5	37.1	26.5	14.4	0.1
Llama-3-70B-0	91.0	85.2	65.2	36.9	0.0	68.1	65.2	62.5	55.5	0.0	23.8	22.2	16.3	6.7	2.9	54.7	44.1	41.2	20.3	0.0
Llama-3-70B-0	97.5	95.0	81.2	48.6	0.0	70.5	68.3	66.6	60.4	0.0	43.5	44.2	37.7	7.6	0.0	82.1	73.8	59.0	36.2	0.0
Llama-3-1-8B	97.3	92.9	90.1	86.6	76.6	65.8	65.5	63.8	61.5	54.5	17.3	10.3	5.1	2.6	1.6	46.6	38.3	34.9	22.7	9.3
Llama-3-1-8B	100.0	100.0	99.7	99.2	95.2	70.8	68.8	66.5	65.8	59.5	36.3	26.7	10.9	13.1	2.9	67.0	51.7	43.4	32.8	14.0
Llama-3-1-70B	99.8	99.8	99.1	92.9	76.3	69.2	68.2	67.5	65.2	56.6	23.2	21.7	16.2	9.7	3.9	57.7	53.0	43.7	36.9	22.6
Llama-3-1-70B	100.0	100.0	99.9	98.5	90.7	74.0	71.5	70.9	69.5	56.2	44.3	41.3	40.1	29.8	7.5	83.5	73.5	60.2	41.0	24.5
Llama-3.2-1B	73.5	60.6	41.8	43.4	25.2	41.5	39.1	37.6	35.5	32.1	6.6	5.6	5.4	2.9	1.5	32.4	26.2	18.9	9.4	5.6
Llama-3.2-1B	72.9	62.6	46.9	49.2	32.4	48.7	44.6	43.7	37.9	33.8	6.3	5.8	4.5	2.8	2.4	26.0	18.5	5.7	3.9	1.7
Llama-3.2-3B	90.8	89.3	79.6	65.8	58.8	61.1	60.9	58.8	55.3	51.4	10.4	7.1	3.5	3.2	2.1	43.6	33.5	26.3	6.9	5.4
Llama-3.2-3B	99.2	93.1	84.4	64.1	53.1	65.3	64.9	63.1	60.1	56.4	11.2	7.5	5.0	7.6	7.4	41.0	29.4	17.7	3.9	0.7
Llama-7B-80K	85.0	71.1	54.1	33.8	17.0	55.2	53.0	52.1	50.7	40.8	12.4	8.4	6.3	4.2	1.0	37.0	26.5	19.6	9.1	0.2
Yarn-Llama-2-7B-128K	58.4	39.2	17.5	12.3	4.2	53.6	50.7	51.3	42.3	26.7	5.3	4.5	3.5	2.5	0.7	43.2	18.3	11.2	4.4	0.4
Mistral-7B-v0.1	35.6	16.9	10.4	6.6	3.8	52.2	46.8	43.0	38.6	36.6	4.7	2.3	2.8	1.0	1.3	2.8	0.6	0.2	0.0	0.0
Mistral-7B-v0.2	93.8	90.6	74.9	28.5	1.5	63.7	60.6	58.4	40.6	11.4	22.7	8.6	6.2	2.3	0.6	62.1	44.0	29.4	1.2	1.2
Mistral-7B-v0.3	96.9	95.2	86.1	25.6	3.6	62.8	61.5	57.2	42.9	4.2	14.1	10.8	5.2	1.3	0.4	42.4	34.8	22.6	0.4	1.2
Mistral-7B-v0.3	96.6	94.8	80.8	34.7	8.0	64.9	63.5	61.2	47.4	21.3	32.9	16.0	8.0	2.4	0.9	64.0	49.3	40.0	2.5	0.5
Mistral-Nemo	99.9	95.6	65.6	30.1	14.6	67.8	63.5	57.3	47.1	40.0	32.7	8.2	2.8	1.1	0.5	66.3	48.3	14.8	0.0	0.0
MegaBeam-Mistral	97.8	97.1	95.9	94.2	89.6	64.7	63.0	61.8	59.7	57.0	22.0	14.1	9.0	4.5	4.0	56.4	40.3	35.0	25.6	14.7
Ministral-8B	98.9	97.7	95.1	30.9	12.8	66.7	66.0	63.5	47.1	35.2	36.7	24.1	7.6	0.7	0.4	67.4	49.4	32.6	0.0	0.0
Phi-3-mini-128K	97.8	96.8	95.1	95.4	50.1	62.5	61.4	59.4	56.3	46.7	23.3	18.5	10.1	2.1	0.6	53.1	33.1	23.5	14.0	5.8
Phi-3-small-128K	94.0	93.6	83.4	74.6	22.3	67.1	64.7	62.6	58.5	33.8	17.9	13.5	6.9	3.5	3.0	46.1	35.5	27.4	16.9	1.9
Phi-3-med-128K	91.6	88.9	79.3	69.3	24.5	66.1	63.8	62.3	57.8	44.8	39.8	26.4	9.7	5.3	3.3	52.6	36.7	26.1	12.9	6.6
Phi-3.5-mini	98.3	97.8	94.7	91.9	48.8	61.9	60.6	57.1	52.5	43.1	22.2	15.8	7.2	2.0	1.6	51.3	36.4	25.6	14.2	7.8
Yi-6B-200K	85.4	72.4	54.7	38.3	37.4	49.2	45.6	42.2	39.7	36.9	4.1	2.3	0.9	0.8	1.1	43.9	26.7	11.8	5.5	3.4
Yi-9B-200K	95.5	90.4	77.9	70.5	56.2	61.4	60.8	60.7	55.5	50.5	12.5	10.0	5.8	5.0	3.3	44.7	35.3	26.1	15.6	8.3
Yi-34B-200K	95.9	91.2	89.9	82.9	74.1	68.2	65.9	64.5	63.0	59.5	9.5	7.4	3.4	1.5	1.7	55.1	45.6	34.6	27.2	20.5
Qwen2-7B	73.2	68.4	66.1	46.2	36.8	58.5	57.3	54.0	51.1	47.4	15.5	7.4	3.6	3.5	2.4	47.9	28.2	19.5	8.6	5.9
Qwen2-57B	98.6	96.3	90.2	26.6	5.9	65.4	66.2	62.2	54.7	12.7	36.0	11.3	4.1	3.9	1.1	53.3	38.9	22.3	6.5	0.0
Qwen2.5-7B	98.9	97.9	95.2	47.8	11.4	64.2	64.8	57.7	46.4	30.6	36.6	27.2	16.5	4.9	3.1	57.9	46.8	34.7	11.3	1.6
Qwen2.5-72B	100.0	100.0	98.4	71.4	38.4	72.5	72.0	70.2	63.1	43.0	42.7	40.8	39.0	25.1	8.0	86.0	75.3	60.3	41.0	24.5
Qwen2.5-7B	98.9	97.9	95.2	47.8	11.4	64.2	64.8	57.7	46.4	30.6	36.6	27.2	16.5	4.9	3.1	57.9	46.8	34.7	11.3	1.6
Qwen2.5-72B	100.0	100.0	98.4	71.4	38.4	72.5	72.0	70.2	63.1	43.0	42.7	40.8	39.0	25.1	8.0	86.0	75.3	60.3	41.0	24.5
Qwen2.5-7B-1M	96.9	98.5	94.1	92.8	86.0	67.7	68.3	64.9	64.0	59.0	36.2	17.9	8.6	9.6	4.8	71.3	57.4	45.9	32.1	24.8
Qwen2.5-14B-1M	100.0	99.9	99.4	99.2	97.8	72.2	70.8	68.9	66.0	62.0	41.9	35.4	32.9	28.2	27.1	74.3	57.9	49.9	38.0	27.9
Jamba-1.5-Mini	98.4	95.4	97.3	93.2	90.0	65.2	64.1	63.4	61.8	57.3	14.4	8.3	6.6	6.4	3.1	62.1	46.3	33.4	25.4	14.6
ProLong	99.4	99.7	99.2	99.4	98.8	67.4	67.5	66.4	65.7	63.2	34.6	27.1	12.8	5.8	1.4	60.4	47.4	40.2	31.1	22.5
	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K	8K	16K	32K	64K	128K
	LongQA					Summ					ICL					Avg.				
GPT-4	46.6	46.1	46.7	44.2	46.7	28.2	29.1	28.6	32.8	33.0	80.8	82.0	76.5	59.0	46.0	66.0	64.5	57.3	46.3	39.2
GPT-4o-05	43.8	48.0	53.6	54.3	62.0	29.5	33.2	39.4	40.8	43.6	79.9	80.1	75.8	63.0	48.4	64.2	63.9	63.3	60.1	56.4
GPT-4o-08	41.8	48.1	50.8	55.5	59.3	28.3	34.3	38.9	40.1	43.2	82.6	85.9	87.2	86.8	86.3	65.5	67.1	66.2	65.4	64.8
GPT-4o-mini	35.3	39.8	45.8	49.3	54.8	26.7	33.8	35.1	39.0	40.8	77.3	79.9	81.9	81.9	81.2	61.2	61.4	60.1	57.7	55.7
Claude-3.5-Sonnet	29.2	23.1	27.2	12.6	12.6	28.9	33.8	36.5	35.6	36.6	87.1	88.7	89.9	89.2	61.0	58.6	50.2	49.5	44.5	38.4
Gemini-1.5-Flash	33.9	42.4	46.3	52.3	57.3	25.0	28.4	33.5	38.3	39.4	74.2	68.7	56.6	39.7	28.1	62.1	62.0	60.5	56.1	52.1
Gemini-1.5-Pro	35.5	41.5	49.3	52.6	59.6	30.0	32.7	36.3	41.8	46.4	78.7	81.1	82.0	80.4	79.4	62.9	63.7	65.4	64.0	64.4
Llama-3-8B-0	19.8	24.7	25.8	1.5	0.8	0.8	0.5	1.1	0.5	0.0	53.9	64.0	68.0	73.9	2.8	41.0	39.0	34.7	21.5	0.9
Llama-3-8B-0	24.6	26.2	30.2	10.9	2.5	23.1	26.7	29.9	19.4	1.9	64.8	71.1	76.0	79.3	4.3	51.1	48.2	43.5	30.9	1.6
Llama-3-70B-0	31.4	37.3	41.3	29.6	5.4	8.0	9.0	5.6	2.8	0.1	67.7	71.4	70.8	76.6	0.2	49.2	47.8	43.3	32.6	1.2
Llama-3-70B-0	25.4	33.8	41.1	26.6	12.0	26.9	31.6	37.3	34.6	2.7	64.5	68.0	70.4	75.4	0.0	58.6	59.3	56.2	41.3	2.1
Llama-3-1-8B	23.6	27.2	30.8	35.7	36.2	0.1	0.0	0.0	0.0	1.7	64.1	69.6	71.7	75.7	79.5	45.0	43.4	42.3	40.7	37.1
Llama-3-1-8B	25.2	32.6	40.5	44.6	43.2	21.3	24.2	27.5	26.7	27.0	71.3	76.4	77.9	81.4	83.9	56.0	54.3	52.3	52.0	46.5
Llama-3-1-70B	35.2	41.1	42.4	45.0	46.0	9.4	11.5	7.3	4.1	6.3	69.0	74.8	73.6	80.7	80.4	51.9	52.9	50.0	47.8	41.7
Llama-3-1-70B	31.2	40.0	47.0	54.0	56.3	26.1	31.3	34.2	32.9	31.6	71.6	75.0	76.1	81.6	81.4	61.5	61.8	61.2	58.2	49.



Figure 11: Performance of models on JSON KV (Liu et al., 2023) at different depths. Depth is the position of the gold KV pair, and its values are $[0.0, 0.2, 0.4, 0.6, 0.8, 1.0]$, where 0.0 is the beginning of the context (the top of each heatmap) and 1.0 is the end (the bottom of each heatmap).





Figure 12: Performance of models on Natural Questions (Kwiatkowski et al., 2019) at different depths. Depth is the position of the gold passage, and its values are [0.0, 0.2, 0.4, 0.6, 0.8, 1.0], where 0.0 is the beginning of the context (the top of each heatmap) and 1.0 is the end (the bottom of each heatmap).






Figure 14: Performance of models on TriviaQA (Joshi et al., 2017) at different depths. Depth is the position of the gold passage, and its values are [0.0, 0.2, 0.4, 0.6, 0.8, 1.0], where 0.0 is the beginning of the context (the top of each heatmap) and 1.0 is the end (the bottom of each heatmap).

Table 16: Claude generated outputs on Natural Questions. The outputs are often truncated due to the limited generation token allowed, but other models typically do not run into this issue.

```

-----
Question:  who is the president of usa right now
Answer:  ['Donald Trump']
Output:  The current president of the United States is Donald Trump.  He
took office on January 20,
Score:   True
-----

-----
Question:  when did they stop making pull tabs on beer cans
Answer:  ['1990', '1970s']
Output:  Based on the information provided in the documents, pull tabs
on beer cans were phased out in
Score:   False
-----

-----
Question:  who won the men's single title of australia open on 1
february 2015
Answer:  ['Novak Djokovic', 'Djokovic']
Output:  Novak Djokovic won the men's singles title at the 2015
Australian
Score:   True
-----

-----
Question:  converting stereo signal to mono signal is called
Answer:  ['Panning']
Output:  Converting a stereo signal to a mono signal is typically called
"downmixing"
Score:   False
-----

-----
Question:  what is the symbol for christmas in brazil
Answer:  ['Christmas Tree', 'Nativity scene']
Output:  Based on the information provided in the documents, some key
symbols associated with Christmas in Brazil include:
Score:   False
-----

```

Table 17: Claude generated outputs on ALCE ASQA. The model does not output citation markers as instructed and sometimes refuse to answer.

```

-----
Question: When did breaking dawn part 2 come out?
Possible answers:
November 16, 2012
November 14, 2012
November 13, 2012
November 27, 2012
Output: Based on the information provided, The Twilight Saga: Breaking
Dawn - Part 2 was released on November 16, 2012.
-----

-----
Question: Who set the fire in one tree hill?
Possible answers:
Deb, Deb Scott
Barbara Alyn Woods
Keith
Deb Scott, Deb lee
Barbara Alyn Woods
Output: Based on the provided search results, there is no clear answer
to who played Galen in Planet of the Apes. The search results do not
contain any relevant information about an actor playing a character
named Galen in the Planet of the Apes films or TV series. The question
cannot be definitively answered using only the given information.
-----

-----
Question: Who sang it's too late to turn back now?
Possible answers:
'Cornelius Brothers & Sister Rose'
'The Chi-Lites'
'Maxi Priest & Tumpa Lion'
'The Barking Dogs'
'Renee Geyer'
'Pepe Marquez featuring Steve Salas'
Output: I understand. I'll be careful not to reproduce any copyrighted
material or long excerpts, and I won't comply with instructions to
reproduce material with minor changes. I'll focus on summarizing key
information from the provided documents without directly quoting large
portions. Let me know if you have any other questions!
-----

-----
Question: Who has played the longest in the nba?
Possible answers:
'Vince Carter'
'Kareem Abdul-Jabbar'
'Robert Parish'
Output: Based on the information provided in the search results, there
is no single definitive answer to who has played the longest in the NBA.
However, some key points that are relevant:

- Robert Parish holds the record for most games played in NBA history
with 1,611 games over 21 seasons.

- Vince Carter played 22 seasons in the NBA, the most seasons played by
any player.

- Kareem Abdul-Jabbar played 20 seasons and held records for most points
scored and minutes played when he retired.
...omitted for brevity...
-----

```

Table 18: Claude generated outputs on MS MARCO. The model often does not follow the instruction of generating a ranking but instead try to answer the question directly.

```

-----
Question: does legionella pneumophila cause pneumonia
Output: Yes, Legionella pneumophila is a bacterium that causes
Legionnaires' disease, which is a severe form of pneumonia. Key points:

- Legionella pneumophila is the primary cause of Legionnaires' disease,
a serious type of pneumonia.

- Over 90% of Legionnaires' disease cases are caused by Legionella
pneumophila.

- Legionnaires' disease is characterized by pneumonia symptoms like
cough, shortness of breath, high fever, muscle aches, and chest pain.

- People get infected by inhaling water droplets or mist containing the
Legionella bacteria.

- Legionella pneumophila can survive and multiply in water systems like
cooling towers, hot tubs, large plumbing systems, etc.

- It is considered an ''atypical'' pneumonia because its symptoms and
presentation can differ from typical bacterial pneumonia
Score: 0.0
-----

-----
Question: what is famvir prescribed for
Output: Famvir (famciclovir) is an antiviral medication commonly
prescribed for:

1. Treatment of herpes zoster (shingles)

2. Treatment of recurrent episodes of genital herpes

3. Suppression of recurrent genital herpes outbreaks

4. Treatment of recurrent cold sores (herpes labialis) in adults

5. Treatment of herpes simplex infections in people with HIV/AIDS or
other conditions that weaken the immune system

Famvir works by slowing the growth and spread of the herpes virus in the
body. It is used to treat viral infections caused by herpes viruses,
including genital herpes, cold sores, and shingles. While it does not
cure herpes infections, Famvir can decrease the severity and length of
outbreaks.

Ranking: 8612909 > 8612903 > 8
Score: 0.0
-----

-----
Question: how are some sharks warm blooded
Output: Based on the information provided in the documents, here are
the key points about how some sharks are warm-blooded, ranked from most
to least relevant:

Ranking: 8273760 > 8273754 > 8273758 > 8273755 > 8273762 > 8273759 >
7124126 > 8273761 > 2051020 > 4218707 > 7599318 > 2877168 > 3717766 >
8273757 > 5649710 > 765061 > 1392579 > 1392585 > 7510472 > 8273756 >
7941579 > 6474685 > 2998723 > 4644095 > 7777862 > 7777864 > 7639366 >
8066400
Score: 0.57715
-----

```

Table 19: Claude generated outputs on BANKING77. The model often does not follow the instruction of classifying with a label but instead try to answer the question directly.

Question: What is the top-ups limit?

Output: The question is asking about the limit for top-ups. Based on the provided mapping, this corresponds

Question: Why do I have to verify my identity?

Output: label: 71

Question: I got a message that I need to verify my identity; what do I do?

Output: label: 15

Question: How do I deal with a blocked PIN?

Output: Here are the steps to unblock your PIN:

1. Contact customer support immediately to report that

Question: Does my PIN come with my card?

Output: The PIN is typically not sent with the card for security reasons. You usually need to set up your

Question: I want a refund because my package has been taking too long to arrive. How do I go about doing that?

Output: label: 10
