



Replacing a shelf nondisruptively in a fabric-attached MetroCluster configuration

ONTAP MetroCluster

netapp-ivanad, ntap-bmegan
April 12, 2021

This PDF was generated from https://docs.netapp.com/us-en/ontap-metrocluster/maintain/task_replace_a_shelf_nondisruptively_in_a_mcc_fc_configuration.html on May 31, 2021. Always check docs.netapp.com for the latest.

Table of Contents

- Replacing a shelf nondisruptively in a fabric-attached MetroCluster configuration 1
 - Disabling access to the shelf 1
 - Replacing the shelf. 4
 - Reenabling access and verifying the operation 4

Replacing a shelf nondisruptively in a fabric-attached MetroCluster configuration

You might need to know how to replace a shelf nondisruptively in a fabric-attached MetroCluster configuration.



This procedure is only for use in a fabric-attached MetroCluster configuration.

Disabling access to the shelf

You must disable access to the shelf before you replace the shelf modules.

Check the overall health of the configuration. If the system does not appear healthy, address the issue first before proceeding.

Steps

1. Offline the affected plexes on the controller where they are hosted:

```
aggr offline plex_name
```

The example shows the commands for offlineing plexes for a controller running cMode.

```
Cluster_A_1::> storage aggregate plex offline -aggr aggr1 -plex plex2
Cluster_A_1::> storage aggregate plex offline -aggr aggr2 -plex plex6
Cluster_A_1::> storage aggregate plex offline -aggr aggr3 -plex plex1
```

2. Verify that the plexes are offline:


```
aggr status -raggr_name
```

The example shows the commands for verifying that the aggregates are offline for a controller running cMode.

```
Cluster_A_1::> storage aggregate show -aggr aggr1
Cluster_A_1::> storage aggregate show -aggr aggr2
Cluster_A_1::> storage aggregate show -aggr aggr3
```

3. Disable the SAS ports or switch ports depending on whether the bridges connecting the target shelf are connecting a single SAS stack or two or more SAS stacks:
 - If the bridges are connecting a single SAS stack, disable the switch ports that the bridges are connected to using the appropriate command for your switch.

The following example shows a pair of bridges that connect a single SAS stack, which contains the target shelf:



Switch ports 8 and 9 on each switch connect the bridges to the network.

The following example shows ports 8 and 9 being disabled on a Brocade switch.

```
FC_switch_A_1:admin> portDisable 8
FC_switch_A_1:admin> portDisable 9

FC_switch_A_2:admin> portDisable 8
FC_switch_A_2:admin> portDisable 9
```

The following example shows port 8 and 9 being disabled on a Cisco switch.

```
FC_switch_A_1# conf t
FC_switch_A_1(config)# int fc1/8
FC_switch_A_1(config)# shut
FC_switch_A_1(config)# int fc1/9
FC_switch_A_1(config)# shut
FC_switch_A_1(config)# end

FC_switch_A_2# conf t
FC_switch_A_2(config)# int fc1/8
FC_switch_A_2(config)# shut
FC_switch_A_2(config)# int fc1/9
FC_switch_A_2(config)# shut
FC_switch_A_2(config)# end
```

- If the bridges are connecting two or more SAS stacks, disable the SAS ports connecting the bridges to the target shelf:


SASportDisable port number



This is not applicable to FibreBridge 6500 bridges.

The following example shows a pair of bridges that connect four SAS stacks. SAS stack 2 contains the

target shelf:



SAS port B connects the bridges to the target shelf. By disabling only SAS port B on both shelves, the other SAS stacks can continue to serve data during the replacement procedure.

In this case, disable the SAS port connecting the bridge to the target shelf:

SASportDisable port number

The following example shows SAS port B being disabled from the bridge and also verifies that it is disabled. You must repeat the command on both bridges.

```
Ready. *
SASPortDisable B

SAS Port B has been disabled.
```

4. If you previously disabled the switch ports, verify that they are disabled:

switchShow

The example shows that the switch ports are disabled on a Brocade switch.

```
FC_switch_A_1:admin> switchShow
FC_switch_A_2:admin> switchShow
```

The example shows that the switch ports are disabled on a Cisco switch.

```
FC_switch_A_1# show interface fc1/6
FC_switch_A_2# show interface fc1/6
```

5. Wait for ONTAP to realize that the disk is missing.
6. Power off the shelf that you want to replace.

Replacing the shelf

You must physically remove all of the cables and the shelf before inserting and cabling the new shelf and shelf modules.

Steps


1. Remove all disks and disconnect all cables from the shelf that is being replaced.
2. Remove the shelf modules.
3. Insert the new shelf.
4. Insert the new disks into the new shelf.
5. Insert the shelf modules.
6. Cable the shelf (SAS or Power).
7. Power on the shelf.

Reenabling access and verifying the operation

After the shelf has been replaced, you need to reenabling access and verify that the new shelf is operating correctly.

Steps

1. Verify that the shelf powers properly and the links on the IOM modules are present.
2. Enable the switch ports or SAS port according to the following scenarios:

Option	Step
If you previously disabled switch ports	<p>a. Enable the switch ports: portEnable port number The example shows the switch port being enabled on a Brocade switch.</p> <pre>Switch_A_1:admin> portEnable 6 Switch_A_2:admin> portEnable 6</pre> <p>The example shows the switch port being enabled on a Cisco switch.</p> <pre>Switch_A_1# conf t Switch_A_1(config)# int fc1/6 Switch_A_1(config)# no shut Switch_A_1(config)# end Switch_A_2# conf t Switch_A_2(config)# int fc1/6 Switch_A_2(config)# no shut Switch_A_2(config)# end</pre>
If you previously disabled a SAS port	<p>a. Enable the SAS port connecting the stack to the shelf location: SASportEnable port number</p> <p>The example shows SAS port A being enabled from the bridge and also verifies that it is enabled.</p> <pre>Ready. * SASPortEnable A SAS Port A has been enabled.</pre> <div>  <p>This is not applicable to ATTO 6500 FibreBridges.</p> </div>

- If you previously disabled the switch ports, verify that they are enabled and online and that all devices are logged in correctly:

switchShow

The example shows the **switchShow** command for verifying that a Brocade switch is online.

```
Switch_A_1:admin> SwitchShow  
Switch_A_2:admin> SwitchShow
```

The example shows the **switchShow** command for verifying that a Cisco switch is online.

```
Switch_A_1# show interface fc1/6  
Switch_A_2# show interface fc1/6
```



After several minutes, ONTAP detects that new disks have been inserted and displays a message for each new disk.

4. Verify that the disks have been detected by ONTAP:

sysconfig -a

5. Online the plexes that were offline earlier:

aggr onlineplex_name

The example shows the commands for placing plexes on a controller running cMode back online.

```
Cluster_A_1::> storage aggregate plex online -aggr aggr1 -plex plex2  
Cluster_A_1::> storage aggregate plex online -aggr aggr2 -plex plex6  
Cluster_A_1::> storage aggregate plex online -aggr aggr3 -plex plex1
```

The plexes begin to resynchronize.



You can monitor the progress of resynchronization using the **aggr status -raggr_name** command.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.