

Robot Operating System (ROS2)

Vilma Muço

Université de Toulon, Master Ingénierie des Systèmes Complexes (ISC) -Erasmus
Mundus MIR

November, 2023



Table of Contents

- Actions
- Excercise




Image taken from *docs.ros.org*

Custom Actions

- ▶ We can custom-define actions in our packages
- ▶ Actions are defined in .action files
- ▶ A request message is sent from an action client to an action server initiating a new goal.
- ▶ A result message is sent from an action server to an action client when a goal is done.
- ▶ Feedback messages are periodically sent from an action server to an action client with updates about a goal.

```
# Request  
---  
# Result  
---  
# Feedback
```

Custom Actions

► Create a new package

```
$cd ~/ros2_ws/src
$ros2 pkg create --license Apache-2.0 p_action_interfaces
$cd p_action_interfaces
$mkdir action
$vi GoToPoint.action
```

► Create an action with goal to reach a point and stop

```
1  # Request
2  float32 x
3  float32 y
4  ---
5  # Result
6  bool success
7  ---
8  # Feedback
9  turtlesim/Pose pose
```

Build the custom action

► Modify the CMakeLists.txt

```
find_package(turtlesim REQUIRED)

find_package(rosidl_default_generators REQUIRED)

rosidl_generate_interfaces(${PROJECT_NAME}
  "action/GoToPoint.action"
  DEPENDENCIES turtlesim
)
ament_package()
```

► Add the required dependencies to our package.xml

```
<buildtool_depend>rosidl_default_generators</buildtool_depend>
<member_of_group>rosidl_interface_packages</member_of_group>
<exec_depend>turtlesim</exec_depend>
```

Build the custom action

```
colcon build --packages-select p_action_interfaces
source install/setup.bash
ros2 interface show p_action_interfaces/action/GoToPoint
```

```
vilma@vilma-Precision-3571:~/ros2_ws$ ros2 interface show p_action_interfaces/action/GoToPoint
# Request
float32 x
float32 y
---
# Result
bool success
---
# Feedback
turtleSim/Pose pose
float32 x
float32 y
float32 theta
float32 linear_velocity
float32 angular_velocity
vilma@vilma-Precision-3571:~/ros2_ws$
```

Writing an action server

```
1
2 class GoToGoal(Node):
3     def __init__(self):
4         super().__init__("go_to_goal")
5
6         self.publisher_ = self.create_publisher(Twist, "turtle1/cmd_vel", 10)
7
8         velocity_callback_group = MutuallyExclusiveCallbackGroup()
9         self.subscription = self.create_subscription(
10             Pose,
11             "turtle1/pose",
12             self.pose_listener_callback,
13             10,
14             callback_group=velocity_callback_group,
15         )
16
17         action_callback_group = MutuallyExclusiveCallbackGroup()
18         self.action_server = ActionServer(
19             self,
20             GoToPoint,
21             "go_to_point",
22             self.action_callback,
23             callback_group=action_callback_group,
24         )
25
26         self.current_pose = Pose()
27         # in the beginning, the turtle is happy where it is until it receives new instructions
28         self.goal_reached = True
29         self.velocity = Twist() # 0 by default
30         self.goal_x = 0.0
31         self.goal_y = 0.0
32         self.EPSILON_ERROR = 0.1
```


Writing an action server

```
1 def action_callback(self, goal_handle):
2     self.get_logger().info('Executing goal...')
3     if not self.goal_reached:
4         print('got new goal before old one reached')
5         # set the goal
6         self.goal_x = goal_handle.request.x
7         self.goal_y = goal_handle.request.y
8         feedback_msg = GoToPoint.Feedback()
9         feedback_msg.pose = self.current_pose
10
11         # while the goal is not reached, send feedback to the client
12         diff_x = abs(self.current_pose.x - self.goal_x)
13         diff_y = abs(self.current_pose.y - self.goal_y)
14         while diff_x > self.EPSILON_ERROR or diff_y > self.EPSILON_ERROR:
15             print('sending feedback')
16             goal_handle.publish_feedback(feedback_msg)
17             feedback_msg.pose = self.current_pose
18             diff_x = abs(self.current_pose.x - self.goal_x)
19             diff_y = abs(self.current_pose.y - self.goal_y)
20             # put only this thread to sleep for 1 seconds
21             time.sleep(1)
22
23         goal_handle.succeed()
24         result = GoToPoint.Result()
25         result.success = True
26         self.goal_reached = True
27         return result
```

Writing an action server

```
1
2 def pose_listener_callback(self, msg):
3     self.current_pose = msg
4     angle = 0.0
5     delta = 0.0
6
7     diff_x = abs(self.current_pose.x - self.goal_x)
8     diff_y = abs(self.current_pose.y - self.goal_y)
9     # calculate the angle between the current pose and the goal pose
10    # and rotate the robot towards the goal
11    angle = math.atan2(self.goal_y - self.current_pose.y, self.goal_x - self.current_pose.x)
12
13    delta = angle - self.current_pose.theta
14    self.velocity.linear.x = 0.0
15
16    distance = math.sqrt(diff_x * diff_x + diff_y * diff_y)
17    if diff_x < self.EPSILON_ERROR and diff_y < self.EPSILON_ERROR:
18        self.velocity.angular.z = 0.0
19    elif delta < -0.02 or delta > 0.02:
20        self.velocity.angular.z = delta * 0.5
21    else:
22        self.velocity.angular.z = 0.0
23        self.velocity.linear.x = distance * 0.5
24
25    # once we have updated what we want to do, publish the velocity
26    if self.velocity.linear.x != 0.0 or self.velocity.angular.z != 0.0:
27        self.publisher_.publish(self.velocity)
```

Writing an action server


```
1 def main(args=None):
2     rclpy.init(args=args)
3
4     go_to_goal = GoToGoal()
5     executor = MultiThreadedExecutor() # needed to run functions concurrently
6     executor.add_node(go_to_goal)
7
8     executor.spin()
9
10    go_to_goal.destroy_node()
11    rclpy.shutdown()
12
13
14 if __name__ == '__main__':
15     main()
```

Run the program

- ▶ Run turtlesim node and the p_action_example package on two different terminals
- ▶ In a third terminal send a goal to the action via command line

```
colcon build --packages-select p_action_example && ros2 run p_action_example go_to_goal  
ros2 run turtlesim turtlesim_node  
ros2 action list  
ros2 action send_goal --feedback /go_to_point p_action_interfaces/action/GoToPoint "{x: 5, y: 6}"
```

Run the program



```
vilma@vilma-Precision-3571: ~/ros2_ws
vilma@vilma-Precision-3571:~/ros2_ws$ ros2 action list
/go_to_point
/turtle1/rotate_absolute
vilma@vilma-Precision-3571:~/ros2_ws$ ros2 action send_goal --feedback /go_to_po
int p_action_interfaces/action/GoToPoint "{x: 5, y: 6}"
Waiting for an action server to become available...
Sending goal:
  x: 5.0
  y: 6.0
Goal accepted with ID: b006fb6d8eae445e9400075212652f43
Feedback:
  pose:
    x: 5.015662670135498
    y: 5.011327743530273
    theta: -2.3822638988494873
    linear_velocity: 0.0
    angular_velocity: 0.0
Feedback:
  pose:
    x: 5.015662670135498
    y: 5.011327743530273
    theta: -2.3822638988494873
```

Action Client

- Create an action client that moves the turtle in a square

```
1 import rclpy
2 from rclpy.action import ActionClient
3 from rclpy.node import Node
4 import time
5 from p_action_interfaces.action import GoToPoint
6
7 class DrawSquareActionClient(Node):
8     def __init__(self):
9         super().__init__('draw_square_action_client')
10        self._action_client = ActionClient(self, GoToPoint, 'go_to_point')
11        # create list with 4 edges of the square in tuple format starting from coordinate (5, 5)
12        # and with distance of a units between each edge going counter-clockwise
13        a = 3.0
14        self.edges = [(5.0, 5.0), (a + 5.0, 5.0), (a + 5.0, a + 5.0), (5.0, a + 5.0), (5.0, 5.0)]
15        self.current_step = 0 # the current edge of the square the turtle is on
16
17    def send_goal(self):
18        x, y = self.edges[self.current_step]
19        goal_msg = GoToPoint.Goal()
20        goal_msg.x = x
21        goal_msg.y = y
22
23        self._action_client.wait_for_server()
```


Action Client

```
1 def send_goal(self):
2     x, y = self.edges[self.current_step]
3     goal_msg = GoToPoint.Goal()
4     goal_msg.x = x
5     goal_msg.y = y
6
7     self._action_client.wait_for_server()
8     self._send_goal_future = self._action_client.send_goal_async(goal_msg,
9     feedback_callback=self.feedback_callback)
10    self._send_goal_future.add_done_callback(self.goal_response_callback)
11
12 def goal_response_callback(self, future):
13     goal_handle = future.result()
14     if not goal_handle.accepted:
15         self.get_logger().info('Goal rejected :(')
16         return
17
18     self.get_logger().info('Goal accepted :)')
19     self._get_result_future = goal_handle.get_result_async()
20     self._get_result_future.add_done_callback(self.get_result_callback)
```

Action Client

```
1  def get_result_callback(self, future):
2      result = future.result().result
3      self.get_logger().info('Result: {0}'.format(result.success))
4      # if result is True go to next step
5      if result.success:
6          self.current_step += 1
7          if self.current_step < len(self.edges):
8              self.send_goal()
9          else:
10             self.get_logger().info('Finished drawing square')
11             rclpy.shutdown()
12
13  def feedback_callback(self, feedback_msg):
14      self.get_logger().info('Feedback: {0}'.format(feedback_msg.feedback.pose))
15
16  def main(args=None):
17      rclpy.init(args=args)
18      action_client = DrawSquareActionClient()
19      action_client.send_goal()
20      rclpy.spin(action_client)
21
22  if __name__ == '__main__':
23      main()
```


Run the program



- Modify the service example code and use the service `/turtle1/set_pen` to draw two circles with 2 different colors



Thank you!!!
Questions?

Temporary page!

\LaTeX was unable to guess the total number of pages correctly. As there was some unprocessed data that should have been added to the final page this extra page has been added to receive it. If you rerun the document (without altering it) this surplus page will go away, because \LaTeX now knows how many pages to expect for this document.