

Roosa Kuusivaara & Väinö-Waltteri Granat

# Characterizing holographic displays via numerical simulations - Report

#### Abstract

Roosa Kuusivaara & Väinö-Waltteri Granat: Characterizing holographic displays via numerical simulations - Report
Laboratory Report
Tampere University
Master's Degree Programme in Signal Processing
September 2023

The abstract is a concise 1-page description of the work: what was the problem, what was done, and what are the results. Do not include charts or tables in the abstract.

These instructions are intended for students of Computer Sciences at the Tampere University. They cover questions of writing a thesis, such as use of the literature, structure of the thesis and style, the external appearance of the thesis and the use of tools. These instructions do not cover the scientific content of the thesis.

**Keywords:** M.Sc. thesis, layout, writing style.

## Contents

1	Introduction		
	1.1	Hologram synthesis	1
	1.2	Retinal Image Formation	1
2	Metl	hodology	2
	2.1	Implementing Hologram Synthesis	2
	2.2	Retinal Image Formation Simulation	2
	2.5	2.1 Field propagation implementation	3
3	Resu	ılts	4
	3.1	MTF Analysis	4
4	Cone	clusions	10
Re	feren	ces	11
ΑŦ	PPEN	IDIX A. Something extra	11

#### 1 Introduction

In this report we describe our work with the 'Characterizing holographic displays via numerical simulations' exercise, for the Advanced Signal Processing Laboratory Course.

In this project we familiarized ourselves with the basics of holographic display, by implementing a part of a holograpics display viewing simulation. We implemented two holographic synthesis methods and a retinal image formation model, by contributing code to a MATLAB codebase given by the course faculty.

#### 1.1 Hologram synthesis

Hologram synthesis describes the method for forming holographic images in 3d space from a given image. In this assignment, instead of using entire 3d space, the analysis can be simplified by considering only a cross section of the 3d space. The hologram is now represented as a 1D array of complex values. This simplification eases the computational load and also makes the process easier to handle.

#### 1.2 Retinal Image Formation

### 2 Methodology

#### 2.1 Implementing Hologram Synthesis

Our implementation of the holographic image viewer included three different methods of holographic image synthesis, one of which was provided in the code base given to us. The ready made synthesis method was holographic stereograph synthesis (HSS), [TODO: explain hss here]. The first synthesis method we implemented was a Fresnel hologram synthesis which is based on the Fresnel diffraction kernel. The second method we implemented was Rayleigh-Sommerfeld synthesis (RSS), which uses Rayleigh-Sommerfeld diffraction kernel. This formula is similar to the Fresnel but has some differences in calculating the hologram.

#### 2.2 Retinal Image Formation Simulation

To be able to view the synthezised holograms, we had to simulate the viewing process of an eye. This was achieved with a simplified wave propagation model, where human eye is represented by a simple lens and a one-dimensional sensor behind the lens in relation to the viewed hologram.

The transmittance of the lens is described by function 2.1

$$T(s) = exp(\frac{-i\pi}{\lambda f}s^2)$$
 (2.1)

where, f is the focal length of the lens.

The propagation of light from the hologram is modeled with a following field function 2.2

$$U(x;z) = \int \mathscr{F}\{U(\xi;z_0)\}(f_{\xi})exp[-2\pi i(f_{\xi}x + f_z z)]df_{\xi}$$
 (2.2)

where,

$$f_z = \sqrt{\frac{1}{\lambda^2} - f_\xi^2} \tag{2.3}$$

[TODO: Explain these functions]

The simplified eye model differs from a real human eye in multiple cases. Firstly, sensor of the human eye consists, [TODO: Add stuff]

#### 2.2.1 Field propagation implementation

The implementation of the field progation was provided to us in the code base, in the propagate Field\_PWD.m file. The file starts with defining the basic parameters, which are current location of the eye, distance from lens to sensor, the focal length of the eye and the physical size of the hologram plane.

In the next step the file sets up the more complex parts of the simulation, like size of the sensor, properties of the propagating light and the sampling grid.

Finally the file executes the field propagation simulation, where each of the sections of the synthezied hologram are propagated trough the wave field and the results are of the sensor are sampled to produces an image as PSF which is returned from the function.

#### 3 Results

In this section we analyze the images produced by the implemented model.

From the simulation we attained an image consisting of multiple overlayed PSF images depicting the hologram formed on the simulated sensor. From the image ?? we can see that from the samples the  $z_f$  value of -0.42 produces the sharpest image, since most of the points fall in the origin. This is different from what would be expected, since in ideal situation the sharpest images should form with the same values as the distance to point source, which in our simulation is -0.4. When the value of  $z_f$  moves away from -0.42 we expected the graph to widen, since image formed won't be as sharp and this is reflected in the figure, as the values closer to -0.42 produce higher graphs.

We also repeated this for Rayleigh-Sommerfield synthesis and Holographic stereogram synthesis, as shown in figures ?? and ??. The result for the Rayleigh-Sommerfield synthesis we basically identical, as the sharpest image, was obtained with the value of -0.42 and further away values produced wider graphs.

As for the holographic stereogram, the results different, in the sense that the sharpest image was produced with a  $z_f$  value of -0.44. Also all the  $z_f$  values produced blurrier images as the graphs were wider. This would indicate that the holographic stereogram produces overall blurrier holograms.

#### 3.1 MTF Analysis

With the multiple PSF images we performed MTF analysis to obtain the value of  $z_f$  which would provide the sharpest image.




Figure 3.1 PSF results of the simulation with Fresnel synthesis, with multiple  $z_f$  values between -0.5 and -0.3




Figure 3.2 PSF results of the simulation with Rayleigh-Sommerfield synthesis, with multiple  $z_f$  values between -0.5 and -0.3







Figure 3.3 PSF results of the simulation with holograpic stereograph synthesis, with multiple  $z_f$  values between -0.5 and -0.3



 $\textbf{\textit{Figure}} \quad \textbf{\textit{3.4}} \ \, \textit{MTF analysis results for Fresnel synthesis}$ 



 $\textbf{\textit{Figure}} \quad \textbf{\textit{3.5}} \ \textit{MTF analysis results for Rayleigh-Sommerfield synthesis}$ 



 $\textbf{\textit{Figure}} \quad \textbf{\textit{3.6}} \ \ MTF \ analysis \ results \ for \ Holographic \ stereograph \ synthesis$ 

## 4 Conclusions

## APPENDIX A. Something extra

Appendices are purely optional. All appendices must be referred to in the body text