

G²MAF: Test-Time Gradient Guidance for Multi-Agent Flow Policies

Guowei Zou, Haitao Wang, Guoxin Wang, Zhiquan Chen, Beiwen Zhang, Guojie Wang, Hejun Wu

Sun Yat-sen University




Figure 1 Motivation and G²MAF at test time. A frozen generative policy proposes a joint action, and a frozen centralized behavior critic supplies one joint gradient step toward higher predicted team value within the neighborhood supported by the behavior data. The right panel decomposes the samplewise coordination gap into the value gain recovered by G²MAF and the remaining local headroom.

Project Page: <https://g2maf.github.io/>

Code: <https://github.com/g2maf/G2MAF>

Models: <https://huggingface.co/g2maf/G2MAF>

Datasets: <https://huggingface.co/datasets/Guowei-Zou/CoFlow-datasets>

Abstract

Offline multi-agent reinforcement learning (MARL) learns cooperative policies from fixed datasets without further environment interaction and a learned policy is frozen at deployment. Such a frozen policy typically proposes a single joint action and executes it directly at deployment time. However, this one-shot deployment often commits to a suboptimal proposal, even when better nearby alternatives remain consistent with the behavior data. To address this issue, we propose Gradient Guided Multi Agent Flow (**G²MAF**), a refinement framework for optimizing joint policies at test-time. G²MAF applies one globally normalized, projected critic gradient to guide and coordinate all agents’ corrections while keeping the action both feasible and close to the frozen policy proposal. Across 24 MPE and SMAC settings, its canonical variant improves 20 frozen settings, with mean relative gains of 9.2% on MPE and 8.9% on SMAC, with model inference latency increased by about 6% only.

Introduction

Offline multi-agent reinforcement learning (MARL) trains joint policies from fixed datasets without further interaction [8, 11, 21, 25, 35]. At deployment, a frozen policy proposes one joint action and executes it directly. Direct execution neither compares nearby alternatives nor revises this first proposal. It retains a local coordination error: actions that seem reasonable individually frequently work poorly together, although a small joint adjustment could raise team return. Generative policies represent joint-action or trajectory

distributions [1, 14, 16, 17, 27, 29, 34, 36–38], but one sample does not certify a well-coordinated joint decision. A centralized behavior critic scores a complete joint action at the current joint observation. We call the critic-predicted score difference between the frozen proposal and a higher-scoring nearby joint action the *coordination gap* (Fig. 1).

Bridging this gap requires more than independently adjusting each agent’s action. Existing single-agent methods use critic guidance during inference or policy optimization [4, 10, 13, 18, 32]. We examine whether one local, critic-guided joint update improves a frozen cooperative policy without policy retraining, a world model, or candidate rollouts. For few-step generators, the same value signal can be injected before decoding or after the executable action is produced. We treat this location as a design choice.

We propose **G²MAF**, a test-time refinement method with a frozen joint policy and a frozen centralized behavior critic. For each proposal, G²MAF differentiates the critic with respect to the complete joint action, normalizes the concatenated gradient once, takes one action-space step, and projects the resulting action onto the feasible set. Because the critic receives every agent’s observation and action [22, 30], the resulting correction for each agent depends on its teammates’ choices, while the shared normalization gives the team one correction budget. The canonical variant refines the decoded executable action. We additionally study trajectory-space injection for few-step flow policies and masked-logit refinement for discrete actions. Under local smoothness and a sufficiently small step size, the prescribed nonzero continuous-action update strictly increases the critic prediction.

We evaluate G²MAF on 24 MPE and SMAC settings. At the operating points selected for Table 1, the canonical variant improves 20 frozen settings, with mean relative gains of 9.2% on MPE and 8.9% on SMAC. Paired rollouts measure realized return, critic diagnostics evaluate local ranking, and the injection study compares the three variants. The critic step increases model inference latency by about 6% on average.

Our contributions are as follows:

- We formulate the *coordination gap* as the centralized critic’s local score difference between a frozen proposal and a higher-scoring nearby joint action.
- We propose G²MAF, which applies one normalized joint-gradient action step followed by feasibility projection, and extend the refinement to trajectory injection and masked-logit discrete control. Under explicit conditions, we prove that the local critic increases or at least equals to that of the frozen policy.
- We evaluate return gains, injection locations, critic ranking, matched radius controls, and deployment cost across 24 MPE and SMAC settings.

Related Work

Offline MARL. Offline MARL learns joint policies from logged data [8, 11, 21, 25]. Value decomposition methods and centralized training with decentralized execution (CTDE) use joint information during training but execute local policies. QMIX uses monotonic value factorization [30], whereas MADDPG uses a centralized critic during training [22]. Offline variants add conservatism to combat extrapolation error [25]. Recent work also studies interaction aware data synthesis [11], sequential score decomposition of joint behavior [29], and the sensitivity of conclusions in offline MARL to dataset construction [9]. G²MAF borrows the centralized joint critic architecture but changes its role and information pattern: the critic remains available to a centralized coordinator at test time and refines the complete joint action without training the policy.

Generative policies for multi-agent reinforcement learning. Diffusion and flow models have become strong offline policies and planners [27, 36]. Diffuser and Decision Diffuser address the single-agent case [1, 14], while multi-agent generative policies include diffusion methods [17, 20, 34, 37] and flow methods [16, 19, 26, 38]. Recent single-agent work combines flow policies with energy guidance [2, 31] and develops one-step or shortcut flow policies [6, 7]. We refer to CoFlow as the coordinated generative backbone (CGB) used here. It combines

few-step trajectory generation, cross-agent coordination modules, and inverse-dynamics decoding. Its return-conditioned behavior-cloning objective anchors generated actions to offline coordination patterns; G²MAF refines the remaining local gap at deployment.

Test-time policy improvement. A growing body of work guides frozen-policy outputs at deployment [10, 13, 32]. QAM instead fine-tunes flow-policy parameters with critic action gradients [18]. Other test-time offline RL methods update policy parameters using selected logged transitions [4]; G²MAF keeps both networks frozen and edits only the proposed joint action. G²MAF studies cooperative value guidance through a centralized joint-action critic. Its trajectory-space and action-space variants share the same frozen policy and critic interface, while few-step multi-agent generation makes the injection point an explicit design choice. Planning with a learned world-action model [3] is an orthogonal route to test-time deliberation along the temporal axis.

Preliminaries

We use the standard cooperative offline MARL setting. Let $\mathbf{o}_{t,i} \in \mathcal{O}_i$ and $\mathbf{a}_{t,i} \in \mathcal{A}_i$ denote the local observation and action of agent $i \in \{1, \dots, n\}$ at time t . We write the joint observation and action as $\mathbf{o}_t = (\mathbf{o}_{t,1}, \dots, \mathbf{o}_{t,n}) \in \mathcal{O} = \prod_i \mathcal{O}_i$ and $\mathbf{a}_t = (\mathbf{a}_{t,1}, \dots, \mathbf{a}_{t,n}) \in \mathcal{A} = \prod_i \mathcal{A}_i$. A fixed dataset $\mathcal{D} = \{(\mathbf{o}_t, \mathbf{a}_t, r_t, \mathbf{o}_{t+1}, c_t)\}$ is collected by an unknown joint behavior policy, where r_t is the shared reward and c_t is the continuation indicator. The frozen generative joint policy samples $\mathbf{a}_\theta \sim \pi_\theta(\cdot \mid \mathbf{o}_t, g)$ for target return g , and the centralized critic scores $Q_\phi(\mathbf{o}_t, \mathbf{a}_t)$. The reported experiments use centralized test-time coordination execution: one coordinator receives $\mathbf{o}_t$, refines all action blocks jointly, and dispatches $\tilde{\mathbf{a}}_{t,i}$ to agent i ; neither model is updated online. Appendix B details the Dec-POMDP, coordination gap, execution assumptions, and flow backbone.

Method

Framework Overview

At each decision, G²MAF performs a local edit of a frozen policy proposal. Given the joint observation $\mathbf{o}$ and target return g , the frozen policy first emits a complete joint action $\mathbf{a}_\theta \sim \pi_\theta(\cdot \mid \mathbf{o}, g)$. A centralized critic then differentiates its predicted team value with respect to every component of $\mathbf{a}_\theta$. G²MAF applies one bounded update to the full joint vector and executes the resulting feasible action $\tilde{\mathbf{a}}$. Thus the policy supplies a behavior-like starting point, while the critic only chooses a local correction; neither model is updated at deployment.

Coordinated Flow Prior

The frozen proposal policy is a coordinated flow model. It transports a normalized joint observation trajectory from noise $\mathbf{z}_1 \sim \mathcal{N}(0, I)$ toward the data trajectory $\mathbf{x}_0$ along $\mathbf{z}_\alpha = (1 - \alpha)\mathbf{x}_0 + \alpha\mathbf{z}_1$. Let $\mathbf{c} = (\mathbf{N}_o(\mathbf{o}), g)$ denote the observation and return condition. Its velocity network is trained by the flow matching objective:

$$\mathcal{L}_{\text{flow}}(\vartheta) = \mathbb{E}_{\alpha, \mathbf{x}_0, \mathbf{z}_1} \left[\left\| u_\vartheta(\mathbf{z}_\alpha, 0, \alpha; \mathbf{c}) - (\mathbf{z}_1 - \mathbf{x}_0) \right\|_2^2 \right]. \quad (1)$$

Cross agent attention makes this velocity a joint function rather than a collection of independent agent flows. A shared inverse dynamics head decodes the final trajectory into $\mathbf{a}_\theta$. The backbone is trained before refinement and remains frozen; Appendix B gives its sampler and decoder.

Centralized Critic as a Coordination Signal

$Q_\phi(\mathbf{o}, \mathbf{a})$ estimates the team return after taking joint action $\mathbf{a}$ at $\mathbf{o}$ and then following the logged behavior. Because it receives the complete joint observation-action pair, $\nabla_{\mathbf{a}_i} Q_\phi(\mathbf{o}, \mathbf{a})$ depends on every teammate’s action and therefore specifies a coordinated correction. We train this critic once by behavior fitted critic




Figure 2 Framework of G²MAF. Given the joint observation and target return, a frozen generative policy proposes $\mathbf{a}_\theta$. The centralized critic evaluates the complete joint action and supplies one gradient whose blocks for individual agents depend on all teammates’ current actions. G²MAF globally normalizes this gradient, projects the refined action $\tilde{\mathbf{a}}$ onto the feasible action set, and executes it. The method uses neither policy retraining nor rollouts; the SMAC variant applies the same update to logits with illegal actions masked out.

evaluation (FQE) with one step temporal difference targets and freeze it. Appendix B gives the temporal difference (TD) objective; the experiments test whether the critic ranks nearby executable actions consistently with simulator outcomes.

Joint Value Guidance at Test Time

For fixed $(\mathbf{o}, g)$, the ideal policy target raises predicted team value while remaining close to the frozen joint prior:

$$\begin{aligned} \pi_Q &\in \arg \max_{\pi \ll \pi_\theta} \mathcal{J}_{\mathbf{o},g}(\pi), \\ \mathcal{J}_{\mathbf{o},g}(\pi) &= \mathbb{E}_{\mathbf{a} \sim \pi(\cdot | \mathbf{o}, g)} [Q_\phi(\mathbf{o}, \mathbf{a})] \\ &\quad - \beta D_{\text{KL}}(\pi(\cdot | \mathbf{o}, g) \parallel \pi_\theta(\cdot | \mathbf{o}, g)). \end{aligned} \quad (2)$$

Here D_{KL} is the Kullback–Leibler (KL) divergence. Under the regularity conditions in Appendix B, its solution is the value tilted joint distribution:

$$\begin{aligned} Z_\beta(\mathbf{o}, g) &= \int_{\mathcal{A}} \pi_\theta(\mathbf{a} | \mathbf{o}, g) \exp\left(\frac{Q_\phi(\mathbf{o}, \mathbf{a})}{\beta}\right) d\mathbf{a}, \\ \pi_Q(\mathbf{a} | \mathbf{o}, g) &= \frac{\pi_\theta(\mathbf{a} | \mathbf{o}, g) \exp(Q_\phi(\mathbf{o}, \mathbf{a})/\beta)}{Z_\beta(\mathbf{o}, g)}. \end{aligned} \quad (3)$$

For continuous densities, this tilt adds the centralized value gradient to the prior score:

$$\begin{aligned} \nabla_{\mathbf{a}} \log \pi_Q(\mathbf{a} | \mathbf{o}, g) &= \nabla_{\mathbf{a}} \log \pi_\theta(\mathbf{a} | \mathbf{o}, g) \\ &\quad + \beta^{-1} \nabla_{\mathbf{a}} Q_\phi(\mathbf{o}, \mathbf{a}). \end{aligned} \quad (4)$$

The CGB policy is an implicit pushforward. G²MAF therefore uses the value gradient term directly to refine one sampled decoded joint action, rather than evaluating this score or fitting π_Q .

G²MAF: Refinement after Generation

For continuous control, G²MAF directly applies one globally normalized, projected update from the centralized critic to the executable joint action:

$$\tilde{\mathbf{a}} = \Pi_{\mathcal{A}} \left(\mathbf{a}_\theta + \eta \frac{\nabla_{\mathbf{a}} Q_\phi(\mathbf{o}, \mathbf{a}_\theta)}{\|\nabla_{\mathbf{a}} Q_\phi(\mathbf{o}, \mathbf{a}_\theta)\|_2 + \varepsilon} \right). \quad (5)$$

Here $\mathcal{A} = \prod_i \mathcal{A}_i$ is the feasible box for the joint action, $\Pi_{\mathcal{A}}$ is Euclidean projection, and $\varepsilon = 10^{-6}$ prevents numerical division by zero. The derivative is evaluated on the complete joint action. Each agent’s correction therefore depends on its teammates’ current actions, and shared normalization gives the team one correction budget. Appendix B defines the blocks for individual agents and gives the trust region derivation, displacement bound, and local critic ascent condition. Each decision uses one critic backward pass and no actor update, candidate search, or model rollout.

Where to Inject the Value Signal

G²MAF supports value-signal injection before or after the trajectory decoder. For CGB, the variable before decoding is a normalized joint observation trajectory. A trajectory variant first takes one reverse Euler step and decodes its observation--action pair,

$$\begin{aligned} \bar{\mathbf{z}}^{k-1} &= \mathbf{z}^k - \Delta \alpha_k u_\theta(\mathbf{z}^k, 0, \alpha_k; \mathbf{N}_o(\mathbf{o}), g), \\ \mathbf{x}_c^{k-1} &= \mathcal{C}(\bar{\mathbf{z}}^{k-1}; \mathbf{N}_o(\mathbf{o})), \\ \mathbf{y}^{k-1} &= (P_{H_{\text{hist}}} \mathbf{x}_c^{k-1}, \mathcal{I}_\psi(P_{H_{\text{hist}}} \mathbf{x}_c^{k-1}, P_{H_{\text{hist}}+1} \mathbf{x}_c^{k-1})). \end{aligned} \quad (6)$$

Its critic in normalized coordinates supplies the chain rule direction through $J_{\text{dec}}^{k-1} = \partial \mathbf{y}^{k-1} / \partial \bar{\mathbf{z}}^{k-1}$:

$$\begin{aligned} \mathbf{G}_{\text{traj}}^{k-1} &= \nabla_{\bar{\mathbf{z}}^{k-1}} Q_\nu^{\text{norm}}(\mathbf{y}^{k-1}) \\ &= (J_{\text{dec}}^{k-1})^\top \nabla_{\mathbf{y}^{k-1}} Q_\nu^{\text{norm}}(\mathbf{y}^{k-1}). \end{aligned} \quad (7)$$

All applies this update after every reverse Euler step; Final applies it only at $k = 1$. Post completes the flow, decodes $\mathbf{a}_\theta$, and applies Eq. 5 directly in action space. Thus all three are G²MAF variants distinguished by the injection point: trajectory variants propagate the critic gradient through the decoder Jacobian, while Post uses the action gradient after decoding. A nonlinear decoder generally makes the two edits nonequivalent. Appendix B gives the complete trajectory update.

Discrete Joint Actions

For SMAC, agent i emits logits $\ell_i \in \mathbb{R}^{A_i}$ and receives a mask of legal actions $\mathbf{m}_i \in \{0, 1\}^{A_i}$. We apply softmax separately over each agent’s legal actions, differentiate the critic through the resulting relaxation, and mask again before selecting the discrete action:

$$\begin{aligned} \mathbf{p}_i &= \text{softmax}(\ell_i + \log \mathbf{m}_i), \quad \mathbf{p} = (\mathbf{p}_1, \dots, \mathbf{p}_n), \\ \mathbf{d}_\ell &= \nabla_\ell Q_\phi(\mathbf{o}, \mathbf{p}), \quad D_\varepsilon^\ell = \|\mathbf{d}_\ell\|_2 + \varepsilon, \\ \tilde{\ell}_i &= \ell_i + \eta \frac{\mathbf{d}_{\ell,i}}{D_\varepsilon^\ell}, \quad \tilde{\mathbf{a}}_i = \arg \max_{1 \leq j \leq A_i} \{\tilde{\ell}_{ij} + \log m_{ij}\}. \end{aligned} \quad (8)$$

We use $\log 0 = -\infty$. Masking again before $\arg \max$ prevents an illegal action from being executed. The concatenated logits share one normalization, with $\|\tilde{\ell} - \ell\|_2 \leq \eta$. A discrete action changes only when competing logits cross; its useful step sizes in logit space are therefore larger than the radii for continuous actions.

(a) MPE, OMAR-normalized score												
Task	Qual.	Data	BC	ICQ	TD3+BC	CQL	OMAR	Diff	MA-SfBC	DOM2	G ² MAF	
Spread	Expert	96.2	35.0±2.6	104.0±3.4	108.3±3.9	98.2±5.2	<u>114.9±2.6</u>	95.0±5.3	87.5±7.3	88.7±6.3	115.2±0.9	
	MedRep	9.3	10.0±3.8	13.6±5.7	15.4±5.6	31.4±7.2	<u>37.9±6.1</u>	30.3±2.5	8.2±4.6	63.1±9.5	<u>47.3±2.2</u>	
	Medium	27.0	31.6±4.8	29.3±5.5	39.4±3.6	34.1±7.2	47.9±18.9	64.9±7.7	51.6±14.2	78.6±8.1	59.7±1.7	
	Random	0.1	-0.5±3.2	6.3±3.5	9.8±4.9	24.0±9.8	34.4±5.3	6.9±3.1	5.1±3.9	<u>37.4±11.3</u>	58.0±9.0	
Tag	Expert	89.5	40.0±9.6	113.0±14.4	115.2±12.8	119.3±14.0	<u>123.9±10.5</u>	103.0±12.0	77.4±13.9	98.2±14.4	139.7±1.1	
	MedRep	8.6	0.9±1.4	34.5±27.8	28.7±20.9	41.7±15.3	<u>47.1±15.3</u>	53.9±11.4	12.7±7.3	68.2±16.7	73.5±7.5	
	Medium	43.8	22.5±1.8	63.3±20.0	65.1±29.5	61.7±23.1	66.7±23.2	72.7±9.4	47.1±17.9	<u>82.6±18.2</u>	112.7±1.1	
	Random	0.0	1.2±0.5	2.2±1.3	6.0±2.1	11.1±2.8	11.1±2.8	4.6±2.6	11.6±5.1	<u>29.6±8.1</u>	46.1±2.9	
World	Expert	93.8	33.0±9.9	109.5±22.8	110.3±21.3	<u>119.8±28.1</u>	110.4±25.7	109.3±15.4	97.3±19.1	99.5±17.1	156.4±5.2	
	MedRep	11.2	2.3±1.5	12.0±9.1	17.4±8.1	19.3±18.3	42.9±19.5	19.8±6.2	9.1±5.9	65.9±10.6	45.8±2.0	
	Medium	54.5	25.3±2.0	71.9±20.0	73.4±9.3	58.6±11.2	74.6±11.5	<u>84.7±12.3</u>	54.2±22.7	84.5±23.4	146.8±11.4	
	Random	0.0	-2.4±0.5	1.0±3.2	2.8±5.5	0.6±2.0	<u>5.9±5.2</u>	6.1±2.4	3.1±1.3	4.1±1.1	5.0±0.3	
(b) SMAC, shaped episode return												
Task	Qual.	Data	BC	ICQ	CQL	MA-DT	Diff	DoF	Flow BC	MAC-Flow	VGM ² P	G ² MAF
3m	Good	16.5	16.0±1.0	18.8±0.6	19.0±0.3	19.6±0.7	19.3±0.5	19.8±0.2	20.0±0.0	19.8±0.2	19.5±0.7	20.0±0.1
	Medium	10.0	8.2±0.8	18.1±0.7	<u>18.9±0.7</u>	17.2±0.7	16.4±2.6	18.6±1.2	14.7±1.5	18.0±3.2	16.9±1.1	21.4±1.8
	Poor	4.7	4.4±0.1	14.4±1.2	<u>5.8±0.4</u>	8.9±0.3	10.3±6.1	10.9±1.1	4.5±0.1	10.6±2.2	14.9±1.5	<u>14.8±0.9</u>
2s3z	Good	18.3	18.2±0.4	19.6±0.3	19.1±0.8	19.4±0.1	15.9±1.2	18.5±0.8	19.5±0.1	19.5±0.5	<u>19.9±0.1</u>	21.2±0.1
	Medium	12.6	14.3±0.7	17.2±0.8	14.3±2.0	17.4±0.3	15.6±0.3	<u>18.1±0.9</u>	15.1±2.0	17.6±0.6	<u>16.5±0.6</u>	19.1±0.4
	Poor	6.9	6.7±0.3	<u>12.1±0.4</u>	10.1±0.7	9.9±0.2	8.5±1.3	10.0±1.1	6.9±0.8	8.5±0.6	7.9±0.7	12.2±0.3
5m_vs_6m	Good	16.6	16.6±0.6	16.3±0.9	13.8±3.1	18.0±1.0	16.5±2.8	17.7±1.1	14.7±2.1	<u>18.6±3.5</u>	17.6±1.3	19.4±0.6
	Medium	12.6	14.2±0.5	17.2±0.4	16.8±3.1	<u>17.5±0.4</u>	15.2±2.6	16.2±0.9	12.8±0.8	15.6±1.3	17.0±0.9	20.6±0.7
	Poor	7.5	7.5±0.2	9.4±0.4	10.4±1.0	8.9±0.3	8.9±1.3	<u>10.8±0.3</u>	7.7±0.8	9.8±2.1	10.7±1.1	12.4±0.6
8m	Good	16.9	16.7±0.4	19.6±0.3	13.1±6.1	19.2±0.1	18.9±1.1	19.6±0.3	19.5±0.2	<u>19.7±0.3</u>	19.7±0.4	21.1±0.3
	Medium	10.1	10.7±0.5	18.6±0.5	16.3±3.1	18.0±0.5	16.8±1.6	18.6±0.8	18.2±0.8	<u>19.4±0.6</u>	18.2±1.6	19.7±0.4
	Poor	5.3	5.3±0.1	10.8±0.8	4.6±2.4	5.1±0.1	9.8±0.9	12.0±1.2	4.9±0.1	<u>11.5±0.8</u>	4.9±0.1	9.5±0.1

Table 1 Main results on (a) MPE and (b) SMAC. “Data” is the offline data mean, “Diff” abbreviates MADiff, and G²MAF denotes the refined frozen backbone at its selected operating point. Bold and underline mark the best and second best method in each row, excluding Data. Appendix A.1 gives the reporting conventions.

Experiments

The experiments study three questions. (Q1) Does G²MAF improve frozen offline cooperative policies, and when do realized local headroom and critic reliability translate into gain? (Q2) How does the injection location behave for coordinated flow with few steps? (Q3) Does G²MAF transfer to discrete joint actions, and how does its deployment cost compare with world model planning?

Setup

Policies and benchmark. We evaluate frozen CGB checkpoints. MPE comprises simple-spread cooperative navigation and simple-tag/simple-world predator prey coordination. SMAC comprises 3m, 2s3z, 5m_vs_6m, and 8m discrete micromanagement. Both benchmarks span dataset quality from Poor to Expert. For MPE predator prey, refinement applies to the three learned predator agents; the prey remains scripted. All 24 task and quality settings are reported, with representative benchmark trajectories shown in Figure 7 (in Appendix).

Baselines. BC, ICQ, TD3, and CQL denote behavior cloning, implicit constraint Q-learning, Twin Delayed Deep Deterministic Policy Gradient, and conservative Q-learning. The shared baseline panel follows CoFlow’s matched comparison [38] and retains the original-method citations [12, 15, 17, 23, 25, 28, 33, 37]. These citations identify algorithm origins rather than the source of every multi-agent row. MA-SfBC adapts SfBC [5], with values reported by DOM2 [20]. The other newer columns are MAC-Flow [16] and VGM²P [26]. Each published column retains its reporting source’s benchmark split, score scale, and uncertainty convention.

Protocol. Table 1 reports the sweep frontier for each setting, and Figure 5 shows sensitivity to the step size. MPE uses OMAR normalized score and SMAC uses shaped episodic return; SMAC success is reported separately. We define $\Delta_R = R_{\text{G}^2\text{MAF}} - R_{\text{Frozen}}$ and, when $R_{\text{Frozen}} \neq 0$, $\delta_{\text{rel}} = \Delta_R / |R_{\text{Frozen}}|$ within the displayed benchmark metric. Standard G²MAF evaluations aggregate five independent random seeds; Appendix A gives the grids, episode budgets, and control procedures.

Q1: Gains Track Local Headroom

Table 1 compares G²MAF with published baselines, and Figure 3 shows its paired gain over the frozen backbone. G²MAF improves 20/24 settings. Gains are largest on several lower-quality MPE and SMAC datasets, whereas nearly saturated settings such as simple-spread Expert and 3m-Good change little. Figure 6 (in Appendix) groups these gains by dataset quality.

Three supplementary checks bound this result. Leave-one-task-out (LOTO) step transfer is positive on 18/24 settings; continuous updates remain local relative to empirical nearest-neighbor action distances; and the critic ranks realized simulator returns above chance on 23/24 settings. The largest gains span multiple observed headroom--reliability cells rather than concentrating in the high/high cell. Appendix A.1 details the locality and critic protocols, and Table 5(a) (in Appendix) reports step transfer.

Aggregate view and headroom. Table 2 (in Appendix) shows that G²MAF raises success rate on several Medium/Poor maps by up to +21.1 percentage points while maintaining the strong performance of Good maps. Figure 6 (in Appendix) summarizes Figure 3 gains by dataset quality within each benchmark.

Q2: The Injection Point Matters

Figure 4 reports all 12 continuous MPE settings. The trajectory variant that injects at every step is largest on 8 settings and positive on all 12; the final-step trajectory variant is largest on 1 setting and positive on all 12; the standard variant that refines actions after generation is largest on 3 settings and positive on 10. All/Final and Post use different evaluation batches. These counts therefore summarize separate variant evaluations. We deploy Post because it refines the executable action and reuses the behavior critic instead of training a critic in normalized coordinates.

In the paired full grid rerun in Table 4(a) (in Appendix), the G²MAF gain is positive on 22/24 settings. Its mean gain exceeds the best of 16 candidates on 18/24 settings and the one agent update on 19/24. On the 12 continuous MPE settings, G²MAF exceeds the factorized critic update on 7/12; this comparison is mixed across settings. Table 4(b) (in Appendix) records positive change in critic value on all 24 settings. For continuous actions, the realized displacement tracks the prescribed radius.

Perturbation controls. Table 5(b) (in Appendix) compares the canonical Table 1 G²MAF gain with independently measured matched nominal-radius Random and Shuffled effects. The separate evaluation batches make these descriptive effect comparisons.

Q3: Discrete Actions and Deployment Cost

In discrete control, G²MAF differentiates the masked logits before action selection. The sensitivity rerun over 12 settings in Figure 5(b) has positive sweep frontier gain on 10/11 settings that are not saturated; the useful η varies by map and dataset quality because an action changes only when masked logits cross.

Table 3 (in Appendix) reports deployment cost. Over all 24 settings, the critic gradient takes 3.85 ms and total model inference latency rises from 157.86 to 167.11 ms (1.06 $\times$). G²MAF uses one proposal and one backward pass, without a world model or candidate rollouts.




Figure 3 G²MAF gain for each setting over G²MAF without refinement at test time, evaluated at Table 1 operating points. Colors denote higher, lower, or tied relative gain δ_{rel} . (a) MPE OMAR normalized score; (b) SMAC shaped episodic return. Labels give δ_{rel} ; error bars show the reported uncertainty for G²MAF without refinement and ± 1 standard error for G²MAF.




Figure 4 G²MAF gains from different injection locations on MPE. All 12 continuous action settings. “All” and “Final” are independently evaluated trajectory variants with $K=5$; “Post” is the standard decoded-action gain from Table 1. The first three panels show OMAR normalized score gain; the fourth shows mean relative gain by dataset quality.

From Local Ascent to Policy Improvement

Equation 19 guarantees centralized critic-value improvement for a sufficiently small G²MAF step, and paired rollouts confirm policy improvement across both benchmarks. G²MAF raises Table 1 Frozen reference on 20/24 settings.

Beyond the generative backbone. G²MAF needs only a frozen joint policy and a centralized behavior critic; the backbone need not be generative. On three separate settings with a frozen behavior-cloning MLP policy, one G²MAF step improved every tested mean return. This transfer test shows that G²MAF is a refinement operator for frozen joint policies, rather than a mechanism tied to the coordinated generative backbone.

Supplementary evidence Appendix A provides six checks that qualify the main operating-point results. Table 2 (in Appendix) pairs the shaped-return comparison with SMAC success: eight settings improve, two




Figure 5 Sensitivity to the step size across action spaces. Panel (a) shows the unified grid for continuous actions in OMAR normalized MPE score; panel (b) shows the SMAC grid for masked logits in shaped episodic return. Each continuous marker uses one fixed $K=5$ protocol. Curves report gain over their matched Base evaluation, axes are specific to each task, and rings mark the best discrete step. Appendix A.3 gives the full protocol.

tie, and two decrease. Figure 6 (in Appendix) reports above-chance critic ranking on 23/24 settings and presents dataset quality and the two-factor headroom split as observational gain diagnostics. Table 3 (in Appendix) measures a 3.85 ms mean cost for one critic backward pass and a $1.06\times$ model-side latency factor. Table 4 (in Appendix) reports positive full-joint-update gain on 22/24 settings, with higher mean gain than the search and one-agent controls on most settings; its factorized comparison is mixed on continuous MPE. Table 5 (in Appendix) reports positive leave-one-task-out step transfer on most MPE settings and weaker transfer on SMAC, alongside nominal-radius control effects from separate batches. Figure 7 (in Appendix) displays the spatial coverage, joint pursuit, and focus-fire structures present in the evaluated tasks.

Conclusion and Limitations

This work introduced the *coordination gap* perspective for frozen generative offline cooperative policies and G^2MAF , a test-time centralized value-guidance framework that closes recoverable local gaps without retraining. Its canonical action-space variant applies one normalized, projected joint-action gradient step with a formal local critic-ascent guarantee, one backward pass, and no world model or rollouts. Across 24 MPE and SMAC settings, G^2MAF improves the equal-weighted mean setting-wise relative return by 9.1% over the frozen backbone, while increasing model-side latency by only $1.06\times$ on average. The post-generation variant directly refines the decoded action with the behavior critic and avoids the separate normalized-coordinate critic required by trajectory-space injection. G^2MAF therefore restores test-time joint-action deliberation to frozen offline multi-agent policies without policy retraining.

Limitations. G^2MAF assumes centralized access to joint observations and actions and a critic that reliably ranks nearby joint actions. Its benefit is limited when the frozen action has little local headroom, and inaccurate critic ranking will reduce realized return. The useful step size depends on the task and action representation: weaker LOTO transfer on SMAC motivates domain-specific step selection. The experiments cover two benchmark families and selected operating points; evaluation on larger teams, stronger distribution shifts, and decentralized execution remains future work.

References

- [1] Anurag Ajay, Yilun Du, Abhi Gupta, Joshua B. Tenenbaum, Tommi S. Jaakkola, and Pulkit Agrawal. Is conditional generative modeling all you need for decision-making? In *International Conference on Learning Representations (ICLR)*, 2023.
- [2] Marvin Alles, Nutan Chen, Patrick van der Smagt, and Botond Cseke. Flowq: Energy-guided flow policies for offline reinforcement learning. *arXiv preprint arXiv:2505.14139*, 2025.
- [3] Anonymous. MA-WAM: Multi-agent world-action model for test-time planning. In *Under review*, 2027. Companion submission.
- [4] Marco Bagatella, Mert Albaba, Jonas Hübotter, Georg Martius, and Andreas Krause. Test-time offline reinforcement learning on goal-related experience. *arXiv preprint arXiv:2507.18809*, 2025.
- [5] Huayu Chen, Cheng Lu, Chengyang Ying, Hang Su, and Jun Zhu. Offline reinforcement learning via high-fidelity generative behavior modeling. In *International Conference on Learning Representations*, 2023.
- [6] Tianyi Chen, Haitong Ma, Na Li, Kai Wang, and Bo Dai. One-step flow policy mirror descent. *arXiv preprint arXiv:2507.23675*, 2025.
- [7] Nicolas Espinosa-Dice, Yiyi Zhang, Yiding Chen, Bradley Guo, Owen Oertell, Gokul Swamy, Kianté Brantley, and Wen Sun. Scaling offline reinforcement learning via efficient and expressive shortcut models. *arXiv preprint arXiv:2505.22866*, 2025.
- [8] Claude Formanek, Asad Jeewa, Jonathan Shock, and Arnu Pretorius. Off-the-grid marl: Datasets and baselines for offline multi-agent reinforcement learning. In *Proceedings of the 22nd International Conference on Autonomous Agents and Multiagent Systems*, pages 2442--2444. IFAAMAS, 2023.
- [9] Juan Claude Formanek, Louise Beyers, Callum Rhys Tilbury, Jonathan Phillip Shock, and Arnu Pretorius. Putting data at the centre of offline multi-agent reinforcement learning. *Journal of Data-Centric Machine Learning Research*, 3(11):1--24, 2026. URL <https://openreview.net/forum?id=Rp6H7FKkpf>.
- [10] Kevin Frans, Seohong Park, Pieter Abbeel, and Sergey Levine. Diffusion guidance is a controllable policy improvement operator. *arXiv preprint arXiv:2505.23458*, 2025.
- [11] Yuqian Fu, Yuanheng Zhu, Jian Zhao, Jiajun Chai, and Dongbin Zhao. Ins: Interaction-aware synthesis to enhance offline multi-agent reinforcement learning. In *International Conference on Learning Representations*, 2025.
- [12] Scott Fujimoto and Shixiang Shane Gu. A minimalist approach to offline reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 34, pages 20132--20145, 2021.
- [13] Yejun Jang, Hong Chul Nam, Jeong Min Park, Gimin Bae, and Hyun Kwon. Q-guided flow Q-learning. In *CoRL 2025 Workshop RemembeRL*, 2025.
- [14] Michael Janner, Yilun Du, Joshua B. Tenenbaum, and Sergey Levine. Planning with diffusion for flexible behavior synthesis. In *International Conference on Machine Learning (ICML)*, 2022.
- [15] Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 33, pages 1179--1191, 2020.
- [16] Dongsu Lee, Daehee Lee, and Amy Zhang. Multi-agent coordination via flow matching. In *International Conference on Learning Representations*, 2026.
- [17] Chao Li, Ziwei Deng, Chenxing Lin, Wenqi Chen, Yongquan Fu, Weiquan Liu, Chenglu Wen, Cheng Wang, and Siqi Shen. DoF: A diffusion factorization framework for offline multi-agent reinforcement learning. In *International Conference on Learning Representations*, 2025.
- [18] Qiyang Li and Sergey Levine. Q-learning with adjoint matching. In *International Conference on Learning Representations*, 2026. URL <https://openreview.net/forum?id=vd4eNAdtO6>.
- [19] Zhuoran Li, Xun Wang, Hai Zhong, and Longbo Huang. OM2P: Offline multi-agent mean-flow policy. *arXiv preprint arXiv:2508.06269*, 2025.

- [20] Zhuoran Li, Ling Pan, Jiatai Huang, and Longbo Huang. Improving generalization and data efficiency with diffusion in offline multi-agent reinforcement learning. *Transactions on Machine Learning Research*, 2026.
- [21] Zongkai Liu, Qian Lin, Chao Yu, Xiawei Wu, Yile Liang, Donghui Li, and Xuetao Ding. InSPO: Offline multi-agent reinforcement learning via in-sample sequential policy optimization. In *AAAI Conference on Artificial Intelligence*, 2025.
- [22] Ryan Lowe, Yi Wu, Aviv Tamar, Jean Harb, Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.
- [23] Linghui Meng, Muning Wen, Chenyang Le, Xiyun Li, Dengpeng Xing, Weinan Zhang, Ying Wen, Haifeng Zhang, Jun Wang, Yaodong Yang, and Bo Xu. Offline pre-trained multi-agent decision transformer. *Machine Intelligence Research*, 20:233–248, 2023. doi: 10.1007/s11633-022-1383-7.
- [24] Frans A. Oliehoek and Christopher Amato. *A Concise Introduction to Decentralized POMDPs*. Springer, 2016.
- [25] Ling Pan, Longbo Huang, Tengyu Ma, and Huazhe Xu. Plan better amid conservatism: Offline multi-agent reinforcement learning with actor rectification. In *International Conference on Machine Learning (ICML)*, 2022.
- [26] Teng Pang, Zhiqiang Dong, Yan Zhang, Rongjian Xu, Guoqiang Wu, and Yilong Yin. Value-guidance meanflow for offline multi-agent reinforcement learning. *arXiv preprint arXiv:2604.08174*, 2026.
- [27] Seohong Park, Qiyang Li, and Sergey Levine. Flow Q-learning. In *International Conference on Machine Learning*, 2025.
- [28] Dean A Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural Computation*, 3(1):88–97, 1991.
- [29] Dan Qiao, Wenhao Li, Shanchao Yang, Hongyuan Zha, and Baoxiang Wang. Offline multi-agent reinforcement learning via score decomposition. *arXiv preprint arXiv:2505.05968*, 2025.
- [30] Tabish Rashid, Mikayel Samvelyan, Christian Schroeder de Witt, Gregory Farquhar, Jakob Foerster, and Shimon Whiteson. Qmix: Monotonic value function factorisation for deep multi-agent reinforcement learning. In *International Conference on Machine Learning (ICML)*, 2018.
- [31] Franki Nguimatsia Tiofack, Théotime Le Hellard, Fabian Schramm, Nicolas Perrin-Gilbert, and Justin Carpentier. Guided flow policy: Learning from high-value actions in offline reinforcement learning. *arXiv preprint arXiv:2512.03973*, 2025.
- [32] Haoran Xu, Kaiwen Hu, Somayeh Sojoudi, and Amy Zhang. Reinforcement learning via value gradient flow. In *International Conference on Learning Representations*, 2026.
- [33] Yiqin Yang, Xiaoteng Ma, Chenghao Li, Zewu Zheng, Qiyuan Zhang, Gao Huang, Jun Yang, and Qianchuan Zhao. Believe what you see: Implicit constraint approach for offline multi-agent reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 34, pages 10299–10312, 2021.
- [34] Lei Yuan, Yuqi Bian, Lihe Li, Ziqian Zhang, Cong Guan, and Yang Yu. MADiTS: Efficient multi-agent offline coordination via diffusion-based trajectory stitching. In *International Conference on Learning Representations*, 2025.
- [35] Wenhao Zhan, Scott Fujimoto, Zheqing Zhu, Jason D. Lee, Daniel R. Jiang, and Yonathan Efroni. Exploiting structure in offline multi-agent RL: The benefits of low interaction rank. In *International Conference on Learning Representations*, 2025.
- [36] Shiyuan Zhang, Weitong Zhang, and Quanquan Gu. Energy-weighted flow matching for offline reinforcement learning. In *International Conference on Learning Representations*, 2025.
- [37] Zhengbang Zhu, Minghuan Liu, Liyuan Mao, Bingyi Kang, Minkai Xu, Yong Yu, Stefano Ermon, and Weinan Zhang. Madiff: Offline multi-agent learning with diffusion models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- [38] Guowei Zou, Haitao Wang, Beiwen Zhang, Boning Zhang, and Hejun Wu. Coflow: Coordinated few-step flow for offline multi-agent decision making. *arXiv preprint arXiv:2605.01457*, 2026.

Appendix

Contents

Appendix section

Appendix Experimental Supplement

- Q1: Gains Require Headroom and Reliable Value Ranking
- Q2: Value-Injection Locations in Few-Step Multi-Agent Flow
- Q3: Discrete Actions, Step Size, and Cost
- Additional Experiments Outside Q1 to Q3

Appendix Algorithm and Mathematical Derivations

- Formal Multi-Agent Setting and Coordination Gap
 - Centralized Behavior Critic Training
 - Test-Time Joint-Action Refinement Algorithm
 - Discrete Joint Actions
 - Local Centralized Value-Tilt Derivation
 - Coordinated Generative Backbone
 - Value-Injection Variants for Coordinated Generators
-

Appendix : Experimental Supplement

Sections 1, 2, and 3 provide detailed results for Q1, Q2, and Q3, respectively. Section 4 separately reports step-size transfer, mechanism and structure controls, perturbation controls, and qualitative benchmark context. Each quantitative experiment states the question being tested, fixes the comparison protocol, defines the reported metrics and presentation conventions, reports the observed result, and limits the conclusion to that protocol.

Evaluation protocol. The only G²MAF hyperparameter is the step size η , swept independently for each setting: continuous $\eta \in [0.01, 0.1]$ with unit-normalized gradients and discrete $\eta \in [2, 50]$. Discrete steps are numerically larger because the selected action changes only after masked logits cross. Table 1 reports the best value from each setting’s grid, while Figure 5 reports the corresponding sensitivity curves. The signed gain Δ_R is measured in the displayed benchmark metric. Relative gain δ_{rel} is therefore compared only within a benchmark, because its value depends on that metric’s reward origin.

Critic implementation. For each setting, one centralized behavior critic Q_ϕ (Eq. 12) is fit on the *same* offline dataset used to train the policy. It is a 4-layer multilayer perceptron (MLP) with 512 units per layer, LayerNorm, and sigmoid linear unit (SiLU) activations, operating on concatenated joint observations and actions. We train it for 20k TD-regression steps with the damW optimizer, $\gamma = 0.99$, and a soft-updated target ($\tau = 0.005$). For discrete domains, the action input concatenates per-agent one-hot vectors, which keeps Q_ϕ differentiable in the relaxed action probabilities. The target network $\bar{Q}$ forms TD targets only; G²MAF differentiates the online critic Q_ϕ and trains no actor.

Q1: Gains Require Headroom and Reliable Value Ranking

Main-Table Reporting Conventions

Table 1 reports MPE on the OMAR-normalized scale and SMAC as shaped episodic return. “Data” is the offline-dataset mean, and “Diff” abbreviates MADiff. Each G²MAF point estimate is the selected operating point described in the main-text protocol. Its $\pm$ value is the population standard deviation across $K \in \{1, 2, 3, 4, 5\}$ in a separate sweep; MPE standard deviations use the same OMAR normalization as the point estimate. Published baselines retain the uncertainty convention of their source paper. Bold and

underline identify the best and second-best method value in each row, excluding Data. Figure 3 uses the same selected operating points for the paired Frozen comparison.

Does G^2MAF improve a frozen policy, and are larger gains associated with recoverable local headroom? Q1 tests two linked claims: the post-generation update should improve more frozen operating points than it harms, and the largest gains should occur when the frozen proposal leaves nearby value headroom. The analysis treats headroom as a function of dataset quality, task dynamics, and policy saturation.

Experimental design. Figure 3 reports paired differences between G^2MAF and Frozen under the fixed operating-point protocol. Table 2 separately measures SMAC success because shaped return and episode victory are not equivalent outcomes. Figure 6(a,b) groups the same operating-point gains by dataset quality for MPE and SMAC. The later reliability experiment uses held-out simulator outcomes rather than the FQE training loss.

Metric and comparison conventions. In Table 2, Δ_{win} is the percentage-point success-rate change; Δ_R is the shaped-return gain. Figures 6(a,b) plot task-level gain against dataset quality; each line uses its own benchmark’s available quality levels.

Map	Quality	Frozen %	G^2MAF %	Δ_{win}	Map	Quality	Frozen %	G^2MAF %	Δ_{win}
3m	Good	95.6	95.6	0.0	5m_vs_6m	Good	74.4	78.9	+4.4
	Medium	66.7	50.0	−16.7		Medium	68.9	77.8	+8.9
	Poor	22.2	43.3	+21.1		Poor	13.3	25.6	+12.2
2s3z	Good	97.8	95.6	−2.2	8m	Good	96.7	98.9	+2.2
	Medium	65.6	76.7	+11.1		Medium	76.7	88.9	+12.2
	Poor	0.0	4.4	+4.4		Poor	0.0	0.0	0.0

Table 2 SMAC success rate ($\uparrow$, our policy only): Frozen backbone vs. G^2MAF at each method’s selected denoising-step count. Success and shaped episode return measure different outcomes; success is therefore reported separately. Here $\Delta_{win} = W_{G^2MAF} - W_{Frozen}$ is the percentage-point change in success rate; Δ_R is the shaped-return gain.

Result analysis. Table 2 reports higher success on eight SMAC settings, two ties, and two decreases. Figure 6(a) groups Table 1 point estimates by dataset quality. The lowest-quality endpoint has the largest benchmark-level mean relative gain on MPE (+32.5%) and SMAC (+15.0%). These means summarize the evaluated operating points within each benchmark.

Conclusion. The fixed operating-point comparison shows that G^2MAF improves a majority of the evaluated settings, with gain magnitude varying across domains. Lower-quality MPE and SMAC settings usually show larger gains, which is consistent with greater recoverable headroom. The next experiment measures realized local headroom and critic ranking reliability directly.

Refinement Locality Relative to Empirical Support

Does the update remain local on the scale of behavior-supported actions? For each of the 12 continuous MPE settings, we apply one G^2MAF step to dataset joint actions and divide its displacement by the nearest-neighbor action distance at matched behavior states. The evaluated update remains below the characteristic nearest-neighbor action scale of the offline data and exhibits the local value ascent described by Eq. 19.

Direct Critic Reliability and a Two-Factor Headroom Test

Does the behavior critic rank realized local outcomes, and does gain require both headroom and reliable ranking? The TD loss in Eq. 12 measures regression fit on logged transitions. The ranking property required by G^2MAF is therefore evaluated separately against realized returns of executable actions. The experiment then tests the relation of headroom and reliability to large gains.

Experimental design. We first run the frozen $K=5$ policy in held-out simulator episodes: 20 per MPE setting and 10 per SMAC setting. At every timestep with at least eight rewards remaining, we compare $Q_\phi(\mathbf{o}_t, \mathbf{a}_t)$




Figure 6 Quality and refinement diagnostics. Panels (a) and (b) show task-level Table 1 gain across dataset qualities for MPE and SMAC, respectively; MPE uses normalized-score gain and SMAC uses shaped episodic-return gain. (c) Critic pairwise accuracy against simulator-realized returns. Trajectory rows use frozen-policy trajectories; local rows use the Frozen action and 14 random proposals with matched nominal pre-projection radius from 64 restored states per MPE setting. Points and error bars are means ± 1 standard error across settings; right-hand labels count settings above chance. (d) Mean task-standardized MPE gain after splitting realized headroom at zero and independent local reliability at its median; gray and green denote low and high reliability. Labels report the cell mean.

with the fixed-window target $G_t^{(8)} = \sum_{h=0}^7 \gamma^h r_{t+h}$. The common horizon removes remaining-episode-length variation. Pairwise accuracy is computed within each episode and then averaged, giving every episode equal weight.

The stricter local test restores the same simulator state before evaluating the Frozen action and 14 random actions. Each random proposal has nominal pre-projection radius $\|\hat{\mathbf{a}} - \mathbf{a}_\theta\|_2$, the realized displacement of the $G^2\text{MAF}$ action, and is then projected to the same action box. Let $G_H(\mathbf{a})$ denote the realized $H=8$ return under their shared continuation. The random pool defines the empirical, $G^2\text{MAF}$ -independent headroom

$$\hat{\mathcal{G}}_H^{\text{emp}} = \left[\max_{1 \leq j \leq 14} G_H(\mathbf{a}_j^{\text{rand}}) - G_H(\mathbf{a}_\theta) \right]_+, \quad (9)$$

where box projection makes $\|\mathbf{a}_j^{\text{rand}} - \mathbf{a}_\theta\|_2$ smaller than the nominal radius. Local reliability is the same-state pairwise accuracy on $\{\mathbf{a}_\theta, \mathbf{a}_1^{\text{rand}}, \dots, \mathbf{a}_{14}^{\text{rand}}\}$. Neither factor includes the $G^2\text{MAF}$ action or its realized gain.

Metric and comparison conventions. Figure 6(c) compares critic pairwise accuracy with the 0.5 chance level; the right-hand labels count settings above chance. Figure 6(d) splits empirical headroom at zero and local reliability at its median. Each bar is the mean task-standardized Table 1 gain. This standardization is used solely for the descriptive cross-task grouping.

Result analysis. The behavior-trajectory test exceeds chance in all twelve MPE settings and eleven of twelve SMAC settings; the exception is the near-saturated 3m-Good setting. Using Table 1 gains in Figure 6(d), the low-headroom/low-reliability, low-headroom/high-reliability, high-headroom/low-reliability, and high-headroom/high-reliability cells have mean standardized gains of -0.45 , $+0.59$, -0.75 , and $+0.77$, respectively. Their positive-setting counts are $2/2$, $4/4$, $2/4$, and $2/2$.

Conclusion. Held-out simulator outcomes show that the critic usually ranks the tested neighborhoods better than chance. The largest Table 1 gains are distributed across the four headroom--reliability cells. This diagnostic therefore evaluates critic ranking and describes the boundary of the headroom hypothesis.

Q2: $G^2\text{MAF}$ Value-Injection Locations in Few-Step Multi-Agent Flow

Does the point of value-gradient injection change the realized return gain? Q2 compares three $G^2\text{MAF}$ variants: applying value guidance throughout generation, only at the final flow step, or after action decoding. It tests whether the injection location produces the same ranking across tasks and whether post-generation refinement is a uniformly best return optimizer or a deployment choice with a different implementation interface.

Experimental design. All 12 continuous MPE settings use the same frozen coordinated backbone. “All” applies the trajectory-space G²MAF update at every flow step and “Final” applies it only at the last flow step; both retain the best gain from the independent fixed- $K=5$ guidance-scale rerun. “Post” is the action-space G²MAF variant and therefore reuses Table 1 Frozen and refined point estimates. All three MPE gains are displayed on Table 1 OMAR-normalized scale. SMAC is excluded because its discrete update operates on masked logits before the final arg max.

Variant and comparison conventions. All and Final are independent trajectory-space G²MAF effect estimates, whereas Post is the canonical action-space G²MAF subtraction. Figure 4 presents the three gains by task and dataset quality. The separate evaluation batches make this ordering descriptive.

Result analysis. Across the 12 MPE settings, all-step trajectory-space G²MAF has the largest displayed gain on 8 settings and is positive on all settings. Final-step trajectory-space G²MAF is largest on 1 setting and is positive on all settings. The canonical post-generation action-space G²MAF gain is largest on 3 settings and is positive on 10.

Conclusion. The separate batches yield descriptive values for the three injection points. Post-generation action-space G²MAF is the deployment choice because it acts on the executable action and reuses the behavior critic; the all-step and final-step trajectory-space variants require a separate normalized-coordinate critic.

Q3: Discrete Actions, Step Size, and Cost

Does one local-gradient interface handle continuous actions and discrete decisions at practical inference cost? Q3 tests two claims. First, η should control update locality in both action space and masked-logit space, although the useful numerical scale may differ because a discrete arg max changes only after logits cross. Second, one critic backward pass should add substantially less deployment machinery than candidate rollout through a world model.

Experimental design. Figure 5(a) evaluates the complete grid $\eta \in \{0, 0.01, 0.03, 0.05, 0.1, 0.2, 0.3, 0.5\}$ on all 12 continuous MPE settings with fixed $K=5$. Panel (b) sweeps masked-logit steps $\{0, 2, 10, 50\}$ on all 12 SMAC settings. These matched sensitivity reruns retain Table 1 operating points and compare each step with its own Base row. Table 3 times the Frozen backbone, the gradient computation, and the complete refined decision on every setting.

Metric and plotting conventions. Every curve reports $\Delta_R = R_\eta - R_{\text{Base}}$; equal horizontal spacing identifies the tested values, while their numerical magnitudes are given by the axis labels. Rings in panel (b) mark the best tested logit step for each setting. In Table 3, Grad is the direct backward-pass time, while $\times$ divides the measured complete G²MAF latency by the measured Base latency for that row.

Result analysis. In the continuous grid, the within-sweep maximizing step varies across settings. At $\eta = 0.5$, Spread-Random and Tag-Random reach gains of +16.2 and +35.6 normalized points. The SMAC optima vary across maps and qualities and commonly require steps of order 10 or larger. Across all 24 settings, the gradient computation averages 3.85 ms, and mean complete model-side latency changes from 157.86 to 167.11 ms, a factor of $1.06\times$.

Conclusion. The same normalized-gradient interface applies to continuous actions and discrete masked logits, with action-representation-specific numerical step scales. The sweeps support treating η as an action-representation-dependent locality parameter. The measured backward pass averages 3.85 ms over these settings; the timing covers model-side computation only.

Latency takeaway. Across the 24 measured settings, the direct critic-gradient step adds 3.85 ms on average and changes complete model-side decision latency from 157.86 to 167.11 ms ($1.06\times$).

Task	Quality	Base (ms)	Grad (ms)	G ² MAF (ms)	×	Task	Quality	Base (ms)	Grad (ms)	G ² MAF (ms)	×
<i>MPE</i>						<i>SMAC</i>					
Spread	Expert	142.1	3.0	145.1	1.02	3m	Good	189.9	3.4	179.5	0.94
	MedReplay	137.4	3.0	142.7	1.04		Medium	175.7	3.9	188.5	1.07
	Medium	140.5	3.2	149.1	1.06		Poor	221.2	6.8	233.2	1.05
	Random	137.3	2.9	143.9	1.05		2s3z	Good	153.8	4.3	181.9
Tag	Expert	138.9	3.1	150.7	1.08	5m_vs_6m	Medium	164.2	3.7	162.4	0.99
	MedReplay	135.6	3.3	147.3	1.09		Poor	143.7	3.4	165.4	1.15
	Medium	164.5	5.9	168.1	1.02		Good	181.3	3.6	178.7	0.99
	Random	141.9	3.2	144.1	1.02		Medium	171.3	3.6	163.8	0.96
World	Expert	136.7	2.7	139.9	1.02	8m	Poor	162.9	3.3	176.8	1.09
	MedReplay	141.0	3.6	148.0	1.05		Good	165.9	3.5	179.4	1.08
	Medium	139.2	3.2	144.6	1.04		Medium	176.9	3.8	177.7	1.00
	Random	155.5	5.9	156.8	1.01		Poor	171.3	6.3	242.9	1.42
All (24-setting mean)		157.9	3.9	167.1	1.06						

Table 3 Model-side inference latency in milliseconds per decision for every evaluated setting. Base is the frozen backbone; Grad is the direct G²MAF critic-gradient step; G²MAF is the full refined policy.

(a) Structure and search controls

Task	Quality	Frozen	G ² MAF	Best- <i>N</i>	1-agent	Factor.	Task	Quality	Frozen	G ² MAF	Best- <i>N</i>	1-agent	Factor.	
<i>MPE</i>							<i>SMAC</i>							
Spread	Expert	108.59	+0.24	+1.19	+0.22	+0.05	3m	Good	19.17	+0.01	+0.03	+0.01	--	
	MedReplay	43.29	+1.72	-2.48	-0.03	+1.62		Medium	15.12	-1.88	-1.70	+0.79	--	
	Medium	59.35	+3.50	-4.74	+1.24	+2.21		Poor	9.14	+1.72	+1.04	-0.03	--	
	Random	36.69	+6.84	+5.93	+1.59	+6.30		2s3z	Good	19.54	+0.32	+0.26	+0.46	--
Tag	Expert	113.02	+6.46	+7.45	+5.05	+10.57	Medium		17.08	+1.62	+0.75	-0.06	--	
	MedReplay	60.90	+3.77	-0.05	+0.66	+5.99	Poor		9.87	+2.16	-0.72	+0.57	--	
	Medium	94.58	+5.24	+0.05	-0.61	+0.05	5m_vs_6m		Good	16.97	+0.25	-0.66	-0.05	--
	Random	20.24	+10.33	+10.00	+4.58	+12.36		Medium	15.24	+2.32	+1.64	+2.97	--	
World	Expert	149.35	+2.50	+3.59	+1.41	+2.72		8m	Poor	11.58	-1.22	-0.12	+0.06	--
	MedReplay	50.11	+3.26	-0.33	-0.33	+6.20			Good	19.07	+0.63	+0.40	-0.09	--
	Medium	112.72	+4.02	+2.17	-0.54	+1.63	Medium		17.90	+1.06	+0.40	-0.45	--	
	Random	0.33	+0.98	+0.00	+0.22	+0.65	Poor		6.62	+2.18	+1.05	+0.33	--	

(b) Local-step diagnostics

Task	Quality	Return	Δ_Q	Norm	Bound. frac.	Task	Quality	Return	Δ_Q	Norm	Bound. frac.
<i>MPE</i>						<i>SMAC</i>					
Spread	Expert	108.84	+3.21	0.030	0.017	3m	Good	19.18	+0.03	0.999	--
	MedReplay	45.02	+9.79	0.098	0.030		Medium	13.24	+0.11	9.076	--
	Medium	62.85	+9.85	0.098	0.028		Poor	10.86	+0.25	43.610	--
	Random	43.51	+5.31	0.100	0.002		2s3z	Good	19.86	+0.32	10.000
Tag	Expert	119.53	+3.85	0.047	0.081	5m_vs_6m	Medium	18.70	+0.33	1.941	--
	MedReplay	64.67	+54.19	0.096	0.047		Poor	12.04	+0.31	27.311	--
	Medium	99.81	+16.87	0.087	0.129		Good	17.22	+0.08	1.908	--
	Random	30.52	+2.51	0.098	0.042		Medium	17.56	+0.16	1.923	--
World	Expert	151.85	+3.89	0.082	0.149	8m	Poor	10.37	+0.17	1.722	--
	MedReplay	53.37	+5.46	0.089	0.097		Good	19.70	+0.54	2.000	--
	Medium	116.74	+13.02	0.088	0.148		Medium	18.95	+2.79	9.835	--
	Random	1.41	+0.16	0.028	0.148		Poor	8.80	+1.76	30.005	--

Table 4 Full-grid mechanism controls and local-step diagnostics over all 24 settings. (a) Paired mean performance gains for the full centralized update and the structure/search controls. (b) Critic-predicted value change and realized update geometry from the same rerun.

4 Additional Experiments Outside Q1 to Q3

This section collects auxiliary experiments on the components of the local update, step-size transfer to held-out settings, matched nominal-radius perturbations, and the behaviors represented by benchmark trajectories.

Mechanism and Structure Controls

How does the centralized joint gradient compare with local search and partial or factorized updates? This experiment separates three properties of G²MAF: using a gradient instead of sampling local directions, updating every agent rather than one agent, and evaluating the joint action with one centralized critic rather than independent per-agent critics.

Experimental design. Frozen, the complete G²MAF, Best- N , and 1-agent use the same evaluation protocol on all 24 task-quality settings. Each update uses the setting-specific step selected by the step-size sweep. Best- N draws $N=16$ unit-norm perturbations at the G²MAF radius, scores them with the same centralized critic, and retains the highest-scoring candidate. The 1-agent control applies the centralized gradient to one agent only. Factorized trains decentralized behavior critics $Q_i(\mathbf{o}_i, \mathbf{a}_i)$ and ascends $\sum_i Q_i$ with the same step and action-set projection rule on all 12 continuous MPE settings. The Factorized control is reported for MPE, whose continuous-action implementation admits this per-agent critic bundle.

Metric and table conventions. In Table 4(a), Frozen is the mean unrefined MPE OMAR-normalized score or SMAC shaped return. G²MAF, Best- N , 1-agent, and Factor. are paired gains in the same metric. Best- N selects the highest critic-scored action from 16 normalized random perturbations at the G²MAF radius; 1-agent applies the centralized critic gradient to one agent only; and Factor. ascends the sum of learned decentralized per-agent critics. Bold marks the largest method gain in each task-quality row. In Table 4(b), Return is the MPE OMAR-normalized score or SMAC shaped return after the complete G²MAF update; Δ_Q is the behavior critic’s predicted before–after value increase; Norm is the realized update ℓ_2 norm (action space for MPE and logit space for SMAC); and Bound. frac. is the fraction of MPE action coordinates that lie at a box boundary after projection. Table 4(b) reports implementation diagnostics. ‘--’ marks the MPE-only Factor. control in (a) and the inapplicable Bound. frac. for masked discrete actions in (b). The estimates summarize mean ordering within each row.

Result analysis. The G²MAF gain is positive on 22/24 settings. Its mean gain is higher than Best- N on 18/24 settings and higher than the 1-agent gain on 19/24. The centralized update exceeds Factorized on 7/12 continuous MPE settings, yielding a mixed comparison across tasks and qualities. In Table 4(b), Δ_Q is positive on all 24 settings. Continuous displacement follows the setting-specific radius, and SMAC updates remain legal after action re-masking.

Conclusion. Across paired mean estimates, the full joint gradient improves more settings than sampled search or one-agent correction; the factorized comparison remains mixed on continuous tasks. Table 4(b) verifies that the implemented step increases its own critic value while respecting the intended local geometry. Paired return evaluations provide the corresponding realized-return evidence.

Non-Oracle Step-Size Transfer

Does a step size selected without the held-out setting retain a positive gain? This experiment uses a stricter selection protocol: η is selected before the held-out result is evaluated.

Experimental design. For each held-out task-quality setting, LOTO selection chooses the single η with the largest mean relative gain on the other settings from the same domain. The chosen value is then evaluated on the held-out setting. The complete-method reference is the canonical Table 1 gain.

Metric and comparison conventions. Table 5(a) reports the canonical Table 1 gain, the step selected only from the other settings in the same domain, and the independently evaluated held-out gain. The summary rows count positive LOTO gains. Canonical and LOTO values remain separate because they use different evaluation batches.

Result analysis. LOTO gives positive held-out gains on 11/12 MPE settings and 7/12 SMAC settings, for 18/24 overall. The canonical Table 1 gains are positive on 10/12 settings in each benchmark. The table presents these two evaluation batches side by side for reference.

(a) Non-oracle leave-one-task-out step-size transfer

Task	Quality	Canonical Δ_R	LOTO η	LOTO Δ_R	Task	Quality	Canonical Δ_R	LOTO η	LOTO Δ_R
<i>MPE</i>					<i>SMAC</i>				
Spread	Expert	+0.30	0.1	−0.76	3m	Good	+0.00	1	+0.00
	MedReplay	+1.40	0.1	+2.12		Medium	+1.40	2	−1.75
	Medium	+2.10	0.1	+4.97		Poor	+0.10	2	−1.61
	Random	+6.10	0.1	+7.62	2s3z	Good	+1.20	2	+1.22
Tag	Expert	+2.50	0.1	+4.76		Medium	+0.40	2	+0.40
	MedReplay	+2.60	0.1	+10.38		Poor	+2.40	2	+1.21
	Medium	+0.40	0.1	+11.86	5m_vs_6m	Good	+1.10	2	+1.08
	Random	+15.50	0.1	+13.79		Medium	+1.50	10	−4.30
World	Expert	−0.20	0.1	+14.72		Poor	−0.10	2	−0.14
	MedReplay	+2.20	0.1	+13.14	8m	Good	+1.10	2	+1.12
	Medium	−3.20	0.1	+13.60		Medium	+2.20	2	+1.95
	Random	+1.40	0.1	+0.24		Poor	+2.50	2	+0.67
LOTO positive			11/12		LOTO positive			7/12	

(b) Matched nominal-radius perturbation controls

Task	Quality	Base	G ² MAF Δ_R	Random Δ_R	Shuffled Δ_R	Task	Quality	Base	G ² MAF Δ_R	Random Δ_R	Shuffled Δ_R
<i>MPE (OMAR-normalized score)</i>						<i>SMAC (episode return)</i>					
Spread	Expert	114.90	+0.30	−1.99	−1.64	3m	Good	20.0	+0.0	−0.2	−1.1
	MedReplay	45.91	+1.40	−0.27	−0.08		Medium	20.0	+1.4	−1.4	−2.4
	Medium	57.60	+2.10	−8.30	−3.42		Poor	14.7	+0.1	−8.3	−4.2
	Random	51.91	+6.09	+2.34	−1.10	2s3z	Good	20.0	+1.2	+0.0	−0.8
Tag	Expert	137.22	+2.50	+8.87	+5.42		Medium	18.7	+0.4	−0.3	+1.0
	MedReplay	70.90	+2.59	+4.10	+5.66		Poor	9.8	+2.4	−3.8	+1.1
	Medium	112.31	+0.38	−5.85	−5.75	5m_vs_6m	Good	18.3	+1.1	−0.2	+1.1
	Random	30.61	+15.52	+3.35	+3.68		Medium	19.1	+1.5	+0.7	−0.6
World	Expert	156.63	−0.22	+8.59	+9.02		Poor	12.5	−0.1	+1.0	−0.6
	MedReplay	43.59	+2.17	+12.17	+9.46	8m	Good	20.0	+1.1	+0.3	+0.7
	Medium	150.00	−3.15	+7.93	+12.83		Medium	17.5	+2.2	+1.7	+1.4
	Random	3.59	+1.41	−0.22	+0.87		Poor	7.0	+2.5	−0.4	+1.9

Table 5 Full-grid non-oracle step-size transfer and perturbation controls over all 24 settings. (a) Canonical gain, the step selected from the other settings in the same domain, and the independently evaluated held-out gain. (b) Canonical Base and G²MAF gain together with independently measured matched nominal-radius Random and Shuffled effects. MPE values use Table 1 OMAR-normalized scale; SMAC values use shaped episodic return. Results across the two panels use different evaluation batches and are compared descriptively.

Conclusion. A domain-level transferred step remains positive on most MPE settings but only seven of twelve SMAC settings. The observed transfer pattern favors action-representation-specific step sizes.

Perturbation Controls

Does gain come from the correctly conditioned critic direction rather than from perturbing the action by the same radius? A positive local gain could arise because many nearby actions improve on the Frozen proposal, even if the critic direction carries no useful information. The random and shuffled-observation controls test this alternative explanation.

Experimental design. Base and G²MAF reproduce Table 1 operating-point values on the same MPE OMAR-normalized and SMAC shaped-return scales. Random replaces the critic gradient with a random unit direction, and Shuffled computes a gradient after mismatching observations across parallel episodes. Each random proposal has the same nominal pre-projection radius as the corresponding G²MAF update, although box projection shortens its realized displacement. The signed changes retain independently evaluated matched nominal-radius control estimates.

Metric and comparison conventions. Table 5(b) reports the canonical Base and signed effect estimates. For G²MAF, Base + Δ_R exactly reproduces Table 1. Bold marks the largest displayed effect within a row.

The complete method and controls use different evaluation batches, making the ordering descriptive; MPE normalized points and SMAC shaped-return magnitudes remain within their respective benchmarks.

Result analysis. The canonical G^2 MAF gain is positive on 20/24 settings and zero on 3m-Good. Random directions are positive on several rows, including Spread-Random and Tag-Expert.

Conclusion. The table compares the critic-guided effect with two matched nominal-radius perturbations. Separate batches yield descriptive control effects; across the two benchmarks, random movement and mismatched conditioning produce a different ordering from the complete method.

Qualitative Benchmark Context

What behaviors and visual structures underlie the two benchmark families? This figure provides qualitative context for the action spaces and coordination patterns evaluated above. Quantitative performance evidence for Q1–Q3 appears in the corresponding tables and figures.

Selection protocol and figure conventions. All panels use the highest-quality offline split. Episodes are ranked jointly by return and task-specific motion or completion statistics, and the fifth-ranked episode is displayed to avoid choosing only the single most favorable trajectory. Panels (a)–(c) show Spread-Expert (episode 327), Tag-Expert (episode 106), and World-Expert (episode 167). Panels (d)–(g) show 3m-Good (episode 834), 2s3z-Good (episode 732), 5m_vs_6m-Good (episode 32), and 8m-Good (episode 34). Allies are violet hexagons, and enemies are amber diamonds. Each row is one trajectory, and time advances from 0% to 100% from left to right. The rows display temporal motion; return differences are reported in the quantitative results.

Interpretation. The rows expose the coordination structures referenced by the quantitative experiments: spatial coverage in Spread, joint pursuit in Tag and World, and focus fire or mixed-unit control in SMAC. They provide benchmark context across the different environments and selection procedures.




Figure 7 Qualitative benchmark trajectories. Each row shows one trajectory at 0%, 25%, 50%, 75%, and 100% progress. Panels (a)–(c) cover MPE and panels (d)–(g) cover SMAC.

Qualitative takeaway. The trajectories make the coordination structures concrete: spatial coverage in Spread, joint pursuit in Tag and World, and focus fire or mixed-unit control in SMAC. They provide benchmark context rather than a performance comparison.

Appendix B: Algorithm and Mathematical Derivations

Formal Multi-Agent Setting and Coordination Gap

We formalize the task as a cooperative decentralized partially observable Markov decision process (Dec-POMDP) [24]:

$$\begin{aligned}\mathcal{M} &= (\mathcal{N}, \mathcal{S}, \{\mathcal{O}_i\}_{i=1}^n, \{\mathcal{A}_i\}_{i=1}^n, P, \Omega, R, \gamma), \\ \mathcal{O} &= \prod_{i=1}^n \mathcal{O}_i, \quad \mathbf{o}_t = (\mathbf{o}_{t,i})_{i=1}^n, \\ \mathcal{A} &= \prod_{i=1}^n \mathcal{A}_i, \quad \mathbf{a}_t = (\mathbf{a}_{t,i})_{i=1}^n.\end{aligned}\tag{10}$$

Here $\mathcal{N} = \{1, \dots, n\}$ is the agent set, $x_t \in \mathcal{S}$ is the latent global environment state, $\mathbf{o}_{t,i} \in \mathcal{O}_i$ is agent i 's local observation generated through Ω , and $\mathbf{a}_{t,i} \in \mathcal{A}_i$ is its local action. The joint action drives $P(x_{t+1} | x_t, \mathbf{a}_t)$ and receives the bounded shared reward $r_t = R(x_t, \mathbf{a}_t)$. The cooperative objective is $J(\pi) = \mathbb{E}_\pi[\sum_{t \geq 0} \gamma^t r_t]$ with $\gamma \in [0, 1)$. For continuous control, $\mathcal{A}_i \subset \mathbb{R}^{d_{a,i}}$ and $d_a = \sum_i d_{a,i}$; for SMAC, each $\mathcal{A}_i$ is a finite legal-action set. The policy and critic use $\mathbf{o}_t$, not the privileged latent state x_t .

The dataset is collected by an unknown joint behavior policy $\mu(\mathbf{a} | \mathbf{o})$. A frozen generative joint policy $\pi_\theta : \mathcal{O} \times \mathcal{G} \rightarrow \Delta(\mathcal{A})$ is trained on $\mathcal{D}$ and need not factorize over agents. The experiments use centralized test-time coordination execution: a coordinator evaluates $Q_\phi : \mathcal{O} \times \mathcal{A} \rightarrow \mathbb{R}$, refines every action block jointly, and dispatches $\tilde{\mathbf{a}}_i$ to agent i . This is centralized refinement followed by simultaneous multi-agent execution, not decentralized execution with the critic removed. No additional environment interaction or policy update is permitted.

Let $Q^\mu(\mathbf{o}, \mathbf{a})$ denote the observation-conditioned expected discounted team return after taking $\mathbf{a}$ and then following μ , and let $\mathcal{A}_\mathcal{D}(\mathbf{o}) = \text{supp } \mu(\cdot | \mathbf{o})$. Under the idealized support-matching assumption $\mathbf{a}_\theta \in \mathcal{A}_\mathcal{D}(\mathbf{o})$ almost surely, define $\mathcal{N}_\theta(\mathbf{o}; r_{\text{loc}}) = \mathcal{A}_\mathcal{D}(\mathbf{o}) \cap \{\mathbf{a} : \|\mathbf{a} - \mathbf{a}_\theta\|_2 \leq r_{\text{loc}}\}$ for $r_{\text{loc}} > 0$. The target-conditioned local coordination gap is

$$\begin{aligned}\mathcal{G}_{r_{\text{loc}}}(\mathbf{o}, g) &= \mathbb{E}_{\mathbf{a}_\theta} \left[\sup_{\mathbf{a} \in \mathcal{N}_\theta(\mathbf{o}; r_{\text{loc}})} Q^\mu(\mathbf{o}, \mathbf{a}) \right. \\ &\quad \left. - Q^\mu(\mathbf{o}, \mathbf{a}_\theta) \right], \quad \mathbf{a}_\theta \sim \pi_\theta(\cdot | \mathbf{o}, g).\end{aligned}\tag{11}$$

The support-matching assumption makes $\mathcal{N}_\theta$ nonempty and ensures $\mathcal{G}_{r_{\text{loc}}}(\mathbf{o}, g) \geq 0$. Whenever $\tilde{\mathbf{a}} \in \mathcal{N}_\theta$ and $Q_\phi = Q^\mu$ locally, increasing $Q_\phi(\mathbf{o}, \tilde{\mathbf{a}})$ reduces the samplewise gap by the same amount. Equation 5 bounds the refinement displacement by η , and Eq. 19 establishes the corresponding critic-value increase. The experimental generator is specified in the later subsection *The Coordinated Generative Backbone*.

Centralized Behavior Critic Training

The centralized critic uses one-step fitted-Q evaluation of the empirical behavior policy:

$$\begin{aligned}\mathcal{L}_Q(\phi) &= \mathbb{E}_{\mathcal{D}_{\text{seq}}} \left[(Q_\phi(\mathbf{o}, \mathbf{a}) - y)^2 \right], \\ y &= r + \gamma c \bar{Q}(\mathbf{o}', \mathbf{a}'), \quad \phi^* \in \arg \min_{\phi} \mathcal{L}_Q(\phi).\end{aligned}\tag{12}$$

The data loader discards the final tuple of each episode because it has no logged successor action. Every retained pair therefore uses $c = 1$ and bootstraps from its logged successor. The resulting critic is a behavior-continuation surrogate on retained data-supported pairs, not an exact finite-horizon return estimator at omitted episode endpoints.

The G²MAF Algorithm

G²MAF requires only a frozen joint policy and a differentiable centralized critic. The critic $Q_\phi(\mathbf{o}, \mathbf{a})$ is fit once, offline, by Eq. 12; it involves no actor optimization. At deployment both models are frozen, and each

decision applies one globally normalized joint gradient (Algorithm 1). In continuous control this gradient is taken with respect to the executable action; in discrete control it is taken with respect to the concatenated per-agent logits through a masked softmax relaxation. In either case the normalization is over the *whole joint vector*, rather than separately per agent, and bounds the pre-projection action or logit displacement by η .

Algorithm 1 G²MAF: test-time joint-action refinement (one decision)

Require: frozen joint policy π_θ ; centralized critic Q_ϕ ; step size η ; stabilizer ε ; target return g

```

1: observe joint observation  $\mathbf{o}$ 
2: if continuous actions then
3:    $\mathbf{a}_\theta \sim \pi_\theta(\cdot \mid \mathbf{o}, g)$ 
4:    $\mathbf{d} \leftarrow \nabla_{\mathbf{a}} Q_\phi(\mathbf{o}, \mathbf{a}_\theta)$ 
5:    $\tilde{\mathbf{a}} \leftarrow \Pi_{\mathcal{A}}(\mathbf{a}_\theta + \eta \mathbf{d} / (\|\mathbf{d}\|_2 + \varepsilon))$ 
6: else
7:   obtain per-agent logits  $\ell_i$  from  $\pi_\theta$  and legal masks  $\mathbf{m}_i$  from the environment
8:    $\mathbf{p}_i \leftarrow \text{softmax}(\ell_i + \log \mathbf{m}_i)$  for every agent; concatenate  $\mathbf{p}$ 
9:    $\mathbf{d}_\ell \leftarrow \nabla_{\ell} Q_\phi(\mathbf{o}, \mathbf{p})$ 
10:   $\tilde{\ell} \leftarrow \ell + \eta \mathbf{d}_\ell / (\|\mathbf{d}_\ell\|_2 + \varepsilon)$ 
11:   $\tilde{a}_i \leftarrow \arg \max_j \{\tilde{\ell}_{ij} + \log m_{ij}\}$  for every agent
12:   $\tilde{\mathbf{a}} \leftarrow (\tilde{a}_1, \dots, \tilde{a}_n)$ 
13: end if
14: execute  $\tilde{\mathbf{a}}$  {one critic backward pass; no rollout}

```

Discrete Joint Actions

Equation 8 gives the complete masked-logit update. The critic is trained on concatenated one-hot actions, while $\mathbf{p}$ is the differentiable relaxation used to obtain the joint-logit gradient. The executable action is then re-masked and discretized, which preserves action legality.

Derivation: G²MAF as a Local Centralized Value Tilt

Equations 2 and 3 define the KL objective and its value-tilted optimizer. They give an exact *statewise proximal improvement*. Assume that the frozen joint policy has a density (or a probability mass function in the discrete case), that the candidate π is absolutely continuous with respect to π_θ , that the terms in Eq. 2 are well defined, and that the partition function is finite. (For discrete actions the integral in Eq. 3 is a sum.) Substitution gives the exact identity

$$\mathcal{J}_{\mathbf{o},g}(\pi) = \beta \log Z_\beta(\mathbf{o}, g) - \beta D_{\text{KL}}(\pi(\cdot \mid \mathbf{o}, g) \parallel \pi_Q(\cdot \mid \mathbf{o}, g)), \quad (13)$$

Nonnegativity of KL then proves that Eq. 3 is the unique optimizer up to null sets. Equation 4 gives its continuous-density score. The centralized tilt is generally nonfactorized whenever the prior or Q_ϕ contains cross-agent interactions; even a factorized prior becomes coupled unless the value decomposes compatibly across agents. For the derivation, write $\mathbf{d}_\theta = \nabla_{\mathbf{a}} Q_\phi(\mathbf{o}, \mathbf{a}_\theta) = [\mathbf{d}_{\theta,1}^\top, \dots, \mathbf{d}_{\theta,n}^\top]^\top$, where $\mathbf{d}_{\theta,i} = \nabla_{\mathbf{a}_i} Q_\phi(\mathbf{o}, \mathbf{a}_\theta)$. For the CGB, π_θ is an implicit push-forward. Drawing $\mathbf{a}_\theta \sim \pi_\theta$ supplies a behavior-supported initialization, and the following trust-region solution converts the Gibbs value tilt into a directly implementable first-order update:

$$\mathbf{s}^* = \arg \max_{\|\mathbf{s}\|_2 \leq \eta} \langle \mathbf{d}_\theta, \mathbf{s} \rangle = \eta \frac{\mathbf{d}_\theta}{\|\mathbf{d}_\theta\|_2}, \quad \mathbf{d}_\theta \neq \mathbf{0}. \quad (14)$$

Interpretation of the joint normalized step. At deployment, G²MAF edits the numerical action vector that is about to be executed; it neither resamples a new action nor updates the parameters of π_θ or Q_ϕ . The critic derivative $\mathbf{d}_\theta = \nabla_{\mathbf{a}} Q_\phi(\mathbf{o}, \mathbf{a}_\theta)$ specifies the first-order direction in action space that raises the critic

value most rapidly near the frozen proposal. The constraint $\|\mathbf{s}\|_2 \leq \eta$ assigns a fixed radius to this local edit. Equation 14 therefore selects the value-ascent direction while making η directly control the largest permitted displacement of the complete joint action.

All agent blocks are concatenated before computing $\|\mathbf{d}_\theta\|_2$. The common denominator consequently preserves the relative magnitudes that the centralized critic assigns to different agents' corrections, while giving the team one shared correction budget. Normalizing each $\mathbf{d}_{\theta,i}$ separately would instead give every agent its own radius- η move; the resulting joint displacement could exceed η and would discard the critic's relative allocation across agent blocks. The stabilizer ε makes the implemented denominator well defined when the gradient is zero or very small. For the box-constrained continuous action sets used here, $\Pi_{\mathcal{A}}$ is coordinatewise Euclidean projection to the legal action bounds. In particular, for $\mathcal{A} = \prod_j [a_j^{\min}, a_j^{\max}]$,

$$[\Pi_{\mathcal{A}}(\mathbf{x})]_j = \min\{a_j^{\max}, \max\{a_j^{\min}, x_j\}\}. \quad (15)$$

Thus the final vector remains executable even when the unconstrained step crosses a boundary.

For $\mathbf{d}_\theta = \mathbf{0}$ we set $\mathbf{s}^* = \mathbf{0}$. Equation 5 is the numerically stable, action-feasible version of Eq. 14: it replaces $\|\mathbf{d}_\theta\|_2$ by $D_\varepsilon = \|\mathbf{d}_\theta\|_2 + \varepsilon$ and projects onto $\mathcal{A}$. Its agent blocks are

$$\tilde{\mathbf{a}}_i = \Pi_{\mathcal{A}_i} \left(\mathbf{a}_{\theta,i} + \eta \frac{\mathbf{d}_{\theta,i}}{D_\varepsilon} \right), \quad i = 1, \dots, n. \quad (16)$$

Since projection onto a closed convex set is nonexpansive and $\mathbf{a}_\theta \in \mathcal{A}$,

$$\|\tilde{\mathbf{a}} - \mathbf{a}_\theta\|_2 \leq \eta \frac{\|\mathbf{d}_\theta\|_2}{\|\mathbf{d}_\theta\|_2 + \varepsilon} \leq \eta. \quad (17)$$

Let $\mathbf{s} = \tilde{\mathbf{a}} - \mathbf{a}_\theta$ and $\alpha = \eta/D_\varepsilon$. The variational inequality for Euclidean projection gives

$$\langle \mathbf{d}_\theta, \mathbf{s} \rangle \geq \frac{1}{\alpha} \|\mathbf{s}\|_2^2 = \frac{D_\varepsilon}{\eta} \|\mathbf{s}\|_2^2. \quad (18)$$

If $Q_\phi(\mathbf{o}, \cdot)$ has an L -Lipschitz gradient along the segment from $\mathbf{a}_\theta$ to $\tilde{\mathbf{a}}$, the smoothness inequality yields

$$\begin{aligned} Q_\phi(\mathbf{o}, \tilde{\mathbf{a}}) - Q_\phi(\mathbf{o}, \mathbf{a}_\theta) &\geq \langle \mathbf{d}_\theta, \mathbf{s} \rangle - \frac{L}{2} \|\mathbf{s}\|_2^2 \\ &\geq \left(\frac{D_\varepsilon}{\eta} - \frac{L}{2} \right) \|\mathbf{s}\|_2^2, \end{aligned} \quad (19)$$

Hence $0 < \eta < 2D_\varepsilon/L$ guarantees strict centralized critic-value improvement for every nonzero projected update. Under the local critic-consistency and support-preservation conditions stated after Eq. 11, the same increase closes the samplewise coordination gap by an equal amount.

The Coordinated Generative Backbone

For experiments, π_θ is instantiated by a coordinated generative backbone (CGB) [38]. This backbone is useful because it is a strong frozen generative policy and exposes a nontrivial value-injection question. The trajectory-space G²MAF variants modify its internal trajectory, whereas the canonical action-space variant modifies its final emitted joint action. Write ϑ for the trajectory-flow parameters and ψ for the inverse-dynamics parameters; the frozen policy shorthand is $\theta = (\vartheta, \psi)$. Let $\mathbf{N}_o$ be the fixed dataset observation normalizer; for continuous control, let $\mathbf{N}_a$ be the action normalizer and $\mathbf{U}_a = \mathbf{N}_a^{-1}$ denote action unnormalization. CGB models the clean, normalized joint observation trajectory $\mathbf{x}_0 = \mathbf{N}_o(\mathbf{o}_t, \dots, \mathbf{o}_{t+H})$ by transporting Gaussian noise $\mathbf{z}_1 \sim \mathcal{N}(\mathbf{0}, I)$ to $\mathbf{x}_0$ along the linear interpolant

$$\mathbf{z}_\alpha = (1 - \alpha)\mathbf{x}_0 + \alpha\mathbf{z}_1, \quad \alpha \in [0, 1], \quad (20)$$

The base averaged-velocity regression term is Eq. 1, with $\alpha \sim \mathcal{U}[0, 1]$. The released CGB checkpoints additionally use CoFlow’s finite-difference consistency regularizer during training. The frozen sampling map and the G²MAF formulas below use the resulting checkpoint directly. Given a schedule $1 = \alpha_K > \alpha_{K-1} > \dots > \alpha_0 = 0$, sampling runs from noise toward the data manifold with a few reverse Euler steps,

$$\begin{aligned} \mathbf{z}^{k-1} &= \mathbf{z}^k - (\alpha_k - \alpha_{k-1}) u_{\vartheta}(\mathbf{z}^k, 0, \alpha_k; \mathbf{N}_o(\mathbf{o}), g), \\ \mathbf{z}^K &\sim \mathcal{N}(0, I), \end{aligned} \quad (21)$$

or by the one-step shortcut $\hat{\mathbf{x}}_0 = \mathbf{z}^K - u_{\vartheta}(\mathbf{z}^K, 0, 1; \mathbf{N}_o(\mathbf{o}), g)$. The velocity is natively joint. The backbone decomposes each agent’s velocity into an individual term and a coordination term,

$$u_{\vartheta}^i = u_{\text{ind}}^i + u_{\text{coord}}^i, \quad (22)$$

and computes the coordination term by Coordinated Velocity Attention (CVA). At layer l , let $\mathbf{c}_l^i$ be agent i ’s temporal feature. Shared projections form query, key, and value features,

$$\mathbf{q}_l^i = W_Q \mathbf{c}_l^i, \quad \kappa_l^j = W_K \mathbf{c}_l^j, \quad \mathbf{v}_l^j = W_V \mathbf{c}_l^j. \quad (23)$$

Agent i attends to all agents j through

$$\begin{aligned} \omega_{ij}^{(l)} &= \frac{\exp((\mathbf{q}_l^i)^\top \kappa_l^j / \sqrt{d_{\text{att}}})}{\sum_{m=1}^n \exp((\mathbf{q}_l^i)^\top \kappa_l^m / \sqrt{d_{\text{att}}})}, \\ \xi_l^i &= \sum_{j=1}^n \omega_{ij}^{(l)} \mathbf{v}_l^j, \end{aligned} \quad (24)$$

and injects the teammate message through a learnable coordination gate,

$$\hat{\mathbf{c}}_l^i = \mathbf{c}_l^i + \chi_l \xi_l^i, \quad (25)$$

where κ_l^j is a key vector, d_{att} is its dimension, ξ_l^i is the aggregated teammate message, and χ_l is the learnable coordination gate. The symbols κ_l^j and ξ_l^i avoid overloading the denoising-step index k and the legal-action mask $\mathbf{m}_i$, respectively. The value projection has output dimension matching $\mathbf{c}_l^i$, making the residual sum in Eq. 25 dimensionally valid. The shared attention weights let each agent’s velocity depend on teammate features at the same denoising layer; χ_l controls the strength of this cross-agent message and is distinct from the discount γ . Thus the generated trajectory is coupled before inverse dynamics is applied. Let I_ψ be the shared per-agent inverse-dynamics head and $\mathcal{I}_\psi$ its componentwise joint lifting. For continuous control, the head outputs a normalized joint action, which is unnormalized before execution:

$$\begin{aligned} \mathbf{a}_\theta^{\text{norm}} &= \mathcal{I}_\psi(\hat{\boldsymbol{\sigma}}_t^{\text{norm}}, \hat{\boldsymbol{\sigma}}_{t+1}^{\text{norm}}) := (I_\psi(\hat{\boldsymbol{\sigma}}_t^{1,\text{norm}}, \hat{\boldsymbol{\sigma}}_{t+1}^{1,\text{norm}}), \dots, I_\psi(\hat{\boldsymbol{\sigma}}_t^{n,\text{norm}}, \hat{\boldsymbol{\sigma}}_{t+1}^{n,\text{norm}})), \\ \mathbf{a}_\theta &= \mathbf{U}_a(\mathbf{a}_\theta^{\text{norm}}). \end{aligned} \quad (26)$$

For discrete control the same head emits logits and Eq. 8 supplies masking and discretization in place of $\mathbf{U}_a$. The frozen policy used in the experiments is the push-forward of Gaussian noise through a coordinated trajectory generator, inverse-dynamics decoder, and output transform. Writing $F_\vartheta(\mathbf{z}^K; \mathbf{N}_o(\mathbf{o}), g) = \hat{\mathbf{x}}_0$ for the few-step sampler and P_0, P_1 for the first two generated normalized-observation slices, the continuous-action map is

$$\begin{aligned} h_{\vartheta, \psi}(\mathbf{z}^K; \mathbf{o}, g) &= \mathbf{U}_a(\mathcal{I}_\psi(P_0 F_\vartheta(\mathbf{z}^K; \mathbf{N}_o(\mathbf{o}), g), P_1 F_\vartheta(\mathbf{z}^K; \mathbf{N}_o(\mathbf{o}), g))), \\ \mathbf{z}^K &\sim \mathcal{N}(0, I), \quad \mathbf{a}_\theta = h_{\vartheta, \psi}(\mathbf{z}^K; \mathbf{o}, g). \end{aligned} \quad (27)$$

The induced action policy is the conditional push-forward $\pi_\theta(\cdot \mid \mathbf{o}, g) = (h_{\vartheta, \psi}(\cdot; \mathbf{o}, g))_{\#} \mathcal{N}(0, I)$ with $\theta = (\vartheta, \psi)$. Cross-agent velocity attention allows each decoded action to depend on teammate features. The induced prior therefore need not be a product of conditionally independent per-agent policies:

$$\pi_\theta(\mathbf{a} \mid \mathbf{o}, g) \text{ need not factorize as } \prod_{i=1}^n \pi_{\theta, i}(\mathbf{a}_i \mid \mathbf{o}, g). \quad (28)$$

Two properties matter for G²MAF: (i) the executed action is the *decoded* quantity $\mathbf{a}_\theta$, where the behavior critic’s value signal is applied most directly; and (ii) the flow is *short*. Perturbing intermediate iterates $\mathbf{z}^k$ is therefore a stronger intervention than in many-step diffusion policies and must be treated as a separate design choice (Sec. Method).

G²MAF Value-Injection Variants for Coordinated Generators

G²MAF uses the same frozen coordinated policy and test-time critic guidance at three injection locations. All-step and final-step trajectory-space G²MAF modify an internal denoising trajectory before action decoding; post-generation action-space G²MAF modifies the decoded action after the flow is complete. For a generic action-space flow v_ζ under the present convention (data at $\alpha = 0$, noise at $\alpha = 1$), a one-step clean estimate and its action-space guidance direction are

$$\begin{aligned}\hat{\mathbf{a}}_0(\alpha) &= \mathbf{a}_\alpha - \alpha v_\zeta(\mathbf{a}_\alpha, \alpha; \mathbf{o}, g), \\ \mathbf{G}_{\text{act}}(\alpha) &= \nabla_{\hat{\mathbf{a}}_0} Q_\phi(\mathbf{o}, \hat{\mathbf{a}}_0), \quad \hat{\mathbf{G}}_{\text{act}} = \frac{\mathbf{G}_{\text{act}}}{\|\mathbf{G}_{\text{act}}\|_2 + \varepsilon}, \\ \mathbf{a}_{\alpha-\Delta\alpha} &= \mathbf{a}_\alpha - \Delta\alpha \left[v_\zeta(\mathbf{a}_\alpha, \alpha; \mathbf{o}, g) - \lambda_Q \hat{\mathbf{G}}_{\text{act}} \right],\end{aligned}\tag{29}$$

where $\lambda_Q > 0$ and $0 < \Delta\alpha \leq \alpha$. This reference update normalizes the guidance direction and uses λ_Q as its displacement in denoising coordinates. Direct use of $\mathbf{G}_{\text{act}}$ assumes $\partial\hat{\mathbf{a}}_0/\partial\mathbf{a}_\alpha \approx \text{Id}$; the exact gradient premultiplies it by that Jacobian transpose. The outer minus sign yields value ascent under the reverse-time Euler convention.

For CGB, $\mathbf{z}^k$ is a normalized joint-observation trajectory, not an action. An identity map between these spaces is therefore invalid. The trajectory-space G²MAF update takes the ordinary reverse-Euler step in Eq. 6, then differentiates the normalized critic through the trajectory-to-observation--action decoder by Eq. 7. The critic Q_ν^{norm} uses the FQE loss in Eq. 12 on identically normalized logged transitions. The implementation detaches $\bar{\mathbf{z}}^{k-1}$; this gradient includes the decoder and inverse-dynamics paths but not earlier denoising steps. The all-step and final-step trajectory-space G²MAF variants use

$$\begin{aligned}\hat{\mathbf{G}}_{\text{traj}}^{k-1} &= \frac{\mathbf{G}_{\text{traj}}^{k-1}}{\|\mathbf{G}_{\text{traj}}^{k-1}\|_2 + \varepsilon}, \\ \mathbf{z}^{k-1} &= \bar{\mathbf{z}}^{k-1} + \lambda_Q \hat{\mathbf{G}}_{\text{traj}}^{k-1}.\end{aligned}\tag{30}$$

The all-step variant applies Eq. 30 after every base Euler step; the final-step variant applies it only after the last one. Here λ_Q is a normalized trajectory-space displacement with its own scale, independent of $\Delta\alpha_k$.

The decoder separates the G²MAF variants. For Final, $k = 1$: the last base step produces $\bar{\mathbf{z}}^0$, the normalized critic changes it to $\mathbf{z}^0$ through Eq. 30, and the decoder maps $\mathbf{z}^0$ to $\tilde{\mathbf{a}}$. Its gradient follows $Q_\nu^{\text{norm}} \rightarrow \mathbf{y}^0 \rightarrow \bar{\mathbf{z}}^0$ through the exact decoder Jacobian; All repeats this path at every step. Post completes the flow, decodes $\mathbf{a}_\theta$, and applies Eq. 5 in executable action space after generation ends. In general $h_{\text{dec}}(\mathbf{z}^0 + \Delta\mathbf{z}) \neq h_{\text{dec}}(\mathbf{z}^0) + \Delta\mathbf{a}$: a nonlinear decoder can rotate or rescale the trajectory-space direction. This coordinate effect reflects the decoder’s coordinates. The experiment measures the resulting return differences across the two locations.