



WeCharge

Sensorless Dynamic Wireless Charging

Bohdan Pakhaliuk, PhD Viktor Shevchenko, PhD Team
September 29, 2026

Chernihiv Polytechnic National University, Ukraine

The Problem

Charging is a bottleneck for anything that moves.

- Vehicles, AGVs, cranes stop moving to charge — downtime, cabling, oversized batteries.
- Existing dynamic charging (DWPT) needs position sensors + dense multi-coil arrays → costly, complex.
- Misalignment kills efficiency; strong fields raise EMF safety concerns.
- Exposed cabling is a single point of failure — a resilience gap during grid or crisis disruption.



\$16.4B

Global wireless power
transfer market, 2025

\$105B

Forecast by 2035

20.4%


CAGR, 2025–2035

- Wireless EV charging is still an **early niche** ($\approx$ \$0.1B in 2025); dynamic (in-motion) charging exists mainly as expensive sensor-based pilots (ORNL, FastInCharge).
- Adjacent pull: industrial AGVs, cranes, public transport, defense & emergency mobility.


Sources: Market Research Future — Wireless Power Transmission Market (2025–2035); Precedence Research — Wireless EV Charging Market (2025–2035).

Our Solution: Hybrid Sensorless Coupling

- Combines inductive + capacitive coupling in one transmitter segment.
- The coupling capacitor doubles as a self-activating switch — it closes the current path only when the receiver overlaps the segment.
- Result: no position sensors, no photocells, no receiver-side beacon. Physics activates the right coil automatically.
- Patent-protected core mechanism.



How It Works




Sensorless — only current-phase measurement needed to detect activation.

Low EMF — capacitive coupling partially shields stray field.

Less copper — high-frequency (up to 1 MHz) GaN converters shrink coils.

Scales — multi-phase track segments, limited only by bus losses.

	Conventional DWPT	WeCharge
Activation	Position sensors	Sensorless
Structure	Multi-coil array	Single hybrid segment
EMF exposure	High, shielded	Reduced (capacitive)
Control	High (array switching)	Low (phase only)
IP position	Open / institutional	Patent LV 15706 B1



Patent LV 15706 B1

Sensorless transmitter activation

Working Prototype

Built & tested, low-power

WPT Conference 2022

Bordeaux, France

Team track record: 11 journal papers, 22 conference papers, 5 patents, 2 books.

Non-dilutive R&D funding secured

4.48M UAH project (2026–2028): theory → simulation → prototype → validation.


Who pays us, and for what

- **IP licensing** of the hybrid sensorless coupling design to EV charging OEMs and integrators.
- **Engineering / pilot-deployment contracts** — logistics & AGV fleets, overhead cranes, factory automation.
- **Public transport pilots** (buses, monorail) via infrastructure partners — lower EMF and no exposed cabling ease regulatory approval.

Target performance

Efficiency up to 90% · 10–20% smaller/lighter coils · up to 30% lower idle losses — validated at prototype scale, being scaled under the current funded project.

Roadmap



Team



Pakhaliuk Bohdan



Shevchenko Viktor



Yatchenko Yevhenii




Strohii Andrii




Zakharchenko Dmytro



Baida Vladyslav



Lysiuk Vladyslav



Zhuk Dmytro

What we're seeking

- **Mentorship** on commercialization and market validation.
- **Contacts with industrial companies** (logistics, cranes, transport) interested in future testing.
- **Advice** on international patent protection.
- **Small-scale support** for prototype components and lab testing.

Let's charge things without ever plugging in.

bohdan.pakhaliuk@stu.cn.ua | Chernihiv Polytechnic National University