



Wi-Fi hotspot or
connect by cable



IP-SatCube

ENABLING
QUICK ACCESS
TO SEAMLESS
SATELLITE
BROADBAND



ONLY 8 KG

*All-in-one compact terminal in
the size of a large laptop*

UP TO 20 Mbps

*Tapping next-generation High Throughput
Satellites (HTS) and widebeam Ku.*

1 MINUTE TO CONNECT

*A highly intuitive user interface makes
operation as simple as using a smartphone.*

www.globaltt.com



Satellite Internet Operator by GLOBALTT



COMPACT DESIGN FOR PEOPLE ON-THE-GO

Highly suitable for wide range of users, such as broadcast media, emergency response, law enforcement, public safety organizations, telemedicine, NGO's, corporate executives and more.

Satcube Ku enables users to create an easy to use Wi-Fi hotspot and get high-speed broadband connection in less than a minute to execute critical on-the-spot work assignments and communication.

INTUITIVE USER INTERFACE

The user is guided by the 3 dimensional "point-and-locate" function to get connected with the Internet over satellite in one minute.



SPECIFICATIONS

DIMENSIONS

470 / 300 / 55 mm
(18,5 / 11,8 / 2,17 inch)

TOTAL WEIGHT

8 kg (17,6 lbs)

DATA RATE

4 Mbps full duplex, up to 20Mbps via HTS satellites

BATTERIES

3 hours transmit time
(three batteries), hot swappable

FREQUENCIES

Tx 13.75 – 14.50 GHz
Rx 10.95 – 12.75 GHz

POLARISATION

Linear Horizontal / Vertical

EIRP

Typical 46 dBW

G/T

9 dB/K

SATELLITE MODEM

iDirect IQ 200 modem, Newtec 2510 modem and UHP 210 modem

POWER CONSUMPTION

130 W

INTERFACES

2 x LAN, 1 x USB host, WLAN Access Point (IEEE 802.11 b/g)

USER INTERFACE

High contrast display

WATER AND DUST

IP65

DC INPUT

24 VDC

AC/DC INPUT RANGE

100 – 240 VAC, 47 – 63 Hz, 150 W

APPROVALS

CE [RED directive (2014/53/UE), EN 301 428]] FCC [Pending approval]

TEMPERATURE

–20°C (4°F) to 50°C (122°F)

ADDRESS :

10 Rue Lenoir
Parc scientifique Einstein
B-1348 Louvain-La-Neuve
Belgium

CONTACT US

info@ipseos.eu | www.ipseos.eu

MAIN SWITCH

A: +32 (0)10 39 50 70 | B: +32 (0)10 48 56 00



Ref: IPSEOS - satcube ver1 : 07/03/2021