

GLOBALTT

SATELLITE INTERNET SERVICE

Kymeta Connect™ offers full-service connectivity solutions for u8 terminals for military. By-the-gigabyte packages are available with either MIR or MIR/CIR capacity. Refer to the Kymeta Connect product sheet for more detail.

GLOBALTT WILL MAKE YOUR COMMUNICATION COMES TRUE

u8 MIL GEO TERMINAL

MAKING MOBILE GLOBAL

The new Kymeta™ u8 terminal provides a complete connectivity solution for communications-on-the-move(COTM) and networks-on-the-move (NOTM) when and where you need it most.

The u8 terminal, with our revolutionary software-defined, electric beam-steering technology, is low profile and easy-to-mount on vehicles and vessels. Our u8 terminals and flyaway systems for the military integrate the iDirect 950mp router and support external modems such as ViaSat CBM400 and most commercial modems.

Broadband by-the-gigabyte connectivity packages are available from Kymeta in either MIR or MIR/CIR plans. Kymeta Connect™ packages provide all-inclusive bundles with monthly rate.

TURNKEY SOLUTIONS

MULTIPLE TERMINAL CONFIGURATIONS PROVIDE THE HARDWARE, SOFTWARE, AND CONNECTIVITY YOU NEED.



DESIGNED FOR MOBILE PLATFORMS

LOW PROFILE, AERODYNAMIC DESIGN, NATIVE DC POWER INPUT, AND NEW ACCESSORIES SIMPLIFY VEHICLE INTEGRATION.



EXTENDED ENVIRONMENTAL COVERAGE

WITH AN ALL OUTDOORS CONSTRUCTION AND IP66 RATING, THE U8 TERMINAL FOR MILITARY IS DESIGNED FOR THE MOST DEMANDING ENVIRONMENTS.



PORTABLE AND RUGGED

WITH A HARDENED REUSABLE SHIPPING CASE, THE KYMETA U8 FLYAWAY FOR MILITARY PROVIDES THE FASTEST OUT-OF-THE-BOX COMMUNICATION ANYWHERE—JUST ADD POWER.



LEO-UPGRADEABLE

THE U8 ANTENNA ANTICIPATES THE ARRIVAL OF KU-BAND LEO CONSTELLATIONS. YOUR TERMINAL CAN BE UPGRADED TO A LEO CONFIGURATION AT A LATER TIME.



KYMETA™



 **GLOBALTT**

www.globaltt.com

u8 GEO Terminal for Military Specifications*

CONNECTIVITY

SETUP TIME OF TERMINAL

Unpackage, lift, mount, and operate in less than 20 minutes

ACQUISITION OF SIGNAL

Less than 1 minute from initiation of acquisition

SATCOM MODEM

Integrated iDirect 950mp satellite router

MECHANICAL

DIMENSIONS

L 90 cm × W 90 cm × H 14 cm
L 35.5 in. × W 35.5 in. × H 5.5 in.

WEIGHT

~32 kg (~70 lb.)

OPERATIONAL TEMPERATURE

-40 °C to +70 °C with shroud;
equiv to +55 °C + solar loading
with shroud

STORAGE TEMPERATURE

-40 °C to +85 °C

INGRESS PROTECTION

IP66

POWER

DC INPUT POWER

12 VDC to 24 VDC

POWER CONSUMPTION

(WITH INTEGRATED MODEM)
~200 W (typical), 600 W (peak)

INTERFACES

NETWORK INTERFACE

Ethernet

ANTENNA

BAND

Ku

ANTENNA TYPE

Electronically scanned array

POLARIZATION

Linear, software-defined

RX FREQUENCY RANGE

10.7 GHz to 12.75 GHz

G/T BROADSIDE

Up to 11.25 dB/K

RX INSTANTANEOUS

BANDWIDTH

250 MHz

TX FREQUENCY RANGE

13.75 GHz to 14.50 GHz

EIRP

Up to 45.5 dBW with 20 W BUC

TRACKING

SCAN ANGLES

Az 360°, El +15° to +90°

TRACKING RECEIVER TYPE

Integrated tracking system
DVB-S2, DVB-S2X

COMPLIANCE

CERTIFICATIONS IN PROGRESS

CE, UL, RoHS, FCC

AVAILABLE CONFIGURATIONS

MILITARY TERMINAL

- u8 antenna with integrated ACU and power supply
- iDirect 950mp satellite modem
- RF chain with 20 W low-profile BUC
- Shroud

MILITARY FLYAWAY

- u8 antenna with integrated ACU and power supply
- iDirect 950MP satellite modem
- RF chain with 20 W low-profile BUC
- Shroud
- Flyaway case



AVAILABLE ACCESSORIES

- Vehicle mount kit
- Vehicle power kit
- Adapter plate for existing u7 mounts
- AC-to-DC power kit
- Cables

AVAILABLE SOFTWARE-ENABLED FEATURES

- Manual positioning (GPS denied) mode
- Full privacy mode
- External GPS support

u8 | **GEO**
FLYAWAY

GLOBALTT



For more information, contact **GLOBALTT**



10 Rue Lenoir, Parc scientifique Einstein,
B-1348 Louvain-La-Neuve, Belgium



info@globaltt.com
www.globaltt.com



+32 (0)10 39 50 70
+32 (0)10 48 56 20